

RTR DAILY 7

1. Below which phase of flight are TCAS RAs generally inhibited?

Mark only one oval.

- ☐ A. Initial climb
- ☐ B. Takeoff roll
- ☐ C. Approach

2. Which failure most degrades TCAS performance?

Mark only one oval.

- ☐ A. Mode C altitude loss
- ☐ B. GNSS signal loss
- ☐ C. VHF radio failure

3. TCAS traffic display range selection affects:

Mark only one oval.

- ☐ A. RA logic
- ☐ B. TA generation
- ☐ C. Pilot awareness only

4. TCAS identifies intruders primarily using:

Mark only one oval.

- ☐ A. ADS-B position
- ☐ B. Primary radar
- ☐ C. SSR replies

5. Which statement about TCAS and ATC separation is correct?

Mark only one oval.

- ☐ A. TCAS ensures legal separation
- ☐ B. TCAS replaces ATC in RVSM
- ☐ C. TCAS is independent of ATC

6. TCAS sensitivity levels are adjusted based on:

Mark only one oval.

- ☐ A. Aircraft mass
- ☐ B. Altitude band
- ☐ C. Weather conditions

7. A "Clear of Conflict" annunciation indicates:

Mark only one oval.

- ☐ A. ATC separation restored
- ☐ B. No further RA commands
- ☐ C. Intruder no longer exists

8. TCAS does NOT provide protection against:

Mark only one oval.

- ☐ A. Aircraft without transponder
- ☐ B. Mode S equipped traffic
- ☐ C. Mode C traffic

9. TCAS RA vertical sense selection prioritizes:

Mark only one oval.

- ☐ A. Passenger comfort
- ☐ B. Minimum deviation
- ☐ C. Collision avoidance

10.

TCAS advisories are based on predicted:

Mark only one oval.

- ☐ A. Track intersection
- ☐ B. Horizontal distance only
- ☐ C. Vertical miss distance

11. MLAT determines aircraft position using:

Mark only one oval.

- ☐ A. Track intersection
- ☐ B. Horizontal distance only
- ☐ C. Vertical miss distance

12. ADS-B OUT broadcasts position derived from:

Mark only one oval.

- ☐ A. Ground radar
- ☐ B. Aircraft GNSS
- ☐ C. ATC multilateration

13. Radar clutter is primarily caused by:

Mark only one oval.

- ☐ A. Weather returns
- ☐ B. Aircraft speed
- ☐ C. Transponder delay

14. SSR garbling occurs when:

Mark only one oval.

- ☐ A. Two replies overlap
- ☐ B. Antenna fails
- ☐ C. Weather is present

15. PSR cannot directly provide:

Mark only one oval.

- ☐ A. Range
- ☐ B. Bearing
- ☐ C. Identity

16. ADS-B surveillance integrity depends mainly on:

Mark only one oval.

- ☐ A. GNSS accuracy
- ☐ B. ATC radar
- ☐ C. TCAS logic

17. Radar update rate is influenced by:

Mark only one oval.

- ☐ A. Antenna rotation speed
- ☐ B. Pulse width
- ☐ C. Transponder code

18. Which surveillance system does NOT require interrogation?

Mark only one oval.

- ☐ A. PSR
- ☐ B. SSR
- ☐ C. Mode S

19. Radar beamwidth primarily affects:

Mark only one oval.

- ☐ A. Range resolution
- ☐ B. Azimuth resolution
- ☐ C. Target speed

20. Secondary radar cannot detect:

Mark only one oval.

- ☐ A. Non-cooperative targets
- ☐ B. Mode C aircraft
- ☐ C. Mode S aircraft

21. MLAT accuracy improves with:

Mark only one oval.

- ☐ A. Fewer sensors
- ☐ B. Wider sensor spacing
- ☐ c. Increased geometry diversity

22. MLAT accuracy improves with:ATC issues: "Mointoin FL190, expect descent."The phrase "expect descent" primarily serves to:

Mark only one oval.

- ☐ A. Modify the clearance
- ☐ B. Authorise pilot anticipation
- ☐ C. Provide planning information

23. Which pilot reply risks being interpreted as acceptance of an instruction that was never issued?

Mark only one oval.

- ☐ A. "Roger."
- ☐ B. "Wilco."
- ☐ C. "Standing by."

24. ATC: "After departure, turn right heading 120."This instruction is legally effective:

Mark only one oval.

- ☐ A. Immediately
- ☐ B. Only after airborne
- ☐ C. Only after pilot readback

25. Which phrase implies future intent rather than present compliance?

Mark only one oval.

- ☐ A. "Turning right heading 270."
- ☐ B. "We will turn right heading 270."
- ☐ C. "Right heading 270."

26. ATC uses "Report passing FL110."Which report would be incorrect?

Mark only one oval.

- ☐ A. "Passing FL110
- ☐ B."Leaving FL110
- ☐ C. "Approaching FL110."

27. Which RT response most weakens ATC's ability to maintain vertical separation?

Mark only one oval.

- ☐ A. "Descending to FL180."
- ☐ B. "Leaving FL180."
- ☐ C. "Descending."

28. ATC: "Cross Runway 09." Which readback is operationally weakest?

Mark only one oval.

- ☐ A. "Cross Runway 09."
- ☐ B. "Crossing Runway 09."
- ☐ C. "Wilco."

29. Which phrase is discouraged because it can sound like an instruction rather than a report?

Mark only one oval.

- ☐ A. "Stop climb."
- ☐ B. "Stopping climb."
- ☐ C."Unable climb."

30. ATC: "Monitor tower 718.7." This requires the pilot to:

Mark only one oval.

- ☐ A. Change frequency and transmit
- ☐ B. Change frequency and listen only
- ☐ C. Remain on present frequency

31. Which reply introduces assumed compliance without confirmation?

Mark only one oval.

- ☐ A. "Roger."
- ☐ B. "Wilco."
- ☐ C. "Affirm."

32. ATC: "Taxi via Alpha, hold short Runway 18." Which readback is incomplete?

Mark only one oval.

- ☐ A. "Via Alpha, hold short Runway 18."
- ☐ B. "Taxi via Alpha."
- ☐ C. "Holding short Runway 18."

33. Which phrase most increases risk during similar callsign operations?

Mark only one oval.

- ☐ A. Using abbreviated callsign early
- ☐ B. Speaking slowly
- ☐ C. Full callsign repetition

34. ATC issues an amended clearance without "Correction". Pilot should:

Mark only one oval.

- ☐ A. Follow the last part only
- ☐ B. Ignore entire message
- ☐ C. Request clarification

35. Which pilot response subtly transfers separation responsibility without ATC instruction?

Mark only one oval.

- ☐ A. "Traffic in sight."
- ☐ B. "Maintaining visual separation."
- ☐ C. "Roger."

36. ATC: "Vacate runway when able." This phrase primarily affects:

Mark only one oval.

- ☐ A. Direction of exit
- ☐ B. Timing of exit
- ☐ C. Speed of exit

37. Which RT phrase is intended to reduce frequency congestion?

Mark only one oval.

- ☐ A. "Standby."
- ☐ B. "Roger."
- ☐ C. "Wilco."

38. ATC: "Continue approach."

This instruction does NOT imply:

Mark only one oval.

- ☐ A. Clearance to land
- ☐ B. Maintain current clearance
- ☐ C. Expect landing clearance

39. Which pilot reply is least suitable to acknowledge a heading instruction?

Mark only one oval.

- ☐ A. "Heading 240."
- ☐ B. "Turning right 240."
- ☐ C. "Roger."

40. ATC: "Hold position." Which action is incorrect?

Mark only one oval.

- ☐ A. Stop movement
- ☐ B. Maintain brakes
- ☐ C. Continue slowly

41. Which RT habit most hides pilot misunderstanding?

Mark only one oval.

- ☐ A. Frequent "Roger"
- ☐ B. Full callsign usage
- ☐ C. Asking for clarification

42. Which phrase implies conditional execution without explicitly stating the condition?

Mark only one oval.

- ☐ A. "After landing traffic .."
- ☐ B. "When ready ... "
- ☐ C. "Expect ... "

43. ATC: "Climb FL200, expedite."

Which readback is weakest?

Mark only one oval.

- ☐ A. "Climbing FL200, expediting."
- ☐ B. "Climb FL200."
- ☐ C. "Wilco."

44. Which phrase should NOT be used to acknowledge a clearance?

Mark only one oval.

- ☐ A. Affirm
- ☐ B. Roger
- ☐ C. Correct

45. ATC: "Say intentions."

Pilot should:

Mark only one oval.

- ☐ A. Read back clearance
- ☐ B. State plan concisely
- ☐ C. Request clearance

46. Which response implies action without authority?

Mark only one oval.

- ☐ A. "Descending."
- ☐ B. "Request descent."
- ☐ C. "Unable descent."

47. ATC: "Maintain present heading."

Which reply adds ambiguity?

Mark only one oval.

- ☐ A. "Maintaining present heading."
- ☐ B. "Present heading."
- ☐ C. "Roger."

48. Which phrase indicates receipt but NOT compliance?

Mark only one oval.

- ☐ A. Wilco
- ☐ B. Roger
- ☐ C. Affirm

49. ATC: "Expect further clearance at time 30."

This is:

Mark only one oval.

☐ A. Clearance

☐ B. Instruction

☐ C. Advisory

50. Which RT error most contributes to runway incursion risk?

Mark only one oval.

☐ A. Missing QNH

☐ B. Missing runway readback

☐ C. Fast speech

This content is neither created nor endorsed by Google.

Google Forms