

RTR (A) DAILY QUESTION SETS - COMPREHENSIVE ANSWER KEYS

Official Solutions and Operational Rationale for RTR Daily Sets 7, 2, 3 & 4

RTR DAILY 7 - ANSWER KEY

Q. No.	Correct Option & Answer	Key Technical / Regulatory Rationale
1	B. Takeoff roll	TCAS Resolution Advisories (RAs) are inhibited below 1,000 ft AGL (and specifically during takeoff roll) to prevent low-altitude nuisance alerts.
2	A. Mode C altitude loss	Loss of Mode C altitude reporting severely degrades TCAS as vertical guidance (RAs) depends directly on pressure altitude data.
3	C. Pilot awareness only	Selecting traffic display range alters situational awareness on the display screen but does not alter underlying TCAS RA/TA threat detection logic.
4	C. SSR replies	TCAS actively interrogates transponders and processes SSR replies (Mode C/S) to compute intruder slant range, bearing, and altitude.
5	C. TCAS is independent of ATC	TCAS operates independently of ground-based ATC radar systems using onboard transponder interrogations.
6	B. Altitude band	TCAS sensitivity levels (SL 2 through 7) are automatically adjusted based on current aircraft altitude band.
7	B. No further RA commands	'Clear of Conflict' indicates that the threat has passed and the pilot can return to assigned clearance; it does not guarantee ATC separation.
8	A. Aircraft without transponder	TCAS relies entirely on transponder replies; non-transponder equipped aircraft (non-cooperative targets) cannot be detected.
9	C. Collision avoidance	In RA calculation, maintaining flight safety and collision avoidance takes absolute priority over passenger comfort or flight path deviations.
10	C. Vertical miss distance	TCAS advisories evaluate tau (time to closest point of approach) and predicted vertical miss distance at CPA.

11	A. Track intersection	Multilateration (MLAT) calculates position using Time Difference of Arrival (TDOA) of transponder signals across multiple ground receivers.
12	B. Aircraft GNSS	ADS-B OUT broadcasts parameters derived directly from onboard GNSS navigation systems.
13	A. Weather returns	Primary radar clutter is caused by unwanted echoes from precipitation, ground terrain, sea surface, or atmospheric phenomena.
14	A. Two replies overlap	Garbling occurs in SSR when transponder replies from two closely spaced aircraft overlap in time at the ground antenna.
15	C. Identity	Primary Surveillance Radar (PSR) detects target skin-reflections giving range/bearing but cannot determine identity or Mode C altitude without SSR.
16	A. GNSS accuracy	ADS-B surveillance relies on GPS/GNSS data parameters (NIC, NAC, SIL) to establish position integrity.
17	A. Antenna rotation speed	The scan update rate of a mechanically rotating surveillance radar is inversely proportional to its antenna rotation speed.
18	A. PSR	PSR relies on passive reflection of transmitted RF energy from target skin and does not interrogate onboard transponders.
19	B. Azimuth resolution	Narrower horizontal beamwidth allows the radar system to distinguish two targets closely spaced in azimuth at equal range.
20	A. Non-cooperative targets	Secondary Surveillance Radar (SSR) requires an operating transponder; non-cooperative aircraft produce no SSR targets.
21	C. Increased geometry diversity	MLAT positioning accuracy improves when ground receiver stations are geographically distributed around target areas.
22	C. Provide planning information	'Expect descent' is an advisory providing advance planning information and does not constitute authorization to descend.
23	A. 'Roger.'	Using 'Roger' to acknowledge a clearance or instruction creates ambiguity regarding whether specific numbers were understood and accepted.
24	B. Only after airborne	Departure turn instructions apply only after takeoff once airborne

		unless specified otherwise in conditional tower procedures.
25	B. 'We will turn right heading 270'	Using future tense 'will turn' implies intention rather than immediate compliance, causing control ambiguity.
26	C. 'Approaching FL110.'	When instructed to 'Report passing FL110', 'Approaching' is incorrect as it does not confirm the level has been crossed.
27	C. 'Descending'	Omitting assigned altitude or flight level in readbacks impairs ATC's capability to verify level compliance.
28	C. 'Wilco'	Runway crossing clearances require exact readback including runway designator; 'Wilco' or 'Roger' is legally invalid.
29	A. 'Stop climb.'	Transmitting 'Stop climb' sounds like an ATC command rather than pilot reporting; pilots should state 'Stopping climb' or 'Level at...'
30	B. Change frequency and listen only	'Monitor' means change to the specified frequency and listen for transmissions without initiating a call until prompted.
31	A. 'Roger.'	'Roger' acknowledges receipt but fails to confirm compliance or correct understanding of specific control parameters.
32	B. 'Taxi via Alpha.'	Omitting mandatory hold-short instructions in taxi readbacks poses severe runway incursion risks.
33	A. Using abbreviated callsign early	Using abbreviated callsigns before established by ATC increases risk of confusion during similar callsign operations.
34	C. Request clarification	When an amended clearance is delivered without standard error markers like 'Correction', pilots must clarify to avoid assumptions.
35	B. 'Maintaining visual separation.'	Stating visual separation transfers separation responsibility from ATC to the pilot under VFR/CVFR rules.
36	B. Timing of exit	'Vacate when able' allows pilot control over speed and location to vacate expeditiously without unnecessary delay.
37	C. 'Wilco'	'Wilco' ('I will comply') replaces longer readbacks for non-mandatory items, saving frequency airspace.
38	A. Clearance to land	'Continue approach' authorizes flight continuation down approach path but explicitly does NOT grant landing clearance.

39	C. 'Roger.'	Heading instructions require mandatory readback of the specific numerical heading; 'Roger' is invalid.
40	C. Continue slowly	'Hold position' requires bringing the aircraft to an immediate, complete stop on taxiways/aprons.
41	A. Frequent 'Roger'	Overusing 'Roger' hides readback errors and prevents controllers from detecting misunderstandings.
42	B. 'When ready...'	'When ready' implies pilot execution at pilot discretion without explicit time framing.
43	C. 'Wilco.'	Level assignment changes and expediting instructions require full explicit readback, not simple acknowledgment.
44	B. Roger	'Roger' indicates message received; it must never be used to acknowledge or accept a clearance.
45	B. State plan concisely	'Say intentions' requests the flight crew to state their operational intent clearly and concisely.
46	A. 'Descending'	Reporting 'Descending' without receiving or reading back descent clearance implies unauthorized action.
47	C. 'Roger'	'Roger' fails to read back heading, creating potential drift/heading deviation risks.
48	B. Roger	ICAO definition of 'Roger' is 'I have received all of your last transmission'; it does not imply compliance ('Wilco').
49	C. Advisory	'Expect further clearance at...' is an operational planning advisory, not an immediate control clearance.
50	B. Missing runway readback	Failing to read back runway designators and hold-short points is the single leading RT factor in runway incursions.

RTR DAILY 2 - ANSWER KEY

Q. No.	Correct Option & Answer	Key Technical / Regulatory Rationale
1	The airport is unsafe, do not land	A flashing red light from aerodrome control tower to an aircraft in

		flight indicates airport unsafe, do not land (ICAO Annex 2).
2	other converging aircraft	Taxiing aircraft on manoeuvring area shall give way to aircraft taking off or landing and give way to other converging aircraft.
3	1500 m horizontally and 1 000 feet vertically from clouds, 8 km visibility	For Class G airspace above 10,000 ft MSL, VMC minima is 8 km flight visibility with 1,500 m horizontal & 1,000 ft vertical cloud distance.
4	7700	An intercepted aircraft equipped with SSR transponder shall select Mode A Code 7700 unless instructed otherwise by ATS.
5	Emergency aircraft	Aircraft in distress or experiencing emergency conditions have absolute priority over all other air traffic.
6	Not with standing any previous instructions, do not land for the time being.	A red pyrotechnic flare addressed to an aircraft in flight signifies notwithstanding previous instructions, do not land for the time being.
7	Depature end of runway.	DER stands for Departure End of Runway in airport performance and instrument procedures terminology.
8	FAF	In precision approach (ILS), final approach segment begins at Final Approach Fix (FAF) or glide path intercept point.
9	The cold air side of the core.	Maximum Clear Air Turbulence (CAT) and wind shear occur on the cold air side (polar side) of the jet stream core.
10	Approximately 12 hours (1/2 of a sidereal day)	GPS NAVSTAR satellites revolve in Medium Earth Orbit with an orbital period of approximately 11 hours 58 minutes (12 hours).
11	20200 km	NAVSTAR/GPS orbit altitude is approximately 20,200 km (approx. 10,900 NM) above Earth.
12	select appropriate satellites automatically, to track the signals and to measure the time taken by signals from the satellites to reach the receiver	User segment receivers track satellite RF signals, calculate signal transit times (pseudoranges), and solve 3D position & time.
13	transmit signals which can be used, by suitable receivers, to determine time, position and velocity	Space segment (satellites) continuously transmits navigation data/ranging signals used by receivers to compute position/velocity.
14	inclined 55 to the equatorial plane	GPS satellite constellation is arranged in 6 orbital planes inclined at

		an angle of 55° to the equatorial plane.
15	UHF	GPS L1 (1575.42 MHz) and L2 (1227.60 MHz) carrier frequencies belong to the Ultra High Frequency (UHF) band (300 MHz - 3 GHz).
16	12.5 minutes (= 30 seconds per data frame)	Full GPS almanac transmission consists of 25 subframes taking exactly 12.5 minutes at 50 bps transmission rate.
17	red full square	On TCAS II display, a Resolution Advisory (RA) is represented by a solid red square symbol.
18	25 hours for flight data, 30 minutes for cockpit voices and warnings horns.	ICAO Annex 6 mandates FDR recording duration of at least 25 hours, and traditional CVR minimum of 30 mins (2 hrs for newer).
19	as far to the rear as practicable	Flight recorders must be installed in the tail section/rear fuselage to maximize survivability in crash impacts.
20	take-off distance equals accelerate-stop distance.	A balanced field length exists when Take-Off Distance Required (TODR) equals Accelerate-Stop Distance Required (ASDR).
21	Climbing FL140, expediting through FL110.	Standard Doc 9432 readback requires full level readback along with expediting constraint parameters.
22	Condition refers to aircraft position, not movement.	Conditional clearances must identify aircraft type and position/movement unambiguously (e.g., 'after the landing B737...').
23	Cease transmission immediately, continue to monitor.	When instructed 'Stop transmitting', pilot must immediately stop RF transmissions and maintain listening watch on frequency.
24	'Say again' is the only ICAO-approved phrase.	ICAO Doc 9432 strictly prohibits 'Request repeat' or 'Repeat'; standard phraseology is 'Say again'.
25	'Over and out.'	Combining 'Over' (inviting reply) and 'Out' (ending communication) is contradictory and strictly prohibited in aviation RT.
26	'Say again all after altitude.'	To request missing clearance portions, use standard phraseology 'Say again all after [word]'.
27	Turn at pilot-selected rate.	Instruction 'Orbit right' implies executing a continuous 360-degree turn to the right at rate-one or standard bank.
28	'Climb to 7,000 ft QNH 1012'	Safety-critical instructions (level assignments, altimeter settings) require verbatim readback; 'Roger' is prohibited.

29	'Negative, I say again...'	When pilot reads back incorrectly, controller corrects using 'Negative, I say again...' followed by correct version.
30	Incorrect must use 'Ready for departure'	At controlled aerodromes, word 'takeoff' is strictly reserved for actual clearance. Pilot must say 'Ready for departure'.
31	Expedite entering runway, rolling takeoff without stopping	Cleared for immediate takeoff requires pilot to line up and depart immediately without stopping on runway.
32	'Standby for my clearance.'	'Standby' instructs pilot to wait while keeping clearance valid and pending execution.
33	Transmit each phrase twice	Phrase 'Words twice' means 'Every word/phrase in this transmission will be spoken twice' to assist under difficult reception.
34	The controller is revising the original instruction	'Correction' followed by revised command indicates controller is modifying previous erroneous instruction.
35	ATC may instruct 'Stop transmitting'	A stuck microphone blocks frequency; controller issues 'Stop transmitting' and attempts selective calling or carrier override.
36	Below 1500 ft AGL	TCAS RA guidance is inhibited at low altitudes (RAs inhibited below 1,000 ft AGL, climb RAs below 1,500 ft AGL).
37	TCAS override ATC	Pilots MUST follow TCAS RA immediately, overriding conflicting ATC vector/level instructions for safety.
38	Mode C altitude + Mode S identity	TCAS II coordination between two aircraft relies on Mode S transponder data exchange containing altitude and identity.
39	TCAS sees horizontal conflict	A 'Don't Climb' RA is issued if vertical separation cannot be assured due to closing geometry detected by TCAS.
40	TCAS detects intruder following same RA	TCAS RA reversal occurs when TCAS senses intruder is not complying or complementary vertical maneuver fails to clear conflict.
41	VOR	The area directly above a VOR station ground transmitter where signals cannot be received is called Cone of Confusion / Silence.
42	Space Wave	Long-range HF communications rely on ionospheric skywave reflections (ionospheric skywave / surface waves).
43	Approximately 123 NM	VHF Line-of-Sight distance formula: $\text{Range (NM)} = 1.23 \times \sqrt{\text{Height (in feet)}}$. For 10,000 ft: $1.23 \times 100 = 123 \text{ NM}$.

44	Odd decimals (e.g., 108.1, 108.15)	ILS Localizer frequencies are paired in 108.10 - 111.95 MHz band using odd-numbered first decimal places.
45	243.0 MHz	Military emergency distress frequency is 243.0 MHz (UHF band), corresponding to VHF Guard 121.5 MHz.
46	It sends unsolicited identity + capability data	Mode S squitter sends spontaneous periodic broadcasts enabling TCAS passive detection of surrounding aircraft.
47	Providing ionospheric delay model	SBAS (WAAS/GAGAN) transmits real-time ionospheric correction grid models drastically improving GNSS vertical accuracy.
48	Scalloping due ground reflection	Multipath reflection of VOR signal from terrain/buildings causes rapid periodic course fluctuation known as scalloping.
49	Low look angle to GEO	Geostationary satellite signals suffer severe attenuation and masking at high latitudes due to low antenna look angles.
50	Clear path where storm tops obscure returns	Radar antenna tilted excessively upward shoots above lower precipitation, giving false impression of clear path.

RTR DAILY 3 - ANSWER KEY

Q. No.	Correct Option & Answer	Key Technical / Regulatory Rationale
1	State 'Unable conditional clearance, traffic not in sight.'	Conditional clearances are prohibited unless pilot visually identifies the reference aircraft.
2	'Stop transmitting' vs 'Stop communications'	'Stop transmitting' instructs immediate RF silence on current frequency, whereas 'Stop communications' is non-standard.
3	'Unable due terrain.'	Pilots must inform ATC immediately if complying with level clearance violates terrain safety using 'Unable' with reason.
4	Read back the entire last transmission.	'Acknowledge last transmission' requires confirmation that message was received and understood (normally full readback).
5	'Stopping climb'	Using verb form 'Stopping climb' clearly states current pilot action without sounding like an ATC instruction.
6	Repeat your message twice.	When controller requests 'Words twice', sender must transmit each

		word or phrase twice.
7	'Traffic not in sight, unable cross.'	Conditional clearance to cross behind landing traffic cannot be accepted if traffic is in IMC or not visually sighted.
8	Using 'Roger' instead of readback for heading.	Omitting numerical readbacks for heading/level using 'Roger' strips controller capability to spot misunderstandings.
9	'Confirm clearance was for [callsign]?'	If doubt exists whether clearance was meant for flight crew, pilot must query ATC directly using 'Confirm...?'
10	'Leaving controlled airspace now'	Immediate safety compliance is paramount when ordered out of controlled airspace; pilot acknowledges and executes.
11	Query both: 'Confirm instruction for [callsign]?'	Conflicting instructions from different ATS sectors must be clarified immediately before maneuvering.
12	'Say again slower.'	Standard ICAO phraseology to request reduced speech rate from controller is 'Say again slower' or 'Speak slower'.
13	Repeat back: 'Confirm 118.17 for [callsign]?'	If frequency digit ambiguity occurs, pilot must verify with ATC prior to switching frequencies.
14	When ready	Phrase 'When ready' delegates timing of climb/descent execution to pilot's operational discretion.
15	Stabilized at 9000 ft	'Report reaching altitude' requires notification only when aircraft is level and stabilized at assigned level.
16	'Unable, TCAS RA.'	During TCAS RA execution, pilot must inform ATC immediately with 'Unable, TCAS RA' and ignore conflicting ATC commands.
17	'Roger.'	Using 'Roger' as readback for heading or level control instruction violates ICAO mandatory readback rules.
18	Cease only on that frequency, continue monitoring	'Stop transmitting' applies specifically to the operating frequency; pilot continues monitoring for instructions.
19	Before giving corrected phrase	Word 'Correction' must precede corrected phrase to signal erroneous information replacement.
20	'Say again all after...'	Standard phraseology to request retransmission of obscured audio is 'Say again all after [word]'.

21	Annex 10 Vol II interoperability requirements	ICAO Annex 10 dictates technical standardizations across signal formats, Mode S protocols, and TCAS collision avoidance.
22	1030/1090 MHz	Secondary Surveillance Radar uses 1030 MHz (ground interrogation) and 1090 MHz (aircraft transponder reply).
23	1030 MHz interference saturates the channel	High RF traffic on 1030 MHz causes transponder receiver suppression and loss of TCAS tracking capability.
24	Identity + position + velocity	ADS-B OUT periodically broadcasts GNSS position, ground velocity, pressure altitude, and Mode S flight identity.
25	Intermittent loss of altitude reporting	Structural shadowing of transponder antenna during high bank angle turns causes intermittent signal loss.
26	'Deviation due [alert], returning when able.'	Standard phraseology when deviating for onboard safety warnings (e.g., EGPWS) is informing ATC of deviation and return.
27	Multilateration + ADS-B + Mode-S coordination	High-density terminal surveillance combines MLAT, ADS-B, and Mode S to maintain separation.
28	Incorrect baro setting inside aircraft	Mode S transponder transmits uncorrected pressure altitude (1013.25 hPa); incorrect baro setting on altimeter affects pilot display, causing mismatch.
29	Low satellite elevation angle	Low elevation angles to geostationary satellites cause severe shadowing and signal loss during simultaneous HF/SATCOM operation.
30	ADS-B OUT	ADS-B OUT relies heavily on Annex 10 standards for system integrity, latency, and position accuracy metrics.
31	Self-ground and inform licensing authority	Under ICAO Annex 1 medical provisions, pilots who suffer medical incapacity must cease flying and notify authority.
32	With every medical	In Indian regulations (DGCA), RT license validity checks and proficiency validations are checked during medical renewals / renewals.
33	Follow the state's published comm failure procedure	During communication failure, PIC must follow ICAO Annex 2 / State published radio failure procedures.
34	Squawk 7600, follow loss procedures	Standard IFR communication failure requires selecting transponder Code 7600 and adhering to published loss procedures.

35	RTR(A) or equivalent	Radio Telephony Restricted (Aeronautical) license grants legal privilege to operate aircraft station radios.
36	Any safety hazard including RT failure	DGCA CAR mandates mandatory reporting of any incident, RT error, or safety hazard affecting flight safety.
37	Authority gradient + workload + frequency congestion	Operational RT effectiveness during emergencies is governed by CRM, cockpit workload, and frequency congestion.
38	Operating any aircraft requiring radio communication	ICAO Annex 1 mandates carrying a valid radio station operator license on any flight requiring radio equipment.
39	Annex 1	Self-assessment of fitness and operational competency standards stem from ICAO Annex 1 Personnel Licensing.
40	Immediate correction, concise, no apology	When an RT error occurs, pilot must immediately transmit 'Correction', give correct data concisely without lengthy chatter.
41	Ignore ATC, stabilize, then inform 'Unable, GPWS alert.'	EGPWS terrain/glideslope alerts take priority over ATC instructions; pilot complies with GPWS and informs ATC.
42	Follow TCAS RA notify ATC	TCAS RA mandates immediate compliance over conflicting ATC commands; inform ATC as soon as workload permits.
43	GPS antenna shading	Loss of GPS satellite tracking due to aircraft attitude shading triggers loss of primary position integrity prior to RAIM alert.
44	GPWS Level off Inform ATC Request new clearance	Safety warnings require immediate level-off/climb, followed by informing ATC and obtaining revised clearance.
45	Mode S reflection or 'ghosting' from multilateration	RF reflections from ground structures can create false transponder targets ('ghost' intruders) on TCAS displays.
46	Predictive terrain caution before loss of guidance	FMS database discrepancies during RNAV approaches trigger predictive terrain warnings due to position mismatch.
47	Troubleshoot VHF first	When VHF comms fail while SELCAL alerts, pilot prioritizes restoring primary VHF line-of-sight communication.
48	Say 'Unable due weather' and offer alternate	Pilot retains ultimate authority for terrain and weather avoidance; decline vector with 'Unable due weather' and request heading.
49	Terrain masking + 1090 MHz interference	Physical terrain blocking plus extreme RF congestion on 1090 MHz degrades both PSR skin-return and SSR/ADS-B reception.

50	Reject turn, inform ATC, comply with EGPWS	EGPWS warning takes absolute priority over ATC vectoring; pilot obeys EGPWS escape guidance and notifies ATC.
----	---	---

RTR DAILY 4 - ANSWER KEY

Q. No.	Correct Option & Answer	Key Technical / Regulatory Rationale
1	c) The clearance cannot be issued immediately due to traffic	Phrase instructs aircraft to stay outside controlled airspace until specified time when ATC can provide joining clearance.
2	The track of the ATS route (left or right-hand pattern)	En-route holding patterns are aligned with inbound track of ATS route unless specified otherwise by ATC.
3	b) The parameters for when and what data the aircraft should report	ADS-C contract specifies reporting triggers (periodic, event, demand) established between ATC and aircraft avionics.
4	c) ADS-C-based procedural control.	Oceanic separation reductions (e.g. 23 NM / 30 NM) are enabled by ADS-C position reports and CPDLC link.
5	c) Exchange routine clearances and messages via data link	CPDLC allows direct digital data exchange of routine clearances, frequency changes, and reports between pilot and controller.
6	b) MAYDAY, MAYDAY, MAYDAY	Fuel emergency threatening imminent danger requires declaring distress using standard prefix 'MAYDAY MAYDAY MAYDAY'.
7	a) Unlawful seizure (hijack)	Transponder Code 7500 is internationally designated for unlawful interference / hijacking.
8	c) Immediately acknowledge the distress message	First station hearing a distress message must immediately acknowledge receipt unless handled by a ground station.
9	b) A protected medical transport under the Geneva Convention	'PAN PAN MEDICAL' identifies medical transports protected under Geneva Conventions.
10	a) 'TRANSMITTING BLIND DUE TO RECEIVER FAILURE'	If receiver fails, pilot transmits intention blind using prefix 'TRANSMITTING BLIND DUE TO RECEIVER FAILURE'.
11	b) Continue on the last assigned route and altitude	Under IFR communication failure in IMC, pilot maintains last assigned route and altitude per standard loss comm procedures.
12	a) Runway Condition Code (RWYCC)	Global Reporting Format (GRF) uses Runway Condition Code (RWYCC

		0 to 6) to report runway surface conditions.
13	c) Poor	RWYCC 1 corresponds to pilot reported braking action of 'POOR'.
14	The presence of snow, ice, or slush on runways	SNOWTAM is a specialized NOTAM series notifying hazardous runway conditions caused by snow, ice, or slush.
15	b) Alert the flight crew of an incoming message without continuous listening	SELCAL alerts flight crew visually/audibly when ground station calls them, removing need for continuous listening watch.
16	b) Alert the flight crew of an incoming message without continuous listening	Repeated question in set 4; SELCAL primary function is alerting crew without continuous headphone monitoring.
17	c) Four letters (from A-S, excluding I, N, O)	SELCAL codes consist of 4 letters selected from A through S (excluding letters I, N, and O) forming two tone pairs.
18	a) Above 10,000 feet AGL and clear of populated areas	Fuel dumping is normally conducted at or above 10,000 ft AGL over designated uninhabited areas or water bodies.
19	b) Severe turbulence is preventing pilot from maintaining the required height-keeping accuracy	Reporting unable RVSM due turbulence alerts ATC that aircraft cannot maintain +/- 65 ft height-keeping precision.
20	a) Follow the RA immediately, ignoring any conflicting ATC instruction	Pilots MUST comply immediately with ACAS RA advisories, overriding conflicting ATC vector or level instructions.
21	c) 'TCAS RA'	Standard ICAO phraseology when initiating maneuver for TCAS RA is '[callsign] TCAS RA'.
22	a) 1,000 feet	In Reduced Vertical Separation Minimum (RVSM) airspace (FL290-FL410), standard vertical separation is 1,000 ft.
23	b) Lacks RVSM approval or is temporarily non-compliant	Non-RVSM approved status indicates aircraft equipment or operator lacks certification to fly in RVSM airspace.
24	c) Mid-air collisions and wake turbulence	SLOP (Strategic Lateral Offset Procedure) allows aircraft to fly 1 or 2 NM right of centerline to reduce collision & wake turbulence risk.
25	b) 121.5 MHz (or backup 123.45 MHz).	In remote/oceanic areas, weather deviations without ATC clearance require broadcasting on Guard 121.5 MHz and air-to-air 123.45 MHz.
26	b) Exchange operational information.	Inter-pilot air-to-air frequency 123.45 MHz is designated for exchanging operational and safety information over remote areas.

27	c) TRANSMISSION BLOCKED BY (call sign of the station blocking), SAY AGAIN	When transmission is blocked by simultaneous carrier interference, pilot states 'TRANSMISSION BLOCKED BY...'
28	a) 7	In radar environment under ICAO loss of comm rules, aircraft maintains last assigned speed/level for 7 minutes before resuming flight plan.
29	b) An odd flight level (e.g., FL 250).	Semi-circular cruising level rule: Magnetic track 000-179 deg uses ODD flight levels (FL250, FL270, etc.).
30	c) MAYDAY, MAYDAY, MAYDAY	Standard radiotelephony distress signal is 'MAYDAY' repeated three times.
31	b) When making an initial call from an aircraft to a ground station you must state the ground station name and suffix first and then your full call-sign.	Initial call structure: [Ground Station Call Sign] + [Aircraft Full Call Sign].
32	a) VIDP.	Delhi Indira Gandhi International Airport ICAO location indicator is VIDP.
33	b) At least two (one automatic fixed, one portable),	DGCA CAR requires commercial passenger aircraft to carry at least two ELTs (one automatic fixed ELT plus portable ELTs).
34	c) 1000 feet.	Below FL290, minimum vertical separation between opposite-direction IFR flights is 1,000 ft.
35	a) Runway in use, altimeter settings, SSR codes, level instructions, heading and speed instructions	Mandatory readback items include runway, altimeter, squawk, level, heading, speed, and hold short clearances.
36	c) Mute background noise	Squelch control on VHF radio receiver silences background atmospheric noise when no RF carrier signal is present.
37	a) HEADING 225 AT THREE THOUSAND FIVE HUNDRED FEET	Headings are spoken as three digits ('HEADING 225'), altitude in thousands/hundreds ('THREE THOUSAND FIVE HUNDRED').
38	a) Pilot mistakenly set FL100 on autopilot, influenced by ATC's phrase 'one hundred.'	Connecting heading 'one hundred' next to level command caused confusion, leading to strict requirement for clear word separation.
39	a) 3 MHz to 30 MHz	VHF band is 30 MHz to 300 MHz (aeronautical VHF 118-137 MHz). Option (a) describes HF band, but in standard questions VHF line-of-sight context is evaluated.

40	a) 120 words per minute	Recommended maximum speech rate in RT communications is 120 words per minute.
41	b) SEVAN	ICAO phonetic pronunciation for numeral 7 is SEVAN, and for 1 is WUN. (Evaluated per ICAO standardized phonetics table).
42	a) Vertical separation from a specific aircraft.	Phraseology 'MAINTAIN AT LEAST... FEET ABOVE/BELOW...' is used by ATC to maintain vertical visual/procedural separation from specified target.
43	c) GOING AROUND.	Mandatory phraseology when executing a missed approach at aerodrome is 'GOING AROUND'.
44	b) Name of the DME station.	DME ARC descriptions must specify arc distance, direction, and specific DME station facility identifier.
45	a) I,N, and O.	SELCAL system excludes letters I, N, and O to prevent visual confusion with numbers 1 and 0.
46	a) A number that summarizes the braking action	RWYCC (0 to 6) provides standardized operational assessment of runway surface braking performance.
47	c) Medium	RWYCC 3 corresponds to pilot reported braking action of 'MEDIUM'.
48	b) Millimeters (mm).	Contamination depth sequence in SNOWTAM / runway condition reports is reported in millimeters (mm).
49	a) CORRECTION.	Standard phraseology to indicate error correction during transmission is 'CORRECTION'.
50	a) Right	If aircraft is left of precision approach centerline, controller instructs turn right to intercept localizer/glidepath.
51	b) Current (Ampere).	In Ohm's Law ($V = I \times R$), 'I' represents electrical current measured in Amperes.