



Input Validation

Annotations for Validation

S. No.	Annotation	Description
1	@NotNull	Ensures that the annotated field is not null.
2	@NotEmpty	Ensures that the annotated field is not null and its size/length is greater than zero. (For collections, arrays, and strings)
3	@NotBlank	Ensures that the annotated string is not null and its trimmed length is greater than zero.
4	@Size	Validates that the annotated element's size falls within the specified range.
5	@Max	Ensures that the annotated element is a number with a value no greater than the specified maximum.
6	@Email	Validates that the annotated string is a valid email address.
7	@Pattern	Validates that the annotated string matches the specified regular expression.
8	@Positive	Ensures that the annotated element is a positive number (greater than zero).
9	@PositiveOrZero	Ensures that the annotated element is a positive number or zero.
10	@Negative	Ensures that the annotated element is a negative number (less than zero).
11	@NegativeOrZero	Ensures that the annotated element is a negative number or zero.
12	@Past	Ensures that the annotated date or calendar value is in the past.
13	@PastOrPresent	Ensures that the annotated date or calendar value is in the past or present.

14	<code>@Future</code>	Ensures that the annotated date or calendar value is in the future.
15	<code>@FutureOrPresent</code>	Ensures that the annotated date or calendar value is in the future or present.
16	<code>@Digits</code>	Ensures that the annotated number has up to a specified number of integer and fraction digits.
17	<code>@DecimalMin</code>	Ensures that the annotated element is a number with a value no less than the specified minimum, allowing for decimal points.
18	<code>@DecimalMax</code>	Ensures that the annotated element is a number with a value no greater than the specified maximum, allowing for decimal points.
19	<code>@AssertTrue</code>	Ensures that the annotated boolean field is true.
20	<code>@AssertFalse</code>	Ensures that the annotated boolean field is false.
21	<code>@Valid</code>	Validates the associated object recursively (applies bean validation to nested objects).

Handling Validation Exceptions

- `MethodArgumentNotValidException` is thrown by the `@Valid` validation
- You can get a list of all the errors from the `bindingResult` of this exception
- You can use this list to return some useful error messages as the API response

In order to make use of the above mentioned pre-defined validators we should be adding a new dependency that allows us to work on all of them. Along with that in the end we will also look at how can I make a **custom** validator.

```
<dependency>
  <groupId>org.springframework.boot</groupId>
```

```
<artifactId>spring-boot-starter-validation</artifactId>
</dependency>
```

At the controller level where information is accepted as part of request body from user we must provide a Validator so that the object recognises when to run the validation.

```
@PostMapping
public ResponseEntity<EmployeeDTO> createNewEmployee(
    @RequestBody @Valid EmployeeDTO inputEmployee
) {
    EmployeeDTO savedEmployee = employeeService.createNewEmployee(inputEmployee);
    return new ResponseEntity<>(savedEmployee, HttpStatus.CREATED);
}
```

At the DTO level which we send back as POJO to the user back in response and also use to accept info from them is where we apply these pre-defined (or) custom validators.

String validators

```
public class EmployeeDTO {
    private long id;

    // checks for presence of field
    @NotNull(message = "Required field in employee: name")
    private String name;
}
```

```
public class EmployeeDTO {
    private long id;

    // checks for not null and length > 0
```

```

    @NotEmpty(message = "Name of the employee cannot be empty")
    private String name;
}

```

```

public class EmployeeDTO {
    private long id;

    // checks for not null and trimmed length > 0
    @NotBlank(message = "Name of the employee cannot be blank")
    @Size(min = 3, max = 10, message = "Number of characters in name should be in the range: [3, 10]")
    private String name;
}

```

Regex Validator

```

public class EmployeeDTO {
    @Pattern(regexp = "^(ADMIN|USER)$", message = "Role of Employee cannot be USER or ADMIN")
    @NotBlank(message = "Role of the employee cannot be blank")
    private String role; // ADMIN, USER
}

```

Email Validators

```

public class EmployeeDTO {
    @NotBlank(message = "Email of the employee cannot be blank")
    @Email(message = "Email should be in valid format")
    private String email;
}

```

Number Validators

```

public class EmployeeDTO {
    @NotNull(message = "Salary of the employee cannot be blank")
    @Positive(message = "Salary of the employee should be positive")
}

```

```

    @Digits(integer = 6, fraction = 2, message = "Salary of the employee can be in the form X,XX,XXX.YY")
    @DecimalMax(value = "100000.99")
    @DecimalMin(value = "100.50")
    private Double salary;
}

```

Date Validator

```

public class EmployeeDTO {
    @PastOrPresent(message = "Date of joining of the employee cannot be in the future")
    private LocalDate dateOfJoining;
}

```

Boolean Validator

```

public class EmployeeDTO {
    @AssertTrue(message = "Employee should be active")
    @JsonProperty("isActive")
    private boolean active;
}

```

Custom Validator Defined by Developer

```

@Retention(RetentionPolicy.RUNTIME)
@Target({ElementType.FIELD, ElementType.PARAMETER})
@Constraint(
    validatedBy = {EmployeeRoleValidator.class}
)
public @interface EmployeeRoleValidation {
    String message() default "Role of Employee can be USER or ADMIN";

    Class<?>[] groups() default {};
}

```

```
Class<? extends Payload>[] payload() default {};  
}
```

```
public class EmployeeRoleValidator implements ConstraintValidator<EmployeeRoleValidation, String> {  
  
    @Override  
    public boolean isValid(String inputRole, ConstraintValidatorContext constraintValidatorContext) {  
        List<String> roles = List.of("USER", "ADMIN");  
        return roles.contains(inputRole);  
    }  
  
}
```

Once we define that, we have to make use of the validator at the DTO level, which would result in something like below

```
public class EmployeeDTO {  
    @NotBlank(message = "Role of the employee cannot be blank")  
    @EmployeeRoleValidation  
    private String role; // ADMIN, USER  
}
```

Full Example Snippet

```
@Getter  
@Setter  
@AllArgsConstructor  
@NoArgsConstructor  
public class EmployeeDTO {  
    private long id;  
  
    // @NotNull(message = "Required field in employee: name") → checks f
```

or presence of field

```
// @NotEmpty(message = "Name of the employee cannot be empty") →  
checks for not null and length > 0
```

```
@NotBlank(message = "Name of the employee cannot be blank") // checks  
for not null and trimmed length > 0
```

```
@Size(min = 3, max = 10, message = "Number of characters in name should  
be in the range: [3, 10]")
```

```
private String name;
```

```
@NotBlank(message = "Email of the employee cannot be blank")
```

```
@Email(message = "Email should be in valid format")
```

```
private String email;
```

```
@NotNull(message = "Age of the employee cannot be blank")
```

```
@Max(value = 80, message = "Age of Employee cannot be greater than  
80")
```

```
@Min(value = 18, message = "Age of Employee cannot be less than 18")
```

```
private Integer age;
```

```
// @Pattern(regexp = "^(ADMIN|USER)$", message = "Role of Employee  
can be USER or ADMIN")
```

```
@NotBlank(message = "Role of the employee cannot be blank")
```

```
@EmployeeRoleValidation
```

```
private String role; // ADMIN, USER
```

```
@NotNull(message = "Salary of the employee cannot be blank")
```

```
@Positive(message = "Salary of the employee should be positive")
```

```
@Digits(integer = 6, fraction = 2, message = "Salary of the employee can  
be in the form X,XX,XXX.YY")
```

```
@DecimalMax(value = "100000.99")
```

```
@DecimalMin(value = "100.50")
```

```
private Double salary;
```

```
@PastOrPresent(message = "Date of joining of the employee cannot be in  
the future")
```

```
private LocalDate dateOfJoining;
```

```
@AssertTrue(message = "Employee should be active")
```

```
@JsonProperty("isActive")  
private boolean active;  
}
```