

Huawei AI Certification Training

HCIA-AI

ModelArts

Experiment Guide

ISSUE:3.0



HUAWEI TECHNOLOGIES CO., LTD.

Copyright © Huawei Technologies Co., Ltd. 2020. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions



and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address: Huawei Industrial Base Bantian, Longgang Shenzhen 518129
People's Republic of China

Website: <http://e.huawei.com>

Huawei Certificate System

Huawei Certification follows the "platform + ecosystem" development strategy, which is a new collaborative architecture of ICT infrastructure based on "Cloud-Pipe-Terminal". Huawei has set up a complete certification system consisting of three categories: ICT infrastructure certification, Platform and Service certification and ICT vertical certification, and grants Huawei certification the only all-range technical certification in the industry.

Huawei offers three levels of certification: Huawei Certified ICT Associate (HCIA), Huawei Certified ICT Professional (HCIP), and Huawei Certified ICT Expert (HCIE).

HCIA-AI V3.0 aims to train and certify engineers who are capable of designing and developing AI products and solutions using algorithms such as machine learning and deep learning.

HCIA-AI V3.0 certification demonstrates that: You know the development history of AI, Huawei Ascend AI system and full-stack all-scenario AI strategies, and master traditional machine learning and deep learning algorithms; you can use the TensorFlow and MindSpore development frameworks to build, train, and deploy neural networks; you are competent for sales, marketing, product manager, project management, and technical support positions in the AI field.

Huawei Certification Portfolio



Huawei Certification



About This Document

Overview

This document is applicable to the candidates who are preparing for the HCIA-AI exam and the readers who want to understand the AI programming basics. After learning this guide, you will be able to perform basic AI programming with ModelArts.

Description

This guide contains two experiments, which are based on how to use ModelArts. It is hoped that trainees or readers can get started with deep learning and have the basic programming capability by ModelArts.

If you are in an area where Huawei Cloud and ModelArts service is not accessible, this chapter can be ignored, it is not necessary for passing the HCIA-AI V3.0 certification.

Background Knowledge Required

To fully understand this course, the readers should have basic Python programming capabilities, knowledge of data structures and deep learning algorithms.

Experiment Environment Overview

Huawei Cloud and ModelArts

Contents

About This Document	3
Overview	3
Description	3
Background Knowledge Required	3
Experiment Environment Overview	3
1 ExeML.....	5
1.1 Introduction.....	5
1.1.1 About This Experiment.....	5
1.1.2 Objectives	5
1.1.3 Experiment Environment Overview.....	5
1.2 Flower Recognition Application	7
1.2.1 Creating a Project	8
1.2.2 Labeling Data	9
1.2.3 Training a Model.....	11
1.2.4 Deploying a Service and Performing Prediction	12
2 Image Classification	13
2.1 Introduction.....	13
2.1.1 About This Experiment.....	13
2.1.2 Objectives	13
2.2 Procedure	13
2.2.1 Create a Notebook	13
2.2.2 Open Notebook and Coding.....	15
2.3 Experiment Code	16
2.3.1 Introducing Dependencies.....	16
2.3.2 Data Preprocessing.....	16
2.3.3 Model Creation	19
2.3.4 Model Training.....	20
2.3.5 Model Evaluation	21
2.4 Summary	22

1 ExeML

1.1 Introduction

1.1.1 About This Experiment

ExeML, a service provided by ModelArts, is the process of automating model design, parameter tuning and training, and model compression and deployment with the labeled data. The process is free of coding and does not require your experience in model development, enabling you to start from scratch. This lab guides you through image classification, object detection, and predictive analytics scenarios.

Image classification is based on image content labeling. An image classification model can predict a label corresponding to an image, and is applicable to scenarios in which image classes are obvious.

1.1.2 Objectives

This lab uses three specific examples to help you quickly create image classification, object detection, and predictive analytics models. The flower recognition experiment recognizes flower classes in images.

1.1.3 Experiment Environment Overview

If you are a first-time ModelArts user, you need to add an access key to authorize ModelArts jobs to access Object Storage Service (OBS) on Huawei Cloud. You cannot create any jobs without an access key. The procedure is as follows:

- Generating an access key: On the management console, move your cursor over your username, and choose **Basic Information > Manage > My Credentials > Access Keys to create an access key**. After the access key is created, the AK/SK file will be downloaded to your local computer. The following picture shows the steps.





Figure 1-1 Huawei Cloud Homepage

Basic Information



Basic Information

Account Name
Account Type
Enterprise Name
Full Name
Designation
Mobile Number
Email Address
Password
Authentication Status
Security Credentials

Save

Edit

Edit

Edit

Edit

View

Manage

Contact Information

The following information will be used to contact you if necessary.

Country/Region
Contact Address
Contact Details

Hong Kong SAR, China

No data available.

No data available.

Edit

Edit

Business Information

The following information will help us provide better services.


Industry

--Select--

Save

Figure 1-2 Basic Information Page

My Credentials



Change

Username

User ID

Account Name

Account ID

Email Address

Mobile Number

Password Strength

Login Authentication

Virtual MFA Device

Projects

Access Keys

Figure 1-3 My Credentials Page

+

Create Access Key

You can create 0 more access keys.


Access Key ID

⌵

Description

Figure 1-4 Create Access Key

- Configuring global settings for ModelArts: Go to the **Settings** page of ModelArts, and enter the AK and SK information recorded in the downloaded AK/SK file to authorize ModelArts modules to access OBS.


Figure 1-5 ModelArts Settings Page

1.2 Flower Recognition Application

The ExeML page consists of two parts. The upper part lists the supported ExeML project types. You can click Create Project to create an ExeML project. The created ExeML projects are listed in the lower part of the page. You can filter the projects by type or search for a project by entering its name in the search box and clicking.

The procedure for using ExeML is as follows:

- Creating a project: To use ModelArts ExeML, create an ExeML project first.
- Labeling data: Upload images and label them by class.
- Training a model: After data labeling is completed, you can start model training.

- Deploying a service and performing prediction: Deploy the trained model as a service and perform online prediction.

1.2.1 Creating a Project

Step 1 Create a project.

On the **ExeML** page, click **Create Project** in **Image Classification**. The **Create Image Classification Project** page is displayed.




Figure 1-6 ModelArts ExeML




Figure 1-7 Create Image Classification Project

Parameters:

- **Billing Mode:** Pay-per-use by default
- **Name:** The value can be modified as required.
- **Description:** The value can be modified as required.
- **Dataset Name:** The value can be modified as required.
- **Input Dataset Path:** Select an OBS path for storing the dataset to be trained. Create an empty folder on OBS first (Click the bucket name to enter the bucket. Then, click **Create Folder**, enter a folder name, and click **OK**). Select the newly created OBS folder as the training data path. Alternatively, you can import required data to OBS in advance. In this example, the data is uploaded to the **/modelarts-demo/auto-learning/image-class** folder.

For details about how to upload data, see: https://support.huaweicloud.com/en-us/modelarts_faq/modelarts_05_0013.html.

To obtain the source data, visit: <https://data-certification.obs.cn-east-2.myhuaweicloud.com/ENG/HCIA-AI/V3.0/modelarts-demo.rar>

- **Output Dataset Path:** Select an OBS path for storing the dataset to be exported. Create an empty folder on OBS, the method of creation is the same as **Input Dataset Path**.

Step 2 Confirm the project creation.

Click **Create Project**. The ExeML project is created.

1.2.2 Labeling Data

Step 1 Upload images.

After an ExeML project is created, the **Label Data** page is automatically displayed.

Click **Add Image** to add images in batches. The dataset path is **modelarts-datasets-and-source-code/ExeML/flower-recognition-application/training-dataset**. If the images have been uploaded to OBS, click **Synchronize Data Source** to synchronize the images to ModelArts.




Figure 1-8 Upload Images

 **NOTE**

- The images to be trained must be classified into at least two classes, and each class must contain at least five images. That is, at least two labels are available and the number of images for each label is not fewer than five.
- You can add multiple labels to an image.

Step 2 Label the images.

In area 1, click **Unlabeled**, and select one or more images to be labeled in sequence, or select **Select Current Page** in the upper right corner to select all images on the current page. In area 2, input a label or select an existing label and press **Enter** to add the label to the images. Then, click **OK**. The selected images are labeled.







Figure 1-9 Label the Images

Step 3 Delete or modify a label in one image.

Click **Labeled** in area 1, and then click an image. To modify a label, click  on the right of the label in area 2, enter a new label on the displayed dialog box, and click . To delete a label, click  on the right of the label in area 2. See Figure 1-10.













All Labels 5		
Label	Count	Operati
daisy	12	 
tulips	7	 
rose	7	 
sunflower	6	 
dandelion	7	 

Figure 1-10 Delete or Modify Label in One Image

Step 4 Delete or modify a label in multiple images.

In area 2, click the label to be modified or deleted, and click  on the right of the label to rename it, or click  to delete it from multiple images. In the dialog box that is displayed, select **Delete label** or **Delete label and images that only contain this label**.




Figure 1-11 Delete or Modify a Label in Multiple Images

1.2.3 Training a Model

After labeling the images, you can train an image classification model. Set the training parameters first and then start automatic training of the model. Images to be trained must be classified into at least two classes, and each class must contain at least five images. Therefore, before training, ensure that the labeled images meet the requirements. Otherwise, the **Train** button is unavailable.

Step 1 Set related parameters.

You can retain the default values for the parameters, or modify Max Training Duration (h) and enable Advanced Settings to set the inference duration. Figure 1-12 shows the training settings.

Training Configuration

Max Training Duration (h) ?

1

Advanced Settings

☒

Max Inference Duration (ms) ?

500

Incremental Training Version ?

None

Train

Figure 1-12 Training Configuration

Parameters:

- Max Training Duration (h):** If the training process is not completed within the maximum training duration, it is forcibly stopped. You are advised to enter a larger value to prevent forcible stop during training.

- **Max Inference Duration (ms):** The time required for inferring a single image is proportional to the complexity of the model. Generally, the shorter the inference time, the simpler the selected model and the faster the training speed. However, the precision may be affected.

Step 2 Train a model.

After setting the parameters, click **Train**. After training is completed, you can view the training result on the **Train Model** tab page.

1.2.4 Deploying a Service and Performing Prediction

Step 1 Deploy the model as a service.

After the model training is completed, you can deploy a version with the ideal precision and in the **Successful** status as a service. To do so, click **Deploy** in the **Version Manager** pane of the **Train Model** tab page. See Figure 1-13. After the deployment is successful, you can choose **Service Deployment > Real-Time Services** to view the deployed service.




Figure 1-13 Train Model

Step 2 Test the service.

After the model is deployed as a service, you can upload an image to test the service. The path of the test data is **modelarts-datasets-and-source-code/ExeML/flower-recognition-application/test-data/daisy.jpg**.

On the **Deploy Service** tab page, click the **Upload** button to select the test image. After the image is uploaded successfully, click **Predict**. The prediction result is displayed in the right pane. See Figure 1-14. Five classes of labels are added during data labeling: tulip, daisy, sunflower, rose, and dandelion. The test image contains a daisy. In the prediction result, "daisy" gets the highest score, that is, the classification result is "daisy".




Figure 1-14 Deploy Service

2 Image Classification

2.1 Introduction

2.1.1 About This Experiment

This experiment is about a basic task in computer vision, that is image recognition. This experiment has been completed in chapter 4. Now, we will do this experiment on ModelArts with GPU.

2.1.2 Objectives

Upon completion of this task, you will be able to:

- Know how to use ModelArts to develop your own model
- Understand the advantages of deep neural network training with GPU acceleration

2.2 Procedure

2.2.1 Create a Notebook

Step 1 Create a Notebook

Open the **ModelArts Homepage** and select **DevEnviron** to create Notebook.




Figure 2-1 ModelArts Homepage

Click the Create button to Create the Notebook environment.





Figure 2-2 Create Notebook

Step 2 Configuration

Clicking the Create button, then you got the configuration page. Here are some parameters, explained as follows:

- **Name:** user-defined.
- **Auto Stop:** user-defined, it is recommended to estimate the usage time in advance.
- **Work Environment:** Here, TF2.1 is fixed, as shown in the **figure 2-3**.
- **Instance Flavor:** GPU: 1xV100 is recommended.



The image shows the 'Create Notebook' configuration page. It includes sections for Billing Mode (Pay-per-use), Name (notebook-ceshi), Description, Auto Stop (enabled), Work Environment (TF-2.1.0&Pytorch-1.4.0-python3.6), Resource Pool (Public resource pools), Type (GPU), Instance Flavor (GPU: 1xv100NV32 CPU: 8 vCPUs | 64 GiB), Storage (EVS), and Disk Space (5 GB). A warning message states: 'The default disk space is 5 GB and free of charge. If the disk space exceeds 5 GB, the additional space is charged by GB from the time when a notebook instance is created to the time the notebook instance is deleted.'


Figure 2-3 Notebook Configuration

Step 3 Finish

Then, at the bottom of this page, click Next button to finish creating notebook.

2.2.2 Open Notebook and Coding

Once the Notebook is created, the Notebook environment that you created will be listed on this page. The Notebook environment can be managed with the Open, Stop, and Delete buttons. Click Open to continue.



Name	Status	Work Environment	Instance Flavor	Description	Created	Created By	Operation
notebook-ceshi	Running (31 minutes until stop)	TF-2.1.0&Pytorch-1.4.0-py...	GPU: 1xv100NV32 CPU: 8 vCPUs ...		Jul 06, 2020 19:27:12 GMT+08:00	whctshir	Open Stop Delete

Figure 2-4 Open Notebook

This interface is a Notebook page, click the **New** button, and then click **TensorFlow-2.1.0** to create a New file, as shown on this figure.




Figure 2-5 Create a New File

This page is a Notebook's code editing interface and its base environment is TensorFlow2.1.0. You can start editing the code.



Figure 2-6 Notebook's Code Editing Interface

2.3 Experiment Code

2.3.1 Introducing Dependencies

Code:

```
import imageio
import numpy as np
import pickle
import os
import matplotlib.pyplot as plt
import tensorflow as tf
from tensorflow import keras
from tensorflow.keras import layers, optimizers, datasets, Sequential
from tensorflow.keras.layers import Conv2D, Activation, MaxPooling2D, Dropout, Flatten, Dense
```

2.3.2 Data Preprocessing

Code:

```
!wget https://data-certification.obs.cn-east-2.myhuaweicloud.com/ENG/HCIA-AI/V3.0/cifar-10-python.tar.gz
```

```
!tar -zxvf cifar-10-python.tar.gz
```

Code:

```
final_tr_data=[]
final_tr_label=[]
final_te_data=[]
final_te_label=[]

# Decompress, return the decompressed dictionary
def unpickle(file):
    fo = open(file, 'rb')
    dict = pickle.load(fo, encoding='latin1')
    fo.close()
    return dict

# Generate training set pictures. If you need png format, you only need to change the picture suffix
name.
for j in range(1, 6):
    dataName = "cifar-10-batches-py//data_batch_" + str(j) # Read the data_batch12345 file in the
current directory. The dataName is actually the path of the data_batch file. The text and the script file
are in the same directory.
    Xtr = unpickle(dataName)
    print(dataName + " is loading...")

    for i in range(0, 10000):
        img = np.reshape(Xtr['data'][i], (3,32, 32)) # Xtr['data'] is picture binary data
        img = img.transpose(1, 2, 0)
        picName = 'train/' + str(Xtr['labels'][i]) + '_' + str(i + (j - 1)*10000) + '.jpg' # Xtr['labels'] is
the label of the picture, the value range is 0-9. In this article, the train folder needs to exist and be in
the same directory as the script file.
        if not os.path.exists('./train'):
            os.mkdir('./train')

        imageio.imwrite(picName, img)
        final_tr_data.append(img)
        final_tr_label.append(Xtr['labels'][i])

    print(dataName + " loaded.")

print("test_batch is loading...")

# Generate test set images
testXtr = unpickle("cifar-10-batches-py//test_batch")
for i in range(0, 10000):
    img = np.reshape(testXtr['data'][i], (3,32, 32))
    img = img.transpose(1, 2, 0)

    picName = 'test/' + str(testXtr['labels'][i]) + '_' + str(i) + '.jpg'
    if not os.path.exists('./test'):
        os.mkdir('./test')
    imageio.imwrite(picName, img)
    final_te_data.append(img)
    final_te_label.append(testXtr['labels'][i])
print("test_batch loaded.")
```

Output:

```
cifar-10-batches-py//data_batch_1 is loading...
cifar-10-batches-py//data_batch_1 loaded.
cifar-10-batches-py//data_batch_2 is loading...
cifar-10-batches-py//data_batch_2 loaded.
cifar-10-batches-py//data_batch_3 is loading...
cifar-10-batches-py//data_batch_3 loaded.
cifar-10-batches-py//data_batch_4 is loading...
cifar-10-batches-py//data_batch_4 loaded.
cifar-10-batches-py//data_batch_5 is loading...
cifar-10-batches-py//data_batch_5 loaded.
test_batch is loading...
test_batch loaded.
```

Code:

```
final_tr_data=np.array(final_tr_data)
print(np.shape(final_tr_data))
y_train=np.array(final_tr_label).reshape(50000,1)
print(np.shape(final_tr_label))

final_te_data=np.array(final_te_data)
print(np.shape(final_te_data))
y_test=np.array(final_te_label).reshape(10000,1)
print(np.shape(final_te_label))
```

Output:

```
(50000, 32, 32, 3)
(50000,)
(10000, 32, 32, 3)
(10000,)
```

Show the first 9 images:

Code:

```
category_dict = {0:'airplane',1:'automobile',2:'bird',3:'cat',4:'deer',5:'dog',
                  6:'frog',7:'horse',8:'ship',9:'truck'}
#Show the first 9 images and their labels
plt.figure()
for i in range(9):
    #create a figure with 9 subplots
    plt.subplot(3,3,i+1)
    #show an image
    plt.imshow(final_tr_data[i])
    #show the label
    plt.ylabel(category_dict[final_tr_label[i]])
plt.show()

#Pixel normalization
x_train = final_tr_data.astype('float32')/255
x_test = final_te_data.astype('float32')/255

num_classes=10
```

Output:




Figure 2-7 First 9 Images with Tags

2.3.3 Model Creation

Code:

```
def CNN_classification_model(input_size = x_train.shape[1:]):
    model = Sequential()
    #the first block with 2 convolutional layers and 1 maxpooling layer
    '''Conv1 with 32 3*3 kernels
        padding="same": it applies zero padding to the input image so that the input image gets
        fully covered by the filter and specified stride.
        It is called SAME because, for stride 1 , the output will be the same as the input.
        output: 32*32*32'''
    model.add(Conv2D(32, (3, 3), padding='same',
                    input_shape=input_size))
    #relu activation function
    model.add(Activation('relu'))
    #Conv2
    model.add(Conv2D(32, (3, 3)))
    model.add(Activation('relu'))
    #maxpooling
    model.add(MaxPooling2D(pool_size=(2, 2),strides =1))

    #the second block
    model.add(Conv2D(64, (3, 3), padding='same'))
    model.add(Activation('relu'))
    model.add(Conv2D(64, (3, 3)))
    model.add(Activation('relu'))
    #maxpooling.the default strides =1
    model.add(MaxPooling2D(pool_size=(2, 2)))

    #Before sending a feature map into a fully connected network, it should be flattened into a
    column vector.
    model.add(Flatten())
    #fully connected layer
    model.add(Dense(128))
    model.add(Activation('relu'))
    #dropout layer.every neuronis set to 0 with a probability of 0.25
    model.add(Dropout(0.25))
```

```

model.add(Dense(num_classes))
#map the score of each class into probability
model.add(Activation('softmax'))

opt = keras.optimizers.Adam(lr=0.0001)

model.compile(loss='sparse_categorical_crossentropy', optimizer=opt, metrics=['accuracy'])
return model
model=CNN_classification_model()
model.summary()

```

Output:

Model: "sequential"		
Layer (type)	Output Shape	Param #
=====		
conv2d (Conv2D)	(None, 32, 32, 32)	896
activation (Activation)	(None, 32, 32, 32)	0
conv2d_1 (Conv2D)	(None, 30, 30, 32)	9248
activation_1 (Activation)	(None, 30, 30, 32)	0
max_pooling2d (MaxPooling2D)	(None, 29, 29, 32)	0
conv2d_2 (Conv2D)	(None, 29, 29, 64)	18496
activation_2 (Activation)	(None, 29, 29, 64)	0
conv2d_3 (Conv2D)	(None, 27, 27, 64)	36928
activation_3 (Activation)	(None, 27, 27, 64)	0
max_pooling2d_1 (MaxPooling2D)	(None, 13, 13, 64)	0
flatten (Flatten)	(None, 10816)	0
dense (Dense)	(None, 128)	1384576
activation_4 (Activation)	(None, 128)	0
dropout (Dropout)	(None, 128)	0
dense_1 (Dense)	(None, 10)	1290
activation_5 (Activation)	(None, 10)	0
=====		
Total params: 1,451,434		
Trainable params: 1,451,434		
Non-trainable params: 0		

2.3.4 Model Training

Code:

```

from tensorflow.keras.callbacks import ModelCheckpoint
model_name = "final_cifar10.h5"
model_checkpoint = ModelCheckpoint(model_name, monitor='loss', verbose=1, save_best_only=True)

#load pretrained models
trained_weights_path = 'cifar10_weights.h5'
if os.path.exists(trained_weights_path):
    model.load_weights(trained_weights_path, by_name=True)
#train

```

```
model.fit(x_train,y_train, batch_size=32, epochs=10,callbacks = [model_checkpoint],verbose=1)
```

Output:

```
Train on 50000 samples
Epoch 1/10
49600/50000 [=====>.] - ETA: 0s - loss: 1.6383 - accuracy: 0.4085
Epoch 00001: loss improved from inf to 1.63644, saving model to final_cifar10.h5
50000/50000 [=====] - 8s 150us/sample - loss: 1.6364 - accuracy: 0.4092
Epoch 2/10
49824/50000 [=====>.] - ETA: 0s - loss: 1.3157 - accuracy: 0.5334
Epoch 00002: loss improved from 1.63644 to 1.31575, saving model to final_cifar10.h5
50000/50000 [=====] - 5s 110us/sample - loss: 1.3157 - accuracy: 0.5335
Epoch 3/10
49792/50000 [=====>.] - ETA: 0s - loss: 1.1694 - accuracy: 0.5867
Epoch 00003: loss improved from 1.31575 to 1.16893, saving model to final_cifar10.h5
50000/50000 [=====] - 5s 109us/sample - loss: 1.1689 - accuracy: 0.5870
Epoch 4/10
49856/50000 [=====>.] - ETA: 0s - loss: 1.0611 - accuracy: 0.6276
Epoch 00004: loss improved from 1.16893 to 1.06089, saving model to final_cifar10.h5
50000/50000 [=====] - 5s 109us/sample - loss: 1.0609 - accuracy: 0.6277
Epoch 5/10
49792/50000 [=====>.] - ETA: 0s - loss: 0.9883 - accuracy: 0.6566
Epoch 00005: loss improved from 1.06089 to 0.98766, saving model to final_cifar10.h5
50000/50000 [=====] - 5s 109us/sample - loss: 0.9877 - accuracy: 0.6568
Epoch 6/10
49856/50000 [=====>.] - ETA: 0s - loss: 0.9272 - accuracy: 0.6754
Epoch 00006: loss improved from 0.98766 to 0.92681, saving model to final_cifar10.h5
50000/50000 [=====] - 5s 109us/sample - loss: 0.9268 - accuracy: 0.6756
Epoch 7/10
49760/50000 [=====>.] - ETA: 0s - loss: 0.8720 - accuracy: 0.6935
Epoch 00007: loss improved from 0.92681 to 0.87214, saving model to final_cifar10.h5
50000/50000 [=====] - 5s 109us/sample - loss: 0.8721 - accuracy: 0.6933
Epoch 8/10
49824/50000 [=====>.] - ETA: 0s - loss: 0.8252 - accuracy: 0.7100
Epoch 00008: loss improved from 0.87214 to 0.82465, saving model to final_cifar10.h5
50000/50000 [=====] - 5s 109us/sample - loss: 0.8246 - accuracy: 0.7101
Epoch 9/10
49888/50000 [=====>.] - ETA: 0s - loss: 0.7775 - accuracy: 0.7288
Epoch 00009: loss improved from 0.82465 to 0.77777, saving model to final_cifar10.h5
50000/50000 [=====] - 5s 108us/sample - loss: 0.7778 - accuracy: 0.7287
Epoch 10/10
49824/50000 [=====>.] - ETA: 0s - loss: 0.7351 - accuracy: 0.7427
Epoch 00010: loss improved from 0.77777 to 0.73529, saving model to final_cifar10.h5
50000/50000 [=====] - 5s 109us/sample - loss: 0.7353 - accuracy: 0.7426
<tensorflow.python.keras.callbacks.History at 0x7f875ac078d0>
```

This experiment is performed on a laptop. The network in this experiment is simple, consisting of four convolutional layers. To improve the performance of this model, you can increase the number of epochs and the complexity of the model.

2.3.5 Model Evaluation

Code:

```
new_model = CNN_classification_model()
new_model.load_weights('final_cifar10.h5')

model.evaluate(x_test, y_test, verbose=1)
```

Output:

```
10000/10000 [=====] - 1s 66us/sample - loss: 0.8327 - accuracy:
0.7134
[0.8326702466964722, 0.7134]
```

Predict on a single image.

Code:

```
#output the possibility of each class
new_model.predict(x_test[0:1])
```

Output:

```
array([[2.3494475e-03, 6.9919275e-05, 8.1065837e-03, 7.8556609e-01,
        2.3783690e-03, 1.8864134e-01, 6.8611270e-03, 1.2157968e-03,
        4.3428279e-03, 4.6843957e-04]], dtype=float32)
```

Code:

```
#output the predicted label
new_model.predict_classes(x_test[0:1])
```

Output:

```
array([3])
```

Plot the first 4 images in the test set and their corresponding predicted labels.

Code:

```
#label list
pred_list = []

plt.figure()
for i in range(0,4):
    plt.subplot(2,2,i+1)
    #plot
    plt.imshow(x_test[i])
    #predict
    pred = new_model.predict_classes(x_test[0:10])
    pred_list.append(pred)
    #Display actual and predicted labels of images
    plt.title("pred:"+category_dict[pred[i]]+"    actual:"+ category_dict[y_test[i][0]])
    plt.axis('off')
plt.show()
```

Output:



Figure 2-8 The First 4 Images with Predicted Labels

2.4 Summary

This chapter describes how to build an image classification model based on ModelArts.