

# GAM250: Advanced Games Programming

## 4: Graphics Programming


# Learning outcomes

- ▶ **Understand** the modern Programmable Graphics Pipeline
- ▶ **Understand** Unity's Material System
- ▶ **Write** Surface and Image Effect Shaders in Unity


# The Graphics Pipeline



# The 3D graphics pipeline




# Vertex processing




# Vertex processing

- ▶ Geometry is provided to the GPU as a **mesh** of **triangles**




# Vertex processing



- ▶ Geometry is provided to the GPU as a **mesh** of **triangles**
- ▶ Each triangle has three **vertices** specified in 3D space ( $x, y, z$ )


# Vertex processing



- ▶ Geometry is provided to the GPU as a **mesh** of **triangles**
- ▶ Each triangle has three **vertices** specified in 3D space ( $x, y, z$ )
- ▶ Vertex processor **transforms** (rotates, moves, scales) vertices and **projects** them into 2D screen space ( $x, y$ )




# Vertex processing




- ▶ Geometry is provided to the GPU as a **mesh** of **triangles**
- ▶ Each triangle has three **vertices** specified in 3D space ( $x, y, z$ )
- ▶ Vertex processor **transforms** (rotates, moves, scales) vertices and **projects** them into 2D screen space ( $x, y$ )
- ▶ May also apply particle simulations, skeletal animations or deformations, etc.

# Rasterisation




# Rasterisation




- Determine **which fragments** are covered by the triangle

# Rasterisation




- ▶ Determine **which fragments** are covered by the triangle
- ▶ In practical terms, “fragment” = “pixel”

# Rasterisation




- ▶ Determine **which fragments** are covered by the triangle
- ▶ In practical terms, “fragment” = “pixel”
- ▶ Vertex processor can associate **data** with each vertex; this is **interpolated** across the fragments

# Fragment processing




# Fragment processing



- Determine the **colour** of each fragment covered by the triangle


# Fragment processing



- Determine the **colour** of each fragment covered by the triangle
- **Textures** are 2D images that can be **wrapped** onto a 3D object




# Fragment processing




- Determine the **colour** of each fragment covered by the triangle
- **Textures** are 2D images that can be **wrapped** onto a 3D object
- Colour is calculated based on **texture**, **lighting** and other properties of the surface being rendered (e.g. shininess, roughness)

# Blending




# Blending

- Combine these fragments with the existing content of the image buffer




# Blending



- ▶ Combine these fragments with the existing content of the image buffer
- ▶ **Depth testing:** if the new fragment is "in front" of the old one, replace it; if it is "behind", discard it

# Blending



- ▶ Combine these fragments with the existing content of the image buffer
- ▶ **Depth testing:** if the new fragment is “in front” of the old one, replace it; if it is “behind”, discard it
- ▶ **Alpha blending:** combine the old and new colours for a semi-transparent appearance

# Shaders

- ▶ The vertex processor and fragment processor are **programmable**

# Shaders

- ▶ The vertex processor and fragment processor are **programmable**
- ▶ Programs for these units are called **shaders**

# Shaders

- ▶ The vertex processor and fragment processor are **programmable**
- ▶ Programs for these units are called **shaders**
- ▶ **Vertex shader**: responsible for geometric transformations, deformations, and projection



# Shaders

- ▶ The vertex processor and fragment processor are **programmable**
- ▶ Programs for these units are called **shaders**
- ▶ **Vertex shader**: responsible for geometric transformations, deformations, and projection
- ▶ **Fragment shader**: responsible for the visual appearance of the surface

# Shaders

- ▶ The vertex processor and fragment processor are **programmable**
- ▶ Programs for these units are called **shaders**
- ▶ **Vertex shader**: responsible for geometric transformations, deformations, and projection
- ▶ **Fragment shader**: responsible for the visual appearance of the surface
- ▶ Vertex shader and fragment shader are separate programs, but the vertex shader can pass arbitrary values through to the fragment shader

# Subsurface Shaders



# Shaders in Unity

- ▶ There are many approaches to writing shaders in Unity

# Shaders in Unity

- ▶ There are many approaches to writing shaders in Unity
  - ▶ Surface Shaders

# Shaders in Unity

- ▶ There are many approaches to writing shaders in Unity
  - ▶ Surface Shaders
  - ▶ Vertex and Fragment Shaders

# Shaders in Unity

- ▶ There are many approaches to writing shaders in Unity
  - ▶ Surface Shaders
  - ▶ Vertex and Fragment Shaders
  - ▶ Fixed Function Shaders

# Shaders in Unity

- ▶ There are many approaches to writing shaders in Unity
  - ▶ Surface Shaders
  - ▶ Vertex and Fragment Shaders
  - ▶ Fixed Function Shaders
- ▶ The best method is to use Surface Shaders, this is the quickest way to get started



# Shaders in Unity

- ▶ There are many approaches to writing shaders in Unity
  - ▶ Surface Shaders
  - ▶ Vertex and Fragment Shaders
  - ▶ Fixed Function Shaders
- ▶ The best method is to use Surface Shaders, this is the quickest way to get started
- ▶ This interacts with the standard lights and shadows in Unity

# Shaders in Unity

- ▶ There are many approaches to writing shaders in Unity
  - ▶ Surface Shaders
  - ▶ Vertex and Fragment Shaders
  - ▶ Fixed Function Shaders
- ▶ The best method is to use Surface Shaders, this is the quickest way to get started
- ▶ This interacts with the standard lights and shadows in Unity
- ▶ Regardless of the shader type, your code will be wrapped in ShaderLab

# ShaderLab

- ▶ ShaderLab is a simple scripting language for defining graphical effects

# ShaderLab

- ▶ ShaderLab is a simple scripting language for defining graphical effects
- ▶ It contains the following

# ShaderLab

- ▶ ShaderLab is a simple scripting language for defining graphical effects
- ▶ It contains the following
  - ▶ Properties - These are shown in the inspector of the material and is a way to expose shader variables

# ShaderLab

- ▶ ShaderLab is a simple scripting language for defining graphical effects
- ▶ It contains the following
  - ▶ Properties - These are shown in the inspector of the material and is a way to expose shader variables
  - ▶ SubShaders - Is a list of pass or the surface shader code itself

# Shading Languages



# High Level Shading Language (HLSL)

- Used for writing **shaders** for Direct3D and Unity3D



# High Level Shading Language (HLSL)

- ▶ Used for writing **shaders** for Direct3D and Unity3D
- ▶ C-like syntax

# High Level Shading Language (HLSL)

- ▶ Used for writing **shaders** for Direct3D and Unity3D
- ▶ C-like syntax
- ▶ But has data types that support mathematical operations

# Programming in HLSL

- ▶ `if` statements, `for` loops, `while` loops, `do while` loops, `switch` statements, `break`, `continue`, `return` all work the same as C++

# Programming in HLSL

- ▶ `if` statements, `for` loops, `while` loops, `do while` loops, `switch` statements, `break`, `continue`, `return` all work the same as C++
- ▶ `//Single-line comments` and `/*Multi-line comments */` work the same too

# Programming in HLSL

- ▶ `if` statements, `for` loops, `while` loops, `do while` loops, `switch` statements, `break`, `continue`, `return` all work the same as C++
- ▶ `//Single-line comments` and `/*Multi-line comments */` work the same too
- ▶ Function definitions and declarations are similar to C#, except that parameters must be declared as `in`, `out` or `inout`

# Programming in HLSL

- ▶ `if` statements, `for` loops, `while` loops, `do while` loops, `switch` statements, `break`, `continue`, `return` all work the same as C++
- ▶ `//Single-line comments` and `/*Multi-line comments */` work the same too
- ▶ Function definitions and declarations are similar to C#, except that parameters must be declared as `in`, `out` or `inout`
- ▶ Recursion is **forbidden**

# Programming in HLSL

- ▶ `if` statements, `for` loops, `while` loops, `do while` loops, `switch` statements, `break`, `continue`, `return` all work the same as C++
- ▶ `//Single-line comments` and `/*Multi-line comments */` work the same too
- ▶ Function definitions and declarations are similar to C#, except that parameters must be declared as `in`, `out` or `inout`
- ▶ Recursion is **forbidden**
- ▶ No `class`

# Data types in HLSL

- ▶ `bool`, `int`, `float`: just like in C++



# Data types in HLSL

- ▶ `bool`, `int`, `float`: just like in C++
- ▶ `float2`, `float3`, `float4`: **vectors** of `floats`

# Data types in HLSL

- ▶ `bool`, `int`, `float`: just like in C++
- ▶ `float2`, `float3`, `float4`: **vectors** of `floats`
- ▶ `float2x2`, `float3x3`, `float4x4`: **square matrices** of `floats`

# Data types in HLSL

- ▶ `bool`, `int`, `float`: just like in C++
- ▶ `float2`, `float3`, `float4`: **vectors** of `floats`
- ▶ `float2x2`, `float3x3`, `float4x4`: **square matrices** of `floats`
- ▶ **Arrays** of constant size e.g. `float myArray[10]`

# Vectors

- An  $n$ -**dimensional vector** is formed of  $n$  numbers

# Vectors

- ▶ An  $n$ -**dimensional vector** is formed of  $n$  numbers
- ▶ E.g. 2-dimensional vectors:

$$(1, 2) \quad (-2.7, 0) \quad (3.4, -12.7)$$

# Vectors

- ▶ An  $n$ -**dimensional vector** is formed of  $n$  numbers
- ▶ E.g. 2-dimensional vectors:

$$(1, 2) \quad (-2.7, 0) \quad (3.4, -12.7)$$

- ▶ E.g. 3-dimensional vectors:

$$(1, 2, 0) \quad (-9, 6, 3.7) \quad (2.1, 2.1, 2.1)$$

# Vectors

- ▶ An  $n$ -**dimensional vector** is formed of  $n$  numbers
- ▶ E.g. 2-dimensional vectors:

$$(1, 2) \quad (-2.7, 0) \quad (3.4, -12.7)$$

- ▶ E.g. 3-dimensional vectors:

$$(1, 2, 0) \quad (-9, 6, 3.7) \quad (2.1, 2.1, 2.1)$$

- ▶ Used to represent **points** or **directions** in  $n$  dimensions

# Vectors

- ▶ An  $n$ -**dimensional vector** is formed of  $n$  numbers
- ▶ E.g. 2-dimensional vectors:

$(1, 2)$        $(-2.7, 0)$        $(3.4, -12.7)$

- ▶ E.g. 3-dimensional vectors:

$(1, 2, 0)$        $(-9, 6, 3.7)$        $(2.1, 2.1, 2.1)$

- ▶ Used to represent **points** or **directions** in  $n$  dimensions
- ▶ Also used to represent e.g. colours in RGB(A) space



# Constructing vectors in GLSL

```
float3 a = float3(1.2, 3.4);  
float3 b = float3(1); // same as float3(1, 1, 1)  
float3 c = float3(a, 5.6); // same as float3(1.2, 3.4, 5.6) ←
```

# Vector maths

# Vector maths

Most operations work **component-wise**:

```
float2 a = float2(1, 2);  
float2 b = float2(3, 4);  
float2 c = a + b; // c == float2(4, 6);  
float2 d = a * b; // d == float2(3, 8);
```

# Vector maths

Most operations work **component-wise**:

```
float2 a = float2(1, 2);  
float2 b = float2(3, 4);  
float2 c = a + b; // c == float2(4, 6);  
float2 d = a * b; // d == float2(3, 8);
```

Can also multiply a **vector** by a **scalar**:

```
float2 e = 3.1 * a; // e == float2(3.1, 6.2)
```

# Accessing components

# Accessing components

Can access the components of a vector as `.x`, `.y`, `.z`, `.w`:

# Accessing components

Can access the components of a vector as `.x`, `.y`, `.z`, `.w`:

```
float4 a = float4(1, 2, 3, 4);  
float b = a.y; // b == 2  
float c = a.z; // c == 3  
a.x = 5;       // a == float4(5, 2, 3, 4)  
a.w = a.y;     // a == float4(5, 2, 3, 2)
```

# Accessing components

Can access the components of a vector as `.x`, `.y`, `.z`, `.w`:

```
float4 a = float4(1, 2, 3, 4);  
float b = a.y; // b == 2  
float c = a.z; // c == 3  
a.x = 5;      // a == float4(5, 2, 3, 4)  
a.w = a.y;    // a == float4(5, 2, 3, 2)
```

Can also use `r g b a` (for colours) and `t u v w` (for texture coordinates)



# Swizzling

# Swizzling

Can access multiple components in one go:

# Swizzling

Can access multiple components in one go:

```
float4 a = float4(1, 2, 3, 4);  
float2 b = a.xy;      // b == float2(1, 2)  
float3 c = a.zyz;     // c == float3(3, 2, 3)  
a.xw = float2(5,6);   // a == float4(5, 2, 3, 6)  
a.xyzw = a.wzyx;     // a == float4(6, 3, 2, 5)
```

# Swizzling

Can access multiple components in one go:

```
float4 a = float4(1, 2, 3, 4);  
float2 b = a.xy;      // b == float2(1, 2)  
float3 c = a.zyz;     // c == float3(3, 2, 3)  
a.xw = float2(5,6);   // a == float4(5, 2, 3, 6)  
a.xyzw = a.wzyx;     // a == float4(6, 3, 2, 5)
```

- **Can** use the same component twice in the **right-hand side** of an assignment

# Swizzling

Can access multiple components in one go:

```
float4 a = float4(1, 2, 3, 4);  
float2 b = a.xy;      // b == float2(1, 2)  
float3 c = a.zyz;     // c == float3(3, 2, 3)  
a.xw = float2(5,6);   // a == float4(5, 2, 3, 6)  
a.xyzw = a.wzyx;     // a == float4(6, 3, 2, 5)
```

- ▶ **Can** use the same component twice in the **right-hand side** of an assignment
- ▶ **Cannot** use the same component twice in the **left-hand side** of an assignment

# Swizzling

Can access multiple components in one go:

```
float4 a = float4(1, 2, 3, 4);  
float2 b = a.xy;      // b == float2(1, 2)  
float3 c = a.zyz;     // c == float3(3, 2, 3)  
a.xw = float2(5,6);   // a == float4(5, 2, 3, 6)  
a.xyzw = a.wzyx;     // a == float4(6, 3, 2, 5)
```

- ▶ **Can** use the same component twice in the **right-hand side** of an assignment
- ▶ **Cannot** use the same component twice in the **left-hand side** of an assignment
- ▶ Swizzling is generally **faster** than the equivalent code without swizzling

# Swizzling

Can access multiple components in one go:

```
float4 a = float4(1, 2, 3, 4);  
float2 b = a.xy;      // b == float2(1, 2)  
float3 c = a.zyz;     // c == float3(3, 2, 3)  
a.xw = float2(5,6);   // a == float4(5, 2, 3, 6)  
a.xyzw = a.wzyx;     // a == float4(6, 3, 2, 5)
```

- ▶ **Can** use the same component twice in the **right-hand side** of an assignment
- ▶ **Cannot** use the same component twice in the **left-hand side** of an assignment
- ▶ Swizzling is generally **faster** than the equivalent code without swizzling
- ▶ Can also use `r g b a` or `t u v w`, but can't mix them (e.g. `.gbr` is valid but `.gzx` is not)

# Texture Data Types



# Texture Data Types

- ▶ Textures are stored in the **Sampler** data type

# Texture Data Types

- ▶ Textures are stored in the **Sampler** data type
- ▶ There are different samplers for different types of texture

# Texture Data Types

- ▶ Textures are stored in the **Sampler** data type
- ▶ There are different samplers for different types of texture
  - ▶ 1D Texture - **sampler1D**

# Texture Data Types

- ▶ Textures are stored in the **Sampler** data type
- ▶ There are different samplers for different types of texture
  - ▶ 1D Texture - **sampler1D**
  - ▶ 2D Texture - **sampler2D**

# Texture Data Types

- ▶ Textures are stored in the **Sampler** data type
- ▶ There are different samplers for different types of texture
  - ▶ 1D Texture - **sampler1D**
  - ▶ 2D Texture - **sampler2D**
  - ▶ 3D Texture - **sampler3D**

# Texture Data Types

- ▶ Textures are stored in the **Sampler** data type
- ▶ There are different samplers for different types of texture
  - ▶ 1D Texture - **sampler1D**
  - ▶ 2D Texture - **sampler2D**
  - ▶ 3D Texture - **sampler3D**
  - ▶ Cube Map - **samplerCube**

# Unity Types

- ▶ NB. When writing shaders you can use different precision data types rather than float (High precision)

# Unity Types

- ▶ NB. When writing shaders you can use different precision data types rather than float (High precision)
  - ▶ Medium precision: **half** - directions, positions



# Unity Types

- ▶ NB. When writing shaders you can use different precision data types rather than float (High precision)
  - ▶ Medium precision: **half** - directions, positions
  - ▶ Low precision: **fixed** - colours

# Unity Types

- ▶ NB. When writing shaders you can use different precision data types rather than float (High precision)
  - ▶ Medium precision: **half** - directions, positions
  - ▶ Low precision: **fixed** - colours
- ▶ On Desktop PCs these are always converted to high precision

# Unity Types

- ▶ NB. When writing shaders you can use different precision data types rather than float (High precision)
  - ▶ Medium precision: **half** - directions, positions
  - ▶ Low precision: **fixed** - colours
- ▶ On Desktop PCs these are always converted to high precision
- ▶ These are important for optimisation for mobile

# Surface Shader

Live Coding

# Post-Processing



# What is Post-Processing

- Is processing that occurs after the scene is rendered

# What is Post-Processing

- ▶ Is processing that occurs after the scene is rendered
- ▶ This allows us to implement effects such as static, distortions etc

# What is Post-Processing

- ▶ Is processing that occurs after the scene is rendered
- ▶ This allows us to implement effects such as static, distortions etc
- ▶ Post-Processing effects can be stacked so that one feeds into the next



# Writing Post-Processing Effects

- ▶ We first have to write a vertex and fragment shader and attach it to a material

# Writing Post-Processing Effects

- ▶ We first have to write a vertex and fragment shader and attach it to a material
- ▶ Create a C# script and override the **OnRenderImage** function

# Writing Post-Processing Effects

- ▶ We first have to write a vertex and fragment shader and attach it to a material
- ▶ Create a C# script and override the **OnRenderImage** function
- ▶ Inside the OnRenderImage function and call the **Graphics.Blit** function with the material as the last parameter

# Writing Post-Processing Effects

- ▶ We first have to write a vertex and fragment shader and attach it to a material
- ▶ Create a C# script and override the **OnRenderImage** function
- ▶ Inside the OnRenderImage function and call the **Graphics.Blit** function with the material as the last parameter
- ▶ Attach the script to the camera

# Post-Processing Live Coding

# Further Reading

- ▶ Game Programming Patterns - <http://gameprogrammingpatterns.com/contents.html>
- ▶ Game Programming Patterns in Unity - <http://www.habrador.com/tutorials/programming-patterns/>
- ▶ Unity Design Patterns - <https://github.com/Naphier/unity-design-patterns>