



COMP110: Principles of Computing

4: Session title here

Learning outcomes

- ▶ **Distinguish** the basic types of logic gate
- ▶ **Use** logic gates to build simple circuits
- ▶ **Explain** how computer memory works

Binary notation






Image credit: <http://www.toothpastefordinner.com>

How we write numbers

How we write numbers

- ▶ We write numbers in **base 10**

How we write numbers

- ▶ We write numbers in **base 10**
- ▶ We have 10 **digits**: $0, 1, 2, \dots, 8, 9$

How we write numbers

- ▶ We write numbers in **base 10**
- ▶ We have 10 **digits**: $0, 1, 2, \dots, 8, 9$
- ▶ When we write 6397, we mean:

How we write numbers

- ▶ We write numbers in **base 10**
- ▶ We have 10 **digits**: $0, 1, 2, \dots, 8, 9$
- ▶ When we write 6397, we mean:
 - ▶ Six thousand, three hundred and ninety seven

How we write numbers

- ▶ We write numbers in **base 10**
- ▶ We have 10 **digits**: $0, 1, 2, \dots, 8, 9$
- ▶ When we write 6397, we mean:
 - ▶ Six thousand, three hundred and ninety seven
 - ▶ (Six thousands) and (three hundreds) and (nine tens) and (seven)

How we write numbers

- ▶ We write numbers in **base 10**
- ▶ We have 10 **digits**: 0, 1, 2, ..., 8, 9
- ▶ When we write 6397, we mean:
 - ▶ Six thousand, three hundred and ninety seven
 - ▶ (Six thousands) and (three hundreds) and (nine tens) and (seven)
 - ▶ $(6 \times 1000) + (3 \times 100) + (9 \times 10) + (7)$

How we write numbers

- ▶ We write numbers in **base 10**
- ▶ We have 10 **digits**: $0, 1, 2, \dots, 8, 9$
- ▶ When we write 6397, we mean:
 - ▶ Six thousand, three hundred and ninety seven
 - ▶ (Six thousands) and (three hundreds) and (nine tens) and (seven)
 - ▶ $(6 \times 1000) + (3 \times 100) + (9 \times 10) + (7)$
 - ▶ $(6 \times 10^3) + (3 \times 10^2) + (9 \times 10^1) + (7 \times 10^0)$

Binary

Binary

- ▶ Binary notation works the same, but is **base 2** instead of **base 10**

Binary

- ▶ Binary notation works the same, but is **base 2** instead of **base 10**
- ▶ We have 2 **digits**: 0, 1

Binary

- ▶ Binary notation works the same, but is **base 2** instead of **base 10**
- ▶ We have 2 **digits**: 0, 1
- ▶ When we write 10001011 in binary, we mean:

Binary

- ▶ Binary notation works the same, but is **base 2** instead of **base 10**
- ▶ We have 2 **digits**: 0, 1
- ▶ When we write 10001011 in binary, we mean:
$$(1 \times 2^7) + (0 \times 2^6) + (0 \times 2^5) + (0 \times 2^4) \\ + (1 \times 2^3) + (0 \times 2^2) + (1 \times 2^1) + (1 \times 2^0)$$

Binary

- ▶ Binary notation works the same, but is **base 2** instead of **base 10**
- ▶ We have 2 **digits**: 0, 1
- ▶ When we write 10001011 in binary, we mean:
$$\begin{aligned} & (1 \times 2^7) + (0 \times 2^6) + (0 \times 2^5) + (0 \times 2^4) \\ & + (1 \times 2^3) + (0 \times 2^2) + (1 \times 2^1) + (1 \times 2^0) \\ & = 2^7 + 2^3 + 2^1 + 2^0 \end{aligned}$$

Binary

- ▶ Binary notation works the same, but is **base 2** instead of **base 10**
- ▶ We have 2 **digits**: 0, 1
- ▶ When we write 10001011 in binary, we mean:
$$(1 \times 2^7) + (0 \times 2^6) + (0 \times 2^5) + (0 \times 2^4)$$
$$+ (1 \times 2^3) + (0 \times 2^2) + (1 \times 2^1) + (1 \times 2^0)$$
$$= 2^7 + 2^3 + 2^1 + 2^0$$
$$= 128 + 8 + 2 + 1 \text{ (base 10)}$$

Binary

- ▶ Binary notation works the same, but is **base 2** instead of **base 10**
- ▶ We have 2 **digits**: 0, 1
- ▶ When we write 10001011 in binary, we mean:
$$(1 \times 2^7) + (0 \times 2^6) + (0 \times 2^5) + (0 \times 2^4)$$
$$+ (1 \times 2^3) + (0 \times 2^2) + (1 \times 2^1) + (1 \times 2^0)$$
$$= 2^7 + 2^3 + 2^1 + 2^0$$
$$= 128 + 8 + 2 + 1 \text{ (base 10)}$$
$$= 139 \text{ (base 10)}$$

Bits, bytes and words

Bits, bytes and words

- ▶ A **bit** is a binary digit

Bits, bytes and words

- ▶ A **bit** is a binary digit
 - ▶ Can store a 0 or 1 (i.e. a boolean value)

Bits, bytes and words

- ▶ A **bit** is a binary digit
 - ▶ Can store a 0 or 1 (i.e. a boolean value)
- ▶ A **byte** is 8 **bits**

Bits, bytes and words

- ▶ A **bit** is a binary digit
 - ▶ Can store a 0 or 1 (i.e. a boolean value)
- ▶ A **byte** is 8 **bits**
 - ▶ Can store a number between 0 and 255 in binary

Bits, bytes and words

- ▶ A **bit** is a binary digit
 - ▶ Can store a 0 or 1 (i.e. a boolean value)
- ▶ A **byte** is 8 **bits**
 - ▶ Can store a number between 0 and 255 in binary
- ▶ A **word** is the number of bits that the CPU works with at once

Bits, bytes and words

- ▶ A **bit** is a binary digit
 - ▶ Can store a 0 or 1 (i.e. a boolean value)
- ▶ A **byte** is 8 **bits**
 - ▶ Can store a number between 0 and 255 in binary
- ▶ A **word** is the number of bits that the CPU works with at once
 - ▶ 32-bit CPU: 32 bits = 1 word

Bits, bytes and words

- ▶ A **bit** is a binary digit
 - ▶ Can store a 0 or 1 (i.e. a boolean value)
- ▶ A **byte** is 8 **bits**
 - ▶ Can store a number between 0 and 255 in binary
- ▶ A **word** is the number of bits that the CPU works with at once
 - ▶ 32-bit CPU: 32 bits = 1 word
 - ▶ 64-bit CPU: 64 bits = 1 word

Bits, bytes and words

- ▶ A **bit** is a binary digit
 - ▶ Can store a 0 or 1 (i.e. a boolean value)
- ▶ A **byte** is 8 **bits**
 - ▶ Can store a number between 0 and 255 in binary
- ▶ A **word** is the number of bits that the CPU works with at once
 - ▶ 32-bit CPU: 32 bits = 1 word
 - ▶ 64-bit CPU: 64 bits = 1 word
- ▶ An n -bit word can store a number between 0 and $2^n - 1$

Bits, bytes and words

- ▶ A **bit** is a binary digit
 - ▶ Can store a 0 or 1 (i.e. a boolean value)
- ▶ A **byte** is 8 **bits**
 - ▶ Can store a number between 0 and 255 in binary
- ▶ A **word** is the number of bits that the CPU works with at once
 - ▶ 32-bit CPU: 32 bits = 1 word
 - ▶ 64-bit CPU: 64 bits = 1 word
- ▶ An n -bit word can store a number between 0 and $2^n - 1$
 - ▶ $2^{16} - 1 = 65,535$

Bits, bytes and words

- ▶ A **bit** is a binary digit
 - ▶ Can store a 0 or 1 (i.e. a boolean value)
- ▶ A **byte** is 8 **bits**
 - ▶ Can store a number between 0 and 255 in binary
- ▶ A **word** is the number of bits that the CPU works with at once
 - ▶ 32-bit CPU: 32 bits = 1 word
 - ▶ 64-bit CPU: 64 bits = 1 word
- ▶ An n -bit word can store a number between 0 and $2^n - 1$
 - ▶ $2^{16} - 1 = 65,535$
 - ▶ $2^{32} - 1 = 4,294,967,295$


Bits, bytes and words

- ▶ A **bit** is a binary digit
 - ▶ Can store a 0 or 1 (i.e. a boolean value)
- ▶ A **byte** is 8 **bits**
 - ▶ Can store a number between 0 and 255 in binary
- ▶ A **word** is the number of bits that the CPU works with at once
 - ▶ 32-bit CPU: 32 bits = 1 word
 - ▶ 64-bit CPU: 64 bits = 1 word
- ▶ An n -bit word can store a number between 0 and $2^n - 1$
 - ▶ $2^{16} - 1 = 65,535$
 - ▶ $2^{32} - 1 = 4,294,967,295$
 - ▶ $2^{64} - 1 = 18,446,744,073,709,551,615$


Computer memory



What does this circuit do?




What does this circuit do?




- This is called a **NAND latch**

What does this circuit do?



- ▶ This is called a **NAND latch**
- ▶ It “remembers” a single boolean value

What does this circuit do?



- ▶ This is called a **NAND latch**
- ▶ It “remembers” a single boolean value
- ▶ Put a few billion of these together (along with some control circuitry) and you’ve got **memory!**