

COMP250: Artificial Intelligence

4: Session title here

Learning outcomes

- ▶ Outcome 1
- ▶ Outcome 2
- ▶ Outcome 3

Planning



Planning

Planning

- ▶ An **agent** in an **environment**

Planning

- ▶ An **agent** in an **environment**
- ▶ The environment has a **state**

Planning

- ▶ An **agent** in an **environment**
- ▶ The environment has a **state**
- ▶ The agent can perform **actions** to change the state

Planning

- ▶ An **agent** in an **environment**
- ▶ The environment has a **state**
- ▶ The agent can perform **actions** to change the state
- ▶ The agent wants to change the state so as to achieve a **goal**

Planning

- ▶ An **agent** in an **environment**
- ▶ The environment has a **state**
- ▶ The agent can perform **actions** to change the state
- ▶ The agent wants to change the state so as to achieve a **goal**
- ▶ Problem: find a sequence of actions that leads to the goal

STRIPS planning

STRIPS planning

- ▶ **S**tanford **R**esearch **I**nstitute **P**roblem **S**olver

STRIPS planning

- ▶ **S**tanford **R**esearch **I**nstitute **P**roblem **S**olver
- ▶ Describes the state of the environment by a set of **predicates** which are true

STRIPS planning

- ▶ **S**tanford **R**esearch Institute **P**roblem **S**olver
- ▶ Describes the state of the environment by a set of **predicates** which are true
- ▶ Models a problem as:

STRIPS planning

- ▶ **S**tanford **R**esearch **I**nstitute **P**roblem **S**olver
- ▶ Describes the state of the environment by a set of **predicates** which are true
- ▶ Models a problem as:
 - ▶ The **initial state** (a set of predicates which are true)

STRIPS planning

- ▶ **S**tanford **R**esearch Institute **P**roblem **S**olver
- ▶ Describes the state of the environment by a set of **predicates** which are true
- ▶ Models a problem as:
 - ▶ The **initial state** (a set of predicates which are true)
 - ▶ The **goal state** (a set of predicates, specifying whether each should be true or false)

STRIPS planning

- ▶ **S**tanford **R**esearch Institute **P**roblem **S**olver
- ▶ Describes the state of the environment by a set of **predicates** which are true
- ▶ Models a problem as:
 - ▶ The **initial state** (a set of predicates which are true)
 - ▶ The **goal state** (a set of predicates, specifying whether each should be true or false)
 - ▶ The set of **actions**, each specifying:


STRIPS planning

- ▶ **S**tanford **R**esearch Institute **P**roblem **S**olver
- ▶ Describes the state of the environment by a set of **predicates** which are true
- ▶ Models a problem as:
 - ▶ The **initial state** (a set of predicates which are true)
 - ▶ The **goal state** (a set of predicates, specifying whether each should be true or false)
 - ▶ The set of **actions**, each specifying:
 - ▶ Preconditions (a set of predicates which must be satisfied for this action to be possible)


STRIPS planning

- ▶ **S**tanford **R**esearch **I**nstitute **P**roblem **S**olver
- ▶ Describes the state of the environment by a set of **predicates** which are true
- ▶ Models a problem as:
 - ▶ The **initial state** (a set of predicates which are true)
 - ▶ The **goal state** (a set of predicates, specifying whether each should be true or false)
 - ▶ The set of **actions**, each specifying:
 - ▶ Preconditions (a set of predicates which must be satisfied for this action to be possible)
 - ▶ Postconditions (specifying what predicates are made true or false by this action)

STRIPS example




STRIPS example



Initial state:

At (A) ,
BoxAt (C) ,
BananasAt (B')

STRIPS example




Initial state:

At (A) ,
BoxAt (C) ,
BananasAt (B')

Goal:

HasBananas

STRIPS example — Actions



Move(x , y)

Pre: At(x)

Post: !At(x), At(y)

ClimbUp(x)

Pre: At(x), BoxAt(x)

Post: !At(x), At(x')

ClimbDown(x')

Pre: At(x'), BoxAt(x)

Post: !At(x'), At(x)

PushBox(x , y)

Pre: At(x), BoxAt(x)


Post: !At(x), At(y),
!BoxAt(x), BoxAt(y)

TakeBananas(x)

Pre: At(x), BananasAt(x)


Post: HasBananas

STRIPS example — Solution




```
Move (A, C)  
PushBox (C, B)  
ClimbUp (B)  
TakeBananas (B' )
```

STRIPS example — Solution




```
Move (A, C)  
PushBox (C, B)  
ClimbUp (B)  
TakeBananas (B')
```


STRIPS example — Solution




```
Move (A, C)  
PushBox (C, B)  
ClimbUp (B)  
TakeBananas (B' )
```

STRIPS example — Solution



Move (A, C)
PushBox (C, B)
ClimbUp (B)
TakeBananas (B')

STRIPS example — Solution



```
Move (A, C)  
PushBox (C, B)  
ClimbUp (B)  
TakeBananas (B' )
```