



COMP220: Graphics & Simulation

3: Mathematics for graphics

Learning outcomes

- ▶ Outcome 1
- ▶ Outcome 2
- ▶ Outcome 3

Vectors




Vectors

A vector has **components**


Vectors

A vector has **components**



Vectors


A vector has **components**




A vector also has **direction**
and **magnitude** (or **length**)

Vectors

A vector has **components**




A vector also has **direction** and **magnitude** (or **length**)




Vectors

A vector has **components**



A vector also has **direction** and **magnitude** (or **length**)



The **origin** is the point represented by the vector $(0, 0, \dots)$

Radians

Radians

- ▶ We often measure angles in **radians**

Radians

- ▶ We often measure angles in **radians**
- ▶ $\pi = 3.14159\dots$

Radians

- ▶ We often measure angles in **radians**
- ▶ $\pi = 3.14159\dots$
- ▶ π radians = 180 degrees = half a circle

Radians

- ▶ We often measure angles in **radians**
- ▶ $\pi = 3.14159\dots$
- ▶ π radians = 180 degrees = half a circle
- ▶ $\frac{\pi}{2}$ radians = 90 degrees = right angle

Radians

- ▶ We often measure angles in **radians**
- ▶ $\pi = 3.14159\dots$
- ▶ π radians = 180 degrees = half a circle
- ▶ $\frac{\pi}{2}$ radians = 90 degrees = right angle
- ▶ Careful! Some things in OpenGL work in **degrees**, others in **radians** (just to confuse you...)


Right hand rule

Right hand rule

OpenGL uses a **right-handed coordinate system**


Right hand rule

OpenGL uses a **right-handed coordinate system**



Right hand rule


OpenGL uses a **right-handed coordinate system**



- The **x-axis** points towards the **right-hand side** of the screen

Right hand rule


OpenGL uses a **right-handed coordinate system**



- ▶ The **x-axis** points towards the **right-hand side** of the screen
- ▶ The **y-axis** points towards the **top** of the screen

Right hand rule

OpenGL uses a **right-handed coordinate system**



- ▶ The **x-axis** points towards the **right-hand side** of the screen
- ▶ The **y-axis** points towards the **top** of the screen
- ▶ The **z-axis** points **out** of the screen

Homogeneous coordinates

Homogeneous coordinates

- ▶ In 3D graphics, it is useful to represent a **point in 3D space** as a **4-dimensional vector**

Homogeneous coordinates

- ▶ In 3D graphics, it is useful to represent a **point in 3D space** as a **4-dimensional vector**
- ▶ The extra coordinate is called w

Homogeneous coordinates

- ▶ In 3D graphics, it is useful to represent a **point in 3D space** as a **4-dimensional vector**
- ▶ The extra coordinate is called w
- ▶ Simple explanation: w should always equal 1 for points in 3D space; having w there makes certain calculations easier

Homogeneous coordinates

- ▶ In 3D graphics, it is useful to represent a **point in 3D space** as a **4-dimensional vector**
- ▶ The extra coordinate is called w
- ▶ Simple explanation: w should always equal 1 for points in 3D space; having w there makes certain calculations easier
 - ▶ (Actually, a point (x, y, z) can be represented as a vector $(x \times w, y \times w, z \times w, w)$ for any $w \neq 0$)


Homogeneous coordinates

- ▶ In 3D graphics, it is useful to represent a **point in 3D space** as a **4-dimensional vector**
- ▶ The extra coordinate is called w
- ▶ Simple explanation: w should always equal 1 for points in 3D space; having w there makes certain calculations easier
 - ▶ (Actually, a point (x, y, z) can be represented as a vector $(x \times w, y \times w, z \times w, w)$ for any $w \neq 0$)
- ▶ In homogeneous coordinates, the origin is $(0, 0, 0, 1)$ not $(0, 0, 0, 0)$!

Matrices



Welcome to the Matrix, Neo.



Matrices

Matrices

- ▶ An $m \times n$ **matrix** is a rectangular array of numbers, having m rows and n columns

Matrices

- ▶ An $m \times n$ **matrix** is a rectangular array of numbers, having m rows and n columns

$$\begin{pmatrix} 3 & 0 & 2.4 \\ 1.7 & -6 & -4.5 \end{pmatrix} \quad \leftarrow \text{A } 2 \times 3 \text{ matrix}$$

Matrices

- ▶ An $m \times n$ **matrix** is a rectangular array of numbers, having m rows and n columns

$$\begin{pmatrix} 3 & 0 & 2.4 \\ 1.7 & -6 & -4.5 \end{pmatrix} \quad \leftarrow \text{A } 2 \times 3 \text{ matrix}$$

- ▶ Note: the plural of **matrix** is **matrices**

Matrices

- ▶ An $m \times n$ **matrix** is a rectangular array of numbers, having m rows and n columns

$$\begin{pmatrix} 3 & 0 & 2.4 \\ 1.7 & -6 & -4.5 \end{pmatrix} \quad \leftarrow \text{A } 2 \times 3 \text{ matrix}$$

- ▶ Note: the plural of **matrix** is **matrices**
- ▶ In computer graphics we mostly work with **square** matrices (number of rows = number of columns)

Multiplying vectors and matrices

Multiplying vectors and matrices

- ▶ Two $n \times n$ matrices can be **multiplied**, giving a new $n \times n$ matrix

Multiplying vectors and matrices

- ▶ Two $n \times n$ matrices can be **multiplied**, giving a new $n \times n$ matrix
- ▶ An $n \times n$ matrix and an n -vector can be **multiplied**, giving a new n -vector

Multiplying vectors and matrices

- ▶ Two $n \times n$ matrices can be **multiplied**, giving a new $n \times n$ matrix
- ▶ An $n \times n$ matrix and an n -vector can be **multiplied**, giving a new n -vector
- ▶ See <https://www.khanacademy.org/math/prec calculus/prec calc-matrices/multiplying-matrices-by-matrices/v/matrix-multiplication-intro>

Multiplying vectors and matrices

- ▶ Two $n \times n$ matrices can be **multiplied**, giving a new $n \times n$ matrix
- ▶ An $n \times n$ matrix and an n -vector can be **multiplied**, giving a new n -vector
- ▶ See <https://www.khanacademy.org/math/prec calculus/prec calc-matrices/multiplying-matrices-by-matrices/v/matrix-multiplication-intro>
- ▶ (But you don't really need to know how to calculate these manually...)

Commutativity

Commutativity

- Multiplication of numbers is **commutative**

Commutativity

- ▶ Multiplication of numbers is **commutative**
 - ▶ $a \times b = b \times a$

Commutativity

- ▶ Multiplication of numbers is **commutative**
 - ▶ $a \times b = b \times a$
 - ▶ e.g. $2 \times 3 = 3 \times 2$

Commutativity

- ▶ Multiplication of numbers is **commutative**
 - ▶ $a \times b = b \times a$
 - ▶ e.g. $2 \times 3 = 3 \times 2$
- ▶ Multiplication of matrices is **not commutative**

Commutativity

- ▶ Multiplication of numbers is **commutative**
 - ▶ $a \times b = b \times a$
 - ▶ e.g. $2 \times 3 = 3 \times 2$
- ▶ Multiplication of matrices is **not commutative**
 - ▶ In general, $A \times B \neq B \times A$

Commutativity

- ▶ Multiplication of numbers is **commutative**
 - ▶ $a \times b = b \times a$
 - ▶ e.g. $2 \times 3 = 3 \times 2$
- ▶ Multiplication of matrices is **not commutative**
 - ▶ In general, $A \times B \neq B \times A$
 - ▶ There may be some matrices where $A \times B = B \times A$, but they are the exception

Transformations



Transformations and matrices

Transformations and matrices

- ▶ A **transformation** is a **mathematical function** that **changes points in space**

Transformations and matrices

- ▶ A **transformation** is a **mathematical function** that **changes points in space**
- ▶ E.g. shifts them, rotates them, scales them, ...

Transformations and matrices

- ▶ A **transformation** is a **mathematical function** that **changes points in space**
- ▶ E.g. shifts them, rotates them, scales them, ...
- ▶ Many useful transformations can be **represented** by matrices

Transformations and matrices

- ▶ A **transformation** is a **mathematical function** that **changes points in space**
- ▶ E.g. shifts them, rotates them, scales them, ...
- ▶ Many useful transformations can be **represented** by matrices
- ▶ Multiplying these matrices together **combines** the transformations

Transformations and matrices

- ▶ A **transformation** is a **mathematical function** that **changes points in space**
- ▶ E.g. shifts them, rotates them, scales them, ...
- ▶ Many useful transformations can be **represented** by matrices
- ▶ Multiplying these matrices together **combines** the transformations
- ▶ Multiplying a vector by the matrix **applies** the transformation

GLM

We will use the **GLM** library to do matrix calculations for us

`http://glm.g-truc.net/`

GLM aims to mirror GLSL data types (`vec4`, `mat4` etc) in C++

Identity

Identity

The identity transformation does not change anything

Identity

The identity transformation does not change anything

```
// Default constructor for glm::mat4 creates an identity matrix ←  
glm::mat4 transform;
```

Translation

Translation

Translation shifts all points by the same vector offset

Translation

Translation shifts all points by the same vector offset

```
transform = glm::translate(transform, glm::vec3(0.3f, 0.5f, 0.0f));
```

Scaling

Scaling

Scaling moves all points closer or further from the origin by the same factor

Scaling

Scaling moves all points closer or further from the origin by the same factor

```
transform = glm::scale(transform, glm::vec3(1.2f, 0.5f ↵  
      , 1.0f));
```

Rotation

Rotation

- ▶ How do we represent a rotation in 3 dimensions?

Rotation

- ▶ How do we represent a rotation in 3 dimensions?
- ▶ One way is by specifying the **axis** (as a vector) and the **angle** (in radians)

Rotation

- ▶ How do we represent a rotation in 3 dimensions?
- ▶ One way is by specifying the **axis** (as a vector) and the **angle** (in radians)
- ▶ Axis always runs through the origin

Rotation

- ▶ How do we represent a rotation in 3 dimensions?
- ▶ One way is by specifying the **axis** (as a vector) and the **angle** (in radians)
- ▶ Axis always runs through the origin

```
float angle = glm::pi<float>() * 0.5f;  
glm::vec3 axis(0, 0, 1);  
transform = glm::rotate(transform, angle, axis);
```

Combining transformations

Combining transformations

```
transform = glm::translate(transform, glm::vec3(0.5f, ↵  
    0.5f, 0.0f));  
transform = glm::rotate(transform, angle, axis);
```

Combining transformations

```
transform = glm::translate(transform, glm::vec3(0.5f, 0.5f, 0.0f));  
transform = glm::rotate(transform, angle, axis);
```

- Transformations **do not commute** in general — changing the order will change the result

Combining transformations

```
transform = glm::translate(transform, glm::vec3(0.5f, 0.5f, 0.0f));  
transform = glm::rotate(transform, angle, axis);
```

- ▶ Transformations **do not commute** in general — changing the order will change the result
- ▶ The order they are applied is the **reverse** of what you might think — i.e. the above rotates **then** translates

Euler angles

Euler angles

- ▶ Any orientation of an object in 3D space can be described by **three** rotations around:

Euler angles

- ▶ Any orientation of an object in 3D space can be described by **three** rotations around:
 - ▶ The x-axis $(1, 0, 0)$

Euler angles


- ▶ Any orientation of an object in 3D space can be described by **three** rotations around:
 - ▶ The x -axis $(1, 0, 0)$
 - ▶ The y -axis $(0, 1, 0)$

Euler angles

- ▶ Any orientation of an object in 3D space can be described by **three** rotations around:
 - ▶ The x -axis $(1, 0, 0)$
 - ▶ The y -axis $(0, 1, 0)$
 - ▶ The z -axis $(0, 0, 1)$

Euler angles

- ▶ Any orientation of an object in 3D space can be described by **three** rotations around:
 - ▶ The x-axis (1, 0, 0)
 - ▶ The y-axis (0, 1, 0)
 - ▶ The z-axis (0, 0, 1)
- ▶ These angles are sometimes called **roll**, **pitch** and **yaw**



Gimbal lock

<https://youtu.be/rrUCBO1Jdt4?t=1m55s>