

COMP250: Artificial Intelligence


## **5: Game Tree Search**

# Next few weeks

- ▶ Week 5: now
- ▶ Week 6: no session (development week)
- ▶ Week 7: AI component peer review

# Minimax search

# Game trees



# Minimax

- ▶ Terminal game states have a **value**
  - ▶ E.g. +1 for a win, -1 for a loss, 0 for a draw
- ▶ I want to **maximise** the value
- ▶ My opponent wants to **minimise** the value
- ▶ Therefore I want to **maximise** the **minimum** value my opponent can achieve
- ▶ This is generally only true for **two-player zero-sum** games

# Minimax search

- ▶ Recursively defines a **value** for non-terminal game states
- ▶ Consider each possible “next state”, i.e. each possible move
- ▶ If it's my turn, the value is the **maximum** value over next states
- ▶ If it's my opponent's turn, the value is the **minimum** value over next states

# Minimax search – example

# Minimax search pseudocode

```
procedure MINIMAX(state, currentPlayer)
  if state is terminal then
    return value of state
  else if currentPlayer = 1 then
    bestValue =  $-\infty$ 
    for each possible nextState do
       $v = \text{MINIMAX}(\text{nextState}, 3 - \text{currentPlayer})$ 
      bestValue = MAX(bestValue,  $v$ )
    return bestValue
  else if currentPlayer = 2 then
    bestValue =  $+\infty$ 
    for each possible nextState do
       $v = \text{MINIMAX}(\text{nextState}, 3 - \text{currentPlayer})$ 
      bestValue = MIN(bestValue,  $v$ )
    return bestValue
```



# Stopping early

**for each** possible nextState **do**

$v = \text{MINIMAX}(\text{nextState}, 3 - \text{currentPlayer})$

$\text{bestValue} = \text{MAX}(\text{bestValue}, v)$

- ▶ State values are always between  $-1$  and  $+1$
- ▶ So if we ever have  $\text{bestValue} = 1$ , we can stop early
- ▶ Similarly when minimising if  $\text{bestValue} = -1$

# Using minimax search

- ▶ To decide what move to play next...
- ▶ Calculate the minimax value for each move
- ▶ Choose the move with the maximum score
- ▶ If there are several with the same score, choose one at random

# Minimax and game theory

- ▶ For a **two-player zero-sum** game with **perfect information** and **sequential moves**
- ▶ Minimax search will always find a **Nash equilibrium**
- ▶ I.e. a minimax player plays **perfectly**
- ▶ **But...**

# Minimax for larger games

- ▶ The game tree for noughts and crosses has only a few thousand states
- ▶ Most games are too large to search fully
  - ▶ Connect 4 has  $\approx 10^{13}$  states
  - ▶ Chess has  $\approx 10^{47}$  states

**Heuristics for search**

# Depth limiting

- ▶ Standard minimax needs to search all the way to **terminal** (game over) states
- ▶ **Depth limiting** is a common technique to apply minimax to larger games
- ▶ Still evaluate terminal states as  $+1 / 0 / -1$
- ▶ For nonterminal states at depth  $d$ , apply a heuristic evaluation instead of searching deeper
- ▶ Evaluation is a number between  $-1$  and  $+1$ , estimating the probable outcome of the game

# 1-ply search

- ▶ Case  $d = 1$
- ▶ For each move, evaluate the state resulting from playing that move
- ▶ This is computationally fast
- ▶ Often easier to design a “which state is better” heuristic than to directly design a “which move to play” heuristic

# Move ordering

- ▶ Minimax can **stop early** if it sees a value of  $+1$  for maximising player or  $-1$  for minimising player
- ▶ Modifications to minimax algorithm (e.g. **alpha-beta pruning**) lead to more of this
- ▶ Thus ordering moves from **best to worst** means faster search
- ▶ How do we know which moves are “best” and “worst”? Use a heuristic!



# Designing heuristics

- ▶ The **playing strength** of depth limited minimax depends heavily on the design of the **heuristic**
- ▶ Good heuristic design requires **in-depth knowledge** of the tactics and strategy of the game
- ▶ Next time we will look at what we can do if we don't possess such knowledge

**Monte Carlo evaluation**

# From last time

- ▶ It is useful to have a **heuristic evaluation function** for nonterminal states
- ▶ Allows 1-ply search, depth-limited minimax, ...
- ▶ Designing a good heuristic requires in-depth knowledge of the game
- ▶ What if you don't have such knowledge?

# Expected value

- ▶ Let  $X$  be a **random variable**
- ▶ Let  $p(x)$  be the probability that  $X$  has value  $x$
- ▶ Then the **expected value** of  $X$  is

$$\sum_x x \cdot p(x)$$

# Expected value — example

- ▶ A slot machine pays out:
  - ▶ £1 with probability 0.05
  - ▶ £5 with probability 0.03
  - ▶ £10 with probability 0.02
  - ▶ Nothing with probability 0.9
- ▶ The expected payout is

$$1 \times 0.05 + 5 \times 0.03 + 10 \times 0.02 + 0 \times 0.9 = 0.4$$

i.e. £0.40

- ▶ What this means: if you play the slot machine  $N$  times, on average you will win  $N \times £0.40$

# “Randomness” in computing

- ▶ Digital computers are **deterministic**, so there's no such thing as true randomness
  - ▶ Cryptographically secure systems use an external source of randomness e.g. atmospheric noise, radioactive decay
- ▶ What we actually have are **pseudo-random number generators (PRNGs)**
- ▶ A PRNG is an algorithm which gives an **unpredictable** sequence of numbers based on a **seed**
- ▶ Sequence is **uniformly distributed**, i.e. all numbers have equal probability
- ▶ Seed is generally based on some source of **entropy**, e.g. system clock, mouse input, electronic noise

# Monte Carlo methods

- ▶ In computing, a **Monte Carlo method** is an algorithm based on **averaging over random samples**
- ▶ The **average** over a large number of samples is a good approximation of the **expected value**
- ▶ Used for **quickly approximating** quantities over **large domains**
- ▶ Generally designed to **converge in the limit**
  - ▶ An **infinite** number of samples would give an **exact** answer
  - ▶ As the **number of samples** increases, the **accuracy** of the answer improves
- ▶ Applications in physics, engineering, finance, weather forecasting, graphics, ...

# Monte Carlo evaluation in games

- ▶ Based on **random rollouts**

**while**  $s$  is not terminal **do**

    let  $m$  be a random legal move from  $s$

    update  $s$  by playing  $m$

- ▶ The **value** of a rollout is the **value** of the terminal state it reaches (i.e. 1 for a win,  $-1$  for a loss, 0 for a draw)
- ▶ Averaging gives the **expected value** of the initial state
- ▶ Higher expected value = more chance of winning



# Monte Carlo search

- ▶ **Flat Monte Carlo search:** 1-ply search with Monte Carlo evaluation
- ▶ How about minimax with  $d > 1$  and Monte Carlo evaluation?
  - ▶ Minimax assumes the evaluation is **deterministic**, but Monte Carlo is not
  - ▶ Not commonly used, mainly because there's something better...

# Monte Carlo Tree Search


# Monte Carlo Tree Search (MCTS)

- ▶ Like Monte Carlo evaluation, based on **rollouts**
- ▶ First few rollouts are **random**
- ▶ However, statistics from these rollouts are used to **bias** future rollouts
- ▶ Bias rollouts towards **plausible** lines of play, i.e. where each player is trying to play the best move

# The MCTS algorithm

- ▶ MCTS builds a **tree**
- ▶ Initially, the tree consists of a single **root node**
- ▶ Each rollout has four stages:
  - ▶ **Selection:** Starting from the root, descend the tree by choosing moves. Continue until we reach a node which does not yet have children for all legal moves.
  - ▶ **Expansion:** Choose a random legal move for which the current node does not have a child node. Add this new node to the tree.
  - ▶ **Simulation:** Perform a Monte Carlo rollout, playing random moves until a terminal state is reached.
  - ▶ **Backpropagation:** For each node visited during **selection** and **expansion**, update the node's statistics based on the result of the simulation.
- ▶ Perform many rollouts, then use the statistics at the top level of the tree to choose the best move

# The MCTS algorithm



# Selection policy

- ▶ Selection must balance:
  - ▶ **Exploitation** of moves that are known to be good
  - ▶ **Exploration** of moves that have not often been tried
- ▶ This can be modelled as a **multi-armed bandit problem**

# Multi-armed bandits

- ▶ We have a row of one-armed bandits (slot machines)
- ▶ We **do not know** the payout probabilities of any of them, and they're all different
- ▶ How to maximise our winnings?
- ▶ Again must balance
  - ▶ **Exploitation** of machines that are known to have a high expected payout
  - ▶ **Exploration** of machines that have not been tried often, to get a better estimate of their expected payout

# Upper Confidence Bound (UCB)

- ▶ For each machine  $m$ , record:
  - ▶  $n_m$ : the number of plays of this machine
  - ▶  $V_m$ : the total winnings from playing this machine
  - ▶  $n = \sum_m n_m$ , total number of plays across all machines
- ▶ At each stage, play the machine for which

$$\frac{V_m}{n_m} + c\sqrt{\frac{\log n}{n_m}}$$

is largest

- ▶  $\frac{V_m}{n_m}$  is the **exploitation** part: average payout from this machine so far
- ▶  $\sqrt{\frac{\log n}{n_m}}$  is the **exploration** part: large if  $n_m$  is small
- ▶  $c$  is a parameter for adjusting the balance between exploitation and exploration



# UCB demo

`http://orangehelicopter.com/academic/bandits.html?ucb`

# Upper Confidence Bound for Trees (UCT)

- ▶ Use UCB as the selection policy
- ▶ In each node  $x$ , record:
  - ▶  $n_x$ : the number of visits to this node
  - ▶  $V_x$ : the total value of rollouts through this node
- ▶ From node  $p$ , choose the child  $q$  such that

$$\frac{V_q}{n_q} + c \sqrt{\frac{\log n_p}{n_q}}$$

is largest

# UCT demo

# Benefits of MCTS

- ▶ “Vanilla” MCTS is **game independent**
- ▶ But if game-specific heuristics are available, they can be used to **enhance** MCTS
- ▶ MCTS is **anytime**
  - ▶ Can stop it after **any** amount of computation (within reason) and get a reasonably good answer
  - ▶ Compare with minimax:  $O(e^d)$  for depth  $d$
- ▶ Does not suffer from **horizon effect**
  - ▶ Minimax at depth  $d$  cannot “see” what happens  $d + 1$  moves in the future
  - ▶ MCTS can build the tree as deep as it likes
  - ▶ Selects which parts of the tree to expand more deeply

# Workshop

# Workshop

- ▶ Clone `https://github.com/Falmouth-Games-Academy/comp250-workshop-5`
- ▶ This is an implementation of Connect-4 in Python 3 with PyGame
- ▶ Edit `ai_player.py` to implement MCTS
- ▶ Use `http://mcts.ai/code/python.html` as a guide