



COMP140: Creative Computing: Codecraft

# 6: Data Structures, Collections, & Generic Types

# Learning outcomes

- ▶ **Understand** the various collection classes in C++
- ▶ **Compare** the collection classes
- ▶ **Implement** an application which uses collection classes

# Common Data Structures



# Introduction

# Introduction

- ▶ In Programming we have concept of reusable data structures which can be used to build applications

# Introduction

- ▶ In Programming we have concept of reusable data structures which can be used to build applications
- ▶ These can be used in order to build larger systems (e.g. Inventory Systems, AI Navigation etc)

# Introduction

- ▶ In Programming we have concept of reusable data structures which can be used to build applications
- ▶ These can be used in order to build larger systems (e.g. Inventory Systems, AI Navigation etc)
- ▶ Most programming languages have these built in

# Introduction

- ▶ In Programming we have concept of reusable data structures which can be used to build applications
- ▶ These can be used in order to build larger systems (e.g. Inventory Systems, AI Navigation etc)
- ▶ Most programming languages have these built in
- ▶ Before writing any system you should always examine these data structures and pick the appropriate one for your Use Case



# Dynamic Array



# The Problem

# The Problem

- ▶ Arrays in C++ are fixed in size

# The Problem

- ▶ Arrays in C++ are fixed in size
- ▶ During development you need to know exactly how many item are going to be in the array

# The Problem

- ▶ Arrays in C++ are fixed in size
- ▶ During development you need to know exactly how many item are going to be in the array
- ▶ If you need to add elements and you don't have enough space, you will need to carry out the following

# The Problem

- ▶ Arrays in C++ are fixed in size
- ▶ During development you need to know exactly how many items are going to be in the array
- ▶ If you need to add elements and you don't have enough space, you will need to carry out the following
  - ▶ Create a new array of the appropriate size

# The Problem

- ▶ Arrays in C++ are fixed in size
- ▶ During development you need to know exactly how many items are going to be in the array
- ▶ If you need to add elements and you don't have enough space, you will need to carry out the following
  - ▶ Create a new array of the appropriate size
  - ▶ Copy elements from the old array into this new one

# The Problem

- ▶ Arrays in C++ are fixed in size
- ▶ During development you need to know exactly how many items are going to be in the array
- ▶ If you need to add elements and you don't have enough space, you will need to carry out the following
  - ▶ Create a new array of the appropriate size
  - ▶ Copy elements from the old array into this new one
  - ▶ Destroy the old array



# The Problem

- ▶ Arrays in C++ are fixed in size
- ▶ During development you need to know exactly how many item are going to be in the array
- ▶ If you need to add elements and you don't have enough space, you will need to carry out the following
  - ▶ Create a new array of the appropriate size
  - ▶ Copy elements from the old array into this new one
  - ▶ Destroy the old array
  - ▶ Add in the new element

# The Problem

- ▶ Arrays in C++ are fixed in size
- ▶ During development you need to know exactly how many item are going to be in the array
- ▶ If you need to add elements and you don't have enough space, you will need to carry out the following
  - ▶ Create a new array of the appropriate size
  - ▶ Copy elements from the old array into this new one
  - ▶ Destroy the old array
  - ▶ Add in the new element
- ▶ The above process can be quite costly

# The Solution

# The Solution

- ▶ Luckily in most programming languages we have a Data Structure which grows in size when we require it

# The Solution

- ▶ Luckily in most programming languages we have a Data Structure which grows in size when we require it
  - ▶ In C++ we have the **vector** class

# The Solution

- ▶ Luckily in most programming languages we have a Data Structure which grows in size when we require it
  - ▶ In C++ we have the **vector** class
- ▶ These classes have the same properties as an array

# The Solution

- ▶ Luckily in most programming languages we have a Data Structure which grows in size when we require it
  - ▶ In C++ we have the **vector** class
- ▶ These classes have the same properties as an array
  - ▶ Items are located contiguously in memory

# The Solution

- ▶ Luckily in most programming languages we have a Data Structure which grows in size when we require it
  - ▶ In C++ we have the **vector** class
- ▶ These classes have the same properties as an array
  - ▶ Items are located contiguously in memory
  - ▶ We can randomly access elements using an index



# The Solution

- ▶ Luckily in most programming languages we have a Data Structure which grows in size when we require it
  - ▶ In C++ we have the **vector** class
- ▶ These classes have the same properties as an array
  - ▶ Items are located contiguously in memory
  - ▶ We can randomly access elements using an index
  - ▶ We can iterate through each element

# The Solution

- ▶ Luckily in most programming languages we have a Data Structure which grows in size when we require it
  - ▶ In C++ we have the **vector** class
- ▶ These classes have the same properties as an array
  - ▶ Items are located contiguously in memory
  - ▶ We can randomly access elements using an index
  - ▶ We can iterate through each element
- ▶ You should consider using a Dynamic Array over a normal array

# The Solution

- ▶ Luckily in most programming languages we have a Data Structure which grows in size when we require it
  - ▶ In C++ we have the **vector** class
- ▶ These classes have the same properties as an array
  - ▶ Items are located contiguously in memory
  - ▶ We can randomly access elements using an index
  - ▶ We can iterate through each element
- ▶ You should consider using a Dynamic Array over a normal array
- ▶ One caveat, Dynamic Arrays are more expensive

# Use Case

# Use Case

- ▶ Manage Enemies as they are spawned into the scene

# Use Case

- ▶ Manage Enemies as they are spawned into the scene
- ▶ Keep track of players as they are added into the game

# Use Case

- ▶ Manage Enemies as they are spawned into the scene
- ▶ Keep track of players as they are added into the game
- ▶ Inventory systems

# C++ Vector Example

```
vector<int> scores;  
scores.push_back(100);  
scores.push_back(200);  
for (int score : scores)  
{  
    std::cout<<"Score is "<<score<<std::endl;  
}  
int player1Score=scores[0];  
scores.erase(scores.begin()+1);
```



# Additional Notes

# Additional Notes

- ▶ Try to avoid insertion/deleting in the middle of the collection

# Additional Notes

- ▶ Try to avoid insertion/deleting in the middle of the collection
- ▶ Searching the collection is linear elements and will increase as more elements are added ( $O(n)$ )

# Additional Notes

- ▶ Try to avoid insertion/deleting in the middle of the collection
- ▶ Searching the collection is linear elements and will increase as more elements are added ( $O(n)$ )
- ▶ insertion/deleting at the end of the collection is constant in performance ( $O(1)$ )

# Generic Types



# Quick Aside - Generic Programming

# Quick Aside - Generic Programming

- ▶ Generic Programming is where you write one piece of code which operates on many different types

# Quick Aside - Generic Programming

- ▶ Generic Programming is where you write one piece of code which operates on many different types
- ▶ This uses a concept called Templates which act in proxy for the type



# Quick Aside - Generic Programming

- ▶ Generic Programming is where you write one piece of code which operates on many different types
- ▶ This uses a concept called Templates which act in proxy for the type
- ▶ The Compiler then generates the code which uses the actual type

# Look back at Vector/List

# Look back at Vector/List

- ▶ In the previous section you would have noticed the following

# Look back at Vector/List

- ▶ In the previous section you would have noticed the following
  - ▶ `vector<int>`

# Look back at Vector/List

- ▶ In the previous section you would have noticed the following
  - ▶ `vector<int>`
- ▶ These are known as generic parameters and you should insert the data type that the collection will handle (including your own data types aka classes and structs)

# Generic Programming

# Generic Programming

- ▶ You can write your own generic classes and functions but this is beyond the scope of this class

# Generic Programming

- ▶ You can write your own generic classes and functions but this is beyond the scope of this class
- ▶ C++ examples - <https://www.codeproject.com/Articles/257589/An-Idiots-Guide-to-Cplusplus-Templates-Part>



# Generic Programming

- ▶ You can write your own generic classes and functions but this is beyond the scope of this class
- ▶ C++ examples - <https://www.codeproject.com/Articles/257589/An-Idiots-Guide-to-Cplusplus-Templates-Part>
- ▶ Word of warning, it is often difficult to write generic code

# Generic Programming

- ▶ You can write your own generic classes and functions but this is beyond the scope of this class
- ▶ C++ examples - <https://www.codeproject.com/Articles/257589/An-Idiots-Guide-to-Cplusplus-Templates-Part>
- ▶ Word of warning, it is often difficult to write generic code
- ▶ If you have errors they are often difficult to isolate as the compiler messages are so cryptic

# Linked List



# The Problem

# The Problem

- ▶ You have started using a dynamic array and you have notice performance is poor on adding/removing

# The Problem

- ▶ You have started using a dynamic array and you have notice performance is poor on adding/removing
- ▶ You then realise that you are adding/removing elements from the middle of the collection

# The Problem

- ▶ You have started using a dynamic array and you have notice performance is poor on adding/removing
- ▶ You then realise that you are adding/removing elements from the middle of the collection
- ▶ You also realise that you don't require random access to elements in the collection

# The Solution



# The Solution

- ▶ In this case a Linked List would be a better choice

# The Solution

- ▶ In this case a Linked List would be a better choice
  - ▶ In C++ we have the **list** class

# The Solution

- ▶ In this case a Linked List would be a better choice
  - ▶ In C++ we have the **list** class
- ▶ Linked Lists contain elements (called Nodes) which usually have a reference (or pointer) to the previous and next Node in the list

# The Solution

- ▶ In this case a Linked List would be a better choice
  - ▶ In C++ we have the **list** class
- ▶ Linked Lists contain elements (called Nodes) which usually have a reference (or pointer) to the previous and next Node in the list
- ▶ This means that there is a slight increase in memory needed when working with lists

# Use Case

# Use Case

- ▶ If you AI character has to visit a series of waypoints, these could be stored in a list

# Use Case

- ▶ If you AI character has to visit a series of waypoints, these could be stored in a list
- ▶ Your Player has a number of quests they can try and complete

# Use Case

- ▶ If you AI character has to visit a series of waypoints, these could be stored in a list
- ▶ Your Player has a number of quests they can try and complete
- ▶ If the AI/Player carries an action and a number of systems need to be notified of the event



# C++ List Example

```
list<vec2> waypoints;

waypoints.push_back(vec2(10,10));
waypoints.push_back(vec2(15,15));
waypoints.push_back(vec2(20,20));

for(vec2 position:waypoints)
{
    std::cout<<"Waypoint Locations "<<position.x<< " ←
               " "<<position.y<<std::endl;
}
```

# C++ List Example

```
waypoints.push_front(vec2(0,0));  
  
auto iter=std::find(waypoints.begin(),waypoints. ←  
                    end(),vec2(15,15));  
waypoints.insert(iter, vec3(25,25));
```

# Additional Notes

# Additional Notes

- ▶ Linked Lists usually support constant time insertions and deletions in the collection ( $O(1)$ )

# Additional Notes

- ▶ Linked Lists usually support constant time insertions and deletions in the collection ( $O(1)$ )
- ▶ Also perform better than dynamic arrays for moving elements around the collection

# Additional Notes

- ▶ Linked Lists usually support constant time insertions and deletions in the collection ( $O(1)$ )
- ▶ Also perform better than dynamic arrays for moving elements around the collection
- ▶ This feature means that Linked Lists are a good data structure if you need to sort your data

# Additional Notes

- ▶ Linked Lists usually support constant time insertions and deletions in the collection ( $O(1)$ )
- ▶ Also perform better than dynamic arrays for moving elements around the collection
- ▶ This feature means that Linked Lists are a good data structure if you need to sort your data
- ▶ Main drawback of Linked Lists is that you can't have direct access to elements in the list, it takes linear time ( $O(n)$ ) to access

Queue





# The Problem

# The Problem

- ▶ If you need to visit items in a certain (e.g front to back)

# The Problem

- ▶ If you need to visit items in a certain (e.g front to back)
- ▶ Examples of this could be waypoints or commands to an AI character

# The Solution

# The Solution

- ▶ In this case a Queue would be a good choice

# The Solution

- ▶ In this case a Queue would be a good choice
  - ▶ in C++ we have the **queue** class

# The Solution

- ▶ In this case a Queue would be a good choice
  - ▶ in C++ we have the **queue** class
- ▶ This is **First-In-Last-Out** data structure

# The Solution

- ▶ In this case a Queue would be a good choice
  - ▶ in C++ we have the **queue** class
- ▶ This is **First-In-Last-Out** data structure
- ▶ You add elements to the end of the queue and you remove elements from the start



# Use Case

# Use Case

- ▶ An RTS game where you can add orders to a unit, these are then carried out sequence

# Use Case

- ▶ An RTS game where you can add orders to a unit, these are then carried out sequence
- ▶ An RTS where you have a base which produces units

# Use Case

- ▶ An RTS game where you can add orders to a unit, these are then carried out sequence
- ▶ An RTS where you have a base which produces units
- ▶ A spawning system, where you have to defeat enemies in a specific order

# C++ Queue Example

```
queue<Command> aiCommands;  
  
aiCommands.push(Command("Attack"));  
aiCommands.push(Command("Recharge"));  
aiCommands.push(Command("Run"));
```

# C++ Queue Example

```
Command nextCommand=aiCommands.front();  
  
aiCommands.pop();
```

# Stack



# The Problem



# The Problem

- ▶ If you need to manage the state of an AI character

# The Problem

- ▶ If you need to manage the state of an AI character
- ▶ If you need to implement a Undo system

# The Solution

# The Solution

- ▶ A Stack would be a good choice

# The Solution

- ▶ A Stack would be a good choice
  - ▶ in C++ we have the **stack** class

# The Solution

- ▶ A Stack would be a good choice
  - ▶ in C++ we have the **stack** class
- ▶ This is **Last-In-First-Out** data structure

# The Solution

- ▶ A Stack would be a good choice
  - ▶ in C++ we have the **stack** class
- ▶ This is **Last-In-First-Out** data structure
- ▶ You add elements to the top of the stack and you remove elements from the top

# C++ Stack Example

```
stack<AIState> aiStates;  
  
aiStates.push(Command("Attack"));  
aiStates.push(Command("Idle"));  
aiStates.push(Command("Run"));
```



# C++ Stack Example

```
Command lastState=aiStates.top();  
  
aiStates.pop()
```

# Associative Array: Map & Dictionary



# The Problem

# The Problem

- ▶ If you need to store one unique copy of an element

# The Problem

- ▶ If you need to store one unique copy of an element
- ▶ You want to access an element via a key

# The Problem

- ▶ If you need to store one unique copy of an element
- ▶ You want to access an element via a key
- ▶ You are doing lots of searches for an element

# The Solution

# The Solution

- ▶ You should use an Associative array



# The Solution

- ▶ You should use an Associative array
  - ▶ in C++ we have the **map** or **unordered\_map** class

# The Solution

- ▶ You should use an Associative array
  - ▶ in C++ we have the **map** or **unordered\_map** class
- ▶ These data structures are structured as key-value pair

# The Solution

- ▶ You should use an Associative array
  - ▶ in C++ we have the **map** or **unordered\_map** class
- ▶ These data structures are structured as key-value pair
- ▶ It allows you to retrieve the items via the key

# The Solution

- ▶ You should use an Associative array
  - ▶ in C++ we have the **map** or **unordered\_map** class
- ▶ These data structures are structured as key-value pair
- ▶ It allows you to retrieve the items via the key
- ▶ This makes it a good choice for looking up large data sets

# Use Case

# Use Case

- ▶ If you are creating a resource management system for handling textures, models or other assets

# Use Case

- ▶ If you are creating a resource management system for handling textures, models or other assets
- ▶ Localisation system, each language is stored in an Associative Array

# Use Case

- ▶ If you are creating a resource management system for handling textures, models or other assets
- ▶ Localisation system, each language is stored in an Associative Array
- ▶ Unit Manager, a class to manage units created in the game



# Use Case

- ▶ If you are creating a resource management system for handling textures, models or other assets
- ▶ Localisation system, each language is stored in an Associative Array
- ▶ Unit Manager, a class to manage units created in the game
- ▶ Save Game System

# C++ Map Example

```
Map<string, int> highScores;

highScores["Brian"]=200;
highScores["Sarah"]=2000;
highScores["Julia"]=4000;

for(auto iter : highScores)
{
    std::cout<<"High Score "+iter.first<<" "<<iter. ←
        second<<std::endl;
}
```

# C++ Map Example

```
auto iter=highScores.find("Brian");  
if (iter!=highScores.end())  
{  
    int score=highScores["Brian"];  
}  
  
highScores.erase("Sarah");
```

# Additional Notes

# Additional Notes

- ▶ Iterating over a map has a slightly annoying syntax

# Additional Notes

- ▶ Iterating over a map has a slightly annoying syntax
- ▶ Associative Arrays tend to have good performance for retrieval ( $O(\log n)$ )

# Additional Notes

- ▶ Iterating over a map has a slightly annoying syntax
- ▶ Associative Arrays tend to have good performance for retrieval ( $O(\log n)$ )
- ▶ If you add an item and its key already exists it may overwrite the value

# Operations on collections





# Sorting

# Sorting

- ▶ Sorting is where we order the items in a collection in a specific order

# Sorting

- ▶ Sorting is where we order the items in a collection in a specific order
- ▶ There are a whole bunch of sorting algorithms including; Insertion sort, Heap sort, Quick sort (please read about these!)

# Sorting

- ▶ Sorting is where we order the items in a collection in a specific order
- ▶ There are a whole bunch of sorting algorithms including; Insertion sort, Heap sort, Quick sort (please read about these!)
- ▶ In C++, this depends on the compiler implementation

# Sorting

- ▶ Sorting is where we order the items in a collection in a specific order
- ▶ There are a whole bunch of sorting algorithms including; Insertion sort, Heap sort, Quick sort (please read about these!)
- ▶ In C++, this depends on the compiler implementation
- ▶ Most of the common data types don't need additional work

# Sorting

- ▶ Sorting is where we order the items in a collection in a specific order
- ▶ There are a whole bunch of sorting algorithms including; Insertion sort, Heap sort, Quick sort (please read about these!)
- ▶ In C++, this depends on the compiler implementation
- ▶ Most of the common data types don't need additional work
- ▶ For custom classes, we have to write our own sorting algorithm

# Sorting C++

# Sorting C++

- ▶ There are few ways to sort a collection



# Sorting C++

- ▶ There are few ways to sort a collection
  1. Provide a custom function for the sort

# Sorting C++

- ▶ There are few ways to sort a collection
  1. Provide a custom function for the sort
  2. Provide a lambda expression for the sort

# Sorting C++

- ▶ There are few ways to sort a collection
  1. Provide a custom function for the sort
  2. Provide a lambda expression for the sort
  3. Your own class has to override the < operator

# Sorting C++

- ▶ There are few ways to sort a collection
  1. Provide a custom function for the sort
  2. Provide a lambda expression for the sort
  3. Your own class has to override the < operator
- ▶ Often you will use option 3 as the default sort

# Sorting C++

- ▶ There are few ways to sort a collection
  1. Provide a custom function for the sort
  2. Provide a lambda expression for the sort
  3. Your own class has to override the < operator
- ▶ Often you will use option 3 as the default sort
- ▶ Which then be override by option 1

# Sorting C++

- ▶ There are few ways to sort a collection
  1. Provide a custom function for the sort
  2. Provide a lambda expression for the sort
  3. Your own class has to override the < operator
- ▶ Often you will use option 3 as the default sort
- ▶ Which then be override by option 1
- ▶ 2 is probably the more modern way of doing it, but syntax can be confusing

# Sorting C++

- ▶ There are few ways to sort a collection
  1. Provide a custom function for the sort
  2. Provide a lambda expression for the sort
  3. Your own class has to override the < operator
- ▶ Often you will use option 3 as the default sort
- ▶ Which then be override by option 1
- ▶ 2 is probably the more modern way of doing it, but syntax can be confusing
- ▶ You have to include the **<algorithm>** header file

# C++ Example - Sorting with Function

```
struct Character
{
    std::string name;
    int health;
    int strength;
}

bool sortByHealth(Character a, Character b){return a. ↵
    health<b.health;}

//Adding omitted!
vector<Character> characters;

//Sort by health
sort(characters.begin(), characters.end(), ↵
    sortByHealth);
```



# C++ Example - Sorting < operator

```
struct Character
{
    std::string name;
    int health;
    int strength;

    bool operator <(const Character& other) const {return ←
        name<other.name;}
}

//Adding omitted!
vector<Character> characters;

//Sort by health
sort(characters.begin(), characters.end());
```

# Exercise



# Exercise 1 - Collections

1. Download one of the following projects as a zip file
  - ▶ BA Students - <https://github.com/Falmouth-Games-Academy/GAM160-Exercises>
  - ▶ BSc Students - <https://github.com/Falmouth-Games-Academy/COMP140-Exercises>
2. Add additional items to the collection
3. Display these to the screen

# Exercise 2 - Sorting

1. Write a default sort, so that the items are sorted by name
2. Sort the collection when the **s** key is pressed
3. Write another sort, to sort by score, trigger this off by a key press
4. Write another sort, to sort by age, trigger this off by a key press

# Exercise 3 - Searching

1. Investigate how to search for items in collections
2. Add code to search for specific items in the collections
3. Add visual representation to show that the search has completed, this could be a colour change or just displaying the found item elsewhere on the screen

# References

[https://docs.unrealengine.com/latest/INT/  
Programming/Development/CodingStandard/](https://docs.unrealengine.com/latest/INT/Programming/Development/CodingStandard/)