



COMP110: Principles of Computing  
**9: Data Structures II**

# Generics in C#



# The problem

# The problem

- ▶ Suppose we want to define a `Pair` class to store two values

# The problem

- ▶ Suppose we want to define a `Pair` class to store two values
- ▶ Something like this...

# The problem

- ▶ Suppose we want to define a `Pair` class to store two values
- ▶ Something like this...

```
class PairOfInts
{
    public int first;
    public int second;

    public PairOfInts(int f, int s)
    {
        first = f;
        second = s;
    }
}
```

# The problem

# The problem

- ▶ This is fine if we just want pairs of `ints`

# The problem

- ▶ This is fine if we just want pairs of `ints`
- ▶ To store a pair of `strings` we would need another class:

# The problem

- ▶ This is fine if we just want pairs of `ints`
- ▶ To store a pair of `strings` we would need another class:

```
class PairOfStrings
{
    public string first;
    public string second;

    public PairOfStrings(string f, string s)
    {
        first = f;
        second = s;
    }
}
```

# The problem

# The problem

- ▶ This quickly gets repetitive!

# The problem

- ▶ This quickly gets repetitive!
- ▶ We could just store a pair of `objects` — in C# `object` can store values of any type

# The problem

- ▶ This quickly gets repetitive!
- ▶ We could just store a pair of `objects` — in C# `object` can store values of any type

```
class PairOfObjects
{
    public object first;
    public object second;

    public PairOfObjects(object f, object s)
    {
        first = f;
        second = s;
    }
}
```

# The problem

- ▶ This quickly gets repetitive!
- ▶ We could just store a pair of `objects` — in C# `object` can store values of any type

```
class PairOfObjects
{
    public object first;
    public object second;

    public PairOfObjects(object f, object s)
    {
        first = f;
        second = s;
    }
}
```

- ▶ However this doesn't let us impose type safety

# The solution

# The solution

- ▶ **Generics** are a feature of C# which let us pass types as “parameters”

# The solution

- ▶ **Generics** are a feature of C# which let us pass types as “parameters”

```
class Pair<ElementType>
{
    public ElementType first;
    public ElementType second;

    public PairOfObjects(ElementType f, ElementType s)
    {
        first = f;
        second = s;
    }
}
```

# The solution

- ▶ **Generics** are a feature of C# which let us pass types as “parameters”

```
class Pair<ElementType>
{
    public ElementType first;
    public ElementType second;

    public PairOfObjects(ElementType f, ElementType s)
    {
        first = f;
        second = s;
    }
}
```

- ▶ ElementType can be any type

# The solution

# The solution

- ▶ When we instantiate the generic class, we pass in the type in angle brackets:

# The solution

- When we instantiate the generic class, we pass in the type in angle brackets:

```
Pair<int> p1 = new Pair<int>(12, 34);  
Pair<string> p2 = new Pair<string>("hello", "world");
```

# Multiple parameters

# Multiple parameters

- Generics can take multiple parameters:

# Multiple parameters

- Generics can take multiple parameters:

```
class Pair<Type1, Type2>
{
    public Type1 first;
    public Type2 second;

    public PairOfObjects(Type1 f, Type2 s)
    {
        first = f;
        second = s;
    }
}
```

```
Pair<int, string> x = new Pair<int, string>(123, "hello");
```

# Why generics?

# Why generics?

- ▶ Generics let us write type safe code which can be adapted to data of different types

# Why generics?

- ▶ Generics let us write type safe code which can be adapted to data of different types
- ▶ Standard libraries in .NET and Unity make use of generics for e.g. collection types

# Why generics?

- ▶ Generics let us write type safe code which can be adapted to data of different types
- ▶ Standard libraries in .NET and Unity make use of generics for e.g. collection types
- ▶ Similar to **templates** in C++

# Basic data structures in C#



# Classes and interfaces

# Classes and interfaces

- ▶ A **class** in C# defines constructors, destructor, methods, properties, fields, ...

# Classes and interfaces

- ▶ A **class** in C# defines constructors, destructor, methods, properties, fields, ...
- ▶ An **interface** defines methods and properties which a class can implement

# Classes and interfaces

- ▶ A **class** in C# defines constructors, destructor, methods, properties, fields, ...
- ▶ An **interface** defines methods and properties which a class can implement
- ▶ An interface is a little like a fully abstract class

# Classes and interfaces

- ▶ A **class** in C# defines constructors, destructor, methods, properties, fields, ...
- ▶ An **interface** defines methods and properties which a class can implement
- ▶ An interface is a little like a fully abstract class
- ▶ A class in C# can only **inherit** from one **class**, but can **implement** several **interfaces**

# IEnumerable

# IEnumerable

- Most collection types in C# implement the `IEnumerable<ElementType>` interface

# IEnumerable

- ▶ Most collection types in C# implement the `IEnumerable<ElementType>` interface
- ▶ This interface allows us to iterate through the elements in the collection, from beginning to end

# IEnumerable

- ▶ Most collection types in C# implement the `IEnumerable<ElementType>` interface
- ▶ This interface allows us to iterate through the elements in the collection, from beginning to end
- ▶ C# provides the `foreach` loop as a convenient way of using this

# IEnumerable

- ▶ Most collection types in C# implement the `IEnumerable<ElementType>` interface
- ▶ This interface allows us to iterate through the elements in the collection, from beginning to end
- ▶ C# provides the `foreach` loop as a convenient way of using this
- ▶ ⇒ any class which implements `IEnumerable<ElementType>` can be used with a `foreach` loop

# Arrays

```
int[] myArray = new int[10];
int[] anotherArray = new int[] { 123, 456, 789 };
```

# Arrays

```
int[] myArray = new int[10];  
int[] anotherArray = new int[] { 123, 456, 789 };
```

- ▶ `int[]` is an array of `ints`

# Arrays

```
int[] myArray = new int[10];
int[] anotherArray = new int[] { 123, 456, 789 };
```

- ▶ `int[]` is an array of `ints`
- ▶ In general, `ElementType[]` is an array of values of type `ElementType`

# Arrays

```
int[] myArray = new int[10];  
int[] anotherArray = new int[] { 123, 456, 789 };
```

- ▶ `int[]` is an array of `ints`
- ▶ In general, `ElementType[]` is an array of values of type `ElementType`
- ▶ Size of the array is set on initialisation with `new`

# Arrays

```
int[] myArray = new int[10];  
int[] anotherArray = new int[] { 123, 456, 789 };
```

- ▶ `int[]` is an array of `ints`
- ▶ In general, `ElementType[]` is an array of values of type `ElementType`
- ▶ Size of the array is set on initialisation with `new`
- ▶ Array **cannot change size** after initialisation

# Arrays

```
int[] myArray = new int[10];  
int[] anotherArray = new int[] { 123, 456, 789 };
```

- ▶ `int[]` is an array of `ints`
- ▶ In general, `ElementType[]` is an array of values of type `ElementType`
- ▶ Size of the array is set on initialisation with `new`
- ▶ Array **cannot change size** after initialisation
- ▶ Use `myArray[i]` to get/set the `i`th element (starting at 0)

# Arrays

```
int[] myArray = new int[10];
int[] anotherArray = new int[] { 123, 456, 789 };
```

- ▶ `int[]` is an array of `ints`
- ▶ In general, `ElementType[]` is an array of values of type `ElementType`
- ▶ Size of the array is set on initialisation with `new`
- ▶ Array **cannot change size** after initialisation
- ▶ Use `myArray[i]` to get/set the `i`th element (starting at 0)
- ▶ Use `myArray.Length` to get the number of elements

# Multi-dimensional arrays

```
int[,] myGrid = new int[20, 15];
```

# Multi-dimensional arrays

```
int[,] myGrid = new int[20, 15];
```

- ▶ `int[,]` is a 2-dimensional array of `ints`

# Multi-dimensional arrays

```
int[,] myGrid = new int[20, 15];
```

- ▶ `int[,]` is a 2-dimensional array of `ints`
- ▶ Use `myArray[x, y]` to get/set elements

# Multi-dimensional arrays

```
int[,] myGrid = new int[20, 15];
```

- ▶ `int[,]` is a 2-dimensional array of `ints`
- ▶ Use `myArray[x, y]` to get/set elements
- ▶ Use `myArray.GetLength(0), myArray.GetLength(1)` to get the “width” and “height”

# Multi-dimensional arrays

```
int[,] myGrid = new int[20, 15];
```

- ▶ `int[,]` is a 2-dimensional array of `ints`
- ▶ Use `myArray[x, y]` to get/set elements
- ▶ Use `myArray.GetLength(0), myArray.GetLength(1)` to get the “width” and “height”
- ▶ Similarly `int[, ,]` is a 3-dimensional array, etc.

# Lists

```
using System.Collections.Generic;  
  
List<int> myList = new List<int>();  
List<int> anotherList = new List<int> { 1, 2, 3, 4 };
```

# Lists

```
using System.Collections.Generic;  
  
List<int> myList = new List<int>();  
List<int> anotherList = new List<int> { 1, 2, 3, 4 };
```

- ▶ Like a list in Python, but can only store values of the specified type (here `int`)

# Lists

```
using System.Collections.Generic;  
  
List<int> myList = new List<int>();  
List<int> anotherList = new List<int> { 1, 2, 3, 4 };
```

- ▶ Like a list in Python, but can only store values of the specified type (here `int`)
- ▶ Append elements with `myList.Add()`

# Lists

```
using System.Collections.Generic;  
  
List<int> myList = new List<int>();  
List<int> anotherList = new List<int> { 1, 2, 3, 4 };
```

- ▶ Like a list in Python, but can only store values of the specified type (here `int`)
- ▶ Append elements with `myList.Add()`
- ▶ Get the number of elements with `myList.Count`

# Strings

```
string myString = "Hello, world!";
```

# Strings

```
string myString = "Hello, world!";
```

- ▶ **string** can be thought of as a collection

# Strings

```
string myString = "Hello, world!";
```

- ▶ `string` can be thought of as a collection
- ▶ In particular, it implements `IEnumerable<char>`

# Strings

```
string myString = "Hello, world!";
```

- ▶ `string` can be thought of as a collection
- ▶ In particular, it implements `IEnumerable<char>`
- ▶ So for example we can iterate over the characters in a string:

```
foreach (char c in myString)
{
    Console.WriteLine(c);
}
```

# Strings are immutable

# Strings are immutable

- ▶ Strings are **immutable** in C#

# Strings are immutable

- ▶ Strings are **immutable** in C#
- ▶ This means that the contents of a string **cannot be changed** once it is created

# Strings are immutable

- ▶ Strings are **immutable** in C#
- ▶ This means that the contents of a string **cannot be changed** once it is created
- ▶ But wait... we change strings all the time, don't we?

```
string myString = "Hello ";
myString += "world";
```

# Strings are immutable

- ▶ Strings are **immutable** in C#
- ▶ This means that the contents of a string **cannot be changed** once it is created
- ▶ But wait... we change strings all the time, don't we?

```
string myString = "Hello ";
myString += "world";
```

- ▶ This isn't changing the string, it's creating a new one and throwing the old one away!

# Strings are immutable

- ▶ Strings are **immutable** in C#
- ▶ This means that the contents of a string **cannot be changed** once it is created
- ▶ But wait... we change strings all the time, don't we?

```
string myString = "Hello ";
myString += "world";
```

- ▶ This isn't changing the string, it's creating a new one and throwing the old one away!
- ▶ Hence building a long string by appending can be slow (appending strings is  $O(n)$ )

# Strings are immutable

- ▶ Strings are **immutable** in C#
- ▶ This means that the contents of a string **cannot be changed** once it is created
- ▶ But wait... we change strings all the time, don't we?

```
string myString = "Hello ";
myString += "world";
```

- ▶ This isn't changing the string, it's creating a new one and throwing the old one away!
- ▶ Hence building a long string by appending can be slow (appending strings is  $O(n)$ )
- ▶ C# has a **mutable** string type: `StringBuilder`

# Dictionaries

# Dictionaries

- Dictionaries are **associative maps**

# Dictionaries

- ▶ Dictionaries are **associative maps**
- ▶ A dictionary maps **keys** to **values**

# Dictionaries

- ▶ Dictionaries are **associative maps**
- ▶ A dictionary maps **keys** to **values**
- ▶ Takes two generic parameters: the **key type** and the **value type**

# Dictionaries

- ▶ Dictionaries are **associative maps**
- ▶ A dictionary maps **keys** to **values**
- ▶ Takes two generic parameters: the **key type** and the **value type**
- ▶ A dictionary is implemented as a **hash table**

# Using dictionaries

```
var age = new Dictionary<string, int> {
    ["Alice"] = 23,
    ["Bob"] = 36,
    ["Charlie"] = 27
};
```

# Using dictionaries

```
var age = new Dictionary<string, int> {  
    ["Alice"] = 23,  
    ["Bob"] = 36,  
    ["Charlie"] = 27  
};
```

Access values using []:

```
Console.WriteLine(age["Alice"]); // prints 23  
age["Bob"] = 40; // overwriting an existing item  
age["Denise"] = 21; // adding a new item  
age.Add("Emily", 29); // adding a new item -- will raise  
// an error if already present
```

# Iterating over dictionaries

# Iterating over dictionaries

- Dictionary<Key, Value> implements  
IEnumerable<KeyValuePair<Key, Value>>

# Iterating over dictionaries

- ▶ Dictionary<Key, Value> implements  
IEnumerable<KeyValuePair<Key, Value>>
- ▶ KeyValuePair<Key, Value> stores Key and Value

# Iterating over dictionaries

- ▶ Dictionary<Key, Value> implements  
IEnumerable<KeyValuePair<Key, Value>>
- ▶ KeyValuePair<Key, Value> stores Key and Value

```
foreach (var keyValue in age)
{
    Console.WriteLine("{0} is {1} years old",
                      kv.Key, kv.Value);
}
```

# Iterating over dictionaries

- ▶ Dictionary<Key, Value> implements  
IEnumerable<KeyValuePair<Key, Value>>
- ▶ KeyValuePair<Key, Value> stores Key and Value

```
foreach (var keyValue in age)
{
    Console.WriteLine("{0} is {1} years old",
                      kv.Key, kv.Value);
}
```

- ▶ (C# tip: the var keyword lets the compiler automatically determine the appropriate type to use for a variable)

# Iterating over dictionaries

- ▶ Dictionary<Key, Value> implements  
IEnumerable<KeyValuePair<Key, Value>>
- ▶ KeyValuePair<Key, Value> stores Key and Value

```
foreach (var keyValue in age)
{
    Console.WriteLine("{0} is {1} years old",
                      kv.Key, kv.Value);
}
```

- ▶ (C# tip: the var keyword lets the compiler automatically determine the appropriate type to use for a variable)
- ▶ Dictionaries are **unordered** — avoid assuming that **foreach** will see the elements in any particular order!

# Hash sets

# Hash sets

- ▶ Sets are **unordered** collections of **unique** elements

# Hash sets

- ▶ Sets are **unordered** collections of **unique** elements
  - ▶ Sets **cannot** contain **duplicate** elements

# Hash sets

- ▶ Sets are **unordered** collections of **unique** elements
  - ▶ Sets **cannot** contain **duplicate** elements
  - ▶ Attempting to `Add` an element already present in the set does nothing

# Hash sets

- ▶ Sets are **unordered** collections of **unique** elements
  - ▶ Sets **cannot** contain **duplicate** elements
  - ▶ Attempting to `Add` an element already present in the set does nothing
- ▶ HashSets are like `Dictionary`s without the values, just the keys

# Hash sets

- ▶ Sets are **unordered** collections of **unique** elements
  - ▶ Sets **cannot** contain **duplicate** elements
  - ▶ Attempting to `Add` an element already present in the set does nothing
- ▶ HashSets are like Dictionaries without the values, just the keys
- ▶ As discussed in Week 5, certain operations are much more efficient (constant time) on hash sets than on lists

# Using sets

```
var numbers = new HashSet<int>{1, 4, 9, 16, 25};
```

# Using sets

```
var numbers = new HashSet<int>{1, 4, 9, 16, 25};
```

Add and remove members with `Add` and `Remove` methods

```
numbers.Add(36);  
numbers.Remove(4);
```

# Using sets

```
var numbers = new HashSet<int>{1, 4, 9, 16, 25};
```

Add and remove members with `Add` and `Remove` methods

```
numbers.Add(36);  
numbers.Remove(4);
```

Test membership with `Contains`

```
if (numbers.Contains(9))  
    Console.WriteLine("Set contains 9");
```

# Linked lists



# Linked list

# Linked list

- Composed of a number of **nodes**

# Linked list

- ▶ Composed of a number of **nodes**
- ▶ Each node contains:

# Linked list

- ▶ Composed of a number of **nodes**
- ▶ Each node contains:
  - ▶ An **item** — the actual data to be stored

# Linked list

- ▶ Composed of a number of **nodes**
- ▶ Each node contains:
  - ▶ An **item** — the actual data to be stored
  - ▶ A pointer or reference to the **previous node** in the list  
(null for the first item)

# Linked list

- ▶ Composed of a number of **nodes**
- ▶ Each node contains:
  - ▶ An **item** — the actual data to be stored
  - ▶ A pointer or reference to the **previous node** in the list (null for the first item)
  - ▶ A pointer or reference to the **next node** in the list (null for the last item)

# Linked list

- ▶ Composed of a number of **nodes**
- ▶ Each node contains:
  - ▶ An **item** — the actual data to be stored
  - ▶ A pointer or reference to the **previous node** in the list (null for the first item)
  - ▶ A pointer or reference to the **next node** in the list (null for the last item)
- ▶ The nodes are **not necessarily contiguous** in memory, unlike an (array-backed) list

# Linked list

- ▶ Composed of a number of **nodes**
- ▶ Each node contains:
  - ▶ An **item** — the actual data to be stored
  - ▶ A pointer or reference to the **previous node** in the list (null for the first item)
  - ▶ A pointer or reference to the **next node** in the list (null for the last item)
- ▶ The nodes are **not necessarily contiguous** in memory, unlike an (array-backed) list



# Linked list

- ▶ Composed of a number of **nodes**
- ▶ Each node contains:
  - ▶ An **item** — the actual data to be stored
  - ▶ A pointer or reference to the **previous node** in the list (null for the first item)
  - ▶ A pointer or reference to the **next node** in the list (null for the last item)
- ▶ The nodes are **not necessarily contiguous** in memory, unlike an (array-backed) list



- ▶ In C#: `LinkedList<ElementType>`

# Operations on linked lists

# Linked lists vs array-backed lists

# Linked lists vs array-backed lists

- ▶ **Inserting** and **removing** from the middle of an array list requires shuffling the following elements to make or fill space

# Linked lists vs array-backed lists

- ▶ **Inserting** and **removing** from the middle of an array list requires shuffling the following elements to make or fill space
- ▶ This makes these operations  $O(n)$

# Linked lists vs array-backed lists

- ▶ **Inserting** and **removing** from the middle of an array list requires shuffling the following elements to make or fill space
- ▶ This makes these operations  $O(n)$
- ▶ Linked list doesn't require this shuffling, so inserting and deleting is  $O(1)$

# Linked lists vs array-backed lists

- ▶ **Inserting** and **removing** from the middle of an array list requires shuffling the following elements to make or fill space
- ▶ This makes these operations  $O(n)$
- ▶ Linked list doesn't require this shuffling, so inserting and deleting is  $O(1)$
- ▶ However...

# Linked lists vs array-backed lists

- ▶ **Inserting** and **removing** from the middle of an array list requires shuffling the following elements to make or fill space
- ▶ This makes these operations  $O(n)$
- ▶ Linked list doesn't require this shuffling, so inserting and deleting is  $O(1)$
- ▶ However...
- ▶ **Finding the  $i$ th element** of an array list is simple pointer arithmetic, which is  $O(1)$

# Linked lists vs array-backed lists

- ▶ **Inserting** and **removing** from the middle of an array list requires shuffling the following elements to make or fill space
- ▶ This makes these operations  $O(n)$
- ▶ Linked list doesn't require this shuffling, so inserting and deleting is  $O(1)$
- ▶ However...
- ▶ **Finding the  $i$ th element** of an array list is simple pointer arithmetic, which is  $O(1)$
- ▶ In a linked list we have to count along the “next” pointers, which is  $O(i)$

# Linked lists vs array-backed lists

- ▶ **Inserting** and **removing** from the middle of an array list requires shuffling the following elements to make or fill space
- ▶ This makes these operations  $O(n)$
- ▶ Linked list doesn't require this shuffling, so inserting and deleting is  $O(1)$
- ▶ However...
- ▶ **Finding the  $i$ th element** of an array list is simple pointer arithmetic, which is  $O(1)$
- ▶ In a linked list we have to count along the “next” pointers, which is  $O(i)$
- ▶ So which data structure is more efficient? It depends what operations we need to do more often

# Workshop



# Workshop Activity

# Workshop Activity

- ▶ **Priority 1:** check you have submitted your research journal!

# Workshop Activity

- ▶ **Priority 1:** check you have submitted your research journal!
- ▶ Then, in your **breakout groups** (from week 2 on LearningSpace):

# Workshop Activity

- ▶ **Priority 1:** check you have submitted your research journal!
- ▶ Then, in your **breakout groups** (from week 2 on LearningSpace):
- ▶ I have put a Word document in your room on Teams (Files tab) — you can edit this collaboratively

# Workshop Activity

- ▶ **Priority 1:** check you have submitted your research journal!
- ▶ Then, in your **breakout groups** (from week 2 on LearningSpace):
- ▶ I have put a Word document in your room on Teams (Files tab) — you can edit this collaboratively
- ▶ For a variety of C# collection types:

# Workshop Activity

- ▶ **Priority 1:** check you have submitted your research journal!
- ▶ Then, in your **breakout groups** (from week 2 on LearningSpace):
- ▶ I have put a Word document in your room on Teams (Files tab) — you can edit this collaboratively
- ▶ For a variety of C# collection types:
  - ▶ What operations are possible?

# Workshop Activity

- ▶ **Priority 1:** check you have submitted your research journal!
- ▶ Then, in your **breakout groups** (from week 2 on LearningSpace):
- ▶ I have put a Word document in your room on Teams (Files tab) — you can edit this collaboratively
- ▶ For a variety of C# collection types:
  - ▶ What operations are possible?
  - ▶ How are they done?

# Workshop Activity

- ▶ **Priority 1:** check you have submitted your research journal!
- ▶ Then, in your **breakout groups** (from week 2 on LearningSpace):
- ▶ I have put a Word document in your room on Teams (Files tab) — you can edit this collaboratively
- ▶ For a variety of C# collection types:
  - ▶ What operations are possible?
  - ▶ How are they done?
  - ▶ What is their time complexity?

# Workshop Activity

- ▶ **Priority 1:** check you have submitted your research journal!
- ▶ Then, in your **breakout groups** (from week 2 on LearningSpace):
- ▶ I have put a Word document in your room on Teams (Files tab) — you can edit this collaboratively
- ▶ For a variety of C# collection types:
  - ▶ What operations are possible?
  - ▶ How are they done?
  - ▶ What is their time complexity?
  - ▶ What is an example scenario where this data structure is appropriate?

# Workshop Activity

- ▶ **Priority 1:** check you have submitted your research journal!
- ▶ Then, in your **breakout groups** (from week 2 on LearningSpace):
- ▶ I have put a Word document in your room on Teams (Files tab) — you can edit this collaboratively
- ▶ For a variety of C# collection types:
  - ▶ What operations are possible?
  - ▶ How are they done?
  - ▶ What is their time complexity?
  - ▶ What is an example scenario where this data structure is appropriate?
- ▶ Use the **Microsoft .NET documentation** along with **googling** and **experimentation** to find out!

# Workshop Activity

- ▶ **Priority 1:** check you have submitted your research journal!
- ▶ Then, in your **breakout groups** (from week 2 on LearningSpace):
- ▶ I have put a Word document in your room on Teams (Files tab) — you can edit this collaboratively
- ▶ For a variety of C# collection types:
  - ▶ What operations are possible?
  - ▶ How are they done?
  - ▶ What is their time complexity?
  - ▶ What is an example scenario where this data structure is appropriate?
- ▶ Use the **Microsoft .NET documentation** along with **googling** and **experimentation** to find out!
- ▶ Reconvene here at **5:45pm** to compare notes