

COMP220: Graphics & Simulation

# 4: Meshes

# Module Roadmap

Worksheet A

Worksheet B

Worksheet C

Worksheet D

Table 1: Indicative Assignment Timeline



Week 2	Show Computing Artefact Work-in-Progress to Supervisor (Part A).
Week 4	Show Computing Artefact Work-in-Progress to Supervisor (Part B).
Week 6	Show Computing Artefact Work-in-Progress to Supervisor (Part B).
Week 8	Show Draft Poster to Supervisor (Part C).
Week 8	Present Poster to Peers (Part D).
Week 9	Peer Review Web Page (Part E).
Week 10	Show Web Page to Supervisor (Part E).
Week 10	Submit Poster and Web Page to LearningSpace (Part F).
Week 13	Present Web Page at Viva (Part F).

More complex meshes



# Winding order

# Winding order


- ▶ It is sometimes important to know which side of a triangle is the “front” and which is the “back”

# Winding order

- ▶ It is sometimes important to know which side of a triangle is the “front” and which is the “back”
- ▶ OpenGL determines this by **winding order**

# Winding order


- ▶ It is sometimes important to know which side of a triangle is the “front” and which is the “back”
- ▶ OpenGL determines this by **winding order**




If the vertices  
go **anticlockwise**, you are  
looking at the **front**

# Winding order

- ▶ It is sometimes important to know which side of a triangle is the “front” and which is the “back”
- ▶ OpenGL determines this by **winding order**



If the vertices go **anticlockwise**, you are looking at the **front**



If the vertices go **clockwise**, you are looking at the **back**



# Backface culling

# Backface culling

```
glEnable(GL_CULL_FACE);
```

# Backface culling

```
glEnable(GL_CULL_FACE);
```

- ▶ This will cause only the front faces of triangles to be drawn

# Backface culling

```
glEnable(GL_CULL_FACE);
```

- ▶ This will cause only the front faces of triangles to be drawn
- ▶ Triangles whose front face is not visible will be **culled**

# Backface culling

```
glEnable(GL_CULL_FACE);
```

- ▶ This will cause only the front faces of triangles to be drawn
- ▶ Triangles whose front face is not visible will be **culled**
- ▶ Culled faces are not passed through the rasteriser or fragment shader

# Backface culling

```
glEnable(GL_CULL_FACE);
```

- ▶ This will cause only the front faces of triangles to be drawn
- ▶ Triangles whose front face is not visible will be **culled**
- ▶ Culled faces are not passed through the rasteriser or fragment shader
- ▶ Saves time, and should make no difference to appearance — as long as all meshes are closed and have correct winding

# When backface culling goes bad?



# Vertices





# Interleaved Vertices

# Interleaved Vertices

- ▶ Up until this point we have been storing vertex positions as floats

# Interleaved Vertices

- ▶ Up until this point we have been storing vertex positions as floats
- ▶ If we need a vertex to have colours, we can store these in a separate Vertex Buffer

# Interleaved Vertices

- ▶ Up until this point we have been storing vertex positions as floats
- ▶ If we need a vertex to have colours, we can store these in a separate Vertex Buffer
- ▶ Or we can create a **C structure** which represents a Vertex, which has member variables which represent positions, colours, normals etc

# Interleaved Vertices

- ▶ Up until this point we have been storing vertex positions as floats
- ▶ If we need a vertex to have colours, we can store these in a separate Vertex Buffer
- ▶ Or we can create a **C structure** which represents a Vertex, which has member variables which represent positions, colours, normals etc
- ▶ This is known as Interleaved Vertices and in

# Interleaved Vertices

- ▶ Up until this point we have been storing vertex positions as floats
- ▶ If we need a vertex to have colours, we can store these in a separate Vertex Buffer
- ▶ Or we can create a **C structure** which represents a Vertex, which has member variables which represent positions, colours, normals etc
- ▶ This is known as Interleaved Vertices and in **MOST** cases is more efficient

# Vertex Structure 1

```
struct Vertex
{
    float x,y,z;
};

Vertex v[]={{-0.5f,-0.5f,0.0f},
            {0.5f,-0.5f,0.0f},
            {0.0f,0.5f,0.0f}};
```

# Vertex Structure 2

```
struct Vertex
{
    float x,y,z;
    float r,g,b,a;
};

Vertex v[]={
    {-0.5f,-0.5f,0.0f,1.0f,0.0f,0.0f ←
    ,1.0f},
    {0.5f,-0.5f,0.0f,0.0f,1.0f,0.0f ←
    ,1.0f},
    {0.0f,0.5f,0.0f,0.0f,0.0f,1.0f,1.0 ←
    f}};
```



# Changes to the Vertex Buffer

# Changes to the Vertex Buffer

- ▶ There will be a slight change to our vertex buffer

# Changes to the Vertex Buffer

- ▶ There will be a slight change to our vertex buffer
- ▶ We have to take into account the size of the Vertex structure and the number of vertices in the buffer

# Vertex Buffer Changes - Old version

```
glBufferData(GL_ARRAY_BUFFER, sizeof( ↵  
    g_vertex_buffer_data), ↵  
    g_vertex_buffer_data, GL_STATIC_DRAW);
```

# Vertex Buffer Changes - new version

```
glBufferData(GL_ARRAY_BUFFER, 3* sizeof(Vertex ↵  
            ), v, GL_STATIC_DRAW);
```

# Changes to the Vertex Array

# Changes to the Vertex Array

- ▶ Since the layout of the vertices have changed in memory, we need to update the Vertex Array Object to reflect this

# Changes to the Vertex Array

- ▶ Since the layout of the vertices have changed in memory, we need to update the Vertex Array Object to reflect this
- ▶ Remember that the VAO describes the format of the vertices to the pipeline and enables the binding of vertex data to attributes in the shader



# Vertex Array Object - Old version

```
glEnableVertexAttribArray(0);  
glVertexAttribPointer(0, 3, GL_FLOAT, GL_FALSE, 0, ( ←  
    void*) 0);
```

# Vertex Array Object - New version

```
glEnableVertexAttribArray(0);  
glVertexAttribPointer(0, 3, GL_FLOAT, GL_FALSE, sizeof ←  
    (Vertex), (void*) 0);  
  
glEnableVertexAttribArray(1);  
glVertexAttribPointer(1, 4, GL_FLOAT, GL_FALSE, sizeof ←  
    (Vertex), (void*) (3*sizeof(float)));
```

# Memory and Vertex Array Object 1

	X	Y	Z	R	G	B	A
$V_0$							
$V_1$							
$V_2$							

# Memory and Vertex Array Object 2

	X	Y	Z	R	G	B	A
$V_0$	-0.5	-0.5	0.0	1.0	0.0	0.0	1.0
$V_1$	0.5	-0.5	0.0	0.0	1.1	0.0	1.0
$V_2$	0.0	0.2	0.0	0.0	0.0	1.0	1.0

# Memory and Vertex Array Object 3 - Stride

← Stride →

$V_0$	-0.5	-0.5	0.0	1.0	0.0	0.0	1.0
$V_1$	0.5	-0.5	0.0	0.0	1.1	0.0	1.0
$V_2$	0.0	0.2	0.0	0.0	0.0	1.0	1.0

# Memory and Vertex Array Object 3 - Offset

 Offset = 3 \* sizeof(float)

$V_0$	-0.5	-0.5	0.0	1.0	0.0	0.0	1.0
$V_1$	0.5	-0.5	0.0	0.0	1.1	0.0	1.0
$V_2$	0.0	0.2	0.0	0.0	0.0	1.0	1.0

# Element Buffer



# Element Buffer



# Element Buffer

- ▶ If we look at the cube sample, we are sending 36 vertices

# Element Buffer

- ▶ If we look at the cube sample, we are sending 36 vertices
- ▶ This is a bit wasteful considering that some of these vertices are duplicates

# Element Buffer

- ▶ If we look at the cube sample, we are sending 36 vertices
- ▶ This is a bit wasteful considering that some of these vertices are duplicates
- ▶ We can use an **Element Buffer** to optimise our drawing


# Element Buffer

- ▶ If we look at the cube sample, we are sending 36 vertices
- ▶ This is a bit wasteful considering that some of these vertices are duplicates
- ▶ We can use an **Element Buffer** to optimise our drawing
- ▶ An Element Buffer holds an integer which is an offset into a Vertex Buffer


# Creating & Using Element Buffer

Live Coding

# Exercise 1 - Let's draw a square!



# Exercise 2 - Let's draw a cube!



# Exercise 3 - Element Buffer

- ▶ Create a cube using an Element Buffer
- ▶ Create a function which fills a Vertex Buffer and Element Buffer for drawing a Sphere



# Further Reading - Interleaved Vertices

- ▶ iOS Development Docs -  
[https://developer.apple.com/library/content/documentation/3DDrawing/Conceptual/OpenGL\\_ES\\_Programming\\_Guide/TechniquesforWorkingwithVertexData/TechniquesforWorkingwithVertexData.html](https://developer.apple.com/library/content/documentation/3DDrawing/Conceptual/OpenGL_ES_Programming_Guide/TechniquesforWorkingwithVertexData/TechniquesforWorkingwithVertexData.html)
- ▶ To interleave or not to interleave - <https://anteru.net/blog/2016/02/14/3119/index.html>
- ▶ Vertex Specification Best Practices -  
[https://www.khronos.org/opengl/wiki/Vertex\\_Specification\\_Best\\_Practices](https://www.khronos.org/opengl/wiki/Vertex_Specification_Best_Practices)

# Further Reading - Element Buffer

- ▶ VBO indexing - <http://www.opengl-tutorial.org/intermediate-tutorials/tutorial-9-vbo-indexing/>
- ▶ Element Buffer - <https://goharsha.com/lwjgl-tutorial-series/element-buffer-objects/>