

COMP250: Artificial Intelligence


10: Deep learning

Neural networks

Artificial Neural Networks (ANNs)


- ▶ **Inspired by** the structure of biological brains
- ▶ Idea has been around since the 1950s
- ▶ Recent resurgence of interest: today's powerful CPUs and GPUs allow much larger ANNs to be used

Real neurons



- ▶ An **electrically excitable** cell
 - ▶ Neurons are **connected together**
 - ▶ Connections can be **excitatory** or **inhibitory**
-
- ▶ If enough excitatory signals are received, the neuron **fires** — sends an electrical signal to the connected neurons
 - ▶ Human brain contains approximately **100 billion** neurons

An artificial neuron



- ▶ A **perceptron**
- ▶ Inputs x_1, \dots, x_m are outputs from **other perceptrons**
- ▶ Each input has a **weight** w_i between -1 and $+1$

Perceptron activation


- ▶ The perceptron calculates a **weighted sum**

$$w_0 + w_1x_1 + \cdots + w_mx_m$$

- ▶ This goes through an **activation function**
- ▶ Simplest: **step function**


$$\text{output} = \begin{cases} 1 & \text{if sum} \geq \text{threshold} \\ 0 & \text{if sum} < \text{threshold} \end{cases}$$

- ▶ More common: **sigmoid function**



An artificial neural network

Input layer Hidden Layers Output Layer



- ▶ A **multilayer perceptron (MLP)**
- ▶ Consists of an **input layer**, several **hidden layers** and an **output layer**
- ▶ Each layer is an array of **perceptrons**
- ▶ Each perceptron's output is connected to **every** perceptron in the next layer

Image classification



- ▶ Classic example:
handwritten digit recognition
- ▶ Given a **raster image**, which of the digits 0 to 9 does it represent?



<https://twitter.com/NaughtThought/status/846262063827730432>

MLPs for image classification

- ▶ **Input:** pixels of the image, reduced down to 1 bit per pixel (i.e. black or white)
 - ▶ Input layer: 1 perceptron per pixel
- ▶ **Output:** 10 bits corresponding to digits 0 to 9, of which exactly one should be set
 - ▶ Output layer: 10 perceptrons
- ▶ **Hidden layers:** ???
 - ▶ Parameters to tune
- ▶ **Weights:** ???

How to set the weights?

- ▶ We need to **train** the network
- ▶ Idea:
 - ▶ Feed in **training data**
 - ▶ When the network happens to give the correct answer, **reinforce** the relevant weights
 - ▶ Repeat until a desired **accuracy** is obtained
- ▶ Note: this requires a large amount of training data that is **tagged**, i.e. for which we already know the correct answer

Stochastic gradient descent

- ▶ **Gradient descent**: opposite of **gradient ascent** a.k.a. **hillclimbing**
- ▶ Want to minimise the **error** over the training data
- ▶ **Stochastic**: perform several training **epochs**
- ▶ Each epoch uses a randomly sampled **subset** of the training data
- ▶ This reduces computation time, and helps to escape local optima

ANN example

<http://playground.tensorflow.org>

Overfitting


- ▶ ANN learns **patterns** in the training data
- ▶ Insufficient training data might result in the network learning “patterns” that are actually random anomalies

Deep learning

Deep learning



- ▶ Basically, the use of large ANNs with **many layers**
- ▶ Often uses **large training sets**
- ▶ Training often uses powerful **GPUs** — many times faster than training on the CPU

Convolutional Neural Networks (ConvNets)



- Layers are **2D arrays**
- Neurons in convolutional layers are only connected to nearby neurons
- There are also fully connected layers


Deep neural networks learn hierarchical feature representations



DeepDream

- ▶ Train a ConvNet to recognise something (e.g. faces, objects, animals)
- ▶ Run the network in “reverse”
 - ▶ Adjust the image (e.g. via gradient ascent) so that it is more strongly recognised by the network

DeepDream



Style transfer

- ▶ Train a ConvNet to recognise a particular artistic style
- ▶ Run the network in “reverse” on an input image
 - ▶ Adjust the image (e.g. via gradient ascent) so that it is more strongly recognised by the network

Style transfer



Source image (**Style**)




Target image (**Content**)



Output ([deepart](#))

A Neural Algorithm of Artistic Style [[Gatys et al. 2015](#)]

Learning to play Atari games (Mnih et al, 2015)



Deep learning for PCG

<https://www.youtube.com/watch?v=3wcpLwvBTYo>