



FALMOUTH  
UNIVERSITY



# COMP110: Principles of Computing

## 3: Basic data types

# Research journal



# Research journal

# Research journal

- ▶ **Read** some seminal papers in computing (listed on the assignment brief)

# Research journal

- ▶ **Read** some seminal papers in computing (listed on the assignment brief)
- ▶ **Choose** one of them

# Research journal

- ▶ **Read** some seminal papers in computing (listed on the assignment brief)
- ▶ **Choose** one of them
- ▶ **Research** how this paper has influenced the field of computing

# Research journal

- ▶ **Read** some seminal papers in computing (listed on the assignment brief)
- ▶ **Choose** one of them
- ▶ **Research** how this paper has influenced the field of computing
- ▶ **Present** (briefly!) your findings

# Research journal

- ▶ **Read** some seminal papers in computing (listed on the assignment brief)
- ▶ **Choose** one of them
- ▶ **Research** how this paper has influenced the field of computing
- ▶ **Present** (briefly!) your findings
- ▶ **Write up** your findings



# Research journal

- ▶ **Read** some seminal papers in computing (listed on the assignment brief)
- ▶ **Choose** one of them
- ▶ **Research** how this paper has influenced the field of computing
- ▶ **Present** (briefly!) your findings
- ▶ **Write up** your findings
  - ▶ Maximum 1500 words

# Research journal

- ▶ **Read** some seminal papers in computing (listed on the assignment brief)
- ▶ **Choose** one of them
- ▶ **Research** how this paper has influenced the field of computing
- ▶ **Present** (briefly!) your findings
- ▶ **Write up** your findings
  - ▶ Maximum 1500 words
  - ▶ With reference to appropriate academic sources

# Marking rubric

See assignment brief on LearningSpace

# Timeline

# Timeline

- **Presentations** in week 7 (4th and 8th November)

# Timeline

- ▶ **Presentations** in week 7 (4th and 8th November)
- ▶ **Peer review** in week 8 (14th November)

# Timeline

- ▶ **Presentations** in week 7 (4th and 8th November)
- ▶ **Peer review** in week 8 (14th November)
- ▶ **Deadline** shortly after (check MyFalmouth)

# Timeline

- ▶ **Presentations** in week 7 (4th and 8th November)
- ▶ **Peer review** in week 8 (14th November)
- ▶ **Deadline** shortly after (check MyFalmouth)
- ▶ Finding and reading academic papers takes time and effort — don't leave it until the last minute!



# Worksheets

- ▶ Worksheet 2 (Binary numbers) due **tomorrow**
- ▶ Worksheet 3 (Flowcharts and pseudocode) due **next Friday**

# Data types



# What is a type?

# What is a type?

- ▶ A **variable** in Python holds a **value**

# What is a type?

- ▶ A **variable** in Python holds a **value**
- ▶ Every value has a **type**

# What is a type?

- ▶ A **variable** in Python holds a **value**
- ▶ Every value has a **type**
- ▶ The type of a value dictates:

# What is a type?

- ▶ A **variable** in Python holds a **value**
- ▶ Every value has a **type**
- ▶ The type of a value dictates:
  - ▶ What sort of data it can hold

# What is a type?

- ▶ A **variable** in Python holds a **value**
- ▶ Every value has a **type**
- ▶ The type of a value dictates:
  - ▶ What sort of data it can hold
  - ▶ How the data is stored in memory




# What is a type?

- ▶ A **variable** in Python holds a **value**
- ▶ Every value has a **type**
- ▶ The type of a value dictates:
  - ▶ What sort of data it can hold
  - ▶ How the data is stored in memory
  - ▶ What operations can be done on it


# Memory

# Memory



- ▶ Memory works like a set of **boxes**


# Memory



Address	Data
0	01001000
1	01100101
2	01101100
3	01101100
4	01101111
5	00100001
...	...

- ▶ Memory works like a set of **boxes**
- ▶ Each box has a number, its **address**

# Memory



Address	Data
0	01001000
1	01100101
2	01101100
3	01101100
4	01101111
5	00100001
...	...

- ▶ Memory works like a set of **boxes**
- ▶ Each box has a number, its **address**
- ▶ Each box contains a **byte** (8 bits)

# Data representation

# Data representation

- ▶ All data is stored as **sequences of bytes**

# Data representation

- ▶ All data is stored as **sequences of bytes**
  - ▶ Sequence of bits, in multiples of 8



# Data representation

- ▶ All data is stored as **sequences of bytes**
  - ▶ Sequence of bits, in multiples of 8
  - ▶ Sequence of numbers between 0–255

# Numeric types



# Integers

# Integers

- ▶ An **integer** is a whole number — positive, negative or zero

# Integers

- ▶ An **integer** is a whole number — positive, negative or zero
- ▶ Python type: `int`

# Integers

- ▶ An **integer** is a whole number — positive, negative or zero
- ▶ Python type: `int`
- ▶ In most languages, `int` is limited to 32 or 64 bits

# Integers

- ▶ An **integer** is a whole number — positive, negative or zero
- ▶ Python type: `int`
- ▶ In most languages, `int` is limited to 32 or 64 bits
- ▶ Python uses **big integers** — number of bits expands automatically to fit the value to be stored

# Integers

- ▶ An **integer** is a whole number — positive, negative or zero
- ▶ Python type: `int`
- ▶ In most languages, `int` is limited to 32 or 64 bits
- ▶ Python uses **big integers** — number of bits expands automatically to fit the value to be stored
- ▶ Stored in memory using binary notation, with 2's complement for negative values



# Integers as bytes

# Integers as bytes

- ▶ A **32-bit** integer is stored as a sequence of **4 bytes**

# Integers as bytes

- ▶ A **32-bit** integer is stored as a sequence of **4 bytes**
- ▶ Example: 314159 in decimal = 100 11001011 00101111 in binary

# Integers as bytes

- ▶ A **32-bit** integer is stored as a sequence of **4 bytes**
- ▶ Example: 314159 in decimal = 100 11001011 00101111 in binary
- ▶ Stored as four bytes:

00000000 00000100 11001011 00101111

or in hexadecimal:

00 04 CB 2F

# Integers as bytes

- ▶ A **32-bit** integer is stored as a sequence of **4 bytes**
- ▶ Example: 314159 in decimal = 100 11001011 00101111 in binary
- ▶ Stored as four bytes:

00000000 00000100 11001011 00101111

or in hexadecimal:

00 04 CB 2F

- ▶ Similarly for other sizes of integer: an  $n$ -bit integer is stored as  $n \div 8$  bytes

# Integers as bytes

- ▶ A **32-bit** integer is stored as a sequence of **4 bytes**
- ▶ Example: 314159 in decimal = 1001100101100101111 in binary
- ▶ Stored as four bytes:

00000000 00000100 11001011 00101111

or in hexadecimal:

00 04 CB 2F

- ▶ Similarly for other sizes of integer: an  $n$ -bit integer is stored as  $n \div 8$  bytes
- ▶ You can think of this as a base-256 numbering system

# Endianness

# Endianness

- ▶ Integers are stored either **big endian** or **little endian**



# Endianness

- ▶ Integers are stored either **big endian** or **little endian**
- ▶ Big endian: the **most significant byte** comes first

00 04 CB 2F

# Endianness

- ▶ Integers are stored either **big endian** or **little endian**
- ▶ Big endian: the **most significant byte** comes first

00 04 CB 2F

- ▶ Little endian: the **least significant byte** comes first

2F CB 04 00

# Endianness

- ▶ Integers are stored either **big endian** or **little endian**
- ▶ Big endian: the **most significant byte** comes first

00 04 CB 2F

- ▶ Little endian: the **least significant byte** comes first

2F CB 04 00

- ▶ Modern PCs (Intel x86 based) use little endian

# Endianness

- ▶ Integers are stored either **big endian** or **little endian**
- ▶ Big endian: the **most significant byte** comes first

00 04 CB 2F

- ▶ Little endian: the **least significant byte** comes first

2F CB 04 00

- ▶ Modern PCs (Intel x86 based) use little endian
- ▶ Little endian may seem unintuitive

# Endianness

- ▶ Integers are stored either **big endian** or **little endian**
- ▶ Big endian: the **most significant byte** comes first

00 04 CB 2F

- ▶ Little endian: the **least significant byte** comes first

2F CB 04 00

- ▶ Modern PCs (Intel x86 based) use little endian
- ▶ Little endian may seem unintuitive
- ▶ However it is more efficient when programs need to convert one size of integer to another

# Floating point numbers

# Floating point numbers

- ▶ What about storing non-integer numbers?

# Floating point numbers

- ▶ What about storing non-integer numbers?
- ▶ Usually we use **floating point** numbers



# Floating point numbers

- ▶ What about storing non-integer numbers?
- ▶ Usually we use **floating point** numbers
- ▶ Python type: `float`

# Floating point numbers

- ▶ What about storing non-integer numbers?
- ▶ Usually we use **floating point** numbers
- ▶ Python type: `float`
- ▶ Details on in-memory representation later in the module

# Floating point numbers

- ▶ What about storing non-integer numbers?
- ▶ Usually we use **floating point** numbers
- ▶ Python type: `float`
- ▶ Details on in-memory representation later in the module
- ▶ (Note: `float` in Python 3 has the same precision as `double` in C++/C#/etc)

# Integers vs floating point numbers

# Integers vs floating point numbers

- ▶ `int` and `float` are different types!

# Integers vs floating point numbers

- ▶ `int` and `float` are different types!
- ▶ `42` and `42.0` are technically different values

# Integers vs floating point numbers

- ▶ `int` and `float` are different types!
- ▶ 42 and 42.0 are technically different values
  - ▶ One is an `int`, the other is a `float`

# Integers vs floating point numbers

- ▶ `int` and `float` are different types!
- ▶ `42` and `42.0` are technically different values
  - ▶ One is an `int`, the other is a `float`
  - ▶ They are stored differently in memory (completely different sequences of bytes)



# Integers vs floating point numbers

- ▶ `int` and `float` are different types!
- ▶ `42` and `42.0` are technically different values
  - ▶ One is an `int`, the other is a `float`
  - ▶ They are stored differently in memory (completely different sequences of bytes)
  - ▶ However `==` etc still know how to compare them sensibly

# Other number formats

# Other number formats

- ▶ **Fixed point:** alternative format for non-integer numbers

# Other number formats

- ▶ **Fixed point:** alternative format for non-integer numbers
  - ▶ More on this later

# Other number formats

- ▶ **Fixed point:** alternative format for non-integer numbers
  - ▶ More on this later
  - ▶ E.g. `decimal` module in Python

# Other number formats

- ▶ **Fixed point:** alternative format for non-integer numbers
  - ▶ More on this later
  - ▶ E.g. `decimal` module in Python
- ▶ **Rational numbers:** store fractions as numerator and denominator

# Other number formats

- ▶ **Fixed point:** alternative format for non-integer numbers
  - ▶ More on this later
  - ▶ E.g. `decimal` module in Python
- ▶ **Rational numbers:** store fractions as numerator and denominator
  - ▶ E.g. `fractions` module in Python

# Other number formats

- ▶ **Fixed point:** alternative format for non-integer numbers
  - ▶ More on this later
  - ▶ E.g. `decimal` module in Python
- ▶ **Rational numbers:** store fractions as numerator and denominator
  - ▶ E.g. `fractions` module in Python
- ▶ **Complex numbers:** stored as a pair of floating point numbers for real and imaginary parts



# Other number formats

- ▶ **Fixed point:** alternative format for non-integer numbers
  - ▶ More on this later
  - ▶ E.g. `decimal` module in Python
- ▶ **Rational numbers:** store fractions as numerator and denominator
  - ▶ E.g. `fractions` module in Python
- ▶ **Complex numbers:** stored as a pair of floating point numbers for real and imaginary parts
  - ▶ E.g. `complex` type in Python

# String types



# Strings

# Strings

- ▶ A **string** represents a sequence of textual characters

# Strings

- ▶ A **string** represents a sequence of textual characters
- ▶ E.g. `"Hello world!"`

# Strings

- ▶ A **string** represents a sequence of textual characters
- ▶ E.g. "Hello world!"
- ▶ Python type: `str`

# String representation

# String representation

- ▶ Stored as sequences of **characters** encoded as **integers**



# String representation

- ▶ Stored as sequences of **characters** encoded as **integers**
- ▶ Often **null-terminated**

# String representation

- ▶ Stored as sequences of **characters** encoded as **integers**
- ▶ Often **null-terminated**
  - ▶ Character number 0 signifies the end of the string

# What is a character?

# What is a character?

- Broadly speaking, a single **printable symbol**

# What is a character?

- ▶ Broadly speaking, a single **printable symbol**
- ▶ There are also some special **non-printable characters**  
e.g. line break

# ASCII

# ASCII

- ▶ American Standard Code for Information Interchange

# ASCII

- ▶ American Standard Code for Information Interchange
- ▶ Defines a standard set of 128 characters (7 bits per character)



# ASCII

- ▶ American Standard Code for Information Interchange
- ▶ Defines a standard set of 128 characters (7 bits per character)
- ▶ Originally developed in the 1960s for teletype machines, but survives in computing to this day

# ASCII

- ▶ American Standard Code for Information Interchange
- ▶ Defines a standard set of 128 characters (7 bits per character)
- ▶ Originally developed in the 1960s for teletype machines, but survives in computing to this day
- ▶ 95 printable characters: upper and lower case English alphabet, digits, punctuation

# ASCII

- ▶ American Standard Code for Information Interchange
- ▶ Defines a standard set of 128 characters (7 bits per character)
- ▶ Originally developed in the 1960s for teletype machines, but survives in computing to this day
- ▶ 95 printable characters: upper and lower case English alphabet, digits, punctuation
- ▶ 33 non-printable characters

Hex	Value	Hex	Value	Hex	Value	Hex	Value	Hex	Value	Hex	Value	Hex	Value	Hex	Value
00	NUL	10	DLE	20	SP	30	0	40	@	50	P	60	`	70	p
01	SOH	11	DC1	21	!	31	1	41	A	51	Q	61	a	71	q
02	STX	12	DC2	22	"	32	2	42	B	52	R	62	b	72	r
03	ETX	13	DC3	23	#	33	3	43	C	53	S	63	c	73	s
04	EOT	14	DC4	24	\$	34	4	44	D	54	T	64	d	74	t
05	ENQ	15	NAK	25	%	35	5	45	E	55	U	65	e	75	u
06	ACK	16	SYN	26	&	36	6	46	F	56	V	66	f	76	v
07	BEL	17	ETB	27	'	37	7	47	G	57	W	67	g	77	w
08	BS	18	CAN	28	(	38	8	48	H	58	X	68	h	78	x
09	HT	19	EM	29	)	39	9	49	I	59	Y	69	i	79	y
0A	LF	1A	SUB	2A	*	3A	:	4A	J	5A	Z	6A	j	7A	z
0B	VT	1B	ESC	2B	+	3B	;	4B	K	5B	[	6B	k	7B	{
0C	FF	1C	FS	2C	,	3C	<	4C	L	5C	\	6C	l	7C	
0D	CR	1D	GS	2D	-	3D	=	4D	M	5D	]	6D	m	7D	}
0E	SO	1E	RS	2E	.	3E	>	4E	N	5E	^	6E	n	7E	~
0F	SI	1F	US	2F	/	3F	?	4F	O	5F	_	6F	o	7F	DEL

# ASCII

# ASCII

- ▶ ASCII works OK for English

# ASCII

- ▶ ASCII works OK for English
- ▶ Standards exist to add another 128 characters (taking us to 8 bits per character)

# ASCII

- ▶ ASCII works OK for English
- ▶ Standards exist to add another 128 characters (taking us to 8 bits per character)
- ▶ E.g. accented characters for European languages, other Western alphabets e.g. Greek, Cyrillic, mathematical symbols



# ASCII

- ▶ ASCII works OK for English
- ▶ Standards exist to add another 128 characters (taking us to 8 bits per character)
- ▶ E.g. accented characters for European languages, other Western alphabets e.g. Greek, Cyrillic, mathematical symbols
- ▶ However 256 characters isn't enough...

# Unicode

# Unicode

- ▶ Standard character set developed from 1987 to present day

# Unicode

- ▶ Standard character set developed from 1987 to present day
- ▶ Currently defines 137994 characters (Unicode 12.1)

# Unicode

- ▶ Standard character set developed from 1987 to present day
- ▶ Currently defines 137994 characters (Unicode 12.1)
- ▶ First 128 characters are the same as ASCII

# Unicode

- ▶ Standard character set developed from 1987 to present day
- ▶ Currently defines 137994 characters (Unicode 12.1)
- ▶ First 128 characters are the same as ASCII
- ▶ Covers most of the world's writing systems

# Unicode

- ▶ Standard character set developed from 1987 to present day
- ▶ Currently defines 137994 characters (Unicode 12.1)
- ▶ First 128 characters are the same as ASCII
- ▶ Covers most of the world's writing systems
- ▶ Also covers mathematical symbols and emoji

# Encoding Unicode



# Encoding Unicode

- ▶ **UTF-32** encodes characters as 32-bit integers

# Encoding Unicode

- ▶ **UTF-32** encodes characters as 32-bit integers
- ▶ **UTF-8** encodes characters as 8, 16, 24 or 32-bit integers

# Encoding Unicode

- ▶ **UTF-32** encodes characters as 32-bit integers
- ▶ **UTF-8** encodes characters as 8, 16, 24 or 32-bit integers
  - ▶ 8-bit characters correspond to the first 128 ASCII characters  $\implies$  backwards compatible

# Encoding Unicode

- ▶ **UTF-32** encodes characters as 32-bit integers
- ▶ **UTF-8** encodes characters as 8, 16, 24 or 32-bit integers
  - ▶ 8-bit characters correspond to the first 128 ASCII characters  $\implies$  backwards compatible
  - ▶ More common Unicode characters are smaller  $\implies$  more efficient than UTF-32

# String representation

# String representation

- ▶ `"Hello world!"` in ASCII or UTF-8 encoding:

# String representation

- ▶ "Hello world!" in ASCII or UTF-8 encoding:

72	101	108	108	111	32	119	111	114	108	100	33	0
----	-----	-----	-----	-----	----	-----	-----	-----	-----	-----	----	---

# UTF-8 representation



# UTF-8 representation

- ▶ For characters in ASCII, UTF-8 is the same:

# UTF-8 representation

- ▶ For characters in ASCII, UTF-8 is the same:
  - ▶  $a \rightarrow [97]$

# UTF-8 representation

- ▶ For characters in ASCII, UTF-8 is the same:
  - ▶  $a \rightarrow [97]$
- ▶ Other characters are encoded as multi-byte sequences:

# UTF-8 representation

- ▶ For characters in ASCII, UTF-8 is the same:
  - ▶  $a \rightarrow [97]$
- ▶ Other characters are encoded as multi-byte sequences:
  - ▶  $ü \rightarrow [195, 188]$

# UTF-8 representation

- ▶ For characters in ASCII, UTF-8 is the same:
  - ▶  $a \rightarrow [97]$
- ▶ Other characters are encoded as multi-byte sequences:
  - ▶  $\ddot{u} \rightarrow [195, 188]$
  - ▶ 串  $\rightarrow [228, 184, 178]$

# UTF-8 representation

- ▶ For characters in ASCII, UTF-8 is the same:
  - ▶  $a \rightarrow [97]$
- ▶ Other characters are encoded as multi-byte sequences:
  - ▶  $\ddot{u} \rightarrow [195, 188]$
  - ▶ 串  $\rightarrow [228, 184, 178]$
  - ▶ 😂  $\rightarrow [240, 159, 152, 130]$

# UTF-8 representation

- ▶ For characters in ASCII, UTF-8 is the same:
  - ▶  $a \rightarrow [97]$
- ▶ Other characters are encoded as multi-byte sequences:
  - ▶  $\ddot{u} \rightarrow [195, 188]$
  - ▶ 串  $\rightarrow [228, 184, 178]$
  - ▶ 😂  $\rightarrow [240, 159, 152, 130]$
- ▶ "Haha 😂" encoded in UTF-8:

# UTF-8 representation

- ▶ For characters in ASCII, UTF-8 is the same:
  - ▶  $a \rightarrow [97]$
- ▶ Other characters are encoded as multi-byte sequences:
  - ▶  $\ddot{u} \rightarrow [195, 188]$
  - ▶ 串  $\rightarrow [228, 184, 178]$
  - ▶ 😂  $\rightarrow [240, 159, 152, 130]$
- ▶ "Haha 😂" encoded in UTF-8:

H	a	h	a	space	😂				null
72	97	104	97	32	240	159	152	130	0



# Strings in Python

# Strings in Python

- ▶ Python 2 had separate types for ASCII and Unicode strings: `str` and `unicode`

# Strings in Python

- ▶ Python 2 had separate types for ASCII and Unicode strings: `str` and `unicode`
- ▶ Python 3 has just the `str` type, which uses Unicode

# Strings in Python

- ▶ Python 2 had separate types for ASCII and Unicode strings: `str` and `unicode`
- ▶ Python 3 has just the `str` type, which uses Unicode
- ▶ String literals are wrapped in `'single quotes'` or `"double quotes"` (there is no difference)

# Escape sequences

# Escape sequences

- ▶ Backslash `\` has a special meaning in string literals — it denotes the start of an **escape sequence**

# Escape sequences

- ▶ Backslash `\` has a special meaning in string literals — it denotes the start of an **escape sequence**
- ▶ Typically used to write **non-printable characters**

# Escape sequences

- ▶ Backslash `\` has a special meaning in string literals — it denotes the start of an **escape sequence**
- ▶ Typically used to write **non-printable characters**
- ▶ Most useful: `"\n"` is a new line



# Escape sequences

- ▶ Backslash `\` has a special meaning in string literals — it denotes the start of an **escape sequence**
- ▶ Typically used to write **non-printable characters**
- ▶ Most useful: `"\n"` is a new line
- ▶ How to type a backslash character? Use `"\\"`

# String literal tricks in Python

# String literal tricks in Python

- ▶ Use triple quotes `'''` or `"""` for a multi-line string

# String literal tricks in Python

- ▶ Use triple quotes `'''` or `"""` for a multi-line string
- ▶ Use `r" "` or `r' '` to turn off escape characters (useful for strings with lots of backslashes, e.g. Windows file paths, regular expressions)

# Text files

# Text files

- ▶ Stored on disk as essentially one long string

# Text files

- ▶ Stored on disk as essentially one long string
- ▶ Line endings are denoted by non-printable characters

# Text files

- ▶ Stored on disk as essentially one long string
- ▶ Line endings are denoted by non-printable characters
  - ▶ Unix format: line feed character (ASCII/UTF-8 character 10, "`\n`")



# Text files

- ▶ Stored on disk as essentially one long string
- ▶ Line endings are denoted by non-printable characters
  - ▶ Unix format: line feed character (ASCII/UTF-8 character 10, `"\n"`)
  - ▶ Windows format: carriage return character (ASCII/UTF-8 character 13) followed by line feed, `"\r\n"`

# Text files

- ▶ Stored on disk as essentially one long string
- ▶ Line endings are denoted by non-printable characters
  - ▶ Unix format: line feed character (ASCII/UTF-8 character 10, `"\n"`)
  - ▶ Windows format: carriage return character (ASCII/UTF-8 character 13) followed by line feed, `"\r\n"`
  - ▶ Most text editors can handle and convert both formats

# Text files

- ▶ Stored on disk as essentially one long string
- ▶ Line endings are denoted by non-printable characters
  - ▶ Unix format: line feed character (ASCII/UTF-8 character 10, `"\n"`)
  - ▶ Windows format: carriage return character (ASCII/UTF-8 character 13) followed by line feed, `"\r\n"`
  - ▶ Most text editors can handle and convert both formats
  - ▶ Most languages allow files to be opened in "text mode" which automatically converts

# Other types



# Booleans

# Booleans

- ▶ A **boolean** can have one of two values: **true** or **false**

# Booleans

- ▶ A **boolean** can have one of two values: **true** or **false**
- ▶ Python type: `bool`

# Booleans

- ▶ A **boolean** can have one of two values: **true** or **false**
- ▶ Python type: `bool`
- ▶ In Python, we have the keywords `True` and `False`



# Booleans

- ▶ A **boolean** can have one of two values: **true** or **false**
- ▶ Python type: `bool`
- ▶ In Python, we have the keywords `True` and `False`
- ▶ Could be represented by a single bit in memory...

# Booleans

- ▶ A **boolean** can have one of two values: **true** or **false**
- ▶ Python type: `bool`
- ▶ In Python, we have the keywords `True` and `False`
- ▶ Could be represented by a single bit in memory...
- ▶ ... but since memory is addressed in bytes (or words of multiple bytes), usually represented as an `int` with 0 meaning `False` and any non-zero (e.g. 1) meaning `True`

# Boolean values

# Boolean values

- ▶ The `if` statement takes a boolean value as its condition:

```
if x > 10:  
    print(x)
```

# Boolean values

- ▶ The `if` statement takes a boolean value as its condition:

```
if x > 10:  
    print(x)
```

- ▶ Variables can also store boolean values:

```
result = (x > 10)    # result now stores True or False  
if result:  
    print(x)
```

# The “None” value

# The “None” value

- ▶ Python has a special value `None` which can be used to denote the “absence” of any other value

# The “None” value

- ▶ Python has a special value `None` which can be used to denote the “absence” of any other value
- ▶ Python type: `NoneType`



# Checking types in Python

# Checking types in Python

- ▶ Call `type()` to check the type of a variable or value

# Checking types in Python

- ▶ Call `type()` to check the type of a variable or value
- ▶ Note that `type()` returns a value of type `type`

# Checking types in Python

- ▶ Call `type()` to check the type of a variable or value
- ▶ Note that `type()` returns a value of type `type`
- ▶ You can use these `type` values like any other value, e.g.

```
if type(x) == int:
    print("x has type int")
elif type(x) == type(y):
    print("x and y have the same type")
```

# Other types

# Other types

- ▶ **Container** types for collecting several values

# Other types

- ▶ **Container** types for collecting several values
  - ▶ `list`, `tuple`, `dict`, `set`, ...

# Other types

- ▶ **Container** types for collecting several values
  - ▶ `list`, `tuple`, `dict`, `set`, ...
- ▶ **Objects** — a way to define your own types



# Other types

- ▶ **Container** types for collecting several values
  - ▶ `list`, `tuple`, `dict`, `set`, ...
- ▶ **Objects** — a way to define your own types
- ▶ Almost everything in Python is a value with a type

# Other types

- ▶ **Container** types for collecting several values
  - ▶ `list`, `tuple`, `dict`, `set`, ...
- ▶ **Objects** — a way to define your own types
- ▶ Almost everything in Python is a value with a type
  - ▶ Functions, modules, classes, exceptions, ...

# Converting types



# Weak vs strong typing

# Weak vs strong typing

- In **weakly typed** languages, a variable can hold a value of any type

# Weak vs strong typing

- ▶ In **weakly typed** languages, a variable can hold a value of any type
  - ▶ Examples: Python, JavaScript

# Weak vs strong typing

- ▶ In **weakly typed** languages, a variable can hold a value of any type
  - ▶ Examples: Python, JavaScript
- ▶ In **strongly typed** languages, the type of a variable must be **declared**

# Weak vs strong typing

- ▶ In **weakly typed** languages, a variable can hold a value of any type
  - ▶ Examples: Python, JavaScript
- ▶ In **strongly typed** languages, the type of a variable must be **declared**
  - ▶ Examples: C#, C++, Java



# Weak typing (example in Python)

```
x = 7
# Now x has type int

x = "hello"
# Now x has type string
```

# Strong typing (example in C#)

```
int x = 7;  
// x is declared with type int  
  
x = "hello";  
// Compile error: cannot convert type "string" to "int"
```

# Type casting

# Type casting

- It is often useful to **cast**, or **convert**, a value from one type to another

# Type casting

- ▶ It is often useful to **cast**, or **convert**, a value from one type to another
- ▶ In Python, this is done by calling the type as if it were a function

# Type casting

- ▶ It is often useful to **cast**, or **convert**, a value from one type to another
- ▶ In Python, this is done by calling the type as if it were a function
  - ▶ `float(17)` → `17.0`

# Type casting

- ▶ It is often useful to **cast**, or **convert**, a value from one type to another
- ▶ In Python, this is done by calling the type as if it were a function
  - ▶ `float(17)` → `17.0`
  - ▶ `int(3.14)` → `3`

# Type casting

- ▶ It is often useful to **cast**, or **convert**, a value from one type to another
- ▶ In Python, this is done by calling the type as if it were a function
  - ▶ `float(17)` → `17.0`
  - ▶ `int(3.14)` → `3`
  - ▶ `str(3.14)` → `"3.14"`



# Type casting

- ▶ It is often useful to **cast**, or **convert**, a value from one type to another
- ▶ In Python, this is done by calling the type as if it were a function
  - ▶ `float(17)` → `17.0`
  - ▶ `int(3.14)` → `3`
  - ▶ `str(3.14)` → `"3.14"`
  - ▶ `str(1 + 1 == 2)` → `"True"`

# Type casting

- ▶ It is often useful to **cast**, or **convert**, a value from one type to another
- ▶ In Python, this is done by calling the type as if it were a function
  - ▶ `float(17)` → `17.0`
  - ▶ `int(3.14)` → `3`
  - ▶ `str(3.14)` → `"3.14"`
  - ▶ `str(1 + 1 == 2)` → `"True"`
  - ▶ `int("123")` → `123`

# Type casting

- ▶ It is often useful to **cast**, or **convert**, a value from one type to another
- ▶ In Python, this is done by calling the type as if it were a function
  - ▶ `float(17)` → `17.0`
  - ▶ `int(3.14)` → `3`
  - ▶ `str(3.14)` → `"3.14"`
  - ▶ `str(1 + 1 == 2)` → `"True"`
  - ▶ `int("123")` → `123`
  - ▶ `int("five")` gives an error

# Operations on types

# Operations on types

- ▶ Certain operations can only be done on certain types of values

# Operations on types

- ▶ Certain operations can only be done on certain types of values
- ▶ Can add two ints:  $2 + 3 \rightarrow 5$

# Operations on types

- ▶ Certain operations can only be done on certain types of values
- ▶ Can add two ints:  $2 + 3 \rightarrow 5$
- ▶ Can add int and float:  $2 + 3.1 \rightarrow 5.1$

# Operations on types

- ▶ Certain operations can only be done on certain types of values
- ▶ Can add two ints:  $2 + 3 \rightarrow 5$
- ▶ Can add int and float:  $2 + 3.1 \rightarrow 5.1$
- ▶ Can add two strings: `"COMP" + "110" → "COMP110"`



# Operations on types

- ▶ Certain operations can only be done on certain types of values
- ▶ Can add two ints:  $2 + 3 \rightarrow 5$
- ▶ Can add int and float:  $2 + 3.1 \rightarrow 5.1$
- ▶ Can add two strings: `"COMP" + "110" → "COMP110"`
- ▶ Can't add string and int: `"COMP" + 110 → error`

# Implicit type conversion

# Implicit type conversion

- ▶ The type casts we saw a few slides ago are **explicit**

# Implicit type conversion

- ▶ The type casts we saw a few slides ago are **explicit**
- ▶ Some languages (not Python) can perform **implicit** type casts to make operations work

# Implicit type conversion

- ▶ The type casts we saw a few slides ago are **explicit**
- ▶ Some languages (not Python) can perform **implicit** type casts to make operations work
- ▶ Sometimes called **type coercion**

# Implicit type conversion

- ▶ The type casts we saw a few slides ago are **explicit**
- ▶ Some languages (not Python) can perform **implicit** type casts to make operations work
- ▶ Sometimes called **type coercion**
- ▶ E.g. in JavaScript, `"COMP" + 110`  $\rightarrow$  `"COMP110"`

# Implicit type conversion

- ▶ The type casts we saw a few slides ago are **explicit**
- ▶ Some languages (not Python) can perform **implicit** type casts to make operations work
- ▶ Sometimes called **type coercion**
- ▶ E.g. in JavaScript, `"COMP" + 110`  $\rightarrow$  `"COMP110"`
- ▶ The integer `110` is implicitly converted to a string `"110"` to make the addition work

# Implicit type conversion

- ▶ The type casts we saw a few slides ago are **explicit**
- ▶ Some languages (not Python) can perform **implicit** type casts to make operations work
- ▶ Sometimes called **type coercion**
- ▶ E.g. in JavaScript, `"COMP" + 110`  $\rightarrow$  `"COMP110"`
- ▶ The integer `110` is implicitly converted to a string `"110"` to make the addition work
- ▶ Equivalent in Python with explicit casts:  
`"COMP" + str(110)`



# Dangers of implicit type conversion

# Dangers of implicit type conversion

- ▶ Rules for implicit type conversion can sometimes be confusing

# Dangers of implicit type conversion

- ▶ Rules for implicit type conversion can sometimes be confusing
- ▶ E.g. in JavaScript:

# Dangers of implicit type conversion

- ▶ Rules for implicit type conversion can sometimes be confusing
- ▶ E.g. in JavaScript:
  - ▶ `"5" + 3 → "53"`

# Dangers of implicit type conversion

- ▶ Rules for implicit type conversion can sometimes be confusing
- ▶ E.g. in JavaScript:
  - ▶ `"5" + 3` → `"53"`
  - ▶ `"5" - 3` → `2`