



COMP110: Principles of Computing  
**8: Data Structures I**



# Administration

# Administration

- ▶ Research Journal Peer Review is **today**

# Administration

- ▶ Research Journal Peer Review is **today**
- ▶ Final deadline is **soon (check MyFalmouth)**

# Arrays and lists



# Memory allocation — recap

# Memory allocation — recap

- ▶ Memory is allocated in **blocks**

# Memory allocation — recap

- ▶ Memory is allocated in **blocks**
- ▶ The program specifies the size, in bytes, of the block it wants

# Memory allocation — recap

- ▶ Memory is allocated in **blocks**
- ▶ The program specifies the size, in bytes, of the block it wants
- ▶ The OS allocates a **contiguous** block of that size

# Memory allocation — recap

- ▶ Memory is allocated in **blocks**
- ▶ The program specifies the size, in bytes, of the block it wants
- ▶ The OS allocates a **contiguous** block of that size
- ▶ The program owns that block until it frees it

# Memory allocation — recap

- ▶ Memory is allocated in **blocks**
- ▶ The program specifies the size, in bytes, of the block it wants
- ▶ The OS allocates a **contiguous** block of that size
- ▶ The program owns that block until it frees it
- ▶ Blocks can be allocated and deallocated at will, but can **never grow or shrink**

# Collection types

# Collection types

- ▶ Memory management is hard and programmers are lazy

# Collection types

- ▶ Memory management is hard and programmers are lazy
- ▶ Collections are an **abstraction**

# Collection types

- ▶ Memory management is hard and programmers are lazy
- ▶ Collections are an **abstraction**
  - ▶ Hide the details of memory allocation, and allow the programmer to write simpler code

# Collection types

- ▶ Memory management is hard and programmers are lazy
- ▶ Collections are an **abstraction**
  - ▶ Hide the details of memory allocation, and allow the programmer to write simpler code
- ▶ Collections are an **encapsulation**

# Collection types

- ▶ Memory management is hard and programmers are lazy
- ▶ Collections are an **abstraction**
  - ▶ Hide the details of memory allocation, and allow the programmer to write simpler code
- ▶ Collections are an **encapsulation**
  - ▶ Bundle together the data's representation in memory along with the algorithms for accessing it

# Arrays

# Arrays

- ▶ An **array** is a contiguous block of memory in which objects are stored, equally spaced, one after the other

# Arrays

- ▶ An **array** is a contiguous block of memory in which objects are stored, equally spaced, one after the other
- ▶ Each array element has an **index**, starting from zero

# Arrays

- ▶ An **array** is a contiguous block of memory in which objects are stored, equally spaced, one after the other
- ▶ Each array element has an **index**, starting from zero
- ▶ Given the address of the 0th element, it is easy to find the  $i$ th element:

$$\text{address}_i = \text{address}_0 + (i \times \text{elementSize})$$

# Arrays

- ▶ An **array** is a contiguous block of memory in which objects are stored, equally spaced, one after the other
- ▶ Each array element has an **index**, starting from zero
- ▶ Given the address of the 0th element, it is easy to find the  $i$ th element:

$$\text{address}_i = \text{address}_0 + (i \times \text{elementSize})$$

- ▶ E.g. if the array starts at address 1000 and each element is 4 bytes, the 3rd element is at address  $1000 + 4 \times 3 = 1012$

# Arrays

- ▶ An **array** is a contiguous block of memory in which objects are stored, equally spaced, one after the other
- ▶ Each array element has an **index**, starting from zero
- ▶ Given the address of the 0th element, it is easy to find the  $i$ th element:

$$\text{address}_i = \text{address}_0 + (i \times \text{elementSize})$$

- ▶ E.g. if the array starts at address 1000 and each element is 4 bytes, the 3rd element is at address  $1000 + 4 \times 3 = 1012$
- ▶ Accessing an array element is **constant time**  $O(1)$

# Lists

# Lists

- ▶ An array is a block of memory, so its size is **fixed** once created

# Lists

- ▶ An array is a block of memory, so its size is **fixed** once created
- ▶ A **list** is a variable size array


# Lists

- ▶ An array is a block of memory, so its size is **fixed** once created
- ▶ A **list** is a variable size array
- ▶ When the list needs to change size, it **creates** a new array, **copies** the contents of the old array, and **deletes** the old array

# Arrays and lists in C#

```
int[] myArray = new int[10];  
  
int[] myOtherArray = new int[] { 2, 3, 5, 7, 11 };  
  
List<int> myList = new List<int>();  
  
List<int> myOtherList = new List<int> { 2, 3, 5, 8, 13 };
```

# Time taken to append an element to a list of size $n$



# Operations on lists

# Operations on lists

- ▶ **Appending** to a list is **amortised constant time**

# Operations on lists

- ▶ **Appending** to a list is **amortised constant time**
  - ▶ Usually  $O(1)$ , but can go up to  $O(n)$  if the list needs to change size

# Operations on lists

- ▶ **Appending** to a list is **amortised constant time**
  - ▶ Usually  $O(1)$ , but can go up to  $O(n)$  if the list needs to change size
- ▶ **Inserting** anywhere other than the end is **linear time**

# Operations on lists

- ▶ **Appending** to a list is **amortised constant time**
  - ▶ Usually  $O(1)$ , but can go up to  $O(n)$  if the list needs to change size
- ▶ **Inserting** anywhere other than the end is **linear time**
  - ▶ Can't just insert new bytes into a memory block — need to move all subsequent list elements to make room

# Operations on lists

- ▶ **Appending** to a list is **amortised constant time**
  - ▶ Usually  $O(1)$ , but can go up to  $O(n)$  if the list needs to change size
- ▶ **Inserting** anywhere other than the end is **linear time**
  - ▶ Can't just insert new bytes into a memory block — need to move all subsequent list elements to make room
- ▶ Similarly, **deleting** anything other than the last element is **linear time**

# Basic data structures in C#



# Classes and interfaces

# Classes and interfaces

- ▶ A **class** in C# defines constructors, destructor, methods, properties, fields, ...

# Classes and interfaces

- ▶ A **class** in C# defines constructors, destructor, methods, properties, fields, ...
- ▶ An **interface** defines methods and properties which a class can implement

# Classes and interfaces

- ▶ A **class** in C# defines constructors, destructor, methods, properties, fields, ...
- ▶ An **interface** defines methods and properties which a class can implement
- ▶ An interface is a little like a fully abstract class

# Classes and interfaces

- ▶ A **class** in C# defines constructors, destructor, methods, properties, fields, ...
- ▶ An **interface** defines methods and properties which a class can implement
- ▶ An interface is a little like a fully abstract class
- ▶ A class in C# can only **inherit** from one **class**, but can **implement** several **interfaces**

# IEnumerable

# IEnumerable

- Most collection types in C# implement the `IEnumerable<ElementType>` interface

# IEnumerable

- ▶ Most collection types in C# implement the `IEnumerable<ElementType>` interface
- ▶ This interface allows us to iterate through the elements in the collection, from beginning to end

# IEnumerable

- ▶ Most collection types in C# implement the `IEnumerable<ElementType>` interface
- ▶ This interface allows us to iterate through the elements in the collection, from beginning to end
- ▶ C# provides the `foreach` loop as a convenient way of using this

# IEnumerable

- ▶ Most collection types in C# implement the `IEnumerable<ElementType>` interface
- ▶ This interface allows us to iterate through the elements in the collection, from beginning to end
- ▶ C# provides the `foreach` loop as a convenient way of using this
- ▶ ⇒ any class which implements `IEnumerable<ElementType>` can be used with a `foreach` loop

# Arrays

```
int[] myArray = new int[10];
int[] anotherArray = new int[] { 123, 456, 789 };
```

# Arrays

```
int[] myArray = new int[10];  
int[] anotherArray = new int[] { 123, 456, 789 };
```

- ▶ `int[]` is an array of `ints`

# Arrays

```
int[] myArray = new int[10];  
int[] anotherArray = new int[] { 123, 456, 789 };
```

- ▶ `int[]` is an array of `ints`
- ▶ In general, `ElementType[]` is an array of values of type `ElementType`

# Arrays

```
int[] myArray = new int[10];  
int[] anotherArray = new int[] { 123, 456, 789 };
```

- ▶ `int[]` is an array of `ints`
- ▶ In general, `ElementType[]` is an array of values of type `ElementType`
- ▶ Size of the array is set on initialisation with `new`

# Arrays

```
int[] myArray = new int[10];  
int[] anotherArray = new int[] { 123, 456, 789 };
```

- ▶ `int[]` is an array of `ints`
- ▶ In general, `ElementType[]` is an array of values of type `ElementType`
- ▶ Size of the array is set on initialisation with `new`
- ▶ Array **cannot change size** after initialisation

# Arrays

```
int[] myArray = new int[10];  
int[] anotherArray = new int[] { 123, 456, 789 };
```

- ▶ `int[]` is an array of `ints`
- ▶ In general, `ElementType[]` is an array of values of type `ElementType`
- ▶ Size of the array is set on initialisation with `new`
- ▶ Array **cannot change size** after initialisation
- ▶ Use `myArray[i]` to get/set the `i`th element (starting at 0)

# Arrays

```
int[] myArray = new int[10];
int[] anotherArray = new int[] { 123, 456, 789 };
```

- ▶ `int[]` is an array of `ints`
- ▶ In general, `ElementType[]` is an array of values of type `ElementType`
- ▶ Size of the array is set on initialisation with `new`
- ▶ Array **cannot change size** after initialisation
- ▶ Use `myArray[i]` to get/set the `i`th element (starting at 0)
- ▶ Use `myArray.Length` to get the number of elements

# Multi-dimensional arrays

```
int[,] myGrid = new int[20, 15];
```

# Multi-dimensional arrays

```
int[,] myGrid = new int[20, 15];
```

- ▶ `int[,]` is a 2-dimensional array of `ints`

# Multi-dimensional arrays

```
int[,] myGrid = new int[20, 15];
```

- ▶ `int[,]` is a 2-dimensional array of `ints`
- ▶ Use `myArray[x, y]` to get/set elements

# Multi-dimensional arrays

```
int[,] myGrid = new int[20, 15];
```

- ▶ `int[,]` is a 2-dimensional array of `ints`
- ▶ Use `myArray[x, y]` to get/set elements
- ▶ Use `myArray.GetLength(0), myArray.GetLength(1)` to get the “width” and “height”

# Multi-dimensional arrays

```
int[,] myGrid = new int[20, 15];
```

- ▶ `int[,]` is a 2-dimensional array of `ints`
- ▶ Use `myArray[x, y]` to get/set elements
- ▶ Use `myArray.GetLength(0), myArray.GetLength(1)` to get the “width” and “height”
- ▶ Similarly `int[, ,]` is a 3-dimensional array, etc.

# Lists

```
using System.Collections.Generic;  
  
List<int> myList = new List<int>();  
List<int> anotherList = new List<int> { 1, 2, 3, 4 };
```

# Lists

```
using System.Collections.Generic;  
  
List<int> myList = new List<int>();  
List<int> anotherList = new List<int> { 1, 2, 3, 4 };
```

- ▶ Like a list in Python, but can only store values of the specified type (here `int`)

# Lists

```
using System.Collections.Generic;  
  
List<int> myList = new List<int>();  
List<int> anotherList = new List<int> { 1, 2, 3, 4 };
```

- ▶ Like a list in Python, but can only store values of the specified type (here `int`)
- ▶ Append elements with `myList.Add()`

# Lists

```
using System.Collections.Generic;  
  
List<int> myList = new List<int>();  
List<int> anotherList = new List<int> { 1, 2, 3, 4 };
```

- ▶ Like a list in Python, but can only store values of the specified type (here `int`)
- ▶ Append elements with `myList.Add()`
- ▶ Get the number of elements with `myList.Count`

# Strings

```
string myString = "Hello, world!";
```

# Strings

```
string myString = "Hello, world!";
```

- ▶ **string** can be thought of as a collection

# Strings

```
string myString = "Hello, world!";
```

- ▶ `string` can be thought of as a collection
- ▶ In particular, it implements `IEnumerable<char>`

# Strings

```
string myString = "Hello, world!";
```

- ▶ `string` can be thought of as a collection
- ▶ In particular, it implements `IEnumerable<char>`
- ▶ So for example we can iterate over the characters in a string:

```
foreach (char c in myString)
{
    Console.WriteLine(c);
}
```

# Strings are immutable

# Strings are immutable

- ▶ Strings are **immutable** in C#

# Strings are immutable

- ▶ Strings are **immutable** in C#
- ▶ This means that the contents of a string **cannot be changed** once it is created

# Strings are immutable

- ▶ Strings are **immutable** in C#
- ▶ This means that the contents of a string **cannot be changed** once it is created
- ▶ But wait... we change strings all the time, don't we?

```
string myString = "Hello ";
myString += "world";
```

# Strings are immutable

- ▶ Strings are **immutable** in C#
- ▶ This means that the contents of a string **cannot be changed** once it is created
- ▶ But wait... we change strings all the time, don't we?

```
string myString = "Hello ";
myString += "world";
```

- ▶ This isn't changing the string, it's creating a new one and throwing the old one away!

# Strings are immutable

- ▶ Strings are **immutable** in C#
- ▶ This means that the contents of a string **cannot be changed** once it is created
- ▶ But wait... we change strings all the time, don't we?

```
string myString = "Hello ";
myString += "world";
```

- ▶ This isn't changing the string, it's creating a new one and throwing the old one away!
- ▶ Hence building a long string by appending can be slow (appending strings is  $O(n)$ )

# Strings are immutable

- ▶ Strings are **immutable** in C#
- ▶ This means that the contents of a string **cannot be changed** once it is created
- ▶ But wait... we change strings all the time, don't we?

```
string myString = "Hello ";
myString += "world";
```

- ▶ This isn't changing the string, it's creating a new one and throwing the old one away!
- ▶ Hence building a long string by appending can be slow (appending strings is  $O(n)$ )
- ▶ C# has a **mutable** string type: `StringBuilder`

# Dictionaries

# Dictionaries

- Dictionaries are **associative maps**

# Dictionaries

- ▶ Dictionaries are **associative maps**
- ▶ A dictionary maps **keys** to **values**

# Dictionaries

- ▶ Dictionaries are **associative maps**
- ▶ A dictionary maps **keys** to **values**
- ▶ Takes two generic parameters: the **key type** and the **value type**

# Dictionaries

- ▶ Dictionaries are **associative maps**
- ▶ A dictionary maps **keys** to **values**
- ▶ Takes two generic parameters: the **key type** and the **value type**
- ▶ A dictionary is implemented as a **hash table**

# Using dictionaries

```
var age = new Dictionary<string, int> {
    ["Alice"] = 23,
    ["Bob"] = 36,
    ["Charlie"] = 27
};
```

# Using dictionaries

```
var age = new Dictionary<string, int> {  
    ["Alice"] = 23,  
    ["Bob"] = 36,  
    ["Charlie"] = 27  
};
```

Access values using []:

```
Console.WriteLine(age["Alice"]); // prints 23  
age["Bob"] = 40; // overwriting an existing item  
age["Denise"] = 21; // adding a new item  
age.Add("Emily", 29); // adding a new item -- will raise  
                      // an error if already present
```

# Iterating over dictionaries

# Iterating over dictionaries

- Dictionary<Key, Value> implements  
IEnumerable<KeyValuePair<Key, Value>>

# Iterating over dictionaries

- ▶ Dictionary<Key, Value> implements  
IEnumerable<KeyValuePair<Key, Value>>
- ▶ KeyValuePair<Key, Value> stores Key and Value

# Iterating over dictionaries

- ▶ Dictionary<Key, Value> implements  
IEnumerable<KeyValuePair<Key, Value>>
- ▶ KeyValuePair<Key, Value> stores Key and Value

```
foreach (var keyValue in age)
{
    Console.WriteLine("{0} is {1} years old",
                      kv.Key, kv.Value);
}
```

# Iterating over dictionaries

- ▶ Dictionary<Key, Value> implements  
IEnumerable<KeyValuePair<Key, Value>>
- ▶ KeyValuePair<Key, Value> stores Key and Value

```
foreach (var keyValue in age)
{
    Console.WriteLine("{0} is {1} years old",
                      kv.Key, kv.Value);
}
```

- ▶ (C# tip: the var keyword lets the compiler automatically determine the appropriate type to use for a variable)

# Iterating over dictionaries

- ▶ Dictionary<Key, Value> implements  
IEnumerable<KeyValuePair<Key, Value>>
- ▶ KeyValuePair<Key, Value> stores Key and Value

```
foreach (var keyValue in age)
{
    Console.WriteLine("{0} is {1} years old",
                      kv.Key, kv.Value);
}
```

- ▶ (C# tip: the var keyword lets the compiler automatically determine the appropriate type to use for a variable)
- ▶ Dictionaries are **unordered** — avoid assuming that **foreach** will see the elements in any particular order!

# Hash sets

# Hash sets

- ▶ Sets are **unordered** collections of **unique** elements

# Hash sets

- ▶ Sets are **unordered** collections of **unique** elements
  - ▶ Sets **cannot** contain **duplicate** elements

# Hash sets

- ▶ Sets are **unordered** collections of **unique** elements
  - ▶ Sets **cannot** contain **duplicate** elements
  - ▶ Attempting to `Add` an element already present in the set does nothing

# Hash sets

- ▶ Sets are **unordered** collections of **unique** elements
  - ▶ Sets **cannot** contain **duplicate** elements
  - ▶ Attempting to `Add` an element already present in the set does nothing
- ▶ HashSets are like `Dictionary`s without the values, just the keys

# Hash sets

- ▶ Sets are **unordered** collections of **unique** elements
  - ▶ Sets **cannot** contain **duplicate** elements
  - ▶ Attempting to `Add` an element already present in the set does nothing
- ▶ HashSets are like Dictionaries without the values, just the keys
- ▶ As discussed in Week 5, certain operations are much more efficient (constant time) on hash sets than on lists

# Using sets

```
var numbers = new HashSet<int>{1, 4, 9, 16, 25};
```

# Using sets

```
var numbers = new HashSet<int>{1, 4, 9, 16, 25};
```

Add and remove members with `Add` and `Remove` methods

```
numbers.Add(36);  
numbers.Remove(4);
```

# Using sets

```
var numbers = new HashSet<int>{1, 4, 9, 16, 25};
```

Add and remove members with `Add` and `Remove` methods

```
numbers.Add(36);  
numbers.Remove(4);
```

Test membership with `Contains`

```
if (numbers.Contains(9))  
    Console.WriteLine("Set contains 9");
```

# Stacks and queues



# Stacks and queues

# Stacks and queues



- ▶ A **stack** is a **last-in first-out (LIFO)** data structure

# Stacks and queues



- ▶ A **stack** is a **last-in first-out (LIFO)** data structure
- ▶ Items can be **pushed** to the **top** of the stack

# Stacks and queues



- ▶ A **stack** is a **last-in first-out (LIFO)** data structure
- ▶ Items can be **pushed** to the **top** of the stack
- ▶ Items can be **popped** from the **top** of the stack

# Stacks and queues



- ▶ A **stack** is a **last-in first-out (LIFO)** data structure
- ▶ Items can be **pushed** to the **top** of the stack
- ▶ Items can be **popped** from the **top** of the stack
- ▶ A **queue** is a **first-in first-out (FIFO)** data structure



# Stacks and queues



- ▶ A **stack** is a **last-in first-out (LIFO)** data structure
- ▶ Items can be **pushed** to the **top** of the stack
- ▶ Items can be **popped** from the **top** of the stack
  
- ▶ A **queue** is a **first-in first-out (FIFO)** data structure
- ▶ Items can be **enqueued** to the **back** of the queue

# Stacks and queues



- ▶ A **stack** is a **last-in first-out (LIFO)** data structure
- ▶ Items can be **pushed** to the **top** of the stack
- ▶ Items can be **popped** from the **top** of the stack
  
- ▶ A **queue** is a **first-in first-out (FIFO)** data structure
- ▶ Items can be **enqueued** to the **back** of the queue
- ▶ Items can be **dequeued** from the **front** of the queue

# Implementing stacks

# Implementing stacks

- ▶ Stacks can be implemented efficiently as lists

# Implementing stacks

- ▶ Stacks can be implemented efficiently as lists
- ▶ Top of stack = end of list

# Implementing stacks

- ▶ Stacks can be implemented efficiently as lists
- ▶ Top of stack = end of list
- ▶ To push an element, use `Add` —  $O(1)$  complexity

# Implementing stacks

- ▶ Stacks can be implemented efficiently as lists
- ▶ Top of stack = end of list
- ▶ To push an element, use `Add` —  $O(1)$  complexity
- ▶ To pop an element we can do something like this:

```
x = myStack[myStack.Count - 1];  
myStack.RemoveAt(myStack.Count - 1);
```

# Implementing stacks

- ▶ Stacks can be implemented efficiently as lists
- ▶ Top of stack = end of list
- ▶ To push an element, use `Add` —  $O(1)$  complexity
- ▶ To pop an element we can do something like this:

```
x = myStack[myStack.Count - 1];  
myStack.RemoveAt(myStack.Count - 1);
```

- ▶ This is also  $O(1)$

# Implementing queues

# Implementing queues

- ▶ Queues can be implemented as lists, but not efficiently

# Implementing queues

- ▶ Queues can be implemented as lists, but not efficiently
- ▶ End of list = back of queue

# Implementing queues

- ▶ Queues can be implemented as lists, but not efficiently
- ▶ End of list = back of queue
- ▶ Enqueue using `Add` —  $O(1)$  complexity

# Implementing queues

- ▶ Queues can be implemented as lists, but not efficiently
- ▶ End of list = back of queue
- ▶ Enqueue using `Add` —  $O(1)$  complexity
- ▶ Dequeue by retrieving and removing from beginning of list:

```
x = myQueue[0];  
myQueue.RemoveAt(0);
```

# Implementing queues

- ▶ Queues can be implemented as lists, but not efficiently
- ▶ End of list = back of queue
- ▶ Enqueue using `Add` —  $O(1)$  complexity
- ▶ Dequeue by retrieving and removing from beginning of list:

```
x = myQueue[0];  
myQueue.RemoveAt(0);
```

- ▶ This is  $O(n)$

# Implementing queues

# Implementing queues

- ▶ End of list = front of queue

# Implementing queues

- ▶ End of list = front of queue
- ▶ Dequeue is like popping from end of list —  $O(1)$  complexity

# Implementing queues

- ▶ End of list = front of queue
- ▶ Dequeue is like popping from end of list —  $O(1)$  complexity
- ▶ Enqueue using `Insert(0, x)` —  $O(n)$  complexity

# Using stacks and queues

# Using stacks and queues

- ▶ C# has `Stack` and `Queue` classes which you should use instead of trying to use a list

# Using stacks and queues

- ▶ C# has `Stack` and `Queue` classes which you should use instead of trying to use a list
- ▶ Python has `deque` (double-ended queue) which can work as either a stack or a list

# Stacks and function calls

# Stacks and function calls

- ▶ Stacks are used to implement **nested function calls**

# Stacks and function calls

- ▶ Stacks are used to implement **nested function calls**
- ▶ Each invocation of a function has a **stack frame**

# Stacks and function calls

- ▶ Stacks are used to implement **nested function calls**
- ▶ Each invocation of a function has a **stack frame**
- ▶ This specifies information like **local variable values** and **return address**

# Stacks and function calls

- ▶ Stacks are used to implement **nested function calls**
- ▶ Each invocation of a function has a **stack frame**
- ▶ This specifies information like **local variable values** and **return address**
- ▶ Calling a function **pushes** a new frame onto the stack

# Stacks and function calls

- ▶ Stacks are used to implement **nested function calls**
- ▶ Each invocation of a function has a **stack frame**
- ▶ This specifies information like **local variable values** and **return address**
- ▶ Calling a function **pushes** a new frame onto the stack
- ▶ Returning from a function **pops** the top frame off the stack

# Stacks and function calls

- ▶ Stacks are used to implement **nested function calls**
- ▶ Each invocation of a function has a **stack frame**
- ▶ This specifies information like **local variable values** and **return address**
- ▶ Calling a function **pushes** a new frame onto the stack
- ▶ Returning from a function **pops** the top frame off the stack
- ▶ Hence the term **stack trace** when using the debugger or looking at error logs