

COMP220: Graphics & Simulation

# 3: Mathematics for graphics

# Learning outcomes

By the end of this session, you should be able to:

- ▶ **Explain** the role of vectors and matrices in computer graphics
- ▶ **Calculate** basic transformation matrices using the GLM library
- ▶ **Explain** the constituents of the model-view-projection matrix

# Transformations



# Transformations and matrices

# Transformations and matrices

- ▶ A **transformation** is a **mathematical function** that **changes points in space**

# Transformations and matrices

- ▶ A **transformation** is a **mathematical function** that **changes points in space**
- ▶ E.g. shifts them, rotates them, scales them, ...

# Transformations and matrices

- ▶ A **transformation** is a **mathematical function** that **changes points in space**
- ▶ E.g. shifts them, rotates them, scales them, ...
- ▶ Many useful transformations can be **represented** by matrices

# Transformations and matrices

- ▶ A **transformation** is a **mathematical function** that **changes points in space**
- ▶ E.g. shifts them, rotates them, scales them, ...
- ▶ Many useful transformations can be **represented** by matrices
- ▶ Multiplying these matrices together **combines** the transformations



# Transformations and matrices

- ▶ A **transformation** is a **mathematical function** that **changes points in space**
- ▶ E.g. shifts them, rotates them, scales them, ...
- ▶ Many useful transformations can be **represented** by matrices
- ▶ Multiplying these matrices together **combines** the transformations
- ▶ Multiplying a vector by the matrix **applies** the transformation

# GLM

# GLM

- ▶ We will use the **GLM** library to do matrix calculations for us

# GLM

- ▶ We will use the **GLM** library to do matrix calculations for us
- ▶ <http://glm.g-truc.net/>

# GLM

- ▶ We will use the **GLM** library to do matrix calculations for us
- ▶ <http://glm.g-truc.net/>
- ▶ GLM aims to mirror GLSL data types (`vec4`, `mat4` etc) in C++

# GLM

- ▶ We will use the **GLM** library to do matrix calculations for us
- ▶ <http://glm.g-truc.net/>
- ▶ GLM aims to mirror GLSL data types (`vec4`, `mat4` etc) in C++
- ▶ Lets us perform calculations with vectors and matrices in C++

# GLM

- ▶ We will use the **GLM** library to do matrix calculations for us
- ▶ <http://glm.g-truc.net/>
- ▶ GLM aims to mirror GLSL data types (`vec4`, `mat4` etc) in C++
- ▶ Lets us perform calculations with vectors and matrices in C++
- ▶ GLM types can be passed into shaders as uniforms, e.g.

```
// transformLocation points to a uniform of type ←  
mat4  
glm::mat4 transform = ...;  
glUniformMatrix4fv(transformLocation, 1, GL_FALSE ←  
    , glm::value_ptr(transform));
```

# Identity



# Identity

The identity transformation does not change anything

# Identity

The identity transformation does not change anything

```
// Default constructor for glm::mat4 creates an identity matrix ←  
glm::mat4 transform;
```

# Translation

# Translation

Translation shifts all points by the same vector offset

# Translation

Translation shifts all points by the same vector offset

```
transform = glm::translate(transform, glm::vec3(0.3f, 0.5f, 0.0f));
```

# Scaling

# Scaling

Scaling moves all points closer or further from the origin by the same factor

# Scaling

Scaling moves all points closer or further from the origin by the same factor

```
transform = glm::scale(transform, glm::vec3(1.2f, 0.5f ↵  
      , 1.0f));
```



# Rotation

# Rotation

- ▶ How do we represent a rotation in 3 dimensions?

# Rotation

- ▶ How do we represent a rotation in 3 dimensions?
- ▶ One way is by specifying the **axis** (as a vector) and the **angle** (in radians)

# Rotation

- ▶ How do we represent a rotation in 3 dimensions?
- ▶ One way is by specifying the **axis** (as a vector) and the **angle** (in radians)
- ▶ Axis always runs through the origin

# Rotation

- ▶ How do we represent a rotation in 3 dimensions?
- ▶ One way is by specifying the **axis** (as a vector) and the **angle** (in radians)
- ▶ Axis always runs through the origin

```
float angle = glm::pi<float>() * 0.5f;  
glm::vec3 axis(0, 0, 1);  
transform = glm::rotate(transform, angle, axis);
```

# Combining transformations

# Combining transformations

```
transform = glm::translate(transform, glm::vec3(0.5f, ↵  
    0.5f, 0.0f));  
transform = glm::rotate(transform, angle, axis);
```

# Combining transformations

```
transform = glm::translate(transform, glm::vec3(0.5f, 0.5f, 0.0f));  
transform = glm::rotate(transform, angle, axis);
```

- Transformations **do not commute** in general — changing the order will change the result



# Combining transformations

```
transform = glm::translate(transform, glm::vec3(0.5f, 0.5f, 0.0f));  
transform = glm::rotate(transform, angle, axis);
```

- ▶ Transformations **do not commute** in general — changing the order will change the result
- ▶ The order they are applied is the **reverse** of what you might think — i.e. the above rotates **then** translates

# Euler angles

# Euler angles

- ▶ Any orientation of an object in 3D space can be described by **three** rotations around:

# Euler angles

- ▶ Any orientation of an object in 3D space can be described by **three** rotations around:
  - ▶ The x-axis  $(1, 0, 0)$

# Euler angles


- ▶ Any orientation of an object in 3D space can be described by **three** rotations around:
  - ▶ The  $x$ -axis  $(1, 0, 0)$
  - ▶ The  $y$ -axis  $(0, 1, 0)$

# Euler angles

- ▶ Any orientation of an object in 3D space can be described by **three** rotations around:
  - ▶ The  $x$ -axis  $(1, 0, 0)$
  - ▶ The  $y$ -axis  $(0, 1, 0)$
  - ▶ The  $z$ -axis  $(0, 0, 1)$

# Euler angles

- ▶ Any orientation of an object in 3D space can be described by **three** rotations around:
  - ▶ The x-axis (1, 0, 0)
  - ▶ The y-axis (0, 1, 0)
  - ▶ The z-axis (0, 0, 1)
- ▶ These angles are sometimes called **roll**, **pitch** and **yaw**



# Gimbal lock

<https://youtu.be/rrUCBOlJdt4?t=1m55s>



# Model, View, Projection



# Model, View, Projection

# Model, View, Projection

Drawing a 3D object on screen generally involves **three** transformations:

# Model, View, Projection

Drawing a 3D object on screen generally involves **three** transformations:

- ▶ **Model:** translate, rotate and scale the object into its place in the scene

# Model, View, Projection

Drawing a 3D object on screen generally involves **three** transformations:

- ▶ **Model**: translate, rotate and scale the object into its place in the scene
- ▶ **View**: translate and rotate the scene to put the observer at the origin

# Model, View, Projection

Drawing a 3D object on screen generally involves **three** transformations:

- ▶ **Model:** translate, rotate and scale the object into its place in the scene
- ▶ **View:** translate and rotate the scene to put the observer at the origin
- ▶ **Projection:** convert points in 3D space to points on the 2D screen

# Model, View, Projection

Drawing a 3D object on screen generally involves **three** transformations:

- ▶ **Model**: translate, rotate and scale the object into its place in the scene
- ▶ **View**: translate and rotate the scene to put the observer at the origin
- ▶ **Projection**: convert points in 3D space to points on the 2D screen

The **model-view-projection (MVP) matrix**:

$$M_{MVP} = M_{\text{projection}} \times M_{\text{view}} \times M_{\text{model}}$$

(remember, multiplication goes in reverse order)

# The model matrix



# The model matrix

Exactly what we've been doing so far today...

# The view matrix

# The view matrix

Need to translate and rotate the scene so that the “camera” is at  $(0, 0, 0)$  and looking in the negative  $z$  direction

# The view matrix

Need to translate and rotate the scene so that the “camera” is at (0,0,0) and looking in the negative z direction

```
glm::mat4 view = glm::lookAt(  
    glm::vec3(2, 0, 2),    // eye  
    glm::vec3(0, 0, 0),    // centre  
    glm::vec3(0, 1, 0)    // up  
);
```

# The view matrix

Need to translate and rotate the scene so that the “camera” is at (0,0,0) and looking in the negative z direction

```
glm::mat4 view = glm::lookAt(  
    glm::vec3(2, 0, 2),    // eye  
    glm::vec3(0, 0, 0),    // centre  
    glm::vec3(0, 1, 0)    // up  
);
```

- `eye` is the position of the camera

# The view matrix

Need to translate and rotate the scene so that the “camera” is at (0,0,0) and looking in the negative z direction

```
glm::mat4 view = glm::lookAt(  
    glm::vec3(2, 0, 2),    // eye  
    glm::vec3(0, 0, 0),    // centre  
    glm::vec3(0, 1, 0)    // up  
);
```

- ▶ `eye` is the position of the camera
- ▶ `centre` is a point for the camera to look at

# The view matrix

Need to translate and rotate the scene so that the “camera” is at (0,0,0) and looking in the negative z direction


```
glm::mat4 view = glm::lookAt(  
    glm::vec3(2, 0, 2),    // eye  
    glm::vec3(0, 0, 0),    // centre  
    glm::vec3(0, 1, 0)    // up  
);
```

- ▶ `eye` is the position of the camera
- ▶ `centre` is a point for the camera to look at
- ▶ `up` is which direction is “up” for the camera (usually the positive y-axis)


# Types of projection



# Types of projection




Perspective projection




Orthographic projection

# Types of projection




Perspective projection




Orthographic projection

- Generally use **perspective** for 3D graphics

# Types of projection



Perspective projection



Orthographic projection

- ▶ Generally use **perspective** for 3D graphics
- ▶ **Orthographic** is useful for 2D or pseudo-2D graphics (e.g. isometric perspective)

# The projection matrix

# The projection matrix

```
glm::mat4 projection = glm::perspective(  
    glm::radians(45.0f), // field of view  
    4.0f / 3.0f,          // aspect ratio  
    0.1f,                 // near clip plane  
    100.0f                // far clip plane  
);
```

# The projection matrix

```
glm::mat4 projection = glm::perspective(  
    glm::radians(45.0f), // field of view  
    4.0f / 3.0f,          // aspect ratio  
    0.1f,                 // near clip plane  
    100.0f                // far clip plane  
);
```

- **Field of view (FOV):** how “wide” or “narrow” the view is

# The projection matrix

```
glm::mat4 projection = glm::perspective(  
    glm::radians(45.0f), // field of view  
    4.0f / 3.0f,          // aspect ratio  
    0.1f,                 // near clip plane  
    100.0f                // far clip plane  
);
```

- ▶ **Field of view (FOV):** how “wide” or “narrow” the view is
- ▶ **Aspect ratio:** should be `screenWidth / screenHeight`

# The projection matrix

```
glm::mat4 projection = glm::perspective(  
    glm::radians(45.0f), // field of view  
    4.0f / 3.0f,          // aspect ratio  
    0.1f,                 // near clip plane  
    100.0f                // far clip plane  
);
```

- ▶ **Field of view (FOV):** how “wide” or “narrow” the view is
- ▶ **Aspect ratio:** should be `screenWidth / screenHeight`
- ▶ **Near and far clip planes:** fragments that fall outside this range of distances from the camera are not drawn



# The projection matrix


```
glm::mat4 projection = glm::perspective(  
    glm::radians(45.0f), // field of view  
    4.0f / 3.0f,          // aspect ratio  
    0.1f,                 // near clip plane  
    100.0f                // far clip plane  
);
```

- ▶ **Field of view (FOV):** how “wide” or “narrow” the view is
- ▶ **Aspect ratio:** should be `screenWidth / screenHeight`
- ▶ **Near and far clip planes:** fragments that fall outside this range of distances from the camera are not drawn


Also available: `glm::ortho` for orthographic projection

# The view frustum

# The view frustum




# The view frustum



- Defined by the **near and far clipping planes** and the **edges of the screen**

# The view frustum



- ▶ Defined by the **near and far clipping planes** and the **edges of the screen**
- ▶ **Nothing outside** the view frustum is visible

# Live Coding - Transformations

# Exercise

- ▶ Using the following link, first implement model transformations and then view and projection
  - ▶ `http://www.opengl-tutorial.org/beginners-tutorials/tutorial-3-matrices/`
- ▶ Play around with the order of the Model Transformation, what happens when you do this?
- ▶ Use the keyboard to move, rotate and scale the triangle
- ▶ Use the Keyboard to move the camera
- ▶ **Stretch Goal:** Create an FPS camera using the mouse and keyboard