

COMP250: Artificial Intelligence

11: Deep Learning











Basically, the use of large ANNs with many layers


- Basically, the use of large ANNs with many layers
- ► Often uses large training sets

- Basically, the use of large ANNs with many layers
- ▶ Often uses large training sets
- Training often uses powerful GPUs many times faster than training on the CPU







▶ Layers are 2D arrays



- ▶ Layers are 2D arrays
- Neurons in convolutional layers are only connected to nearby neurons



- ▶ Layers are 2D arrays
- Neurons in convolutional layers are only connected to nearby neurons
- There are also fully connected layers



► Train a ConvNet to recognise something (e.g. faces, objects, animals)

- Train a ConvNet to recognise something (e.g. faces, objects, animals)
- ▶ Run the network in "reverse"

- Train a ConvNet to recognise something (e.g. faces, objects, animals)
- Run the network in "reverse"
  - Adjust the image (e.g. via gradient ascent) so that it is more strongly recognised by the network






Train a ConvNet to recognise a particular artistic style

- ▶ Train a ConvNet to recognise a particular artistic style
- Run the network in "reverse" on an input image

- ▶ Train a ConvNet to recognise a particular artistic style
- Run the network in "reverse" on an input image
  - Adjust the image (e.g. via gradient ascent) so that it is more strongly recognised by the network





A Neural Algorithm of Artistic Style [Gatys et al. 2015]


► Two ANNs trained in parallel

- Two ANNs trained in parallel
  - One to generate "fake" artefacts

- ► Two ANNs trained in parallel
  - One to generate "fake" artefacts
  - One to distinguish "real" from "fake"

- Two ANNs trained in parallel
  - One to generate "fake" artefacts
  - One to distinguish "real" from "fake"
- ► http://research.nvidia.com/publication/ 2017-10\_Progressive-Growing-of

# Learning to play Atari games (Mnih et al, 2015)



 MCTS with ANNs for move pruning, simulation playouts and state evaluation

- MCTS with ANNs for move pruning, simulation playouts and state evaluation
- ANNs trained on both expert human matches and self-play (reinforcement learning)

- MCTS with ANNs for move pruning, simulation playouts and state evaluation
- ANNs trained on both expert human matches and self-play (reinforcement learning)
- ▶ Defeated Lee Sedol, world Go champion

► Similar MCTS+ANN architecture to AlphaGo

- ► Similar MCTS+ANN architecture to AlphaGo
- Trained by reinforcement learning (self-play) only

- Similar MCTS+ANN architecture to AlphaGo
- Trained by reinforcement learning (self-play) only
- After only 9 hours\* of training, defeated Stockfish (one of the strongest chess programs available) in a 100-match tournament

- Similar MCTS+ANN architecture to AlphaGo
- Trained by reinforcement learning (self-play) only
- After only 9 hours\* of training, defeated Stockfish (one of the strongest chess programs available) in a 100-match tournament
  - \* On a cluster of 5000 of Google's custom Tensor Processing Units

- Similar MCTS+ANN architecture to AlphaGo
- Trained by reinforcement learning (self-play) only
- After only 9 hours\* of training, defeated Stockfish (one of the strongest chess programs available) in a 100-match tournament
  - \* On a cluster of 5000 of Google's custom Tensor Processing Units
- Stockfish is based on decades of research by expert chess players and AI programmers — AIphaZero started from no chess-specific knowledge whatsoever (other than the rules of the game)

### Deep learning for PCG

https://www.youtube.com/watch?v=3wcpLwvBTYo