



COMP220: Graphics & Simulation
5: Textures & Models



Learning outcomes

By the end of this week, you should be able to:

- ▶ **Explain** how a 2D texture image can be wrapped onto a 3D model.
- ▶ **Explain** how a complex 3D model is represented in memory.
- ▶ **Write** programs which draw textured meshes to the screen.

Agenda

Agenda

- ▶ Lecture (async):
 - ▶ **Explore** options and settings for applying textures to meshes.
 - ▶ **Introduce** mesh file formats and the FBX structure.

Agenda

- ▶ Lecture (async):
 - ▶ **Explore** options and settings for applying textures to meshes.
 - ▶ **Introduce** mesh file formats and the FBX structure.
- ▶ Workshop (sync):
 - ▶ **Apply** simple textures to our OpenGL primitives.
 - ▶ **Implement** code to load models from file using Assimp.

Basic texture mapping



Shaders vs. textures

Shaders vs. textures

- ▶ **Shaders** determine surface appearance based on **interpolated per-vertex** properties.

Shaders vs. textures

- ▶ **Shaders** determine surface appearance based on **interpolated per-vertex** properties.
- ▶ **Textures** are 2D images (or arrays of values) that allow properties to be **varied across the surface**.

Shaders vs. textures

- ▶ **Shaders** determine surface appearance based on **interpolated per-vertex** properties.
- ▶ **Textures** are 2D images (or arrays of values) that allow properties to be **varied across the surface**.
- ▶ Values may represent colours, transparency, surface normals, surface displacements, light reflectance parameters etc.

Shaders vs. textures

- ▶ **Shaders** determine surface appearance based on **interpolated per-vertex** properties.
- ▶ **Textures** are 2D images (or arrays of values) that allow properties to be **varied across the surface**.
- ▶ Values may represent colours, transparency, surface normals, surface displacements, light reflectance parameters etc.
- ▶ **But** we can still only pass values at vertices...

Texture coordinates

- We use **UV coordinates** to refer to points in a texture

Texture coordinates

- ▶ We use **UV coordinates** to refer to points in a texture
- ▶ u axis is horizontal and ranges from 0 (left) to 1 (right)

Texture coordinates

- ▶ We use **UV coordinates** to refer to points in a texture
- ▶ u axis is horizontal and ranges from 0 (left) to 1 (right)
- ▶ v axis is vertical and ranges from 0 (bottom) to 1 (top)


Texture coordinates

- ▶ We use **UV coordinates** to refer to points in a texture
- ▶ u axis is horizontal and ranges from 0 (left) to 1 (right)
- ▶ v axis is vertical and ranges from 0 (bottom) to 1 (top)
- ▶ (So really just another name for xy coordinates in texture space)

Texture coordinates

- ▶ We use **UV coordinates** to refer to points in a texture
- ▶ u axis is horizontal and ranges from 0 (left) to 1 (right)
- ▶ v axis is vertical and ranges from 0 (bottom) to 1 (top)
- ▶ (So really just another name for xy coordinates in texture space)
- ▶ Basic idea of texture mapping: give each vertex a uv coordinate, and interpolate across the triangle

UV coordinates



Character textures



Texture parameters



Texture wrapping

What happens if we assign a coordinate outside the uv range?

Texture wrapping

What happens if we assign a coordinate outside the *uv* range?

- The **wrapping** parameter determines what happens for texture coordinates < 0 or > 1

Texture wrapping

What happens if we assign a coordinate outside the *uv* range?

- The **wrapping** parameter determines what happens for texture coordinates < 0 or > 1




GL_REPEAT



GL_MIRRORED_REPEAT



GL_CLAMP_TO_EDGE



GL_CLAMP_TO_BORDER

Image source: <https://learnopengl.com/Getting-started/Textures>

Texture filtering

How do we map a floating-point texture coordinate to the correct **texel** (texture element)?

Texture filtering

How do we map a floating-point texture coordinate to the correct **texel** (texture element)?

- ▶ **Nearest neighbour** selects the texel with the closest centre (Manhattan distance).

Texture filtering

How do we map a floating-point texture coordinate to the correct **texel** (texture element)?

- ▶ **Nearest neighbour** selects the texel with the closest centre (Manhattan distance).
- ▶ **(Bi)linear** takes an interpolated value from neighbouring texels.

Texture filtering

How do we map a floating-point texture coordinate to the correct **texel** (texture element)?

- ▶ **Nearest neighbour** selects the texel with the closest centre (Manhattan distance).
- ▶ **(Bi)linear** takes an interpolated value from neighbouring texels.
- ▶ Can specify different modes for scaling up and down.

Texture filtering

How do we map a floating-point texture coordinate to the correct **texel** (texture element)?

- ▶ **Nearest neighbour** selects the texel with the closest centre (Manhattan distance).
- ▶ **(Bi)linear** takes an interpolated value from neighbouring texels.
- ▶ Can specify different modes for scaling up and down.



Image source: <https://learnopengl.com/Getting-started/Textures>

Mipmaps

On faraway objects, a fragment may cover many texels...

Mipmaps

On faraway objects, a fragment may cover many texels...

- ▶ A **mipmap** is a set of textures with each scaled to half the size of the last.

Mipmaps

On faraway objects, a fragment may cover many texels...

- ▶ A **mipmap** is a set of textures with each scaled to half the size of the last.
- ▶ Chosen based on the distance to the camera.

Mipmaps

On faraway objects, a fragment may cover many texels...

- ▶ A **mipmap** is a set of textures with each scaled to half the size of the last.
- ▶ Chosen based on the distance to the camera.
- ▶ "Multum in parvo" = "much in a small space"

Mipmaps

On faraway objects, a fragment may cover many texels...

- ▶ A **mipmap** is a set of textures with each scaled to half the size of the last.
- ▶ Chosen based on the distance to the camera.
- ▶ "Multum in parvo" = "much in a small space"
- ▶ Pregenerated (on request) by OpenGL: faster processing/better quality for more memory.



Mipmaps

On faraway objects, a fragment may cover many texels...

- ▶ A **mipmap** is a set of textures with each scaled to half the size of the last.
- ▶ Chosen based on the distance to the camera.
- ▶ "Multum in parvo" = "much in a small space"
- ▶ Pregenerated (on request) by OpenGL: faster processing/better quality for more memory.




Image source: <https://learnopengl.com/Getting-started/Textures>

Texture dimensions

- ▶ In the old days, OpenGL required textures to have **power of two** dimensions

Texture dimensions

- ▶ In the old days, OpenGL required textures to have **power of two** dimensions
 - ▶ 2, 4, 8, 16, 32, 64, 128, 256, 512, 1024, ...

Texture dimensions

- ▶ In the old days, OpenGL required textures to have **power of two** dimensions
 - ▶ 2, 4, 8, 16, 32, 64, 128, 256, 512, 1024, ...
- ▶ Nowadays **non-power of two (NPOT)** textures are widely supported

Texture dimensions

- ▶ In the old days, OpenGL required textures to have **power of two** dimensions
 - ▶ 2, 4, 8, 16, 32, 64, 128, 256, 512, 1024, ...
- ▶ Nowadays **non-power of two (NPOT)** textures are widely supported
- ▶ Still better to stick to powers of two as some things work better (e.g. mipmapping)

Texture dimensions

- ▶ In the old days, OpenGL required textures to have **power of two** dimensions
 - ▶ 2, 4, 8, 16, 32, 64, 128, 256, 512, 1024, ...
- ▶ Nowadays **non-power of two (NPOT)** textures are widely supported
- ▶ Still better to stick to powers of two as some things work better (e.g. mipmapping)
- ▶ NB: **rectangular** textures are fine, but **square** textures make UV coordinates saner

Transparency



Alpha

- We are used to working with colours in **RGB** space

Alpha

- ▶ We are used to working with colours in **RGB** space
- ▶ We can also work in **RGBA** space, where A = alpha = transparency

Alpha

- ▶ We are used to working with colours in **RGB** space
- ▶ We can also work in **RGBA** space, where A = alpha = transparency
- ▶ $A = 0 \implies$ fully transparent


Alpha

- ▶ We are used to working with colours in **RGB** space
- ▶ We can also work in **RGBA** space, where A = alpha = transparency
- ▶ $A = 0 \implies$ fully transparent
- ▶ $A = 1$ (or $A = 255$) \implies fully opaque


Alpha

- We are used to working with colours in **RGB** space
- We can also work in **RGBA** space, where A = alpha = transparency
- $A = 0 \implies$ fully transparent
- $A = 1$ (or $A = 255$) \implies fully opaque


Use of Alpha Channel to create Transparent Image



Original Image
RGB - 24 bpp



Alpha Channel
A - 8 bpp



Transparent Image
RGBA - 32 bpp

Transparency and depth testing

- Recall we are using **depth testing**



Transparency and depth testing

- ▶ Recall we are using **depth testing**
 - ▶ Each fragment on screen remembers its **depth** (distance from the camera)

Transparency and depth testing

- ▶ Recall we are using **depth testing**
 - ▶ Each fragment on screen remembers its **depth** (distance from the camera)
 - ▶ A new fragment is drawn **only if** its depth value is **less** than the current depth value



Transparency and depth testing

- ▶ Recall we are using **depth testing**
 - ▶ Each fragment on screen remembers its **depth** (distance from the camera)
 - ▶ A new fragment is drawn **only if** its depth value is **less** than the current depth value
 - ▶ I.e. don't draw objects that should be behind something that was already drawn

Transparency and depth testing

- ▶ Recall we are using **depth testing**
 - ▶ Each fragment on screen remembers its **depth** (distance from the camera)
 - ▶ A new fragment is drawn **only if** its depth value is **less** than the current depth value
 - ▶ I.e. don't draw objects that should be behind something that was already drawn
- ▶ But if the object in front is (semi-)transparent, we want to see the object behind it!



Transparency and depth testing

- ▶ Recall we are using **depth testing**
 - ▶ Each fragment on screen remembers its **depth** (distance from the camera)
 - ▶ A new fragment is drawn **only if** its depth value is **less** than the current depth value
 - ▶ I.e. don't draw objects that should be behind something that was already drawn
- ▶ But if the object in front is (semi-)transparent, we want to see the object behind it!
- ▶ Solution: draw semi-transparent objects **after** opaque objects, and in **back to front** order

Complex meshes



Mesh Formats

- ▶ Typically we invent our own mesh format (see Doom's MD6, Valve's smd formats)

Mesh Formats

- ▶ Typically we invent our own mesh format (see Doom's MD6, Valve's smd formats)
- ▶ These formats are optimised for realtime rendering and are very efficient


Mesh Formats

- ▶ Typically we invent our own mesh format (see Doom's MD6, Valve's smd formats)
- ▶ These formats are optimised for realtime rendering and are very efficient
- ▶ Usually developers write exporters for Maya or 3DSMax to support their format

Mesh Formats

- ▶ Typically we invent our own mesh format (see Doom's MD6, Valve's smd formats)
- ▶ These formats are optimised for realtime rendering and are very efficient
- ▶ Usually developers write exporters for Maya or 3DSMax to support their format
- ▶ We are going to use FBX (Autodesk Filmbox) as our model format, this known as an 'interchange' format

Quick Tour of the FBX Format



Next steps

- ▶ **Review** the additional asynchronous material for more background on texture properties and a preview of ways to structure code for importing meshes/models.
- ▶ **Attend** the workshop to practice loading textures and meshes from file.