9: CONSTRAINT SATISFACTION

COMP702: CLASSICAL ARTIFICIAL INTELLIGENCE



PAPER CLUB

For next week's seminar, please read:

A.M. Smith, M. Mateas. Answer Set Programming for Procedural Content Generation: A Design Space Approach, IEEE Transactions on Computational Intelligence and AI in Games, 2011.

(PDF Link on LearningSpace)

CONSTRAINT SATISFACTION PROBLEMS

CONSTRAINT SATISFACTION PROBLEMS (CSP)

- A Constraint Satisfaction Problem (CSP) is defined by:
 - A set $\{X_1, \dots, X_n\}$ of variables
 - A set $\{D_1, \dots, D_n\}$ of domains, specifying what values each variable can take
 - A set $\{C_1, \dots, C_m\}$ of constraints that the variables must satisfy
- A solution is an assignment of a value to every variable which satisfies all the constraints

SUDOKU

- A 9x9 grid
- Each square contains a number 1-9
- A number cannot appear more than once in any given row, column, or 3x3 square outlined in bold
- Some numbers are given the puzzle is to fill in the rest
- A properly designed Sudoku puzzle has exactly one solution

4				8		6		
	5	9	4		7	_		
			9		I	5	2	
9		3						
	6						I	
						9		8
	3	2	I		5			
		8	2		6	7	3	
		6		7				9

SUDOKU AS A CSP

- Variables: a subset of $\{X_{1,1}, X_{1,2}, ..., X_{9,9}\}$
 - One variable per empty square
- All have the same domain: $D_{i,j} = \{1, ..., 9\}$
- Constraints:
 - $X_{i,j} \neq X_{i,k}$ for all i,j,k with $j \neq k$
 - $X_{j,i} \neq X_{k,i}$ for all i, j, k with $j \neq k$
 - $X_{i,j} \neq X_{k,l}$ for i,j and k,l in the same 3x3 square

4				8		6		
	5	9	4		7	_		
			9		I	5	2	
9		3						
	6						I	
						9		8
	3	2	I		5			
		8	2		6	7	3	
		6		7				9

SOLVING SUDOKU BACKTRACKING

- Pick an empty square
- Try a possible value for that empty square
- Try to solve the rest of the puzzle (recursively)
- If we run into a dead end, go back and try a different value

SOLVING SUDOKU BACKTRACKING

```
Procedure SolveBacktracking(square)

For n=1,\dots,9

If square can have value n

Set value of square to n

If square is the last empty square or SolveBacktracking(next_empty_square)

Return true

End If

End If

End For

Clear the value of square

Return false

End Procedure
```

SOLVING SUDOKU CONSTRAINT PROPAGATION

- Each empty square keeps track of which numbers it could possibly contain
- Update every square
- If a square has only one possible number, fill it in
- Repeat until stuck


BACKTRACKING VS CONSTRAINT PROPAGATION

- Backtracking always finds a solution, but is inefficient
- Constraint propagation is efficient, but doesn't always find a solution
- More sophisticated constraint propagation algorithms do exist
- We could also combine the two
 - Use backtracking to "unstick" constraint propagation
 - Use constraint propagation to narrow down the options that backtracking needs to consider

WAVE FUNCTION COLLAPSE

WAVE FUNCTION COLLAPSE

- Procedural Content Generation algorithm
- Invented by Maxim Gumin in 2016
- Named after a concept from quantum mechanics



WAVE FUNCTION COLLAPSE THE IDEA

- Space is divided into cells, each of which has a state
 - E.g. pixels with a colour; voxels with a 3D mesh from a modular kit
- Constraints on what cell states can neighbour each other are extracted from examples
 - A basic form of machine learning
 - Constraints are probabilistic not just what is allowed next to a given cell, but what is more or less likely
- Each cell has a probability distribution over states
- A cell is chosen, its state is set according to its probabilities, neighbouring cells are updated according to constraints
- The algorithm backtracks if it gets stuck

CHOOSING THE NEXT CELL

Named after Claude Shannon (1916-2001), the "father of Information Theory"

A cell is chosen which has minimal Shannon entropy

$$S = -\sum_{i} P_i \log P_i$$

Lower Shannon entropy = less uncertainty about the possible value of the cell

WAVE FUNCTION COLLAPSE RESOURCES

- https://github.com/mxgmn/WaveFunctionCollapse
- http://www.procjam.com/tutorials/wfc/
- http://oskarstalberg.com/game/wave/wave.html
- https://twitter.com/exutumno