



COMP702: Classical Artificial Intelligence

8: Planning

STRIPS


Planning

- ▶ An **agent** in an **environment**
- ▶ The environment has a **state**
- ▶ The agent can perform **actions** to change the state
- ▶ The agent wants to change the state so as to achieve a **goal**
- ▶ Problem: find a sequence of actions that leads to the goal

STRIPS planning

- ▶ **Stanford Research Institute Problem Solver**
- ▶ Describes the state of the environment by a set of **predicates** which are true
- ▶ Models a problem as:
 - ▶ The **initial state** (a set of predicates which are true)
 - ▶ The **goal state** (a set of predicates, specifying whether each should be true or false)
 - ▶ The set of **actions**, each specifying:
 - ▶ Preconditions (a set of predicates which must be satisfied for this action to be possible)
 - ▶ Postconditions (specifying what predicates are made true or false by this action)

STRIPS example




Initial state:

At (A) ,
BoxAt (C) ,
BananasAt (B')

Goal:

HasBananas

STRIPS example — Actions



`Move(x, y)`

Pre: `At(x)`

Post: `!At(x), At(y)`

`ClimbUp(x)`

Pre: `At(x), BoxAt(x)`

Post: `!At(x), At(x')`

`ClimbDown(x')`

Pre: `At(x'), BoxAt(x)`

Post: `!At(x'), At(x)`

`PushBox(x, y)`

Pre: `At(x), BoxAt(x)`


Post: `!At(x), At(y),
!BoxAt(x), BoxAt(y)`

`TakeBananas(x)`


Pre: `At(x), BananasAt(x)`

Post: `!BananasAt(x), HasBananas`


STRIPS example — Solution




STRIPS example — Solution




STRIPS example — Solution



STRIPS example — Solution



STRIPS example — Solution



Finding the solution

- ▶ For a given state, we can construct a list of all **valid actions** based on their **preconditions**
- ▶ We can also find the **next state** resulting from each action based on their **postconditions**
- ▶ We can construct a **tree** of states and actions
- ▶ We can then **search** this tree to find a goal state

GOAP

GOAP

- ▶ **G**oal **O**riented **A**ction **P**lanning
- ▶ Originally developed for F.E.A.R. (2005), since used in several games
- ▶ A modified version of STRIPS specifically for real-time planning in video games

GOAP

- ▶ Each agent has a **goal set**
 - ▶ Multiple goals with differing **priority**
 - ▶ Goals are like in STRIPS — sets of predicates that the agent wants to satisfy
- ▶ Each agent also has a set of **actions**
 - ▶ Like in STRIPS — actions have preconditions and postconditions
 - ▶ Unlike STRIPS, each action also has a **cost**

Action sets

- ▶ Different types of agent could have the **same goals** but **different action sets**
- ▶ This will result in those agents achieving those goals in **different ways**
- ▶ NB this doesn't have to be explicitly coded — it **emerges** from the GOAP system
- ▶ E.g. this was used by the F.E.A.R. team to quickly add new enemy types

Action sets

Soldier

- 1 AI/Actions/Attack
- 2 AI/Actions/AttackCrouch
- 3 AI/Actions/SuppressionFire
- 4 AI/Actions/SuppressionFireFromCover
- 5 AI/Actions/FlushOutWithGrenade
- 6 AI/Actions/AttackFromCover
- 7 AI/Actions/BlindFireFromCover
- 8 AI/Actions/AttackGrenadeFromCover
- 9 AI/Actions/AttackFromView
- 10 AI/Actions/DrawWeapon
- 11 AI/Actions/HolsterWeapon
- 12 AI/Actions/ReloadCrouch
- 13 AI/Actions/ReloadCovered
- 14 AI/Actions/InspectDisturbance
- 15 AI/Actions/LookAtDisturbance
- 16 AI/Actions/SurveyArea
- 17 AI/Actions/DodgeRoll
- 18 AI/Actions/DodgeShuffle
- 19 AI/Actions/DodgeCovered
- 20 AI/Actions/Uncover
- 21 AI/Actions/AttackMelee

Assassin


- 1 AI/Actions/Attack
- 2 AI/Actions/InspectDisturbance
- 3 AI/Actions/LookAtDisturbance
- 4 AI/Actions/SurveyArea
- 5 AI/Actions/AttackMeleeUncloaked
- 6 AI/Actions/TraverseBlockedDoor
- 7 AI/Actions/UseSmartObjectNodeMounted
- 8 AI/Actions/MountNodeUncloaked
- 9 AI/Actions/DismountNodeUncloaked
- 10 AI/Actions/TraverseLinkUncloaked
- 11 AI/Actions/AttackFromAmbush
- 12 AI/Actions/DodgeRollParanoid
- 13 AI/Actions/AttackLungeUncloaked
- 14 AI/Actions/LopeToTargetUncloaked

Rat

- 1 AI/Actions/Animate
- 2 AI/Actions/Idle
- 3 AI/Actions/GotoNode
- 4 AI/Actions/UseSmartObjectNode

Layering

- ▶ Goal set allows different behaviours with different priorities to be **layered**
- ▶ E.g. enemy AI in F.E.A.R.:



Implementing GOAP

- ▶ An **abstracted** view of the game world is used for planning
- ▶ Represented as a fixed-length array (or struct) of values
- ▶ Predicates (preconditions, postconditions, goals) represented in terms of this array representation
- ▶ Most implementations also allow for **programmatic** preconditions (e.g. calling the pathfinding system to check availability of a path)

Implementing GOAP

- ▶ Not difficult to implement
- ▶ Open-source implementations do exist
- ▶ Not built into Unity or Unreal, but asset store packages are available

Finding the plan

- ▶ As in STRIPS, we can build a **tree** whose nodes are world states and edges are available actions
- ▶ Since actions have costs, we can use A* to find the lowest cost path to the goal
- ▶ Plan is a **queue** of actions that the agent then executes
- ▶ If the plan is interrupted or fails then the agent can **replan**

GOAP vs behaviour trees

- ▶ BT: Designer specifies “how”
- ▶ GOAP: Designer specifies “what” — “how” is in whatever system is used to implement actions (FSMs in F.E.A.R.; could use BTs or hand coding)
- ▶ Both: actions (tasks in BT) are modular and reusable between agents
- ▶ GOAP: goals are also modular and reusable
- ▶ BT: goals are not represented explicitly
- ▶ BT can be classified as **authored behaviour**
- ▶ GOAP can be classified as **computational intelligence**

Workshop