fy-m1: Teaching an Open Model to Chat in Everyday Malagasy

Version 0.1 — full human ratings in v0.2

by Fandresena Raharinaivo

October 2026

Abstract

Open language models that cover Malagasy tend to answer like an official letter: formal, stiff, and often half-translated from French or English. People in Madagascar do not text like that. We fine-tune an open model, McGill-NLP/AfriqueQwen3.5-9B-50Langs-Instruct-v1 [McGill-NLP, 2026], with QLoRA on a single free T4 GPU so that it replies the way a friend would: short, friendly, mixing in French, and using everyday spelling. The training mix combines real family chats that passed a strict automatic anonymisation gate, synthetic chats from an open permissively licensed model, short formal chats built from Malagasy Wikipedia, and identity chats written by the data owner. On **pending** fresh everyday prompts we report the share of replies that drift into full French or English (base: **pending**; fy-m1: **pending**), blind LLM-judge scores, and regression checks on reading (Belebele) and translation (FLORES+). No private text is released. A blind human comparison reports early votes here; the full panel's result comes in v0.2.

1 Introduction

Malagasy is the national language of Madagascar, but most Malagasy text online is formal: news, Wikipedia, religious and government writing. Models trained on that text learn that register. When a user writes a short, casual message, they get back a polished paragraph that no one would send to a friend.

Everyday Malagasy looks different. French words are mixed in freely, including French verbs used with Malagasy grammar ("lancer-na"). Spelling is phonetic and shortened ("zany" for "izany"). Replies are short, with humour and emoji. For this project that mixed style is the target, not an error: a reply only counts as drifting if it is entirely French or English with no Malagasy in it.

Our goal is modest and measurable: a model that is clearly better than its base model at everyday Malagasy chat, without losing much general Malagasy ability, trained and served at zero cost, and released under a simple open licence. We contribute (i) a base-model comparison for Malagasy chat on free hardware, (ii) a privacy-first pipeline that turns a family's chat export into training data without anyone reading the text, and (iii) fy-m1 itself, with every number in this paper written by a script from measured outputs.

2 Related work

Malagasy in multilingual models. Malagasy is covered by large multilingual benchmarks such as Belebele [Bandarkar et al., 2024] and FLORES [Goyal et al., 2022, NLLB Team et al., 2022], now maintained as FLORES+ [Burchell et al., 2024, Open Language Data Initiative, 2024]. Recent open models list Malagasy among their languages, including the Gemma family [Gemma Team, 2025,

Google, 2026] and AfriqueQwen, a Qwen-based model adapted to African languages [McGill-NLP, 2026]. These benchmarks measure formal reading and translation; none measures casual chat.

Parameter-efficient fine-tuning. LoRA [Hu et al., 2022] learns small low-rank adapters on a frozen model; QLoRA [Dettmers et al., 2023] keeps the frozen model in 4-bit, so a model of about ten billion parameters trains on one 16 GB GPU. We use Unsloth [Han et al., 2023] for speed and memory.

Evaluation and compression. LLM judges are a cheap proxy for human preference [Zheng et al., 2023]; we use one blind and treat it as a signal, not a verdict. Language ID uses GlotLID [Kargaran et al., 2023], translation uses chrF++ [Popović, 2017]. Vocabulary trimming follows Ushio et al. [2023]; layer pruning [Gromov et al., 2024] is left for later.

3 Data

We describe the data but do not share it: part of it is private conversations. Only counts are published (`results/data_stats.json`, `results/data_gate.json`).

Real chats. The main source is one family's Messenger export (1 thread). All participants consented to the use of their messages, and every sender's side is used as the assistant in turn. The export never leaves the data owner's laptop. A local script splits it into short multi-turn conversations on long gaps, merges back-to-back messages from the same sender, and replaces names, nicknames (also inside message text and handles), phone numbers, emails and links with fakes or placeholders (`docs/anonymisation.md`).

Strict automatic gate. No person reads the cleaned text; a strict automatic gate replaces the owner review we first planned. Of 260 cleaned conversations, it dropped 68: 0 for a long digit run (a possible phone number), 4 for an email, link or handle, 15 for too many unknown words and 56 for needing more than five fake names. A word is kept only if a known-word list has it: common Malagasy words, Malagasy Wikipedia vocabulary [Wikimedia Foundation, 2023], Malagasy web text from HPLT 2.0 [HPLT project, 2025], and French and English words from `wordfreq` [Speer, 2022]. French first names from INSEE [INSEE, 2023] never count as known words. Any other word is replaced with a fake name; a word only the web-text list knows is never cleared in a name position. This over-masks rare words on purpose: 353 words were replaced in total, a median of 2 and at most 5 per kept conversation. 192 conversations (436 messages) passed.

Synthetic chats. Real chats are far too few on their own, so an open model run by us writes everyday chats, few-shot prompted with cleaned real chats. Only permissively licensed generators are allowed, because synthetic chats are training data and their licence reaches fy-m1: the code refuses any other. The generator was **pending** (licence **pending**); an automatic filter kept **pending** of **pending** generated chats, and an automatic sample gate checked them before use. No closed-API model output is in the training data.

Formal slice. **pending** short "tell me about" chats built from Malagasy Wikipedia paragraphs, so facts and standard spelling survive. The slice is kept small so it does not pull the style back to formal.

Identity chats. **pending** short exchanges, written by the data owner in their own words, answer "who are you?" consistently (fy-m1, made by Fan's lab, built on an open model) and politely refuse harmful requests.

In total the model trained on **pending** examples (**pending** synthetic).

4 Choosing the base model

We compared open instruction models that fit QLoRA training on a free 16 GB T4 GPU. Each candidate was loaded in 4-bit and scored on: reading comprehension (Belebele, `plt_Latn`), both as plain-text 0-shot completion (one protocol for every candidate) and in the model's chat format; translation in both directions with English (FLORES+ devtest, chrF++); tokens per Malagasy word; a short QLoRA smoke run on a T4 (seconds per step); and a blind greeting gate, in which the judge of Section 6 scored 20 everyday greeting answers per model with model names hidden. The owner's rule sets the licence: fy-m1 ships under a simple open licence, so the base must have one.

Table 1 shows the measured values (`results/model_selection.json`, `results/greeting_gate.json`). We chose McGill-NLP/AfriqueQwen3.5-9B-50Langs-Instruct-v1 (licence CC-BY-4.0). It has the best English→Malagasy translation we measured (chrF++ 49.7, versus 36.8 for Gemma 3 12B; Gemma 4 12B: **pending**). On the greeting gate it ties Gemma 4 12B (judge mean 2.90 versus 2.85; Malagasy replies 95.0% versus 90.0%), and chat-format Belebele is equal within noise (74.2% versus 75.0%). Its T4 smoke ran in 16-bit at 83.3 seconds per step (Gemma 3: 122.4; Gemma 4: **pending**, expected to be slower because it is expected to need 32-bit on a T4), which saves free GPU time. We did not wait for Gemma 4's FLORES+ and smoke runs; it stays a comparison row.

Gemma 3 12B [Gemma Team, 2025] is a measured baseline only: its terms of use would make fy-m1 a Gemma derivative, which rules it out under the licence rule (greeting judge mean 1.90). AfriqueQwen-8B was dropped early: it is a base model with no chat-tuned twin. A known risk of the chosen base is one reply in Hausa and some prompt echoes in its greeting answers; training on everyday chats targets exactly that.

Model	Licence	Belebele		chrF++		Tokens	Greeting
		text	chat	mg→en	en→mg	/word	judge (1–5)
McGill-NLP/AfriqueQwen-8B	CC-BY-4.0	**pending**	**pending**	**pending**	**pending**	2.95	**pending**
McGill-NLP/AfriqueQwen3.5-9B-50Langs-Instruct-v1	CC-BY-4.0	66.7%	74.2%	56.2	49.7	2.83	2.90
google/gemma-3-12b-it	Gemma Terms of Use	69.7%	75.1%	51.8	36.8	2.79	1.90
google/gemma-4-12B-it	Apache-2.0	**pending**	75.0%	**pending**	**pending**	2.79	2.85

Table 1: Base-model candidates, all loaded in 4-bit. Higher is better except tokens per word. "pending" means not measured. AfriqueQwen-8B is a base model: no chat score, not judged.

5 Training

We train with QLoRA [Dettmers et al., 2023]: the base model is frozen in 4-bit NF4 and we learn LoRA adapters [Hu et al., 2022] on all linear layers, with rank **pending** and alpha **pending**, using

Unsloth [Han et al., 2023] on a free Kaggle GPU (**pending**), with Colab's free tier as a backup. Settings: learning rate **pending** with a **pending** schedule, sequence length **pending**, effective batch size **pending**, **pending** epochs (**pending** steps, **pending** of training). Loss is computed on assistant turns only, in the base model's own chat template with thinking turned off; every assistant turn carries the same empty thinking block the model sees when answering. A fixed system prompt in Malagasy names the model. Free sessions disconnect, so checkpoints go to a private repository during training and a new session resumes from the latest one; a run refuses to resume if its settings or code changed. Training code reaches the GPU only as a synced copy of the clean main branch. Early stopping uses the repository's own tested rule. Final training loss was **pending**; best held-out loss was **pending**.

6 Evaluation

We generated answers from the base model and fy-m1 to **pending** fresh everyday prompts with the same system prompt and sampling settings (Table 2). The prompts were written fresh, not taken from the chats, so the test set holds no private text and is public (`eval/prompts.jsonl`).

Drift. A reply counts as Malagasy if GlotLID [Kargaran et al., 2023] says so, or if at least a tenth of its words are common Malagasy words; mixed Malagasy–French passes. A reply that is fully French or English drifts.

LLM judge. An LLM judge scored both answer sets blind, with labels hidden and order shuffled, on a published 1–5 rubric for naturalness and correctness [Zheng et al., 2023]. Methods disclosure: the judge is **pending**; rubric in `src/fym1/eval/judge_rubric.md`. The greeting gate of Section 4 used the same rubric with Claude Opus 5.5 (claude-opus-5-5), blind, run as judging agents in Claude Code. Judge scores are a cheap signal, not a substitute for native speakers.

Regression checks. Belebele accuracy, FLORES+ chrF++ in both directions, and held-out chat perplexity should not get much worse after fine-tuning.

Leak gate. Any fy-m1 answer that shares a run of 8 words with the real training chats blocks release. **pending** of fy-m1 answers had such a run; there were **pending** distinct matched runs, of which **pending** were judged generic phrases and **pending** were rejected. The check is strict and automatic: only the matched words are looked at, never the chat around them, and any rejected run means fixing the data, filtering or retraining. An automatic identity check also covers the identity and safety answers.

Blind human comparison (early votes). Native speakers rate pairs of answers in a public "arena": same prompt, two unlabelled answers in random order, pick the more natural one. These are the early votes in at release: **pending** votes from **pending** raters; fy-m1 win rate **pending** (95% Wilson interval **pending**–**pending**; Wilson, 1927). With so few raters this is a first signal, not a result. The full panel's numbers come in v0.2.

Reproducibility. The test prompts, rubric, code and notebooks are public. Version 0.1 releases only aggregate scores; the per-prompt answers of both models come in v0.2, after the human comparison closes, so raters cannot tell which model wrote which answer. The real training chats stay private, so training can be rerun only on other data.

Measure	Base	fy-m1
Drift to full French/English (↓)	**pending**	**pending**
Naturalness, LLM judge, 1–5 (↑)	**pending**	**pending**
Correctness, LLM judge, 1–5 (↑)	**pending**	**pending**
Held-out chat perplexity (↓)	**pending**	**pending**
Belebele accuracy (↑)	**pending**	**pending**
FLORES+ chrF++ mg→en (↑)	**pending**	**pending**
FLORES+ chrF++ en→mg (↑)	**pending**	**pending**

Table 2: Base model versus fy-m1. Belebele and FLORES+ are regression checks: they should not fall much.

7 Making the model smaller: vocabulary trimming

Much of a multilingual model's vocabulary is for scripts and languages fy-m1 never uses. Following Ushio et al. [2023], we keep only the tokens seen in Malagasy, French and English text, plus all special and byte-fallback tokens, and drop the matching embedding and output rows. The trim ships only if it passes three gates: held-out Malagasy text round-trips through the new tokenizer unchanged; greedy answers are unchanged for at least 95% of the test prompts; and Belebele stays within one point. Result: gates **pending**. Vocabulary **pending** → **pending** tokens; parameters **pending** → **pending**; download **pending** → **pending**; speed on the demo CPU **pending** → **pending** tokens/s. Removing whole layers [Gromov et al., 2024] would save more but needs healing with extra training that free GPU time cannot pay for; we leave it for v0.2.

8 Limitations

- The real chats come from one family. The style reflects their everyday speech, not every region or dialect, and most of the volume is synthetic.
- Synthetic chats inherit the generator's habits and mistakes; the automatic sample gate is not a native speaker.
- The strict gate over-masks: rare words and texting spellings get replaced with fake names, which makes the real chats a little less natural.
- The human comparison has only early votes from **pending** raters. Until the full panel is in, the main evidence is automatic.
- The drift metric can be a little low: English that contains a Malagasy name or a quoted Malagasy word can pass as Malagasy.
- An LLM judge may not understand Malagasy slang well; its scores can be wrong in either direction.
- The model can be slow on a free CPU, get facts wrong, and invent things. We train once or twice on free hardware, so settings are not carefully tuned.

9 Ethics, consent and privacy

Everyone in the conversations consented to their messages being used. The raw export never left the data owner's laptop; no person read the cleaned text, and only conversations that passed the strict gate were used. The cleaned data lives in a private dataset and is not released; nor are raw answers until v0.2. Before release, the leak gate checks that the model does not repeat training text. The anonymiser has known limits, listed in `docs/anonymisation.md` and pinned as expected-failure tests: names of people outside the chat typed as plain text, a name that is also an everyday word at the start of a sentence, phone numbers written in words or split over two messages, and some addresses and place names. The strict gate and the leak gate are the backstops for these. The model was trained with a small set of polite refusals and gets a basic safety check before release, but it is not a safety-tested product.

10 Licence and credits

Licence. fy-m1's weights are released under CC-BY-4.0, the base model's licence (CC-BY-4.0), with attribution to McGill-NLP [2026]. The code is Apache-2.0. Gemma 3 was used only as a measured baseline; none of its outputs are in the training data.

Credits. Base model: AfriqueQwen by McGill-NLP [McGill-NLP, 2026]. Data cleaning uses `wordfreq` by Robyn Speer [Speer, 2022] (word data CC-BY-SA 4.0; derived word lists keep that licence and attribution), word case counts from Malagasy Wikipedia [Wikimedia Foundation, 2023] (CC-BY-SA 4.0), HPLT 2.0 cleaned Malagasy web text [HPLT project, 2025] (packaging CC0 1.0; only a word list is kept), and the INSEE first-name file [INSEE, 2023] (Licence Ouverte / Etalab 2.0). The formal slice uses Malagasy Wikipedia. Evaluation uses Belebele [Bandarkar et al., 2024], FLORES+ [Open Language Data Initiative, 2024] and GlotLID [Kargaran et al., 2023]. Training uses Unsloth [Han et al., 2023], on free GPUs from Kaggle and Google Colab.

11 What comes next (v0.2)

- The full panel's blind human comparison, with confidence intervals.
- Each model's answer to each test prompt.
- The layer-pruning experiment.
- Longer training and more everyday data.

References

Lucas Bandarkar, Davis Liang, Benjamin Muller, Mikel Artetxe, Satya Narayan Shukla, Donald Husa, Naman Goyal, Abhinandan Krishnan, Luke Zettlemoyer, and Madian Khabsa. The belebele benchmark: a parallel reading comprehension dataset in 122 language variants. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar, editors, *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 749–775, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.44. URL `https://aclanthology.org/2024.acl-long.44/`.

Laurie Burchell, Jean Maillard, Antonios Anastasopoulos, Christian Federmann, Philipp Koehn, and Skyler Wang. Findings of the WMT 2024 shared task of the open language data initiative. In Barry Haddow, Tom Kocmi, Philipp Koehn, and Christof Monz, editors, *Proceedings of the Ninth Conference on Machine Translation*, pages 110–117, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.wmt-1.4. URL https://aclanthology.org/2024.wmt-1.4/.

Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. QLoRA: Efficient finetuning of quantized LLMs. In *Advances in Neural Information Processing Systems*, volume 36, 2023. URL https://arxiv.org/abs/2305.14314.

Gemma Team. Gemma 3 Technical Report. *arXiv preprint arXiv:2503.19786*, 2025.

Google. Gemma 4 12B Instruct. Hugging Face model card, https://huggingface.co/google/gemma-4-12B-it, 2026. Licence Apache-2.0.

Naman Goyal, Cynthia Gao, Vishrav Chaudhary, Peng-Jen Chen, Guillaume Wenzek, Da Ju, Sanjana Krishnan, Marc'Aurelio Ranzato, Francisco Guzmán, and Angela Fan. The Flores-101 evaluation benchmark for low-resource and multilingual machine translation. *Transactions of the Association for Computational Linguistics*, 10:522–538, 2022. doi: 10.1162/tacl_a_00474. URL https://aclanthology.org/2022.tacl-1.30/.

Andrey Gromov, Kushal Tirumala, Hassan Shapourian, Paolo Glorioso, and Daniel A. Roberts. The unreasonable ineffectiveness of the deeper layers. *arXiv preprint arXiv:2403.17887*, 2024. URL https://arxiv.org/abs/2403.17887.

Daniel Han, Michael Han, and Unsloth team. Unsloth. https://github.com/unslothai/unsloth, 2023.

HPLT project. HPLT 2.0 cleaned. Hugging Face dataset, https://huggingface.co/datasets/HPLT/HPLT2.0_cleaned, 2025. Packaging and annotations CC0 1.0.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022. URL https://arxiv.org/abs/2106.09685.

INSEE. Fichier des prénoms. https://www.insee.fr/fr/statistiques/7633685, 2023. Licence Ouverte / Etalab 2.0.

Amir Hossein Kargaran, Ayyoob Imani, François Yvon, and Hinrich Schuetze. GlotLID: Language identification for low-resource languages. In Houda Bouamor, Juan Pino, and Kalika Bali, editors, *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 6155–6218, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-emnlp.410. URL https://aclanthology.org/2023.findings-emnlp.410/.

McGill-NLP. AfriqueQwen3.5-9B-50Langs-Instruct-v1. Hugging Face model card, https://huggingface.co/McGill-NLP/AfriqueQwen3.5-9B-50Langs-Instruct-v1, 2026. Licence CC-BY-4.0.

NLLB Team, Marta R. Costa-jussà, James Cross, Onur Çelebi, Maha Elbayad, et al. No language left behind: Scaling human-centered machine translation. *arXiv preprint arXiv:2207.04672*, 2022. URL https://arxiv.org/abs/2207.04672.

Open Language Data Initiative. FLORES+. Hugging Face dataset, https://huggingface.co/datasets/openlanguagedata/flores_plus, 2024.

Maja Popović. chrF++: words helping character n-grams. In Ondřej Bojar, Christian Buck, Rajen Chatterjee, Christian Federmann, Yvette Graham, Barry Haddow, Matthias Huck, Antonio Jimeno Yepes, Philipp Koehn, and Julia Kreutzer, editors, *Proceedings of the Second Conference on Machine Translation*, pages 612–618, Copenhagen, Denmark, September 2017. Association for Computational Linguistics. doi: 10.18653/v1/W17-4770. URL https://aclanthology.org/W17-4770/.

Robyn Speer. wordfreq. https://github.com/rspeer/wordfreq, 2022. Code Apache-2.0, word data CC-BY-SA 4.0.

Asahi Ushio, Yi Zhou, and Jose Camacho-Collados. Efficient multilingual language model compression through vocabulary trimming. In Houda Bouamor, Juan Pino, and Kalika Bali, editors, *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 14725–14739, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-emnlp.981. URL https://aclanthology.org/2023.findings-emnlp.981/.

Wikimedia Foundation. Wikipedia dataset (wikimedia/wikipedia). Hugging Face dataset, https://huggingface.co/datasets/wikimedia/wikipedia, 2023. Text CC-BY-SA 4.0.

Edwin B. Wilson. Probable inference, the law of succession, and statistical inference. *Journal of the American Statistical Association*, 22(158):209–212, 1927.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-bench and chatbot arena. In *Advances in Neural Information Processing Systems*, volume 36, 2023. URL https://arxiv.org/abs/2306.05685.