

Motif-Aware Graph Embeddings

Anonymous authors

Abstract

In this paper, we propose two motif-aware approaches for the unsupervised and semi-supervised graph embedding task. Our first model applies the most significant motif pattern on a graph as a guiding pattern for random walks. We then use a skipgram model with noise contrastive estimation to learn the graph embedding from generated random walk context. The second model employs the higher-order organization (i.e. motifs organization) of complex networks, and injects the higher-order connectivity patterns into each layer in a deep graph convolutional networks. We demonstrate the effectiveness of our motif-aware approaches on node labels classification, link prediction, and t-SNE visualization.

1 Introduction

1.1 Complex network and machine learning

Network modeling have been an essential tool for a wide range of scientific fields [Newman, 2010; Bader *et al.*, 2003; Tang *et al.*, 2012; Milo *et al.*, 2002; Benson *et al.*, 2016]. The network science view usually reveals the underlying structure of a complex system. Based on the system’s network structure, scientists can make predictions and explanation about the system’s behavior. For example, in biology, the study on neuronal systems connectivity indicated that the component arrangement of a neural system is optimized for short processing paths rather than wiring lengths [Kaiser and Hilgetag, 2006]. Similarly, social networks analysis provides communities structures as well as social interaction patterns [West *et al.*, 2014; Barabási, 2014]. However, along with the information explosion, the large graph-structured data poses a great challenge for traditional network analysis methods in term of scalability and complexity. To deal with such challenges, one promising approach is to apply machine learning methods (especially deep learning) methods to network problems.

Bridging the gap between network science and machine learning is also a challenging task. Due to the irregularity in network and graph-structured data, it is desirable to have a *meaningful* and structural network representation for machine learning application. Traditionally, vector representation can

be obtained via graph spectral methods. However, spectral methods are shown to be unscalable without estimation methods TODO: find theoretical citation [Perozzi *et al.*, 2014; Grover and Leskovec, 2016]. Recently, inspired by the skipgram model in natural language processing [Mikolov and Dean, 2013], Perozzi *et al.* proposed their scalable graph embedding algorithm named DeepWalk. Their results node classification proved the effectiveness of their algorithm in learning a lower dimensionality representation of a complex network. Subsequence works to DeepWalk further improved node classification accuracy by modifying graph context generation process [Tang *et al.*, 2015; Cao *et al.*, 2015; Grover and Leskovec, 2016]. On the other hand, more direct (and more effective) approaches were proposed in [Yang *et al.*, 2016; Kipf and Welling, 2016a]. Instead of learning the network representation using only network structure (e.g. adjacency matrix), Yang *et al.* proposed to injects the known labeling and node feature into the representation learning process. Kipf and Welling further improved results from plane-toid [Yang *et al.*, 2016] by applying graph convolution technique in their deep network model. These aforementioned approaches are similar in the sense that they all learn a latent representation of a complex network from data, then use this representation to solve a network problem using various machine learning tools.

1.2 Motif in complex network

There are three scale of network analysis: macroscopic, mesoscopic, and microscopic. The macroscopic scale displays a network as a whole to study its robustness [Callaway *et al.*, 2000] or dynamics TODO: find citation [Barabási, 2014]. In contrast, the microscopic scale studies the pair-wise interactions between nodes in a network which is specific to the given system TODO: find citation [Newman, 2010]. On the other hand, the mesoscopic scale is an intermediate in which we consider the network is a composition of sub-graphs. In many research, especially computational biology, the mesoscopic components are called *motifs*, and it is common to think of them as building blocks for a complex system [Milo *et al.*, 2002].

Definition 1.1. *Network motif* Given a graph $G = V, E$, define a subgraph $G' = V', E'$ with $V' \subseteq V$; $E' \subset E$ s.t. $i, j \in V' \forall e_{ij} \in E'$ and $|V'| \ll |V|$. Recurring subgraphs are called *network motif* when they are statistically significant.

Also referred as higher-order organization by Benson *et al.*, network motifs are believed to represent the underlying mechanism of a complex system [Alon, 2007; 2006; Mangan and Alon, 2003]. For instance, the directional bi-fan motif TODO: figure and its simplified undirectional version TODO: figure are crucial in a citation network. Beside having a statistical significance, bi-fan motif is also intuitively sensible in citation network as it represents the citation mechanism as an activity in a subgraph. The correlation of recurring subgraphs and system functionality has been studied extensively in biological systems such as transcription networks [Mangan and Alon, 2003] and brain networks [Van Den Heuvel and Pol, 2010; Honey *et al.*, 2007]. As networks motifs have been recognized as the fundamental building block of a complex systems, using them as a structural guidance for machine learning on graph data can yield positive improvements.

2 Methods

In this section, we present the detail of our methods. Firstly, we propose the basis for the network motif selection from a network. Secondly, we present two approaches employing motif patterns to learn graph embeddings: *motifwalk* and *mcn*.

2.1 Motif laplacian

The formal definition of the motif co-occurrence matrix for a motif \uparrow on an unweighted, directed graph G is given by:

$$M_{i,j} = \sum_{(v, \chi_A), v \in \mathcal{V}_G}$$

Present laplacian and power of laplacian of graph. Present motif types and laplacian for each type. Algorithms and estimation techniques. Discuss about the change in maximum eigenvalue due to the weighted motif laplacian.

2.2 Biased random walk - motifwalk

Present the original motifwalk model.

2.3 Motif convolutional architecture

In this section we propose our motif convolutional deep neural network architecture for semi-supervised graph labeling tasks. Graph convolution is a signal processing technique in which a network of signals reside on nodes (e.g. sensor network) is processed in the graph spectral domain defined on the graph structure. The convolution on a graph G of a function of the graph Laplacian g_θ (also called a filter or a kernel) and a signal x is defined as:

$$g_\theta * x = U g_\theta U^\top x,$$

where $L = U \Lambda U^\top$, U is the Fourier basis and Λ is called the frequencies of the graph. Graph convolution has been shown effective in processing graph-structured data, and also argued to be the generalization of convolutional networks [Shuman *et al.*, 2013; Defferrard *et al.*, 2016; Kipf and Welling, 2016a]. In practice, given a graph where each node has a feature vector, we can treat the feature vector of the graph as signals. The

output y of these "signals" filtered by g_θ on the graph is given by the graph convolution and deconvolution operations:

$$y = g_\theta(U \Lambda U^\top)x = U(g_\theta(\Lambda)U^\top)x \quad (1)$$

Computing equation 1 is computationally expensive due to the matrix multiplication and eigenvector decomposition operations. Therefore, fast estimation methods such as Chebyshev polynomial was suggested in [?]. Based on the further linear approximation proposed by Kipf and Welling, we propose our two layers motif convolutional network model as:

$$\begin{aligned} Z_{\text{forward}} &= f(X, A, M) \\ &= \text{softmax}(\hat{M} \text{ReLU}(\hat{A} X W^{(0)}) W^{(1)}), \end{aligned} \quad (2)$$

where A and M is a binary adjacency matrix and motif co-occurrence matrix respectively; \hat{A} and \hat{M} are constructed by the *renormalization trick* as suggested in [Kipf and Welling, 2016a]; X contains the feature vectors for each graph node; $W^{(0)}$ and $W^{(1)}$ are learnable variables. With the backpropagation learning algorithm, the weight of layer k is updated as follow:

$$\frac{\partial E}{\partial W_{i,j}^{(k)}} = \sum_{s=1}^S [x]^\top \frac{\partial E}{\partial y_{k,j}} \quad (3)$$

3 Experiments

3.1 Datasets and observations

3.2 Motif significance

3.3 Architectures

4 Results

4.1 Unsupervised

Traditional task on blogcatalog and others. Link prediction. t-SNE.

4.2 Semi-supervised

Task on featured networks.

5 Related work

5.1 Spectral approaches

5.2 Skipgram-based approaches

5.3 Deep neural network approaches

6 Discussion

Our paper's contributions are proposing an extension to the graph convolutional architecture; proposing the uses and demonstrate the importance of motifs in real world networks.

Limitation:

6.1 Layout

Print manuscripts two columns to a page, in the manner in which these instructions are printed. The exact dimensions for pages are:

- left and right margins: .75"
- column width: 3.375"

- gap between columns: .25"
- top margin—first page: 1.375"
- top margin—other pages: .75"
- bottom margin: 1.25"
- column height—first page: 6.625"
- column height—other pages: 9"

All measurements assume an $8\frac{1}{2}'' \times 11''$ page size. For A4-size paper, use the given top and left margins, column width, height, and gap, and modify the bottom and right margins as necessary.

6.2 Format of Electronic Manuscript

For the production of the electronic manuscript, you must use Adobe's *Portable Document Format* (PDF). A PDF file can be generated, for instance, on Unix systems using `ps2pdf` or on Windows systems using Adobe's Distiller. There is also a website with free software and conversion services: <http://www.ps2pdf.com/>. For reasons of uniformity, use of Adobe's *Times Roman* font is strongly suggested. In L^AT_EX2e, this is accomplished by putting

```
\usepackage{times}
```

in the preamble.¹

Additionally, it is of utmost importance to specify the American **letter** format (corresponding to $8\frac{1}{2}'' \times 11''$) when formatting the paper. When working with `dvips`, for instance, one should specify `-t letter`.

6.3 Title and Author Information

Center the title on the entire width of the page in a 14-point bold font. Below it, center the author name(s) in a 12-point bold font, and then center the address(es) in a 12-point regular font. Credit to a sponsoring agency can appear on the first page as a footnote.

Blind Review

In order to make blind reviewing possible, authors must omit their names and affiliations when submitting the paper for review. In place of names and affiliations, provide a list of content areas. When referring to one's own work, use the third person rather than the first person. For example, say, "Previously, Gottlob [?] has shown that...", rather than, "In our previous work [?], we have shown that..." Try to avoid including any information in the body of the paper or references that would identify the authors or their institutions. Such information can be added to the final camera-ready version for publication.

6.4 Abstract

Place the abstract at the beginning of the first column 3'' from the top of the page, unless that does not leave enough room for the title and author information. Use a slightly smaller width than in the body of the paper. Head the abstract with

"Abstract" centered above the body of the abstract in a 12-point bold font. The body of the abstract should be in the same font as the body of the paper.

The abstract should be a concise, one-paragraph summary describing the general thesis and conclusion of your paper. A reader should be able to learn the purpose of the paper and the reason for its importance from the abstract. The abstract should be no more than 200 words long.

6.5 Text

The main body of the text immediately follows the abstract. Use 10-point type in a clear, readable font with 1-point leading (10 on 11).

Indent when starting a new paragraph, except after major headings.

6.6 Headings and Sections

When necessary, headings should be used to separate major sections of your paper. (These instructions use many headings to demonstrate their appearance; your paper should have fewer headings.)

Section Headings

Print section headings in 12-point bold type in the style shown in these instructions. Leave a blank space of approximately 10 points above and 4 points below section headings. Number sections with arabic numerals.

Subsection Headings

Print subsection headings in 11-point bold type. Leave a blank space of approximately 8 points above and 3 points below subsection headings. Number subsections with the section number and the subsection number (in arabic numerals) separated by a period.

Subsubsection Headings

Print subsubsection headings in 10-point bold type. Leave a blank space of approximately 6 points above subsubsection headings. Do not number subsubsections.

Special Sections

You may include an unnumbered acknowledgments section, including acknowledgments of help from colleagues, financial support, and permission to publish.

Any appendices directly follow the text and look like sections, except that they are numbered with capital letters instead of arabic numerals.

The references section is headed "References," printed in the same style as a section heading but without a number. A sample list of references is given at the end of these instructions. Use a consistent format for references, such as that provided by BibT_EX. The reference list should not include unpublished work.

6.7 Citations

Citations within the text should include the author's last name and the year of publication, for example [?]. Append lower-case letters to the year in cases of ambiguity. Treat multiple authors as in the following examples: [?] or [?] (for more than two authors) and [?] (for two authors). If the author portion

¹You may want also to use the package `latexsym`, which defines all symbols known from the old L^AT_EX version.

of a citation is obvious, omit it, e.g., Nebel [?]. Collapse multiple citations as follows: [?; ?].

6.8 Footnotes

Place footnotes at the bottom of the page in a 9-point font. Refer to them with superscript numbers.² Separate them from the text by a short line.³ Avoid footnotes as much as possible; they interrupt the flow of the text.

7 Illustrations

Place all illustrations (figures, drawings, tables, and photographs) throughout the paper at the places where they are first discussed, rather than at the end of the paper. If placed at the bottom or top of a page, illustrations may run across both columns.

Illustrations must be rendered electronically or scanned and placed directly in your document. All illustrations should be in black and white, as color illustrations may cause problems. Line weights should be 1/2-point or thicker. Avoid screens and superimposing type on patterns as these effects may not reproduce well.

Number illustrations sequentially. Use references of the following form: Figure 1, Table 2, etc. Place illustration numbers and captions under illustrations. Leave a margin of 1/4-inch around the area covered by the illustration and caption. Use 9-point type for captions, labels, and other text in illustrations.

Acknowledgments

The preparation of these instructions and the L^AT_EX and Bib_TE_X files that implement them was supported by Schlumberger Palo Alto Research, AT&T Bell Laboratories, and Morgan Kaufmann Publishers. Preparation of the Microsoft Word file was supported by IJCAI. An early version of this document was created by Shirley Jowell and Peter F. Patel-Schneider. It was subsequently modified by Jennifer Balentine and Thomas Dean, Bernhard Nebel, and Daniel Pagenstecher. These instructions are the same as the ones for IJCAI-05, prepared by Kurt Steinkraus, Massachusetts Institute of Technology, Computer Science and Artificial Intelligence Lab.

A L^AT_EX and Word Style Files

The L^AT_EX and Word style files are available on the IJCAI-17 website, <http://www.ijcai-17.org/>. These style files implement the formatting instructions in this document.

The L^AT_EX files are `ijcai17.sty` and `ijcai17.tex`, and the Bib_TE_X files are `named.bst` and `ijcai17.bib`. The L^AT_EX style file is for version 2e of L^AT_EX, and the Bib_TE_X style file is for version 0.99c of Bib_TE_X (not version 0.98i). The `ijcai17.sty` file is the same as the `ijcai07.sty` file used for IJCAI-07.

The Microsoft Word style file consists of a single file, `ijcai17.doc`. This template is the same as the one used for IJCAI-07.

²This is how your footnotes should appear.

³Note the line separating these footnotes from the text.

These Microsoft Word and L^AT_EX files contain the source of the present document and may serve as a formatting sample.

Further information on using these styles for the preparation of papers for IJCAI-17 can be obtained by contacting pcchair@ijcai-17.org.

References

- [Alon, 2006] Uri Alon. *An introduction to systems biology: design principles of biological circuits*. CRC press, 2006.
- [Alon, 2007] Uri Alon. Network motifs: theory and experimental approaches. *Nature Reviews Genetics*, 8(6):450–461, 2007.
- [Bader *et al.*, 2003] Gary D Bader, Doron Betel, and Christopher WV Hogue. Bind: the biomolecular interaction network database. *Nucleic acids research*, 31(1):248–250, 2003.
- [Barabási, 2014] Albert-László Barabási. Network science book. *Network Science*, 2014.
- [Benson *et al.*, 2016] Austin R Benson, David F Gleich, and Jure Leskovec. Higher-order organization of complex networks. *Science*, 353(6295):163–166, 2016.
- [Callaway *et al.*, 2000] Duncan S Callaway, Mark EJ Newman, Steven H Strogatz, and Duncan J Watts. Network robustness and fragility: Percolation on random graphs. *Physical review letters*, 85(25):5468, 2000.
- [Cao *et al.*, 2015] Shaosheng Cao, Wei Lu, and Qiongkai Xu. Grarep: Learning graph representations with global structural information. In *Proceedings of the 24th ACM International on Conference on Information and Knowledge Management*, pages 891–900. ACM, 2015.
- [Defferrard *et al.*, 2016] Michaël Defferrard, Xavier Bresson, and Pierre Vandergheynst. Convolutional neural networks on graphs with fast localized spectral filtering. In *Advances in Neural Information Processing Systems*, pages 3837–3845, 2016.
- [Grover and Leskovec, 2016] Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2016.
- [Honey *et al.*, 2007] Christopher J Honey, Rolf Kötter, Michael Breakspear, and Olaf Sporns. Network structure of cerebral cortex shapes functional connectivity on multiple time scales. *Proceedings of the National Academy of Sciences*, 104(24):10240–10245, 2007.
- [Kaiser and Hilgetag, 2006] Marcus Kaiser and Claus C Hilgetag. Nonoptimal component placement, but short processing paths, due to long-distance projections in neural systems. *PLoS Comput Biol*, 2(7):e95, 2006.
- [Kipf and Welling, 2016a] Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

- [Kipf and Welling, 2016b] Thomas N Kipf and Max Welling. Variational graph auto-encoders. *arXiv preprint arXiv:1611.07308*, 2016.
- [Mangan and Alon, 2003] Shmoolik Mangan and Uri Alon. Structure and function of the feed-forward loop network motif. *Proceedings of the National Academy of Sciences*, 100(21):11980–11985, 2003.
- [Mikolov and Dean, 2013] T Mikolov and J Dean. Distributed representations of words and phrases and their compositionality. *Advances in neural information processing systems*, 2013.
- [Milo *et al.*, 2002] Ron Milo, Shai Shen-Orr, Shalev Itzkovitz, Nadav Kashtan, Dmitri Chklovskii, and Uri Alon. Network motifs: simple building blocks of complex networks. *Science*, 298(5594):824–827, 2002.
- [Newman, 2010] Mark Newman. *Networks: an introduction*. Oxford university press, 2010.
- [Perozzi *et al.*, 2014] Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: Online learning of social representations. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 701–710. ACM, 2014.
- [Shuman *et al.*, 2013] David I Shuman, Sunil K Narang, Pascal Frossard, Antonio Ortega, and Pierre Vandergheynst. The emerging field of signal processing on graphs: Extending high-dimensional data analysis to networks and other irregular domains. *IEEE Signal Processing Magazine*, 30(3):83–98, 2013.
- [Tang *et al.*, 2012] Lei Tang, Xufei Wang, and Huan Liu. Scalable learning of collective behavior. *IEEE Transactions on Knowledge and Data Engineering*, 24(6):1080–1091, 2012.
- [Tang *et al.*, 2015] Jian Tang, Meng Qu, Mingzhe Wang, Ming Zhang, Jun Yan, and Qiaozhu Mei. Line: Large-scale information network embedding. In *Proceedings of the 24th International Conference on World Wide Web*, pages 1067–1077, 2015.
- [Van Den Heuvel and Pol, 2010] Martijn P Van Den Heuvel and Hilleke E Hulshoff Pol. Exploring the brain network: a review on resting-state fmri functional connectivity. *European Neuropsychopharmacology*, 20(8):519–534, 2010.
- [West *et al.*, 2014] Robert West, Hristo S Paskov, Jure Leskovec, and Christopher Potts. Exploiting social network structure for person-to-person sentiment analysis. *arXiv preprint arXiv:1409.2450*, 2014.
- [Yang *et al.*, 2016] Zhilin Yang, William W. Cohen, and Ruslan Salakhutdinov. Revisiting semi-supervised learning with graph embeddings. In *Proceedings of the 33rd International Conference on Machine Learning*. ICML, 2016.