

# Generate a Table and Fill with Data Row by Row or Random Data

back to [Fan's Intro Math for Econ](#), [Matlab Examples](#), or [MEconTools Repositories](#)

## An Empty Table, Filled with Loop Row by Row

First, generate an empty table.

```
% Make N by 2 matrix of fieldname + value type
mt_st_variable_names_types = [{"category", "string"}; ...
    ["wage", "double"]; ...
    ["skilled", "logical"]; ...
    ["labdemand", "double"]; ...
    ["labsupply", "double"]; ...
    ["labsupplyprob", "string"]; ...
    ["rho_manual", "double"]; ...
    ["rho_routine", "double"]; ...
    ["rho_analytical", "double"]; ...
];
% Make table using fieldnames & value types from above
tb_equilibrium = table('Size',[0,size(mt_st_variable_names_types,1)],...
    'VariableNames', mt_st_variable_names_types(:,1),...
    'VariableTypes', mt_st_variable_names_types(:,2));
% display table
disp(size(tb_equilibrium));
```

0 9

Second, over a loop, fill the table with values row by row.

```
for it_rho_set=[1,2,3]
    if (it_rho_set == 1)
        cl_data_row = {'C001',1, true,1,1,0.5,0.5,0.5,0.5};
    elseif (it_rho_set == 2)
        cl_data_row = {'C002',1, 0 ,1.2,0.6,0.5,0.45,0.5,0.5};
    elseif (it_rho_set == 3)
        cl_data_row = {'C011',1.1,false,1.2,0.6,0.5,0.45,0.45,0.45};
    end
    tb_equilibrium = [tb_equilibrium; cl_data_row];
end
disp(tb_equilibrium);
```

category	wage	skilled	labdemand	labsupply	labsupplyprob	rho_manual	rho_routine	rho_analy
"C001"	1	1	1	1	"0.5"	0.5	0.5	0.5
"C002"	1	0	1.2	0.6	"0.5"	0.45	0.5	0.5
"123"	1.1	0	1.2	0.6	"0.5"	0.45	0.45	0.45

## Generate a Table with M Variables of Random Data

Generate a numeric table with random varlues and a string column

```
% Numeric Matrix
```

```

it_num_cols = 4;
it_num_rows = 5;
mt_data = rand([it_num_rows, it_num_cols]);

% Generate Table
tb_test = array2table(mt_data);

% Generate Row and Column Names
cl_col_names = strcat('col_', string((1:it_num_cols)));
cl_row_names = strcat('row_', string((1:it_num_rows)));

tb_test.Properties.VariableNames = matlab.lang.makeValidName(cl_col_names);
tb_test.Properties.RowNames = matlab.lang.makeValidName(cl_row_names);

% Generate two string variable
rng(456);
cl_st_var1 = strcat('data=', string(rand([it_num_rows,1])));
cl_st_var2 = strcat('data=', string(rand([it_num_rows,1])));
tb_test = addvars(tb_test, cl_st_var1, cl_st_var2);

% Display Table
disp(tb_test);

```

	<u>col_1</u>	<u>col_2</u>	<u>col_3</u>	<u>col_4</u>	<u>cl_st_var1</u>	<u>cl_st_var2</u>
row_1	0.43568	0.4688	0.18092	0.14604	"data=0.24876"	"data=0.60411"
row_2	0.38527	0.57	0.11816	0.54272	"data=0.16307"	"data=0.8857"
row_3	0.57571	0.6457	0.24273	0.8571	"data=0.78364"	"data=0.75912"
row_4	0.14609	0.72334	0.0081834	0.20021	"data=0.80852"	"data=0.18111"
row_5	0.68659	0.68067	0.36007	0.13463	"data=0.62563"	"data=0.15017"