Matlab Array Reshape, Repeat and Expand Examples

back to Fan's Reusable Matlab Repository or Dynamic Asset Repository.

Basic Examples of Reshape

```
a = [1,2,3,4,5,6]';
b = reshape(a, [3,2])
b = 3 \times 2
    1
         4
    2
         5
    3
b(:)
ans = 6 \times 1
    1
    2
    3
    4
    5
    6
a = [1,2,3;4,5,6;7,8,9;10,11,12]
a = 3 \times 4
         4 7
    1
                  10
         5 8 11
    2
         6 9
                   12
b = reshape(a, [6,2])
b = 6 \times 2
    1
         7
    2
         8
        9
    3
    4 10
    5
       11
```

Stack Two Matrix of Equal Column Count Together

```
a = [1,2;3,4];
a_stacked = [a;a;a];
disp(a_stacked);

1     2
3     4
1     2
3     4
1     2
3     4
1     2
3     4
```

Repeat/Duplicate Matrix Downwards

There is a 2 by 3 matrix, to be repeated 4 times, downwards. This is useful for replicating data matrix for say counterfactual purposes.

Below, we have two ways of repeating a matrix downwards. Copy as whole, or copy row by row.

```
row count = 2;
col count = 3;
repeat_mat_count = 2;
data vec = 1:(row count*col count);
searchMatrix = reshape(data_vec,row_count,col_count);
% To repeat matrix downwards
rep_rows_idx = [1:row_count]'*ones(1,repeat_mat_count);
rep rows idx = rep rows idx(:);
rep_cols_idx = [1:col_count];
rep cols idx = rep cols idx(:);
searchMatrixRep_stack = searchMatrix(rep_rows_idx, rep_cols idx);
% To insert repeated rows following original rows
rep_rows_idx = ([1:row_count]'*ones(1,repeat_mat_count))';
rep_rows_idx = rep_rows_idx(:);
searchMatrixRep dup = searchMatrix(rep rows idx, rep cols idx);
disp(searchMatrix)
```

1 3 5 2 4 6

disp(searchMatrixRep_stack)

1 3 5 2 4 6 1 3 5

disp(searchMatrixRep_dup)

1 3 5 1 3 5 2 4 6 2 4 6

Index Dimension Transform

```
it_inner_fin = 5; it_outter_fin = 3;
it_inner_cur = it_outter_fin it_outter_cur = it_inner_fin
ar_it_cols_idx = 1:1:(it_inner_fin*it_outter_fin) ar_it_cols_inner_dim = repmat(1:it_inner_cur, [it_outter_cur, 1])
ar_it_cols_inner_dim(:)'
```

```
mt_it_cols_idx = reshape(ar_it_cols_idx, [it_inner_cur, it_outter_cur])' mt_it_cols_idx(:)'
```

ans = 1×15

```
it_inner_fin = 5;
it_outter_fin = 3;
ar_it_cols_idx = 1:1:(it_inner_fin*it_outter_fin)
ar_it_cols_idx = 1×15
                             6 7 8
                                            9
                                                 10
                                                           12
         2
                                                      11
                                                              13 • • •
mt_it_cols_idx = reshape(ar_it_cols_idx, [it_outter_fin, it_inner_fin])'
mt_it_cols_idx = 5 \times 3
    1
         2
    4
         5
              6
   7
        8
             9
   10
        11
             12
   13
        14
             15
mt_it_cols_idx(:)'
```

9 . . .