

FF_GRAPH_GRID Examples: X, Y and Color Line Plots


[back to Fan's Intro Math for Econ](#), [Matlab Examples](#), or [Dynamic Asset Repositories](#)

This is the example vignette for function: `ff_graph_grid` from the [MEconTools Package](#). This function can graph out value and policy functions given one state vector (x-axis), conditional on other states (line groups). Can handle a few lines (scatter + lines), or many groups (jet spectrum).

Test FF_GRAPH_GRID Defaults

Call the function with defaults.


```
ff_graph_grid();
```



Test FF_GRAPH_GRID Two Random Normal Lines and Labels

There are two autoregressive time series, plot out the time two time series.

```
% Generate the two time series
rng(456);
mt_value = normrnd(100,10,[2, 50]);
ar_row_grid = ["individual 1", "individual 2"];
ar_col_grid = 1:50;
mp_support_graph = containers.Map('KeyType', 'char', 'ValueType', 'any');
mp_support_graph('cl_st_graph_title') = {'Time Series Two Individuals'};
mp_support_graph('cl_st_ytitle') = {'Values'};
mp_support_graph('cl_st_xtitle') = {'Periods'};
mp_support_graph('bl_graph_logy') = false; % do not log
ff_graph_grid(mt_value, ar_row_grid, ar_col_grid, mp_support_graph);
```



Test FF_GRAPH_GRID Many Lines


Plot many lines, with auto legend.

```
% Generate some Data
rng(456);
ar_row_grid = linspace(-4, 11, 100);
ar_col_grid = linspace(-1, 1, 1000);
rng(123);
mt_value = 0.2*ar_row_grid' + exp(ar_col_grid) + rand([length(ar_row_grid), length(ar_col_grid)]);
% container map settings
mp_support_graph = containers.Map('KeyType', 'char', 'ValueType', 'any');
mp_support_graph('cl_st_graph_title') = {'value(a,z), a=x, z=color'};
mp_support_graph('cl_st_ytitle') = {'value(a,z)'};
mp_support_graph('cl_st_xtitle') = {'Savings States, a'};
mp_support_graph('st_legend_loc') = 'southeast';
mp_support_graph('bl_graph_logy') = false; % do not log
```

```

mp_support_graph('st_rowvar_name') = 'z=';
mp_support_graph('it_legend_select') = 3; % how many shock legends to show
mp_support_graph('st_rounding') = '6.2f'; % format shock legend
% Call function
ff_graph_grid(mt_value, ar_row_grid, ar_col_grid, mp_support_graph);

```



Test FF_GRAPH_GRID Many Lines Legend Exogenous

Plot many lines, exogenously set legend

```

% Generate the two time series
rng(456);
ar_row_grid = linspace(-4, 11, 15);
ar_col_grid = linspace(-1, 1, 100000);
rng(123);
mt_value = 0.2*ar_row_grid' - exp(ar_col_grid) + rand([length(ar_row_grid), length(ar_col_grid)]);
% setting shock vector name exogenously here
ar_row_grid = string(num2str(ar_row_grid', "shock=%6.2f"));
% container map settings
mp_support_graph = containers.Map('KeyType', 'char', 'ValueType', 'any');
mp_support_graph('cl_st_graph_title') = {'value(a,z), a=x, z=color'};
mp_support_graph('cl_st_ytitle') = {'value(a,z)'};
mp_support_graph('cl_st_xtitle') = {'Savings States, a'};
mp_support_graph('st_legend_loc') = 'eastoutside';
mp_support_graph('bl_graph_logy') = false; % do not log
mp_support_graph('it_legend_select') = 15;
% Call function
ff_graph_grid(mt_value, ar_row_grid, ar_col_grid, mp_support_graph);

```

