Multinomial Logit Core Functions

This is the example vignette for function: **bfw_mp_func_supply** from the **PrjLabEquiBFW Package**. This function generates a container map with key multinomial logit supply-side equations.

Test BL_LOG_WAGE is false

Default test

```
bl_log_wage = false;
bl_verbose = true;
mp_func_supply = bfw_mp_func_supply(bl_log_wage, bl_verbose);
```

```
----------------------------------------
xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
CONTAINER NAME: mp_func Functions
xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
                          i     idx
                         ___    ___    ____________________________________________________________________________________________________

    fc_ar_prob_wrk       "1"    "1"    "@(arpsi0,psi1,mtwage,probdenom)fc_v_occ(reshape(arpsi0,[1,length(arpsi0)]),ps
    fc_log_pmdpo_occ     "2"    "2"    "@(psi0,psi1,arwage,pie1,pie2,pie3,pie4,pie5,pie6,t,prbchd,prbmar,prbapp,prbjs
    fc_prob_denom        "3"    "3"    "@(arpsi0,psi1,arpie,arwage1,arwage2,arwage3,t,prbchd,prbmar,prbapp,prbjsy)fc_
    fc_prob_lei          "4"    "4"    "@(arpie,t,prbchd,prbmar,prbapp,prbjsy,probdenom)fc_v_lei(arpie(1),arpie(2),ar
    fc_s1                "5"    "5"    "@(p1,G_1,zeta_1_0,zeta_1_1)G_1./(1+(exp(-zeta_1_0-zeta_1_1.*p1)))"
    fc_s2                "6"    "6"    "@(p2,G_2,zeta_2_0,zeta_2_1)G_2./(1+(exp(-zeta_2_0-zeta_2_1.*p2)))"
    fc_supply            "7"    "7"    "@(potlabor,prob)potlabor.*prob"
```

Test BL_LOG_WAGE is false

Default test

```
bl_log_wage = true;
mp_func_supply = bfw_mp_func_supply(bl_log_wage, bl_verbose);
```

```
----------------------------------------
xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
CONTAINER NAME: mp_func Functions
xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
                          i     idx
                         ___    ___    ____________________________________________________________________________________________________

    fc_ar_prob_wrk       "1"    "1"    "@(arpsi0,psi1,mtwage,probdenom)fc_v_occ(reshape(arpsi0,[1,length(arpsi0)]),ps
    fc_log_pmdpo_occ     "2"    "2"    "@(psi0,psi1,arwage,pie1,pie2,pie3,pie4,pie5,pie6,t,prbchd,prbmar,prbapp,prbjs
    fc_prob_denom        "3"    "3"    "@(arpsi0,psi1,arpie,arwage1,arwage2,arwage3,t,prbchd,prbmar,prbapp,prbjsy)fc_
    fc_prob_lei          "4"    "4"    "@(arpie,t,prbchd,prbmar,prbapp,prbjsy,probdenom)fc_v_lei(arpie(1),arpie(2),ar
    fc_s1                "5"    "5"    "@(p1,G_1,zeta_1_0,zeta_1_1)G_1./(1+(exp(-zeta_1_0-zeta_1_1.*p1)))"
    fc_s2                "6"    "6"    "@(p2,G_2,zeta_2_0,zeta_2_1)G_2./(1+(exp(-zeta_2_0-zeta_2_1.*p2)))"
    fc_supply            "7"    "7"    "@(potlabor,prob)potlabor.*prob"
```