

R Examples Generate Tibble Dataframes

Fan Wang

2020-04-01

Contents

Generate Dataframe 1

Generate Dataframe

Go to the [RMD](#), [R](#), [PDF](#), or [HTML](#) version of this file. Go back to [fan's REconTools Package](#), [R Code Examples Repository \(bookdown site\)](#), or [Intro Stats with R Repository \(bookdown site\)](#).

Generate Tibble given Matrixes and Arrays Given Arrays and Matrixes, Generate Tibble and Name Variables/Columns

- naming tibble columns
- tibble variable names
- dplyr rename tibble
- dplyr rename tibble all variables
- dplyr rename all columns by index
- dplyr tibble add index column
- see also: [SO-51205520](#)

```
# Base Inputs
ar_col <- c(-1,+1)
mt_rnorm_a <- matrix(rnorm(4,mean=0,sd=1), nrow=2, ncol=2)
mt_rnorm_b <- matrix(rnorm(4,mean=0,sd=1), nrow=2, ncol=4)

# Combine Matrix
mt_combine <- cbind(ar_col, mt_rnorm_a, mt_rnorm_b)
colnames(mt_combine) <- c('ar_col',
                           paste0('matcolvar_grpa_', seq(1,dim(mt_rnorm_a)[2])),
                           paste0('matcolvar_grpb_', seq(1,dim(mt_rnorm_b)[2])))

# Variable Names
ar_st_varnames <- c('var_one',
                    paste0('tibcolvar_ga_', c(1,2)),
                    paste0('tibcolvar_gb_', c(1,2,3,4)))

# Combine to tibble, add name col1, col2, etc.
tb_combine <- as_tibble(mt_combine) %>% rename_all(~c(ar_st_varnames))

# Add an index column to the dataframe, ID column
tb_combine <- tb_combine %>% rowid_to_column(var = "ID")

# Change all gb variable names
tb_combine <- tb_combine %>%
```

```

      rename_at(vars(starts_with("tibcolvar_gb_")),
                funs(str_replace(., "_gb_", "_gbrenamed_")))

# Tibble back to matrix
mt_tb_combine_back <- data.matrix(tb_combine)

# Display
kable(mt_combine) %>% kable_styling_fc_wide()

```

ar_col	matcolvar_grpa_1	matcolvar_grpa_2	matcolvar_grpb_1	matcolvar_grpb_2	matcolvar_grpb_3	matcolvar_grpb_4
-1	-0.0833691	-0.0285468	1.368602	1.516471	1.368602	1.516471
1	0.2533185	-0.0428705	-0.225771	-1.548753	-0.225771	-1.548753

```
kable(tb_combine) %>% kable_styling_fc_wide()
```

ID	var_one	tibcolvar_ga_1	tibcolvar_ga_2	tibcolvar_gbrenamed_1	tibcolvar_gbrenamed_2	tibcolvar_gbrenamed_3	tibcolvar_gbrenamed_4
1	-1	-0.0833691	-0.0285468	1.368602	1.516471	1.368602	1.516471
2	1	0.2533185	-0.0428705	-0.225771	-1.548753	-0.225771	-1.548753

```
kable(mt_tb_combine_back) %>% kable_styling_fc_wide()
```

ID	var_one	tibcolvar_ga_1	tibcolvar_ga_2	tibcolvar_gbrenamed_1	tibcolvar_gbrenamed_2	tibcolvar_gbrenamed_3	tibcolvar_gbrenamed_4
1	-1	-0.0833691	-0.0285468	1.368602	1.516471	1.368602	1.516471
2	1	0.2533185	-0.0428705	-0.225771	-1.548753	-0.225771	-1.548753

Rename Tibble with Numeric Column Names After reshaping, often could end up with variable names that are all numeric, integers for example, how to rename these variables to add a common prefix for example.

```

# Base Inputs
ar_col <- c(-1,+1)
mt_rnorm_c <- matrix(rnorm(4,mean=0,sd=1), nrow=5, ncol=10)
mt_combine <- cbind(ar_col, mt_rnorm_c)

# Variable Names
ar_it_cols_ctr <- seq(1, dim(mt_rnorm_c)[2])
ar_st_varnames <- c('var_one', ar_it_cols_ctr)

# Combine to tibble, add name col1, col2, etc.
tb_combine <- as_tibble(mt_combine) %>% rename_all(~c(ar_st_varnames))

# Add an index column to the dataframe, ID column
tb_combine_ori <- tb_combine %>% rowid_to_column(var = "ID")

# Change all gb variable names
tb_combine <- tb_combine_ori %>%
  rename_at(
    vars(num_range(' ', ar_it_cols_ctr)),
    funs(paste0("rho", . , 'var'))
  )

# Display
kable(tb_combine_ori) %>% kable_styling_fc_wide()

```

ID	var_one	1	2	3	4	5	6	7	8	9	10
1	-1	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542
2	1	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542	0.2159416
3	-1	0.2159416	0.3796395	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542	0.2159416	0.3796395
4	1	0.3796395	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137
5	-1	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542

```
kable(tb_combine) %>% kable_styling_fc_wide()
```

ID	var_one	rho1var	rho2var	rho3var	rho4var	rho5var	rho6var	rho7var	rho8var	rho9var	rho10var
1	-1	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542
2	1	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542	0.2159416
3	-1	0.2159416	0.3796395	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542	0.2159416	0.3796395
4	1	0.3796395	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137
5	-1	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542	0.2159416	0.3796395	0.5846137	0.1238542

Tibble Row and Column and Summarize Show what is in the table: 1, column and row names; 2, contents inside table.

```
tb_iris <- as_tibble(iris)
print(rownames(tb_iris))
```

```
## [1] "1" "2" "3" "4" "5" "6" "7" "8" "9" "10" "11" "12" "13" "14" "15" "16"
## [28] "28" "29" "30" "31" "32" "33" "34" "35" "36" "37" "38" "39" "40" "41" "42" "43"
## [55] "55" "56" "57" "58" "59" "60" "61" "62" "63" "64" "65" "66" "67" "68" "69" "70"
## [82] "82" "83" "84" "85" "86" "87" "88" "89" "90" "91" "92" "93" "94" "95" "96" "97"
## [109] "109" "110" "111" "112" "113" "114" "115" "116" "117" "118" "119" "120" "121" "122" "123" "124"
## [136] "136" "137" "138" "139" "140" "141" "142" "143" "144" "145" "146" "147" "148" "149" "150"
```

```
colnames(tb_iris)
```

```
## [1] "Sepal.Length" "Sepal.Width" "Petal.Length" "Petal.Width" "Species"
```

```
colnames(tb_iris)
```

```
## [1] "Sepal.Length" "Sepal.Width" "Petal.Length" "Petal.Width" "Species"
```

```
summary(tb_iris)
```

```
## Sepal.Length Sepal.Width Petal.Length Petal.Width Species
## Min. :4.300 Min. :2.000 Min. :1.000 Min. :0.100 setosa :50
## 1st Qu.:5.100 1st Qu.:2.800 1st Qu.:1.600 1st Qu.:0.300 versicolor:50
## Median :5.800 Median :3.000 Median :4.350 Median :1.300 virginica :50
## Mean :5.843 Mean :3.057 Mean :3.758 Mean :1.199
## 3rd Qu.:6.400 3rd Qu.:3.300 3rd Qu.:5.100 3rd Qu.:1.800
## Max. :7.900 Max. :4.400 Max. :6.900 Max. :2.500
```

Tibble Sorting

- dplyr arrange desc reverse
- dplyr sort

```
# Sort in Ascending Order
```

```
tb_iris %>% select(Species, Sepal.Length, everything()) %>%
  arrange(Species, Sepal.Length) %>% head(10) %>%
  kable() %>% kable_styling_fc()
```

```
# Sort in Descending Order
```

```
tb_iris %>% select(Species, Sepal.Length, everything()) %>%
```

Species	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width
setosa	4.3	3.0	1.1	0.1
setosa	4.4	2.9	1.4	0.2
setosa	4.4	3.0	1.3	0.2
setosa	4.4	3.2	1.3	0.2
setosa	4.5	2.3	1.3	0.3
setosa	4.6	3.1	1.5	0.2
setosa	4.6	3.4	1.4	0.3
setosa	4.6	3.6	1.0	0.2
setosa	4.6	3.2	1.4	0.2
setosa	4.7	3.2	1.3	0.2

```
arrange(desc(Species), desc(Sepal.Length)) %>% head(10) %>%
kable() %>% kable_styling_fc()
```

Species	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width
virginica	7.9	3.8	6.4	2.0
virginica	7.7	3.8	6.7	2.2
virginica	7.7	2.6	6.9	2.3
virginica	7.7	2.8	6.7	2.0
virginica	7.7	3.0	6.1	2.3
virginica	7.6	3.0	6.6	2.1
virginica	7.4	2.8	6.1	1.9
virginica	7.3	2.9	6.3	1.8
virginica	7.2	3.6	6.1	2.5
virginica	7.2	3.2	6.0	1.8

REconTools Summarize over Tible Use R4Econ's summary tool.

```
df_summ_stats <- ff_summ_percentiles(tb_iris)
kable(t(df_summ_stats)) %>% kable_styling_fc_wide()
```

stats	n	NAobs	ZEROobs	mean	sd	cv	min	p01	p05	p10	p25	p50	p75	p90	p95	p99	max
Petal.Length	150	0	0	3.758000	1.7652982	0.4697441	1.0	1.149	1.300	1.4	1.6	4.35	5.1	5.80	6.100	6.700	6.9
Petal.Width	150	0	0	1.199333	0.7622377	0.6355511	0.1	0.100	0.200	0.2	0.3	1.30	1.8	2.20	2.300	2.500	2.5
Sepal.Length	150	0	0	5.843333	0.8280661	0.1417113	4.3	4.400	4.600	4.8	5.1	5.80	6.4	6.90	7.255	7.700	7.9
Sepal.Width	150	0	0	3.057333	0.4358663	0.1425642	2.0	2.200	2.345	2.5	2.8	3.00	3.3	3.61	3.800	4.151	4.4