

Mesh Matrices, Arrays and Scalars Values of States, Choices, Shocks and Parameters in R Together

Fan Wang

2020-04-18

Contents

| | |
|---|---|
| Mesh Matrices, Arrays and Scalars | 1 |
|---|---|

Mesh Matrices, Arrays and Scalars

Go to the [RMD](#), [R](#), [PDF](#), or [HTML](#) version of this file. Go back to [fan's REconTools Package](#), [R4Econ Repository \(bookdown site\)](#), or [Intro Stats with R Repository](#).

- `r.expand.grid` meshed array to matrix
- `r.meshgrid`
- `r.array` to matrix
- `r.reshape` array to matrix
- `dplyr` permutations rows of matrix and element of array
- `tidyr.expand_grid` mesh matrix and vector

Mesh Two or More Vectors with `expand_grid` In the example below, we have a matrix that is 2 by 2 (endogenous states), a vector that is 3 by 1 (choices), and another matrix that is 4 by 3 (exogenous states shocks).

We want to generate a tibble dataset that meshes the matrix and the vector, so that all combinations show up. Additionally, we want to add some additional values that are common across all rows to the meshed dataframe.

Note `expand_grid` is a from `tidyr` 1.0.0.

```
# A. Generate the 5 by 2 Matrix (ENDO STATES)
# it_child_count = N, the number of children
it_N_child_cnt = 2
# P fixed parameters, nN is N dimensional, nP is P dimensional
ar_nN_A = seq(-2, 2, length.out = it_N_child_cnt)
ar_nN_alpha = seq(0.1, 0.9, length.out = it_N_child_cnt)
fl_rho = 0.1
fl_lambda = 1.1
mt_nP_A_alpha = cbind(ar_nN_A, ar_nN_alpha, fl_rho, fl_lambda)
ar_st_varnames <- c('s_A', 's_alpha', 'p_rho', 'p_lambda')
tb_states_endo <- as_tibble(mt_nP_A_alpha) %>%
  rename_all(~c(ar_st_varnames)) %>%
  rowid_to_column(var = "state_id")

# B. Choice Grid
it_N_choice_cnt = 3
fl_max = 10
```

```

fl_min = 0
ar_nN_d = seq(fl_min, fl_max, length.out = it_N_choice_cnt)
ar_st_varnames <- c('c_food')
tb_choices <- as_tibble(ar_nN_d) %>%
  rename_all(~c(ar_st_varnames)) %>%
  rowid_to_column(var = "choice_id")

# C. Shock Grid
set.seed(123)
it_N_shock_cnt = 4
ar_nQ_shocks = exp(rnorm(it_N_shock_cnt, mean=0, sd=1))
ar_st_varnames <- c('s_eps')
tb_states_exo <- as_tibble(ar_nQ_shocks) %>%
  rename_all(~c(ar_st_varnames)) %>%
  rowid_to_column(var = "shock_id")

# dataframe expand with other non expanded variables
ar_st_varnames <-
tb_states_shk_choices <- tb_states_endo %>%
  expand_grid(tb_choices) %>%
  expand_grid(tb_states_exo) %>%
  select(state_id, choice_id, shock_id,
         s_A, s_alpha, s_eps, c_food,
         p_rho, p_lambda)

# display
kable(tb_states_shk_choices) %>% kable_styling_fc()

```

Using `expand_grid` directly over arrays

```

# expand grid with dplyr
expand_grid(x = 1:3, y = 1:2, z = -3:-1)

```

Mesh Arrays with `expand.grid` Given two arrays, mesh the two arrays together.

```

# use expand.grid to generate all combinations of two arrays

it_ar_A = 5
it_ar_alpha = 10

ar_A = seq(-2, 2, length.out=it_ar_A)
ar_alpha = seq(0.1, 0.9, length.out=it_ar_alpha)

mt_A_alpha = expand.grid(A = ar_A, alpha = ar_alpha)

mt_A_meshed = mt_A_alpha[,1]
dim(mt_A_meshed) = c(it_ar_A, it_ar_alpha)

mt_alpha_meshed = mt_A_alpha[,2]
dim(mt_alpha_meshed) = c(it_ar_A, it_ar_alpha)

# display
kable(mt_A_meshed) %>%
  kable_styling_fc()

```

| state_id | choice_id | shock_id | s_A | s_alpha | s_eps | c_food | p_rho | p_lambda |
|----------|-----------|----------|-----|---------|-----------|--------|-------|----------|
| 1 | 1 | 1 | -2 | 0.1 | 0.5709374 | 0 | 0.1 | 1.1 |
| 1 | 1 | 2 | -2 | 0.1 | 0.7943926 | 0 | 0.1 | 1.1 |
| 1 | 1 | 3 | -2 | 0.1 | 4.7526783 | 0 | 0.1 | 1.1 |
| 1 | 1 | 4 | -2 | 0.1 | 1.0730536 | 0 | 0.1 | 1.1 |
| 1 | 2 | 1 | -2 | 0.1 | 0.5709374 | 5 | 0.1 | 1.1 |
| 1 | 2 | 2 | -2 | 0.1 | 0.7943926 | 5 | 0.1 | 1.1 |
| 1 | 2 | 3 | -2 | 0.1 | 4.7526783 | 5 | 0.1 | 1.1 |
| 1 | 2 | 4 | -2 | 0.1 | 1.0730536 | 5 | 0.1 | 1.1 |
| 1 | 3 | 1 | -2 | 0.1 | 0.5709374 | 10 | 0.1 | 1.1 |
| 1 | 3 | 2 | -2 | 0.1 | 0.7943926 | 10 | 0.1 | 1.1 |
| 1 | 3 | 3 | -2 | 0.1 | 4.7526783 | 10 | 0.1 | 1.1 |
| 1 | 3 | 4 | -2 | 0.1 | 1.0730536 | 10 | 0.1 | 1.1 |
| 2 | 1 | 1 | 2 | 0.9 | 0.5709374 | 0 | 0.1 | 1.1 |
| 2 | 1 | 2 | 2 | 0.9 | 0.7943926 | 0 | 0.1 | 1.1 |
| 2 | 1 | 3 | 2 | 0.9 | 4.7526783 | 0 | 0.1 | 1.1 |
| 2 | 1 | 4 | 2 | 0.9 | 1.0730536 | 0 | 0.1 | 1.1 |
| 2 | 2 | 1 | 2 | 0.9 | 0.5709374 | 5 | 0.1 | 1.1 |
| 2 | 2 | 2 | 2 | 0.9 | 0.7943926 | 5 | 0.1 | 1.1 |
| 2 | 2 | 3 | 2 | 0.9 | 4.7526783 | 5 | 0.1 | 1.1 |
| 2 | 2 | 4 | 2 | 0.9 | 1.0730536 | 5 | 0.1 | 1.1 |
| 2 | 3 | 1 | 2 | 0.9 | 0.5709374 | 10 | 0.1 | 1.1 |
| 2 | 3 | 2 | 2 | 0.9 | 0.7943926 | 10 | 0.1 | 1.1 |
| 2 | 3 | 3 | 2 | 0.9 | 4.7526783 | 10 | 0.1 | 1.1 |
| 2 | 3 | 4 | 2 | 0.9 | 1.0730536 | 10 | 0.1 | 1.1 |

| | | | | | | | | | |
|----|----|----|----|----|----|----|----|----|----|
| -2 | -2 | -2 | -2 | -2 | -2 | -2 | -2 | -2 | -2 |
| -1 | -1 | -1 | -1 | -1 | -1 | -1 | -1 | -1 | -1 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |

```
kable(mt_alpha_meshed) %>%
  kable_styling_fc_wide()
```

| | | | | | | | | | |
|-----|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----|
| 0.1 | 0.1888889 | 0.2777778 | 0.3666667 | 0.4555556 | 0.5444444 | 0.6333333 | 0.7222222 | 0.8111111 | 0.9 |
| 0.1 | 0.1888889 | 0.2777778 | 0.3666667 | 0.4555556 | 0.5444444 | 0.6333333 | 0.7222222 | 0.8111111 | 0.9 |
| 0.1 | 0.1888889 | 0.2777778 | 0.3666667 | 0.4555556 | 0.5444444 | 0.6333333 | 0.7222222 | 0.8111111 | 0.9 |
| 0.1 | 0.1888889 | 0.2777778 | 0.3666667 | 0.4555556 | 0.5444444 | 0.6333333 | 0.7222222 | 0.8111111 | 0.9 |
| 0.1 | 0.1888889 | 0.2777778 | 0.3666667 | 0.4555556 | 0.5444444 | 0.6333333 | 0.7222222 | 0.8111111 | 0.9 |

Two Identical Arrays, individual attributes, each column is an individual for a matrix, and each row is also an individual.

```
# use expand.grid to generate all combinations of two arrays
```

```
it_ar_A = 5

ar_A = seq(-2, 2, length.out=it_ar_A)
mt_A_A = expand.grid(Arow = ar_A, Arow = ar_A)
mt_Arow = mt_A_A[,1]
dim(mt_Arow) = c(it_ar_A, it_ar_A)
```

```
mt_Acol = mt_A_A[,2]
dim(mt_Acol) = c(it_ar_A, it_ar_A)

# display
kable(mt_Arow) %>%
  kable_styling_fc()
```

| | | | | |
|----|----|----|----|----|
| -2 | -2 | -2 | -2 | -2 |
| -1 | -1 | -1 | -1 | -1 |
| 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 |
| 2 | 2 | 2 | 2 | 2 |

```
kable(mt_Acol) %>%
  kable_styling_fc()
```

| | | | | |
|----|----|---|---|---|
| -2 | -1 | 0 | 1 | 2 |
| -2 | -1 | 0 | 1 | 2 |
| -2 | -1 | 0 | 1 | 2 |
| -2 | -1 | 0 | 1 | 2 |
| -2 | -1 | 0 | 1 | 2 |