

R Decompose File Paths to Get Folder and Files Names

Fan Wang

2021-01-10

Contents

1 File Path	1
1.1 Compose a Path	1
1.2 Substring and File Name	1
1.3 Get Subset of Path Folder Names	2

1 File Path

Go to the [RMD](#), [R](#), [PDF](#), or [HTML](#) version of this file. Go back to [fan's REconTools Package](#), [R Code Examples](#) Repository ([bookdown site](#)), or [Intro Stats with R](#) Repository ([bookdown site](#)).

1.1 Compose a Path

File Path might contain information related to the file, decompose the file path, keep the final N folder names, to be possibly stored as a variable in the datafile stored inside.

```
# Compose together a path
print(paste0('Platform$file.sep', Platform$file.sep))

## [1] "Platform$file.sep/"

spn_file_path = file.path("C:", "Users", "fan", "R4Econ", "amto", "tibble",
                          "fs_tib_basics.Rmd",
                          fsep = Platform$file.sep)

# print
print(spn_file_path)

## [1] "C:/Users/fan/R4Econ/amto/tibble/fs_tib_basics.Rmd"
```

1.2 Substring and File Name

From path, get file name without suffix.

- r string split
- r list last element
- r get file name from path
- r get file path no name

```
st_example <- 'C:/Users/fan/R4Econ/amto/tibble/fs_tib_basics.Rmd'
st_file_wth_suffix_s <- tail(strsplit(st_example, "/")[[1]],n=1)
st_file_wno_suffix_s <- tools::file_path_sans_ext(basename(st_example))
st_fullpath_nosufx_s <- sub('\\.Rmd$', '', st_example)
st_fullpath_noname_s <- dirname(st_example)
```

```

print(paste0('st_file_wth_suffix_s:', st_file_wth_suffix_s))

## [1] "st_file_wth_suffix_s:fs_tib_basics.Rmd"
print(paste0('st_file_wno_suffix_s:', st_file_wno_suffix_s))

## [1] "st_file_wno_suffix_s:fs_tib_basics"
print(paste0('st_fullpath_nosufx_s:', st_fullpath_nosufx_s))

## [1] "st_fullpath_nosufx_s:C:/Users/fan/R4Econ/amto/tibble/fs_tib_basics"
print(paste0('st_fullpath_noname_s:', st_fullpath_noname_s))

## [1] "st_fullpath_noname_s:C:/Users/fan/R4Econ/amto/tibble"

```

1.3 Get Subset of Path Folder Names

File Path might contain information related to the file, decompose the file path, keep the final N folder names, to be possibly stored as a variable in the datafile stored inside.

```

# Compose together a path
spn_example <- 'C:/Users/fan/R4Econ/amto/tibble/fs_tib_basics.Rmd'
# Replace default system slash, assume spn was generated by system.
ls_srt_folders_file <- strsplit(st_example, .Platform$file.sep)[[1]]
# Keep the last N layers
it_folders_names_to_keep = 2
snm_file_name <- tail(strsplit(st_example, "/")[[1]],n=1)
ls_srt_folders_keep <- head(tail(ls_srt_folders_file, it_folders_names_to_keep+1),
                           it_folders_names_to_keep)

# Show folder names
print(paste0('snm_file_name:', snm_file_name))

## [1] "snm_file_name:fs_tib_basics.Rmd"
print(paste0('last ', it_folders_names_to_keep, ' folders:'))

## [1] "last 2 folders:"
print(ls_srt_folders_keep)

## [1] "amto"    "tibble"

```

Shorter lines, to make copying easier.

```

# inputs
it_folders_names_to_keep = 2
spn_example <- 'C:/Users/fan/R4Econ/amto/tibble/fs_tib_basics.Rmd'
# copy these
ls_srt_folders_name_keep <- tail(strsplit(st_example, "/")[[1]], n=it_folders_names_to_keep+1)
snm_file_name <- tail(ls_srt_folders_name_keep, 1)
ls_srt_folders_keep <- head(ls_srt_folders_name_keep, it_folders_names_to_keep)
# print
print(paste0('snm_file_name:', snm_file_name))

## [1] "snm_file_name:fs_tib_basics.Rmd"
print(paste0('last ', it_folders_names_to_keep, ' folders:'))

## [1] "last 2 folders:"

```

```
print(ls_srt_folders_keep)
```

```
## [1] "amto"  "tibble"
```