

TIDYR Pivot Wider and Pivot Longer Examples

Fan Wang

2020-04-14

Contents

| | |
|------------------------|---|
| Long to Wide | 1 |
|------------------------|---|

Long to Wide

Go to the [RMD](#), [R](#), [PDF](#), or [HTML](#) version of this file. Go back to [fan's REconTools Package](#), [R4Econ Repository \(bookdown site\)](#), or [Intro Stats with R Repository](#).

Using the [pivot_wider](#) function in tidyR to reshape panel or other data structures

Panel Long Attendance Roster to Wide There are N students in class, but only a subset of them attend class each day. If student id_i is in class on day Q , the teacher records on a sheet the date and the student ID. So if the student has been in class 10 times, the teacher has ten rows of recorded data for the student with two columns: column one is the student ID, and column two is the date on which the student was in class. Suppose there were 50 students, who on average attended exactly 10 classes each during the semester, this means we have $10 \cdot 50$ rows of data, with differing numbers of rows for each student. This is shown as `df_panel_attend_date` generated below.

Now we want to generate a new dataframe, where each row is a date, and each column is a student. The values in the new dataframe shows, at the Q^{th} day, how many classes student i has attended so far. The following results is also in a REconTools Function. This is shown as `df_attend_cumu_by_day` generated below.

First, generate the raw data structure, `df_panel_attend_date`:

```
# Define
it_N <- 3
it_M <- 5
svr_id <- 'student_id'

# from : support/rand/fs_rand_draws.Rmd
set.seed(222)
df_panel_attend_date <- as_tibble(matrix(it_M, nrow=it_N, ncol=1)) %>%
  rowid_to_column(var = svr_id) %>%
  uncount(V1) %>%
  group_by(!sym(svr_id)) %>% mutate(date = row_number()) %>%
  ungroup() %>% mutate(in_class = case_when(rnorm(n(),mean=0,sd=1) < 0 ~ 1, TRUE ~ 0)) %>%
  filter(in_class == 1) %>% select(!sym(svr_id), date) %>%
  rename(date_in_class = date)

# Print
kable(df_panel_attend_date) %>%
  kable_styling_fc()
```

| student_id | date_in_class |
|------------|---------------|
| 1 | 2 |
| 1 | 4 |
| 2 | 1 |
| 2 | 2 |
| 2 | 5 |
| 3 | 2 |
| 3 | 3 |
| 3 | 5 |

Second, generate wider data structure, *df_attend_cumu_by_day*:

```
# Define
svr_id <- 'student_id'
svr_date <- 'date_in_class'
st_idcol_prefix <- 'sid_'

# Generate cumulative enrollment counts by date
df_panel_attend_date_addone <- df_panel_attend_date %>% mutate(attended = 1)
kable(df_panel_attend_date_addone) %>%
  kable_styling_fc()
```

| student_id | date_in_class | attended |
|------------|---------------|----------|
| 1 | 2 | 1 |
| 1 | 4 | 1 |
| 2 | 1 | 1 |
| 2 | 2 | 1 |
| 2 | 5 | 1 |
| 3 | 2 | 1 |
| 3 | 3 | 1 |
| 3 | 5 | 1 |

```
# Pivot Wide
df_panel_attend_date_wider <- df_panel_attend_date_addone %>%
  pivot_wider(names_from = svr_id,
              values_from = attended)
kable(df_panel_attend_date_wider) %>%
  kable_styling_fc()
```

| date_in_class | 1 | 2 | 3 |
|---------------|----|----|----|
| 2 | 1 | 1 | 1 |
| 4 | 1 | NA | NA |
| 1 | NA | 1 | NA |
| 5 | NA | 1 | 1 |
| 3 | NA | NA | 1 |

```
# Sort and rename
# rename see: https://fanwangecon.github.io/R4Econ/amto/tibble/fs\_tib\_basics.html
ar_unique_ids <- sort(unique(df_panel_attend_date %>% pull(!!sym(svr_id))))
df_panel_attend_date_wider_sort <- df_panel_attend_date_wider %>%
  arrange(!!sym(svr_date)) %>%
  rename_at(vars(num_range('1', ar_unique_ids))
            , list(~paste0(st_idcol_prefix, . , ')))
```

```
)
kable(df_panel_attend_date_wider_sort) %>%
  kable_styling_fc()
```

| date_in_class | sid_1 | sid_2 | sid_3 |
|---------------|-------|-------|-------|
| 1 | NA | 1 | NA |
| 2 | 1 | 1 | 1 |
| 3 | NA | NA | 1 |
| 4 | 1 | NA | NA |
| 5 | NA | 1 | 1 |

```
# replace NA and cumusum again
# see: R4Econ/support/function/fs_func_multivar for renaming and replacing
df_attend_cumu_by_day <- df_panel_attend_date_wider_sort %>%
  mutate_at(vars(contains(st_idcol_prefix)), list(~replace_na(., 0))) %>%
  mutate_at(vars(contains(st_idcol_prefix)), list(~cumsum(.)))

kable(df_attend_cumu_by_day) %>%
  kable_styling_fc()
```

| date_in_class | sid_1 | sid_2 | sid_3 |
|---------------|-------|-------|-------|
| 1 | 0 | 1 | 0 |
| 2 | 1 | 2 | 1 |
| 3 | 1 | 2 | 2 |
| 4 | 2 | 2 | 2 |
| 5 | 2 | 3 | 3 |

The structure above is also a function in Fan's [REconTools](#) Package, here the function is tested:

```
# Parameters
df <- df_panel_attend_date
svr_id_i <- 'student_id'
svr_id_t <- 'date_in_class'
st_idcol_prefix <- 'sid_'

# Invoke Function
ls_df_rosterwide <- ff_panel_expand_longrosterwide(df, svr_id_t, svr_id_i, st_idcol_prefix)
df_roster_wide_func <- ls_df_rosterwide$df_roster_wide
df_roster_wide_cumu_func <- ls_df_rosterwide$df_roster_wide_cumu

# Print
print(df_roster_wide_func)
```

```
## # A tibble: 5 x 4
##   date_in_class sid_1 sid_2 sid_3
##         <int> <dbl> <dbl> <dbl>
## 1             1    NA     1    NA
## 2             2     1     1     1
## 3             3    NA    NA     1
## 4             4     1    NA    NA
## 5             5    NA     1     1
```

```
print(df_roster_wide_cumu_func)
```

```
## # A tibble: 5 x 4
```

| ## | date_in_class | sid_1 | sid_2 | sid_3 |
|------|---------------|-------|-------|-------|
| ## | <int> | <dbl> | <dbl> | <dbl> |
| ## 1 | 1 | 0 | 1 | 0 |
| ## 2 | 2 | 1 | 2 | 1 |
| ## 3 | 3 | 1 | 2 | 2 |
| ## 4 | 4 | 2 | 2 | 2 |
| ## 5 | 5 | 2 | 3 | 3 |