

# Arrays Operations in R

Fan Wang

2020-04-01

## Contents

Array Basics . . . . .	1
------------------------	---

### Array Basics

Go to the [RMD](#), [R](#), [PDF](#), or [HTML](#) version of this file. Go back to [fan's REconTools Package](#), [R Code Examples Repository \(bookdown site\)](#), or [Intro Stats with R Repository \(bookdown site\)](#).

### Multidimensional Arrays

```
ar_a <- c(1,2,3)
ar_b <- c(1,2,3/1,2,3)
rep(0, length(ar_a))
```

### Repeat one Number by the Size of an Array

```
## [1] 0 0 0
```

```
# Multidimensional Array
# 1 is r1c1t1, 1.5 in r2c1t1, 0 in r1c2t1, etc.
# Three dimensions, row first, column second, and tensor third
x <- array(c(1, 1.5, 0, 2, 0, 4, 0, 3), dim=c(2, 2, 2))
dim(x)
```

### Generate 2 Dimensional Array

```
## [1] 2 2 2
```

```
print(x)
```

```
## , , 1
##
##      [,1] [,2]
## [1,]  1.0   0
## [2,]  1.5   2
##
## , , 2
##
##      [,1] [,2]
## [1,]    0   0
## [2,]    4   3
```

## Array Slicing

**Remove Elements of Array** Select elements with direct indexing, or with head and tail functions. Get the first two elements of three elements array.

```
# Remove last element of array
vars.group.bydf <- c('23', 'dfa', 'wer')
vars.group.bydf[-length(vars.group.bydf)]
```

```
## [1] "23" "dfa"
```

```
# Use the head function to remove last element
head(vars.group.bydf, -1)
```

```
## [1] "23" "dfa"
```

```
head(vars.group.bydf, 2)
```

```
## [1] "23" "dfa"
```

Get last two elements of array.

```
# Remove first element of array
vars.group.bydf <- c('23', 'dfa', 'wer')
vars.group.bydf[2:length(vars.group.bydf)]
```

```
## [1] "dfa" "wer"
```

```
# Use Tail function
tail(vars.group.bydf, -1)
```

```
## [1] "dfa" "wer"
```

```
tail(vars.group.bydf, 2)
```

```
## [1] "dfa" "wer"
```

## NA in Array

```
# Convert Inf and -Inf to NA
x <- c(1, -1, Inf, 10, -Inf)
na_if(na_if(x, -Inf), Inf)
```

Check if NA is in Array

```
## [1] 1 -1 NA 10 NA
```