Meshgrid Arrays in R

Fan Wang

2020-04-01

Contents

Array Basics

Go back to fan's REconTools Package, R4Econ Repository, or Intro Stats with R Repository.

Multidimesional Arrays

```r
# Multidimensional Array
# 1 is r1c1t1, 1.5 in r2c1t1, 0 in r1c2t1, etc.
# Three dimensions, row first, column second, and tensor third
x <- array(c(1, 1.5, 0, 2, 0, 4, 0, 3), dim=c(2, 2, 2))
dim(x)
```

Generate 2 Dimensional Array

```
## [1] 2 2 2
```

```r
print(x)
```

```
## , , 1
##
##      [,1] [,2]
## [1,]  1.0    0
## [2,]  1.5    2
##
## , , 2
##
##      [,1] [,2]
## [1,]    0    0
## [2,]    4    3
```

Array Slicing

```r
# Remove last element of array
vars.group.bydf <- c('23','dfa', 'wer')
vars.group.bydf[-length(vars.group.bydf)]
```

Remove Elements of Array

```
## [1] "23"  "dfa"
```

NA in Array

```r
# Convert Inf and -Inf to NA
x <- c(1, -1, Inf, 10, -Inf)
na_if(na_if(x, -Inf), Inf)
```

Check if NA is in Array

```
## [1]  1 -1 NA 10 NA
```