

# A Collection of Python Examples

Fan Wang

2020-05-31



# Contents

<b>Preface</b>	<b>5</b>
<b>1 Array, Matrix, Dataframe</b>	<b>7</b>
1.1 Array . . . . .	7
1.1.1 Strings . . . . .	7
1.2 Dictionary . . . . .	8
1.2.1 Dictionary . . . . .	8
<b>2 Get Data</b>	<b>11</b>
2.1 Environmental Data . . . . .	11
2.1.1 ECMWF ERA5 Data . . . . .	11
<b>3 System and Support</b>	<b>17</b>
3.1 Command Line . . . . .	17
3.1.1 Python Command Line . . . . .	17
3.1.2 Run Matlab Functions . . . . .	17
3.2 File In and Out . . . . .	19
3.2.1 Read and Write and Convert . . . . .	19
3.2.2 Folder Operations . . . . .	23
3.2.3 Parse Yaml . . . . .	28
3.3 Install Python . . . . .	32
3.3.1 Core Installations . . . . .	32
<b>A Index and Code Links</b>	<b>35</b>
A.1 Array, Matrix, Dataframe links . . . . .	35
A.1.1 Section 1.1 Array links . . . . .	35
A.1.2 Section 1.2 Dictionary links . . . . .	35
A.2 Get Data links . . . . .	35
A.2.1 Section 2.1 Environmental Data links . . . . .	35
A.3 System and Support links . . . . .	35
A.3.1 Section 3.1 Command Line links . . . . .	35
A.3.2 Section 3.2 File In and Out links . . . . .	35
A.3.3 Section 3.3 Install Python links . . . . .	36



# Preface

This is a work-in-progress [website](#) consisting of python tutorials and examples to accomplish. Files are written with [RMD](#) (Allaire et al., 2020). Materials are gathered from various [projects](#) in which python code is used for research and paper-administrative tasks. Files are from [Fan](#)'s [pyfan](#) repository which has an associated [package](#). The package functionalize various tasks tested out in the Rmd files. In addition, the [pyecon](#) repository and the associated [package](#) ([readthedocs](#)) contain functions and rmd files related explicitly to solving economic models.

From [Fan](#)'s other repositories: For dynamic borrowing and savings problems, see [Dynamic Asset Repository \(Matlab\)](#); For code examples, see also [Matlab Example Code](#), [R Example Code](#), and [Stata Example Code](#); For intro econ with Matlab, see [Intro Mathematics for Economists](#), and for intro stat with R, see [Intro Statistics for Undergraduates](#). See [here](#) for all of [Fan](#)'s public repositories.

The site is built using [Bookdown](#) (Xie, 2020).

Please contact [FanWangEcon](#) for issues or problems.



# Chapter 1

## Array, Matrix, Dataframe

### 1.1 Array

#### 1.1.1 Strings

Go back to [fan's Python Code Examples Repository \(bookdown site\)](#).

##### 1.1.1.1 Search if Names Include Strings

Given a list of strings, loop but skip if string contains elements string list.

```
# define string
ls_st_ignore = ['abc', 'efg', 'xyz']
ls_st_loop = ['ab cefg sdf', '12345', 'xyz', 'abc xyz', 'good morning']

# zip and loop and replace
for st_loop in ls_st_loop:
    if sum([st_ignore in st_loop for st_ignore in ls_st_ignore]):
        print('skip:', st_loop)
    else:
        print('not skip:', st_loop)
```

```
## skip: ab cefg sdf
## not skip: 12345
## skip: xyz
## skip: abc xyz
## not skip: good morning
```

##### 1.1.1.2 Replace a Set of Strings in String

Replace terms in string

```
# define string
st_full = """
abc is a great efg, probably xyz. Yes, xyz is great, like efg.
eft good, EFG capitalized, efg good again.
A B C or abc or ABC. Interesting xyz.
"""

# define new and old
ls_st_old = ['abc', 'efg', 'xyz']
ls_st_new = ['123', '456', '789']

# zip and loop and replace
for old, new in zip(ls_st_old, ls_st_new):
```

```

st_full = st_full.replace(old, new)

# print
print(st_full)

##
## 123 is a great 456, probably 789. Yes, 789 is great, like 456.
## eft good, EFG capitalized, 456 good again.
## A B C or 123 or ABC. Interesting 789.

```

## 1.2 Dictionary

### 1.2.1 Dictionary

Go back to [fan's Python Code Examples Repository](#) ([bookdown site](#)).

#### 1.2.1.1 Create a List of Dictionaries

```

import datetime
import pprint
ls_dc_exa = [
    {"file": "mat_matlab",
     "title": "One Variable Graphs and Tables",
     "description": "Frequency table, bar chart and histogram",
     "val": 1,
     "date": datetime.date(2020, 5, 2)},
    {"file": "mat_two",
     "title": "Second file",
     "description": "Second file.",
     "val": [1, 2, 3],
     "date": datetime.date(2020, 5, 2)},
    {"file": "mat_algebra_rules",
     "title": "Opening a Dataset",
     "description": "Opening a Dataset.",
     "val": 1.1,
     "date": datetime.date(2018, 12, 1)}
]
pprint.pprint(ls_dc_exa, width=1)

## [{'date': datetime.date(2020, 5, 2),
##   'description': 'Frequency '
##                 'table, '
##                 'bar '
##                 'chart '
##                 'and '
##                 'histogram',
##   'file': 'mat_matlab',
##   'title': 'One '
##            'Variable '
##            'Graphs '
##            'and '
##            'Tables',
##   'val': 1},
##  {'date': datetime.date(2020, 5, 2),
##   'description': 'Second '
##                 'file.',
##   'file': 'mat_two',
##   'title': 'Second '

```



```
##         'file',
##   'val': [1,
##          2,
##          3]],
## {'date': datetime.date(2018, 12, 1),
##   'description': 'Opening '
##                 'a '
##                 'Dataset.',
##   'file': 'mat_algebra_rules',
##   'title': 'Opening '
##           'a '
##           'Dataset',
##   'val': 1.1}]
```

### 1.2.1.2 Select by Keys in Dictionary

Given a list of dictionary, search if key name is in list:

```
# string to search through
ls_str_file_ids = ['mat_matlab', 'mat_algebra_rules']
# select subset
ls_dc_selected = [dc_exa
                   for dc_exa in ls_dc_exa
                   if dc_exa['file'] in ls_str_file_ids]
# print
pprint.pprint(ls_dc_selected, width=1)
```

```
## [{'date': datetime.date(2020, 5, 2),
##   'description': 'Frequency '
##                 'table, '
##                 'bar '
##                 'chart '
##                 'and '
##                 'histogram',
##   'file': 'mat_matlab',
##   'title': 'One '
##           'Variable '
##           'Graphs '
##           'and '
##           'Tables',
##   'val': 1},
## {'date': datetime.date(2018, 12, 1),
##   'description': 'Opening '
##                 'a '
##                 'Dataset.',
##   'file': 'mat_algebra_rules',
##   'title': 'Opening '
##           'a '
##           'Dataset',
##   'val': 1.1}]
```

Search and Select by Multiple Keys in Dictionary. Using two keys below:

```
# string to search through
ls_str_file_ids = ['mat_matlab', 'mat_algebra_rules']
# select subset
ls_dc_selected = [dc_exa
                   for dc_exa in ls_dc_exa
                   if ((dc_exa['file'] in ls_str_file_ids)
                       and
```

```
(dc_exa['val']== 1))]  
  
# print  
pprint.pprint(ls_dc_selected, width=1)  
  
## [{'date': datetime.date(2020, 5, 2),  
##   'description': 'Frequency '  
##                 'table, '  
##                 'bar '  
##                 'chart '  
##                 'and '  
##                 'histogram',  
##   'file': 'mat_matlab',  
##   'title': 'One '  
##         'Variable '  
##         'Graphs '  
##         'and '  
##         'Tables',  
##   'val': 1}]
```

# Chapter 2

## Get Data

### 2.1 Environmental Data

#### 2.1.1 ECMWF ERA5 Data

Go back to [fan's Python Code Examples Repository](#) ([bookdown site](#)).

##### 2.1.1.1 Basic Conda Setup

1. Download [Anaconda](#) for Python 3. For more involved conda instructions see [here](#)
2. Open up *anaconda prompt* with admin rights (right click choose as admin).

```
# Inside anaconda prompt
where python
where anaconda
# C:/ProgramData/Anaconda3/Scripts/anaconda.exe
# C:/ProgramData/Anaconda3/python.exe
```

3. Add to Path
4. Install cdsapi and eccodes

```
conda config --add channels conda-forge
conda install -c conda-forge eccodes -y
```

##### 2.1.1.2 Account Registration

1. Register for an [account](#)
2. [Agree to Licence](#)
3. Go to your CDS user page copy the url and key: [Get url and key](#)
  - this has UID, 4XXXX, and API KEY, 4XXXXfXXX-XXXf-4XXX-9XXX-7XXXebXXfdXX
  - together they should look like: 4XXXX:4XXXXfXXX-XXXf-4XXX-9XXX-7XXXebXXfdXX
4. Open up an editor (notepad++ for example), create an empty file, paste the url and your UID:APIKEY into the file as below. Save file as: *C:/Users/fan/.cdsapirc*. Under user root, as *.cdsapirc* file. Note *.cdsapirc* is the file name, you are saving that under the directory *C:/Users/fan/*.

```
url: https://cds.climate.copernicus.eu/api/v2
key: 4XXXX:4XXXXfXXX-XXXf-4XXX-9XXX-7XXXebXXfdXX
```

##### 2.1.1.3 Run API Request via Jupyter Notebook

1. open up Jupyter Notebook (this opens up a browser page)

- cd "C:/Users/fan/Downloads"
  - jupyter notebook
2. create a new *python3* file somewhere you like
  3. name the file *cdstest* (saved as ipynb file)
  4. paste the code below inside the *ipynb* file you opened (modify *spt\_root*):

```
import cdsapi
import urllib.request
# download folder
spt_root = "C:/Users/fan/downloads/_data/"
spn_dl_test_grib = spt_root + "test_china_temp.grib"
# request
c = cdsapi.Client()
res = c.retrieve("reanalysis-era5-pressure-levels",
{
    'product_type': 'reanalysis',
    'variable': 'temperature',
    'pressure_level': '1000',
    'year': '2008',
    'month': '01',
    'day': '01',
    'time': '12:00',
    'format': 'netcdf',
    'area'      : [53.31, 73, 4.15, 135],
    'grid'      : [1.0, 1.0],
    "format": "grib"
},
    spn_dl_test_grib
)
# show results
print('print results')
print(res)
print(type(res))
```

5. click run

#### 2.1.1.4 Run API request via Ipython

1. In Anaconda Prompt: *ipython*
2. Open a file in notepad++ or elsewhere, copy the code above over and edit the *spt\_root* to reflect your directories
3. Select the entire code in the notepad++ page, and copy all lines
4. Now inside ipython, type percentage and paste: %paste
5. This should run the file above and save the grib file in the folder you specified with the name you specified.

#### 2.1.1.5 Convert CRIB data to CSV

1. inside conda prompt cd into the folder where you downloaded the grib file
2. *grib\_ls* shows what is in the grib file
3. *grib\_get\_data* translates grib to csv

```
cd "C:/Users/fan/downloads/_data/"
grib_ls test_china_temp.grib
grib_get_data test_china_temp.grib > test_china_temp_raw.csv
```

### 2.1.1.6 More Advanced Download Setup and Instructions

**2.1.1.6.1 Conda Enviornment and Installation** In conda, set up a conda environment for downloading ECMWF data using the ECMWF API. ([Conda Set-up](#))

```
# Set up
conda deactivate
conda list env
conda env remove -n wk_ecmwf
conda create -n wk_ecmwf -y
conda activate wk_ecmwf

# Add conda-forge to channel in env
conda config --env --add channels conda-forge
conda config --get channels
conda config --get channels --env

# Install
conda install cdsapi -y
conda install -c conda-forge eccodes -y
```

This creates the conda env that we are using here for python.

**2.1.1.6.2 Config File .cdsapirc** Open up the *cdsapirc*, create new if does not exist. Below, open up the file and save the text. See [Python Reading and Writing to File Examples](#).

First, get the [text](#) for the config file:

```
stf_cds_cdsapirc = """\
url: https://cds.climate.copernicus.eu/api/v2
key: 46756:4000fe9a-498f-4ce8-9caf-7796eb64fd9d\
"""
print(stf_cds_cdsapirc)

## url: https://cds.climate.copernicus.eu/api/v2
## key: 46756:4000fe9a-498f-4ce8-9caf-7796eb64fd9d
```

Second save text to file:

```
# Relative file name
spt_file_cds = "C:/Users/fan/"
snm_file_cds = ".cdsapirc"
spn_file_cds = spt_file_cds + snm_file_cds
# Open new file
fl_cdsapirc_contents = open(spn_file_cds, 'w')
# Write to File
fl_cdsapirc_contents.write(stf_cds_cdsapirc)
# Close
```

```
## 93
```

```
fl_cdsapirc_contents.close()
```

```
# Open the config file to check
code "C:/Users/fan/.cdsapirc"
```

### 2.1.1.7 Generate API Requests

Go to the sites below, choose download data, pick what is needed, and then select *Show API request* at the bottom of page:

**ERA5 pressure levels from 1979 to present**

- [ERA5 hourly pressure](#)

- [ERA5 monthly pressure](#)

#### ERA5 single levels from 1979 to present

- [ERA5 hourly pressure](#)
- [ERA5 monthly pressure](#)

##### 2.1.1.7.1 API Request China Temp Test API function is [here](#).

Select based on China's area, some testing data and download grib file. The data is from 2008, Jan 1st, at 12 noon?

Open up Jupyter notebook: *jupyter notebook*

```
# import module in conda env wk_ecmwf
import cdsapi
import urllib.request

# download folder
spt_root = "C:/Users/fan/pyfan/vig/getdata/envir/"
spn_dl_test_grib = spt_root + "_data/test/test_china_temp.grib"

# request
c = cdsapi.Client()
res = c.retrieve("reanalysis-era5-pressure-levels",
{
    'product_type': 'reanalysis',
    'variable': 'temperature',
    'pressure_level': '1000',
    'year': '2008',
    'month': '01',
    'day': '01',
    'time': '12:00',
    'format': 'netcdf',
    'area'      : [53.31, 73, 4.15, 135],
    'grid'      : [1.0, 1.0],
    "format": "grib"
},
    spn_dl_test_grib
)
# show results
```

```
## 2020-05-31 12:17:20,308 INFO Welcome to the CDS
## 2020-05-31 12:17:20,308 INFO Sending request to https://cds.climate.copernicus.eu/api/v2/resource
## 2020-05-31 12:17:21,024 INFO Request is completed
## 2020-05-31 12:17:21,025 INFO Downloading http://136.156.133.41/cache-compute-0013/cache/data8/ada
##   0%|          | 0.00/6.33k [00:00<?, ?B/s]                               2020-05-31
print('print results')
```

```
## print results
```

```
print(res)
```

```
## Result(content_length=6480,content_type=application/x-grib,location=http://136.156.133.41/cache-c
print(type(res))
```

```
# download
# response = urllib.request.urlopen('http://www.example.com/')
# html = response.read()
```

```
## <class 'cdsapi.api.Result'>
```



Chinese Long and Lat, Temperature Pressure, 2008 Jan 1st at 12 noon?

Latitude	Longitude	Value
53.15	73	260.6515
53.15	74	259.9796
53.15	75	259.2227
53.15	76	258.5929
53.15	77	258.2765
53.15	78	258.0636
53.15	79	258.0069
53.15	80	257.7267
53.15	81	258.8370
53.15	82	260.9239
53.15	83	262.5440
53.15	84	263.9083
53.15	85	264.8976
53.15	86	264.6729
53.15	87	264.1827
53.15	88	265.0587
53.15	89	264.9425
53.15	90	266.2960
53.15	91	269.0958
53.15	92	270.3165
53.15	93	269.0030
53.15	94	268.4210
53.15	95	264.9591
53.15	96	261.9249
53.15	97	264.5304
53.15	98	265.3995
53.15	99	268.2374
53.15	100	269.9444
53.15	101	272.6202
53.15	102	270.6798
53.15	103	270.0919
53.15	104	269.6876
53.15	105	271.4718
53.15	106	271.2403
53.15	107	271.1163
53.15	108	269.3849
53.15	109	270.7247
53.15	110	269.6388
53.15	111	268.6622
53.15	112	267.6036
53.15	113	267.4796
53.15	114	266.6983
53.15	115	266.2911
53.15	116	266.5880
53.15	117	265.4513
53.15	118	264.4630
53.15	119	260.6183
53.15	120	259.3018
53.15	121	258.4161
53.15	122	258.8429



## Chapter 3

# System and Support

### 3.1 Command Line

#### 3.1.1 Python Command Line

Go back to [fan's Python Code Examples Repository](#) ([bookdown site](#)).

##### 3.1.1.1 Execute Command Line Python Functions

- run python from command line
- run python function with parameters from command line

Here run python from command line inside python itself.

Run: - from py.fan.util.rmd.mattexmd import fp\_mlxte2md - fp\_mlxte2md(spt\_root='C:/Users/fan/Math4Econ/mat  
ls\_srt\_subfolders=None, st\_rglob\_tex='twogoods.tex', verbose=True)

Run: - python -c "from pyfan.util.rmd.mattexmd import fp\_mlxte2md; fp\_mlxte2md(spt\_root='C:/Users/fan/Math4  
ls\_srt\_subfolders=None, st\_rglob\_tex='twogoods.tex', verbose=True)"

#### 3.1.2 Run Matlab Functions

Go back to [fan's Python Code Examples Repository](#) ([bookdown site](#)).

##### 3.1.2.1 Generate A template Matlab Script

Generate an example matlab script file with parameter  $x$ .

```
# Example Matlab Function
```

```
stf_m_contents = ""\
```

```
a = x + 1
```

```
b = 10*x\
```

```
""
```

```
# Print
```

```
print(stf_m_contents)
```

```
# Open new file
```

```
## a = x + 1
```

```
## b = 10*x
```

```
fl_m_contents = open("_m/fs_test.m", 'w')
```

```
# Write to File
```

```
fl_m_contents.write(stf_m_contents)
```

```
# print
```

```
## 18
```

```
fl_m_contents.close()
```

### 3.1.2.2 Run the Matlab Function from Commandline

- [run matlab function from command line](#)
- [Retrieving the output of subprocess.call](#)
- <https://www.mathworks.com/help/matlab/ref/matlabwindows.html>

First, check where matlab is installed:

```
import subprocess
cmd_popen = subprocess.Popen(["where", "matlab"],
                             stdin=subprocess.PIPE,
                             stdout=subprocess.PIPE,
                             stderr=subprocess.PIPE)
output, err = cmd_popen.communicate()
print(output.decode('utf-8'))
```

```
## C:\Program Files\MATLAB\R2019b\bin\matlab.exe
```

Second, run the matlab file, first define the parameter x:

```
import os
# print and set directory
print(os.getcwd())
```

```
## C:\Users\fan\pyfan
```

```
os.chdir('_m')
print(os.getcwd())
# run matlab script saved prior
# running command line: matlab -batch "fs_test; exit"
```

```
## C:\Users\fan\pyfan\_m
```

```
cmd_popen = subprocess.Popen(["matlab", "-batch", "\"x=1; fs_test; exit\""],
                             stdin=subprocess.PIPE,
                             stdout=subprocess.PIPE,
                             stderr=subprocess.PIPE)
output, err = cmd_popen.communicate()
print(output.decode('utf-8'))
```

```
##
## a =
##
##      2
##
##
## b =
##
##     10
##
```

Third, run the function again, but with  $x=3$ :

```
os.chdir('_m')
print(os.getcwd())
```

```
## C:\Users\fan\pyfan\_m
```

```
print(subprocess.Popen(["matlab", "-batch", "\"x=5; fs_test; exit\""],
                      stdin=subprocess.PIPE,
```

```

        stdout=subprocess.PIPE,
        stderr=subprocess.PIPE).communicate()[0].decode('utf-8'))

##
## a =
##
##      6
##
##
## b =
##
##      50
##

```

## 3.2 File In and Out

### 3.2.1 Read and Write and Convert

Go back to [fan's Python Code Examples Repository](#) ([bookdown site](#)).

- python create a text file
- python write file from paragraphs

#### 3.2.1.1 Generate a tex file

Will a bare-bone tex file with some texts inside, save inside the `*_file*` subfolder.

First, create the text text string, note the the linebreaks utomatically generate linebreaks, note that slash need double slash:

```

# Create the Tex Text
# Note that trible quotes begin first and end last lines
stf_tex_contents = """\documentclass[12pt,english]{article}
\usepackage[bottom]{footmisc}
\usepackage[urlcolor=blue]{hyperref}
\begin{document}
\title{A Latex Testing File}
\author{\href{http://fanwangecon.github.io/}{Fan Wang} \thanks{See information \href{https://fan
\maketitle
Ipsum information dolor sit amet, consectetur adipiscing elit. Integer Latex placerat nunc orci.
\paragraph{\href{https://papers.ssrn.com/sol3/papers.cfm?abstract_id=3140132}{Data}}
Village closure information is taken from a village head survey.\footnote{Generally students went t
\end{document}}"""
# Print
print(stf_tex_contents)

```

```

## \documentclass[12pt,english]{article}
## \usepackage[bottom]{footmisc}
## \usepackage[urlcolor=blue]{hyperref}
## \begin{document}
## \title{A Latex Testing File}
## \author{\href{http://fanwangecon.github.io/}{Fan Wang} \thanks{See information \href{https://fanw
## \maketitle
## Ipsum information dolor sit amet, consectetur adipiscing elit. Integer Latex placerat nunc orci.
## \paragraph{\href{https://papers.ssrn.com/sol3/papers.cfm?abstract_id=3140132}{Data}}
## Village closure information is taken from a village head survey.\footnote{Generally students went
## \end{document}

```

Second, write the contents of the file to a new tex file stored inside the `*_file*` subfolder of the directory:

```

# Relative file name
srt_file_tex = "_file/"
sna_file_tex = "test_fan"
srn_file_tex = srt_file_tex + sna_file_tex + ".tex"
# Open new file
fl_tex_contents = open(srn_file_tex, 'w')
# Write to File
fl_tex_contents.write(stf_tex_contents)
# print

## 617
fl_tex_contents.close()

```

### 3.2.1.2 Replace Strings in a tex file

Replace a set of strings in the file just generated by a set of alternative strings.

```

# Open file Get text
fl_tex_contents = open(srn_file_tex)
stf_tex_contents = fl_tex_contents.read()
print(srn_file_tex)

# define new and old

## _file/test_fan.tex

ls_st_old = ['information', 'Latex']
ls_st_new = ['INFOREPLACE', 'LATEX']

# zip and loop and replace
for old, new in zip(ls_st_old, ls_st_new):
    stf_tex_contents = stf_tex_contents.replace(old, new)
print(stf_tex_contents)

# write to file with replacements

## \documentclass[12pt,english]{article}
## \usepackage[bottom]{footmisc}
## \usepackage[urlcolor=blue]{hyperref}
## \begin{document}
## \title{A LATEX Testing File}
## \author{\href{http://fanwangecon.github.io/}{Fan Wang} \thanks{See INFOREPLACE \href{https://fanw}
## \maketitle
## Ipsum INFOREPLACE dolor sit amet, consectetur adipiscing elit. Integer LATEX placerat nunc orci.
## \paragraph{\href{https://papers.ssrn.com/sol3/papers.cfm?abstract_id=3140132}{Data}}
## Village closure INFOREPLACE is taken from a village head survey.\footnote{Generally students went
## \end{document}

sna_file_edited_tex = "test_fan_edited"
srn_file_edited_tex = srt_file_tex + sna_file_edited_tex + ".tex"
fl_tex_ed_contents = open(srn_file_edited_tex, 'w')
fl_tex_ed_contents.write(stf_tex_contents)

## 617
fl_tex_ed_contents.close()

```

### 3.2.1.3 Convert Tex File to Pandoc and Compile Latex

Compile tex file to pdf and clean up the extraneous pdf outputs. See [ff\\_pdf\\_gen\\_clean](#).

```

import subprocess
import os

# Change to local directory so path in tex respected.
os.chdir("C:/Users/fan/pyfan/vig/support/inout")

# Convert tex to pdf
subprocess.call(['C:/texlive/2019/bin/win32/xelatex.exe', '-output-directory',
                srt_file_tex, srn_file_edited_tex], shell=False)
# Clean pdf extraneous output

## 0
ls_st_remove_suffix = ['aux', 'log', 'out', 'bbl', 'blg']
for st_suffix in ls_st_remove_suffix:
    srn_cur_file = srt_file_tex + sna_file_edited_tex + "." + st_suffix
    if (os.path.isfile(srn_cur_file)):
        os.remove(srt_file_tex + sna_file_edited_tex + "." + st_suffix)

```

Use pandoc to convert tex file

```

import subprocess

# md file name
srn_file_md = srt_file_tex + "test_fan_edited.md"
# Convert tex to md
subprocess.call(['pandoc', '-s', srn_file_tex, '-o', srn_file_md])
# Open md file

## 0

fl_md_contents = open(srn_file_md)
print(fl_md_contents.read())

## ---
## author:
## - '[Fan Wang](http://fanwangecon.github.io/) [^1]'
## title: A Latex Testing File
## ---
##
## Ipsum information dolor sit amet, consectetur adipiscing elit. Integer
## Latex placerat nunc orci.
##
## ##### [Data](https://papers.ssrn.com/sol3/papers.cfm?abstract_id=3140132)
##
## Village closure information is taken from a village head survey.[^2]
##
## [^1]: See information
##       [Tex4Econ](https://fanwangecon.github.io/Tex4Econ/) for more.
##
## [^2]: Generally students went to schools.

```

#### 3.2.1.4 Search for Files with Suffix in Several Folders

- python search all files in folders with suffix

Search for files in several directories that have a particular suffix. Then decompose directory into sub-components.

Search file inside several folders (not recursively in subfolders):

```

from pathlib import Path

# directories to search in
ls_spt_srh = ["C:/Users/fan/R4Econ/amto/",
              "C:/Users/fan/R4Econ/function/"]

# get file names in folders (not recursively)
ls_spn_found = [spn_file for spt_srh in ls_spt_srh
                 for spn_file in Path(spt_srh).glob('*.Rmd')]
for spn_found in ls_spn_found:
    print(spn_found)

```

```

## C:\Users\fan\R4Econ\amto\main.Rmd
## C:\Users\fan\R4Econ\function\main.Rmd

```

Search file recursively in all subfolders of folders:

```

from pathlib import Path

# directories to search in
ls_spt_srh = ["C:/Users/fan/R4Econ/amto/array/",
              "C:/Users/fan/R4Econ/amto/list"]

# get file names recursively in all subfolders
ls_spn_found = [spn_file for spt_srh in ls_spt_srh
                 for spn_file in Path(spt_srh).rglob('*.R')]
for spn_found in ls_spn_found:
    drive, path_and_file = os.path.splitdrive(spn_found)
    path_no_suffix = os.path.splitext(spn_found)[0]
    path_no_file, file = os.path.split(spn_found)
    file_no_suffix = Path(spn_found).stem
    print('file:', file, '\ndrive:', drive,
          '\nfile no suffix:', file_no_suffix,
          '\nfull path:', spn_found,
          '\npt no file:', path_no_file,
          '\npt no suf:', path_no_suffix, '\n')

## file: fs_ary_basics.R
## drive: C:
## file no suffix: fs_ary_basics
## full path: C:\Users\fan\R4Econ\amto\array\htmlpdf\fs_ary_basics.R
## pt no file: C:\Users\fan\R4Econ\amto\array\htmlpdf
## pt no suf: C:\Users\fan\R4Econ\amto\array\htmlpdf\fs_ary_basics
##
## file: fs_ary_generate.R
## drive: C:
## file no suffix: fs_ary_generate
## full path: C:\Users\fan\R4Econ\amto\array\htmlpdf\fs_ary_generate.R
## pt no file: C:\Users\fan\R4Econ\amto\array\htmlpdf
## pt no suf: C:\Users\fan\R4Econ\amto\array\htmlpdf\fs_ary_generate
##
## file: fs_ary_mesh.R
## drive: C:
## file no suffix: fs_ary_mesh
## full path: C:\Users\fan\R4Econ\amto\array\htmlpdf\fs_ary_mesh.R
## pt no file: C:\Users\fan\R4Econ\amto\array\htmlpdf
## pt no suf: C:\Users\fan\R4Econ\amto\array\htmlpdf\fs_ary_mesh
##
## file: fs_ary_string.R

```

```
## drive: C:
## file no suffix: fs_ary_string
## full path: C:\Users\fan\R4Econ\amto\array\htmlpdf\fs_ary_string.R
## pt no file: C:\Users\fan\R4Econ\amto\array\htmlpdf
## pt no suf: C:\Users\fan\R4Econ\amto\array\htmlpdf\fs_ary_string
##
## file: fs_listr.R
## drive: C:
## file no suffix: fs_listr
## full path: C:\Users\fan\R4Econ\amto\list\htmlpdf\fs_listr.R
## pt no file: C:\Users\fan\R4Econ\amto\list\htmlpdf
## pt no suf: C:\Users\fan\R4Econ\amto\list\htmlpdf\fs_listr
##
## file: fs_lst_basics.R
## drive: C:
## file no suffix: fs_lst_basics
## full path: C:\Users\fan\R4Econ\amto\list\htmlpdf\fs_lst_basics.R
## pt no file: C:\Users\fan\R4Econ\amto\list\htmlpdf
## pt no suf: C:\Users\fan\R4Econ\amto\list\htmlpdf\fs_lst_basics
```

### 3.2.2 Folder Operations

Go back to [fan's Python Code Examples Repository](#) ([bookdown site](#)).

#### 3.2.2.1 New Folder and Files

1. create a folder and subfolder
2. create two files in the new folder

```
import pathlib

# folder root
srt_folder = "_folder/"

# new folder
srt_subfolder = srt_folder + "fa/"
# new subfolder
srt_subfolder = srt_subfolder + "faa/"
# generate folders recursively
pathlib.Path(srt_subfolder).mkdir(parents=True, exist_ok=True)

# Open new file
fl_tex_contents_aa = open(srt_subfolder + "file_a.txt", 'w')
# Write to File
fl_tex_contents_aa.write('contents of file a')

## 18
fl_tex_contents_aa.close()

# Open another new file and save
fl_tex_contents_ab = open(srt_subfolder + "file_b.txt", 'w')
# Write to File
fl_tex_contents_ab.write('contents of file b')

## 18
fl_tex_contents_ab.close()
```

Generate more folders without files:

```
# generate folders recursively
pathlib.Path("_folder/fb/fba/").mkdir(parents=True, exist_ok=True)
# generate folders recursively
pathlib.Path("_folder/fc/").mkdir(parents=True, exist_ok=True)
# generate folders recursively
pathlib.Path("_folder/fd/").mkdir(parents=True, exist_ok=True)
```

### 3.2.2.2 Copy a File from One Folder to Another

Move the two files from `*_folder/fa/faa*` to `*_folder/faa*` as well as to `*_folder/fb/faa`. Use `shutil.copy2*` so that more metadata is copied over. But `copyfile` is faster.

- [How do I copy a file in Python?](#)

Moving one file:

```
import shutil
# Faster method
shutil.copyfile('_folder/fa/faa/file_a.txt', '_folder/fb/file_a.txt')
# More metadata copied, and don't need to specify name

## '_folder/fb/file_a.txt'
shutil.copy2('_folder/fa/faa/file_a.txt', '_folder/fb/fba')

## '_folder/fb/fba\\file_a.txt'
```

### 3.2.2.3 Copy Folder to Multiple Destinations

Move Entire Folder, [How do I copy an entire directory of files into an existing directory using Python?](#):

```
from distutils.dir_util import copy_tree

# Move contents from fa/faa/ to fc/faa
srt_curroot = '_folder/fa/'
srt_folder = 'faa/'
srt_newroot = '_folder/fc/'

# Full source and destination
srt_sourc = srt_curroot + srt_folder
srt_desct = srt_newroot + srt_folder

# Check/Create new Directory
pathlib.Path(srt_desct).mkdir(parents=True, exist_ok=True)

# Move
copy_tree(srt_sourc, srt_desct)

## ['_folder/fc/faa/file_a.txt', '_folder/fc/faa/file_b.txt']
```

Move contents to multiple destinations:

```
from distutils.dir_util import copy_tree
# Check/Create new Directory
pathlib.Path('_folder/fd/faa/fa_images').mkdir(parents=True, exist_ok=True)
pathlib.Path('_folder/fd/faa/fb_images').mkdir(parents=True, exist_ok=True)
pathlib.Path('_folder/fd/faa/fc_images').mkdir(parents=True, exist_ok=True)
pathlib.Path('_folder/fd/faa/fz_img').mkdir(parents=True, exist_ok=True)
pathlib.Path('_folder/fd/faa/fz_other').mkdir(parents=True, exist_ok=True)

# Move
copy_tree('_folder/fa/faa/', '_folder/fd/faa/fa_images')
```



```
## ['_folder/fd/faa/fa_images\\file_a.txt', '_folder/fd/faa/fa_images\\file_b.txt']
copy_tree('_folder/fa/faa/', '_folder/fd/faa/fb_images')

## ['_folder/fd/faa/fb_images\\file_a.txt', '_folder/fd/faa/fb_images\\file_b.txt']
copy_tree('_folder/fa/faa/', '_folder/fd/faa/fc_images')

## ['_folder/fd/faa/fc_images\\file_a.txt', '_folder/fd/faa/fc_images\\file_b.txt']
copy_tree('_folder/fa/faa/', '_folder/fd/faa/fz_img')

## ['_folder/fd/faa/fz_img\\file_a.txt', '_folder/fd/faa/fz_img\\file_b.txt']
copy_tree('_folder/fa/faa/', '_folder/fd/faa/fz_other')
# Empty Folder

## ['_folder/fd/faa/fz_other\\file_a.txt', '_folder/fd/faa/fz_other\\file_b.txt']
pathlib.Path('_folder/fd/faa/fd_images').mkdir(parents=True, exist_ok=True)
pathlib.Path('_folder/fd/faa/fe_images').mkdir(parents=True, exist_ok=True)
```

### 3.2.2.4 Search for Files in Folder

Find the total number of files in a folder.

```
import pathlib
# the number of files in folder found with search critiera
st_file_search = '*.txt'
ls_spn = [Path(spn).stem for spn in Path('_folder/fd/faa/fa_images').rglob(st_file_search)]
print(ls_spn)

# count files in a non-empty folder

## ['file_a', 'file_b']
srn = '_folder/fd/faa/fa_images'
[spn for spn in Path(srn).rglob(st_file_search)]

## [WindowsPath('_folder/fd/faa/fa_images/file_a.txt'), WindowsPath('_folder/fd/faa/fa_images/file_b')]
bl_folder_is_empty = len([spn for spn in Path(srn).rglob(st_file_search)])>0
print(bl_folder_is_empty)

# count files in an empty folder

## True
srn = '_folder/fd/faa/fd_images'
[spn for spn in Path(srn).rglob(st_file_search)]

## []
bl_folder_is_empty = len([spn for spn in Path(srn).rglob(st_file_search)])>0
print(bl_folder_is_empty)

## False
```

### 3.2.2.5 Search for Folder Names

- [python search for folders containing strings](#)

Search for folders with certain search word in folder name, and only keep if folder actually has files.

```
import os

# get all folder names in folder
```

```

ls_spt = os.listdir('_folder/fd/faa/')
print(ls_spt)

# Select only subfolder names containing _images

## ['fa_images', 'fb_images', 'fc_images', 'fd_images', 'fe_images', 'fz_img', 'fz_other', '_img']
srt = '_folder/fd/faa/'
st_search = '_images'
ls_srt_found = [srt + spt
                 for spt in os.listdir(srt)
                 if st_search in spt]
print(ls_srt_found)

## ['_folder/fd/faa/fa_images', '_folder/fd/faa/fb_images', '_folder/fd/faa/fc_images', '_folder/fd/

```

### 3.2.2.6 Find Non-empty Folders by Name

Search:

1. Get subfolders in folder with string in name
2. Only collect if there are files in the subfolder

```

import pathlib

# Select only subfolder names containing _images
srt = '_folder/fd/faa/'
# the folder names must contain _images
st_srt_srh = '_images'
# there must be files in the folder with this string
st_fle_srh = '*.txt'

# All folders that have String
ls_srt_found = [srt + spt
                 for spt in os.listdir(srt)
                 if st_srt_srh in spt]
print(ls_srt_found)

# All folders that have String and that are nonempty

## ['_folder/fd/faa/fa_images', '_folder/fd/faa/fb_images', '_folder/fd/faa/fc_images', '_folder/fd/
ls_srt_found = [srt + spt
                 for spt in os.listdir(srt)
                 if ((st_srt_srh in spt)
                     and
                     (len([spn for spn
                           in Path(srt + spt).rglob(st_fle_srh)])>0)) ]
print(ls_srt_found)

## ['_folder/fd/faa/fa_images', '_folder/fd/faa/fb_images', '_folder/fd/faa/fc_images']

```

### 3.2.2.7 Found Folders to new Folder

1. Search for subfolders by folder name string in a folder
2. Select nonempty subfolders
3. Move nonempty subfolders to one new folder
4. Move this single combination folder

The results here are implemented as function in the [pyfan](#) package: [fp\\_agg\\_move\\_subfiles](#).

```

import pathlib
import os
import shutil
from distutils.dir_util import copy_tree

# 1 Define Parameters

# Select only subfolder names containing _images
srt = '_folder/fd/faa/'
# the folder names must contain _images
st_srt_srh = '_images'
# there must be files in the folder with this string
st_file_srh = '*.txt'

# new aggregating folder name
srt_agg = '_img'

# folders to move aggregation files towards
ls_srt_dest = ['_folder/fd/faa/', '_folder/']

# delete source
bl_delete_source = False

# 2 Gather Folders
ls_ls_srt_found = [[srt + spt, spt]
                    for spt in os.listdir(srt)
                    if ((st_srt_srh in spt)
                        and
                        (len([spn for spn
                            in Path(srt + spt).rglob(st_file_srh)])>0)) ]
print(ls_ls_srt_found)

# 3 Loop over destination folders, loop over source folders
## [['_folder/fd/faa/fa_images', 'fa_images'], ['_folder/fd/faa/fb_images', 'fb_images'], ['_folder/
for srt in ls_srt_dest:

    # Move each folder over
    for ls_srt_found in ls_ls_srt_found:

        # Paths
        srt_source = ls_srt_found[0]
        srt_dest = os.path.join(srt, srt_agg, ls_srt_found[1])

        # dest folders
        pathlib.Path(srt_dest).mkdir(parents=True, exist_ok=True)

        # move
        copy_tree(ls_srt_found[0], srt_dest)

# 4. Delete Sources

## ['_folder/fd/faa/_img\\fa_images\\file_a.txt', '_folder/fd/faa/_img\\fa_images\\file_b.txt']
## ['_folder/fd/faa/_img\\fb_images\\file_a.txt', '_folder/fd/faa/_img\\fb_images\\file_b.txt']
## ['_folder/fd/faa/_img\\fc_images\\file_a.txt', '_folder/fd/faa/_img\\fc_images\\file_b.txt']
## ['_folder/_img\\fa_images\\file_a.txt', '_folder/_img\\fa_images\\file_b.txt']
## ['_folder/_img\\fb_images\\file_a.txt', '_folder/_img\\fb_images\\file_b.txt']
## ['_folder/_img\\fc_images\\file_a.txt', '_folder/_img\\fc_images\\file_b.txt']

```

```
if bl_delete_source:
    for ls_srt_found in ls_ls_srt_found:
        shutil.rmtree(ls_srt_found[0])
```

### 3.2.3 Parse Yaml

Go back to [fan's Python Code Examples Repository](#) ([bookdown site](#)).

Use the [PyYAML](#) to parse yaml.

#### 3.2.3.1 Write and Create a Simple YAML file

First, Yaml as a string variable:

```
# Create the Tex Text
# Note that tribble quotes begin first and end last lines
stf_tex_contents = """\
- file: matrix_matlab
  title: "One Variable Graphs and Tables"
  description: |
    Frequency table, bar chart and histogram.
    R function and lapply to generate graphs/tables for different variables.
  core:
  - package: r
    code: |
      c('word1','word2')
      function()
      for (ctr in c(1,2)) {}
  - package: dplyr
    code: |
      group_by()
  date: 2020-05-02
  output:
    pdf_document:
      pandoc_args: '../_output_kniti_pdf.yaml'
      includes:
        in_header: '../preamble.tex'
  urlcolor: blue
- file: matrix_algebra_rules
  title: "Opening a Dataset"
  titleshort: "Opening a Dataset"
  description: |
    Opening a Dataset.
  core:
  - package: r
    code: |
      setwd()
  - package: readr
    code: |
      write_csv()
  date: 2020-05-02
  date_start: 2018-12-01
- file: matrix_two
  title: "Third file"
  titleshort: "Third file"
  description: |
    Third file description."""
# Print
print(stf_tex_contents)
```

```
## - file: matrix_matlab
##   title: "One Variable Graphs and Tables"
##   description: |
##     Frequency table, bar chart and histogram.
##     R function and lapply to generate graphs/tables for different variables.
##   core:
##   - package: r
##     code: |
##       c('word1','word2')
##       function()
##       for (ctr in c(1,2)) {}
##   - package: dplyr
##     code: |
##       group_by()
##   date: 2020-05-02
##   output:
##     pdf_document:
##       pandoc_args: '../_output_kniti_pdf.yaml'
##       includes:
##         in_header: '../preamble.tex'
##   urlcolor: blue
## - file: matrix_algebra_rules
##   title: "Opening a Dataset"
##   titleshort: "Opening a Dataset"
##   description: |
##     Opening a Dataset.
##   core:
##   - package: r
##     code: |
##       setwd()
##   - package: readr
##     code: |
##       write_csv()
##   date: 2020-05-02
##   date_start: 2018-12-01
## - file: matrix_two
##   title: "Third file"
##   titleshort: "Third file"
##   description: |
##     Third file description.
```

Second, write the contents of the file to a new tex file stored inside the `*_file*` subfolder of the directory:

```
# Relative file name
srt_file_tex = "_file/"
sna_file_tex = "test_yaml_fan"
srn_file_tex = srt_file_tex + sna_file_tex + ".yaml"
# Open new file
fl_tex_contents = open(srn_file_tex, 'w')
# Write to File
fl_tex_contents.write(stf_tex_contents)
# print
```

```
## 908
```

```
fl_tex_contents.close()
```

### 3.2.3.2 Select Subset of Values by Key

Load Yaml file created prior, the output is a list of dictionaries:

```

import yaml
import pprint
# Open yaml file
fl_yaml = open(srn_file_tex)
# load yaml
ls_dict_yaml = yaml.load(fl_yaml, Loader=yaml.BaseLoader)
# type
type(ls_dict_yaml)

## <class 'list'>
type(ls_dict_yaml[0])
# display

## <class 'dict'>
pprint.pprint(ls_dict_yaml, width=1)

## [{'core': [{'code': "c('word1','word2')\n"
##           'function()\n'
##           'for '
##           '(ctr '
##           'in '
##           'c(1,2)) '
##           '{}\n',
##           'package': 'r'},
##          {'code': 'group_by()\n',
##           'package': 'dplyr'}]],
##  'date': '2020-05-02',
##  'description': 'Frequency '
##                'table, '
##                'bar '
##                'chart '
##                'and '
##                'histogram.\n'
##                'R '
##                'function '
##                'and '
##                'lapply '
##                'to '
##                'generate '
##                'graphs/tables '
##                'for '
##                'different '
##                'variables.\n',
##  'file': 'matrix_matlab',
##  'output': {'pdf_document': {'includes': {'in_header': '../preamble.tex'},
##                                'pandoc_args': '../_output_kniti_pdf.yaml'}},
##  'title': 'One '
##           'Variable '
##           'Graphs '
##           'and '
##           'Tables',
##  'urlcolor': 'blue'},
## {'core': [{'code': 'setwd()\n',
##           'package': 'r'},
##          {'code': 'write_csv()\n',
##           'package': 'readr'}]],
##  'date': '2020-05-02',

```

```
##  'date_start': '2018-12-01',
##  'description': 'Opening '
##                'a '
##                'Dataset.\n',
##  'file': 'matrix_algebra_rules',
##  'title': 'Opening '
##          'a '
##          'Dataset',
##  'titleshort': 'Opening '
##              'a '
##              'Dataset'},
## {'description': 'Third '
##               'file '
##               'description.',
##  'file': 'matrix_two',
##  'title': 'Third '
##          'file',
##  'titleshort': 'Third '
##              'file'}}
```

Select yaml information by *file* name which is a key shared by components of the list:

```
ls_str_file_ids = ['matrix_two']
ls_dict_selected = [dict_yaml for dict_yaml in ls_dict_yaml if dict_yaml['file'] in ls_str_file_ids]
pprint.pprint(ls_dc_selected, width=1)
```

```
## [{'date': datetime.date(2020, 5, 2),
##   'description': 'Frequency '
##                 'table, '
##                 'bar '
##                 'chart '
##                 'and '
##                 'histogram',
##   'file': 'mat_matlab',
##   'title': 'One '
##           'Variable '
##           'Graphs '
##           'and '
##           'Tables',
##   'val': 1}]
```

### 3.2.3.3 Dump List of Dictionary as YAML

- `py yaml dump pipe`

Given a list of dictionaries, dump values to yaml. Note that dumped output does not use pipe for long sentences, but use single quote and space line, which works with the `rmdparse.py` function without problem.

```
ls_dict_selected = [dict_yaml for dict_yaml in ls_dict_yaml
                    if dict_yaml['file'] in ['matrix_two', 'matrix_matlab']]
print(yaml.dump(ls_dict_selected))
```

```
## - core:
##   - code: 'c(''word1'', ''word2'')
##
##     function()
##
##     for (ctr in c(1,2)) {}
##
##     '
```

```
## package: r
## - code: 'group_by()'
##
##
## package: dplyr
## date: '2020-05-02'
## description: 'Frequency table, bar chart and histogram.'
##
## R function and lapply to generate graphs/tables for different variables.
##
##
## file: matrix_matlab
## output:
## pdf_document:
## includes:
## in_header: ../preamble.tex
## pandoc_args: ../_output_kniti_pdf.yaml
## title: One Variable Graphs and Tables
## urlcolor: blue
## - description: Third file description.
## file: matrix_two
## title: Third file
## titleshort: Third file
```

## 3.3 Install Python

### 3.3.1 Core Installations

Go back to [fan's Python Code Examples Repository](#) ([bookdown site](#)).

Use the [PyYAML](#) to parse yaml.

#### 3.3.1.1 Git Bash

1. Download and install [git](#)

#### 3.3.1.2 Conda Install

1. Download [Anaconda](#) for Python 3. For more involved conda instructions see [here](#)
2. Get where you installed conda: open up *anaconda prompt* with admin rights (press windows button, and search for anaconda prompt, right click on the resulting terminal icon, choose as admin, a terminal opens up).

```
where python
where anaconda
```

```
# C:/ProgramData/Anaconda3/Scripts/anaconda.exe
# C:/ProgramData/Anaconda3/python.exe
```

3. Add to Path: open up windows *Path* and copy the paths found above inside.

##### 3.3.1.2.1 Add To Path Details To Add Anaconda to Path, In Windows

1. Search for: Environment Variables
2. Edit Environment Variables
3. Add new to Path (lower half):
  - C:/ProgramData/Anaconda3/Scripts/
  - C:/ProgramData/Anaconda3/
4. Now open up regular windows command Prompt, Type in: conda -version
5. Close and Open up Git Bash: conda -version



Alternatively, in windows, directly search for Path, and add the python and anaconda exe paths to paths.



# Appendix A

## Index and Code Links

### A.1 Array, Matrix, Dataframe links

#### A.1.1 Section 1.1 Array links

1. [Python String Manipulation Examples](#): [rmd](#) | [r](#) | [pdf](#) | [html](#)
  - Various string manipulations
  - **py**: `zip()`

#### A.1.2 Section 1.2 Dictionary links

1. [Python Dictionary Exampels and Usages](#): [rmd](#) | [r](#) | [pdf](#) | [html](#)
  - List comprehension with dictionary
  - **py**: `dc = {'key': "name", 'val': 1}`

### A.2 Get Data links

#### A.2.1 Section 2.1 Environmental Data links

1. [CDS ECMWF Global Enviornmental Data Download](#): [rmd](#) | [r](#) | [pdf](#) | [html](#)
  - Using Python API get get ECMWF ERA5 data.

### A.3 System and Support links

#### A.3.1 Section 3.1 Command Line links

1. [Run Python from Command Line Examples](#): [rmd](#) | [r](#) | [pdf](#) | [html](#)
  - Run python functions from command line.
2. [Run Matlab Command Line Operations](#): [rmd](#) | [r](#) | [pdf](#) | [html](#)
  - Generate a matlab script and run the script with parameters.
  - **subprocess**: `cmd = Popen(ls_str, stdin=PIPE, stdout=PIPE, stderr=PIPE) + cmd.communicate()`
  - **decode**: `decode('utf-8')`
  - **os**: `chdir() + getcwd()`

#### A.3.2 Section 3.2 File In and Out links

1. [Python Reading and Writing to File Examples](#): [rmd](#) | [r](#) | [pdf](#) | [html](#)
  - Reading from file and replace strings in file.
  - Convert text file to latex using pandoc and clean.
  - Search for files in several folders with file substring.
  - Get path root, file name, file stem, etc from path.
  - **py**: `open() + write() + replace() + [c for b in [[1,2],[2,3]] for c in b]`

- **subprocess:** *call()*
  - **pathlib:** *Path().rglob()* + *Path().stem*
  - **os:** *remove()* + *listdir()* + *path.isfile()* + *path.splitdrive()* + *os.path.splitext()* + *os.path.split()*
2. **Python Directory and Folder Operations:** [rmd](#) | [r](#) | [pdf](#) | [html](#)
    - Generate new folders and files.
    - Generate subfolder recursively.
    - Copying and moving files across folders.
    - Aggregate subfolders into a folder and move.
    - **py:** *open(srt, 'w') + write() + close()*
    - **os:** *os.listdir()* + *os.path.join('/', 'c:', 'fa', 'fb')*
    - **pathlib:** *Path(srt).mkdir(parents=True, exist\_ok=True)* + *[Path(spn).stem for spn in Path(srt).rglob(st)]*
    - **shutil:** *shutil.copyfile('/fa/fl.txt', '/fb/fl.txt')* + *shutil.copy2('/fa/fl.txt', '/fb')* + *shutil.rmtree('/fb')*
    - **distutils:** *dir\_util.copy\_tree('/fa', '/fb')*
  3. **Python Yaml File Parsing:** [rmd](#) | [r](#) | [pdf](#) | [html](#)
    - Parse and read yaml files.
    - **yaml:** *load(fl\_yaml, Loader=yaml.BaseLoader)* + *dump()*
    - **pprint:** *pprint.pprint(ls\_dict\_yaml, width=1)*

### A.3.3 Section 3.3 Install Python links

1. **Basic Conda Setup Instructions:** [rmd](#) | [r](#) | [pdf](#) | [html](#)
  - Conda and git installations
  - **bash:** *where*

# Bibliography

- Allaire, J., Xie, Y., McPherson, J., Luraschi, J., Ushey, K., Atkins, A., Wickham, H., Cheng, J., Chang, W., and Iannone, R. (2020). *rmarkdown: Dynamic Documents for R*. R package version 2.1.
- Xie, Y. (2020). *bookdown: Authoring Books and Technical Documents with R Markdown*. R package version 0.18.