

Performance Modeling of Computer Systems and Networks

Prof. Vittoria de Nitto Personè


Performance Sensitivity to the
Service time distribution

Università degli studi di Roma Tor Vergata
Department of Civil Engineering and Computer Science Engineering

Copyright © Vittoria de Nitto Personè, 2021
<https://creativecommons.org/licenses/by-nc-nd/4.0/>



1



2

The Khinchin Pollaczek equation (KP)

$$E(N_Q) = \frac{\rho^2}{2(1-\rho)} [1 + C^2], \quad E(T_Q) = \frac{\rho}{1-\rho} \frac{C^2 + 1}{2} E(S)$$

$$C^2(S) = \frac{\sigma^2(S)}{E^2(S)}$$

Expected waiting time in an M/G/1 queue can be huge, even under very low utilization ρ , if C^2 is huge.

$$D \longrightarrow C^2 = 0$$

$$M \longrightarrow C^2 = 1$$

$$E_k \longrightarrow C^2 = \frac{1}{k}$$

$$H_2 \longrightarrow C^2 = g(p) = \frac{1}{2p(1-p)} - 1$$


Prof. Vittoria de Nitto Personè

3

3

Expected waiting time as load grows: Erlang case

$$E(S) = 0.5 \text{ s } \mu = 2 \text{ job/s}$$



$$E(S_i) = \frac{0.5}{3} = 0.166666666 \text{ s}$$

$$\sigma^2(S) = \frac{1}{k} \left(\frac{1}{\mu} \right)^2 = 0.0833333$$

Prof. Vittoria de Nitto Personè


4

4

Expected waiting time as load grows: Hyperexponential case

Analytical models
M/G/1

$$E(S)=0.5 \text{ s } \mu=2 \text{ job/s}$$



$$\sigma^2(S) = g(p) \left(\frac{1}{\mu} \right)^2 = 0.53125$$

$$g(p) = \frac{1}{2p(1-p)} - 1 = 2.125$$

Prof. Vittoria de Nitto Personè

5

5

The Khinchin Pollaczek equation (KP)

Analytical models
M/G/1

$$g(p) = \frac{1}{2p(1-p)} - 1$$


$$E(N_Q) = \frac{\rho^2}{2(1-\rho)} [1 + C^2], \quad E(T_Q) = \frac{\rho}{1-\rho} \frac{C^2 + 1}{2} E(S)$$

Service time	$E(N_Q)$	$E(T_Q)$
Deterministic, M/D/1	$\frac{\rho^2}{2(1-\rho)}$	$\frac{\rho E(S)}{2(1-\rho)}$
Markovian, M/M/1	$\frac{\rho^2}{1-\rho}$	$\frac{\rho E(S)}{1-\rho}$
K-Erlang, M/E _k /1 $\sigma^2(S) = \frac{E(S)^2}{k}$	$\frac{\rho^2}{2(1-\rho)} \left(1 + \frac{1}{k} \right)$	$\frac{\rho E(S)}{2(1-\rho)} \left(1 + \frac{1}{k} \right)$
Hyperexpo, M/H ₂ /1 $\sigma^2(S) = E(S)^2 g(p)$	$\frac{\rho^2}{2(1-\rho)} (1 + g(p))$	$\frac{\rho E(S)}{2(1-\rho)} (1 + g(p))$


Prof. Vittoria de Nitto Personè

6


6




7




8




9



10




11



12

A TP system accepts and processes a stream of transactions, mediated through a (large) buffer:




- Transactions arrive “randomly” at some specified rate
- The TP server is capable of servicing transactions at a given service *rate*

Q: If both the arrival rate and service rate are doubled, what happens to the mean response time?

Prof. Vittoria de Nitto Personè

13

13



- The arrival rate is 15tps
- The mean service time per transaction is 58.37ms

Q: What happens to the mean response time if the arrival rate increases by 10%?

Prof. Vittoria de Nitto Personè

14

14

$$E(T_Q) = \frac{\rho}{1-\rho} \frac{C^2+1}{2} E(S)$$

$$E(T_{Q'}) = \frac{\rho'}{1-\rho'} \frac{C^2+1}{2} E(S)$$

$$\frac{E(T_Q)}{E(T_{Q'})} \approx 0,27 \approx \frac{1}{3,7}$$

Prof. Vittoria de Nitto Personè

15

15

Heavy tail distributions properties

esponenziale \longrightarrow memoryless
failure rate costante

Heavy tail \longrightarrow failure rate decrescente
(Pareto: $r(x) = \alpha / x, x > 1$)

Prof. Vittoria de Nitto Personè

16

16

Where they are

Jobs Unix

Sizes files websites $\alpha \approx 1.1$

Internet topology

Packet n° IP flows 1% → 50%

Natural phenomena

Prof. Vittoria de Nitto Personè

17

17

Pareto

$$f(x) = \alpha k^\alpha x^{-\alpha-1} \quad k \leq x < \infty$$

α , parametro di forma

$$E[X] = \frac{\alpha k}{\alpha - 1} \quad \alpha > 1$$

$$\sigma^2[X] = \frac{\alpha k^2}{(\alpha - 1)^2(\alpha - 2)} \quad \alpha > 2$$

Bounded Pareto

$$f(x) = \alpha x^{-\alpha-1} \frac{k^\alpha}{1 - \left(\frac{k}{p}\right)^\alpha} \quad k \leq x \leq p, 0 < \alpha < 2$$

(Vilfredo Pareto, 15 July 1848 – 19 August 1923, economista e sociologo)

Prof. Vittoria de Nitto Personè

18

18

Pareto

$$E(T_Q) = \frac{\rho}{1-\rho} \frac{C^2 + 1}{2} E(S)$$

$$C^2(S) = \frac{\sigma^2(S)}{E^2(S)}$$

$$E[T_Q] = \frac{\rho E[S]}{1-\rho} \frac{1 + \alpha(\alpha-2)}{2\alpha(\alpha-2)}$$

$$\alpha > 2$$

Prof. Vittoria de Nitto Personè

19

19

Pareto study as load grows

$$E(S) = 0.5 \text{ s } \mu = 2 \text{ job/s}$$

$$E(T_Q)$$

ro list	$\alpha = 2,01$	$\alpha = 2,05$	$\alpha = 2,1$	$\alpha = 2,15$	determ	3-Erlang	expo	hyper
0,3	5,437633262	1,152439024	0,617346939	0,439368771	0,107	0,142	0,213	0,333
0,5	12,68781095	2,68902439	1,44047619	1,025193798	0,25	0,333	0,5	0,781
0,7	30	6,274390244	3,361111111	2,392118863	0,583	0,778	1,167	1,823
0,9	114,1902985	24,20121951	12,96428571	9,226744186	2,25	3	4,5	7,031

$$k = 0.2512$$


$$k = 0.2619$$

$$E[S] = \frac{\alpha k}{\alpha - 1} \quad \longrightarrow \quad k = \frac{\alpha - 1}{\alpha} E[S]$$


Prof. Vittoria de Nitto Personè

20

20



21



22