

System Verification and Validation Plan for 2D-RAPP

Ziyang(Ryan) Fang

April 14, 2025

Revision History

Date	Version	Notes
Feb 24	1.0	Notes

Contents

1	Symbols, Abbreviations, and Acronyms	iv
2	General Information	1
2.1	Summary	1
2.2	Objectives	2
2.3	Challenge Level and Extras	3
2.4	Relevant Documentation	3
3	Plan	3
3.1	Verification and Validation Team	3
3.2	SRS Verification Plan	4
3.3	Design Verification Plan	4
3.4	Verification and Validation Plan Verification Plan	4
3.5	Implementation Verification Plan	5
3.6	Automated Testing and Verification Tools	5
3.7	Software Validation Plan	6
4	System Tests	6
4.1	Tests for Functional Requirements	6
4.1.1	Path Planning and Obstacle Avoidance	6
4.1.2	Inverse Kinematics (IK) Solver Validation	8
4.2	Tests for Nonfunctional Requirements	10
4.2.1	Performance and Computational Efficiency	10
4.3	Traceability Between Test Cases and Requirements	11
5	Unit Test Description	11
5.1	Unit Testing Scope	11
5.2	Unit Testing Strategy	12
5.3	Tests for Functional Requirements	12
5.3.1	Collision Detection Module Tests	12
5.3.2	IK Solver Module Tests	13
5.3.3	Path Planner Module Tests	14
5.4	Tests for Nonfunctional Requirements	14
5.4.1	Performance and Computational Efficiency	14
5.5	Traceability Between Test Cases and Modules	15

6	Appendix	16
6.1	Symbolic Parameters	16

List of Tables

1	Traceability Matrix for System Tests	11
2	Traceability Matrix between Modules and Tests	15
[Remove this section if it isn't needed —SS]		

List of Figures

[Remove this section if it isn't needed —SS]

1 Symbols, Abbreviations, and Acronyms

Symbol	Description
q	Joint angle (rad)
\dot{q}	Joint angular velocity (rad/s)
\ddot{q}	Joint angular acceleration (rad/s ²)
L	Link length (mm)

This document describes the Verification and Validation (V&V) plan for our software system, which focuses on collision-free path planning for a 2D robotic manipulator in an environment with circular obstacles. The system generates a valid trajectory from a given start configuration to a goal configuration while ensuring that the robotic arm does not collide with obstacles. The verification and validation process aims to assess the correctness, efficiency, and robustness of the path-planning algorithm and collision detection mechanism. The document outlines our approach, objectives, and the tests to be performed to ensure that the system meets the specified requirements. A roadmap of the plan is as follows:

- Section 1 covers general information about the software, its purpose, and the primary V&V objectives.
- Section 2 provides details on the V&V plan, the team, and the methods and tools used.
- Section 3 describes the system-level tests for both functional and non-functional requirements.
- Section 4 focuses on unit-level testing, including scope, test coverage, and traceability to modules.

2 General Information

2.1 Summary

The software under test is a **2D Robot Arm Path-Planning System** that computes collision-free trajectories for a robotic manipulator with circular obstacles. The system:

- Discretizes the robot's joint space and represents possible configurations on a toroidal grid.
- Uses the A* algorithm to compute a valid trajectory from the start configuration to the goal configuration in joint space.
- Detects and avoids collisions by checking intersections between the robotic arm links and circular obstacles.

2.2 Objectives

The primary objective of this Verification and Validation (V&V) plan is to ensure the correctness, reliability, and efficiency of the 2D Robot Arm Path-Planning System. This system computes collision-free trajectories for a robotic manipulator navigating around circular obstacles. The specific objectives are:

- **Build confidence in software correctness:** Ensure that the planned paths are collision-free and feasible in joint space.
- **Validate the effectiveness of A* path planning:** Verify that the system correctly finds a valid trajectory between the initial and goal configurations.
- **Ensure robustness of collision detection:** Confirm that obstacle avoidance is correctly implemented and that no invalid paths are generated.
- **Assess computational efficiency:** Measure execution time and memory usage to ensure the system performs well under different obstacle configurations.

Out of Scope:

- **Usability Testing:** The system is evaluated based on correctness and performance, not user experience or interface design.
- **Real-world Hardware Validation:** The plan verifies software functionality but does not include hardware implementation or physical robot testing.
- **External Library Verification:** The system assumes that third-party numerical and optimization libraries (e.g., NumPy) are already tested by their providers.

This plan prioritizes correctness, efficiency, and collision-free navigation, acknowledging that usability and physical testing are beyond the current project scope.

2.3 Challenge Level and Extras

Challenge Level: General (per agreement with the course instructor). **Extras:**

- A brief user manual for researchers/engineers.
- Potential code walkthroughs and extended design documentation, as time and resources permit.

2.4 Relevant Documentation

- **Software Requirements Specification (SRS)** : This defines the required functionalities for the 2D robot arm path planner, including input constraints, output specifications, and performance requirements. [Ziyang \(2025\)](#)
- **Other Project Documents** (MG, MIS, etc.): These documents describe the design and detailed modules of the system. They are relevant for deriving unit tests and ensuring that design decisions align with requirements.
- **Code Reference:** An example is the A* toroidal grid code for obstacle navigation, which will be referenced or adapted for verifying path-planning correctness.

3 Plan

This section outlines the multiple stages of the verification and validation (V&V) process. First, the V&V team is introduced. Then, verification plans for the SRS, design, V&V plan, and implementation are described. Finally, automated testing and verification tools are briefly discussed.

3.1 Verification and Validation Team

The following personnel will be involved in the verification and validation of the 2D Robot Arm Path Planning system:

- **Ziyang Fang:** The author of the program. Responsible for the creation of the V&V plan, implementation of the tests, and analysis of results.

- **Dr. Spencer Smith:** The project supervisor. Responsible for reviewing the V&V plan, test cases, and overall validation of the system.
- **Alaap Grandhi:** The domain expert. Responsible for reviewing the V&V plan, ensuring scientific correctness, and verifying test coverage.

3.2 SRS Verification Plan

To ensure the SRS is complete, correct, and consistent, we will use the following verification methods:

- **Supervisor Review:** Dr. Spencer Smith will review the SRS for completeness and clarity. A structured checklist will be provided to guide feedback.
- **Domain Expert Review:** Alaap Grandhi will review the SRS to ensure technical accuracy and feasibility.
- **Issue Tracker:** Feedback from reviews will be logged as GitHub issues, and necessary modifications will be made accordingly.
- **Peer Feedback:** Classmates will provide additional feedback to identify any unclear or missing requirements.

3.3 Design Verification Plan

- **Classmate / Peer Design Review:** We will have scheduled walk-through sessions where classmates provide feedback on the design documents (MG, MIS).
- **Design Checklists:** We will ensure that each requirement in the SRS is addressed at the design level. Checklists will cover topics like modularity, clarity, and traceability to requirements.

3.4 Verification and Validation Plan Verification Plan

- **Internal Review:** The same team members will review this V&V plan for completeness and feasibility.
- **Mutation of Plan:** Introduce hypothetical changes (mutations) to test if the plan remains robust and comprehensive.

3.5 Implementation Verification Plan

- **Unit Tests:** We will write unit tests for each major component, automated by a suitable framework (e.g., `pytest` for Python).
- **Static Analysis:** Use a linter (e.g., `flake8`), possibly additional tools like `pylint` or `mypy`, to verify code standards and catch potential errors.
- **Code Walkthroughs:** During final presentations or peer sessions, we will review code segments dealing with core algorithms (IK solver, collision detection, path planning).

3.6 Automated Testing and Verification Tools

- **Continuous Integration (CI):** GitHub Actions is used to run automated test suites on every pull request and commit to ensure code reliability.
- **Unit Testing Framework:** The project uses `pytest` for unit testing, which provides powerful fixtures and easy test case management.
- **Coverage Analysis:** The tool `coverage.py` is used to measure code coverage, ensuring critical components are well-tested.
- **Static Code Analysis:** `flake8` is used to check for style violations and potential errors in Python code.
- **Type Checking:** `mypy` is used to enforce type annotations and detect type inconsistencies.
- **Performance Profiling:** `cProfile` is used for runtime performance analysis to identify bottlenecks in critical functions.
- **Memory Profiling:** `memory-profiler` helps track memory usage during execution to detect leaks and optimize performance.
- **Automated Dependency Management:** `pip-tools` is used to manage dependencies and ensure a stable development environment.

3.7 Software Validation Plan

- **Supervisor/Stakeholder Review:** If an external stakeholder is available, we will present a demo (Rev 0) to validate the requirements match real-world needs.
- **Comparison with Known Benchmarks:** Use small or known scenarios to validate the solution’s correctness against expected paths/angles.

4 System Tests

System-level tests will address functional requirements (such as collision avoidance and path planning success) and nonfunctional requirements (such as performance and accuracy). These tests will be conducted after individual modules pass unit tests to ensure the entire system functions as expected.

4.1 Tests for Functional Requirements

This section defines tests for key functional areas of the **2D Robot Arm Path Planning System**. The goal is to ensure that the system correctly computes collision-free paths and generates feasible inverse kinematics (IK) solutions using a **distance-geometric representation**.

The test cases are derived from the functional requirements specified in the [Software Requirements Specification \(SRS\)](#).

4.1.1 Path Planning and Obstacle Avoidance

This section ensures that the system can generate valid and collision-free paths from the start to the goal configuration under different environmental constraints.

Collision-Free Path Generation

1. Test ID: T1 – Basic Collision-Free Path Planning

Control: Automatic

Initial State:

- A robotic arm with n joints and defined link lengths.

- A workspace containing circular obstacles.
- An initial joint configuration and a valid goal position.

Input:

- Initial joint angles q_{init} .
- Goal position $(x_{\text{goal}}, y_{\text{goal}})$.
- Known obstacle locations and radii.

Output:

- A valid sequence of joint angles $q(t)$ ensuring obstacle avoidance.
- No intersection between the robotic arm and any obstacle.

Test Case Derivation:

- Ensures that the system correctly computes a valid path from the initial to the goal state.
- Verifies that no link in the arm collides with obstacles in the workspace.

How Test Will Be Performed:

- Run the path-planning algorithm in a predefined test environment.
- Verify that the generated path respects collision constraints.
- Compare computed paths with analytical or manually validated paths.
- Log computational time and efficiency statistics.

2. Test ID: T2 – Path Planning with Multiple Obstacles

Control: Automatic

Initial State:

- Same as T1, but with multiple circular obstacles forming narrow pathways.

Input:

- A more complex environment with multiple obstacles blocking direct paths.

Output:

- The planned trajectory successfully avoids all obstacles.
- The trajectory remains kinematically feasible.

Test Case Derivation:

- Ensures that the system can find feasible paths in more constrained environments.
- Verifies that the algorithm correctly generates alternative paths around obstacles.

How Test Will Be Performed:

- Introduce additional obstacles in varying configurations.
- Validate computed trajectories using visualization tools.

4.1.2 Inverse Kinematics (IK) Solver Validation

This section verifies that the system's inverse kinematics solver correctly computes feasible joint configurations for a given end-effector position.

Feasibility of IK Solutions

1. **Test ID: T3 – Basic IK Feasibility**

Control: Automatic

Initial State:

- A robotic arm with n joints and known link lengths.

Input:

- A reachable target position $(x_{\text{goal}}, y_{\text{goal}})$.

Output:

- A valid set of joint angles (q_1, q_2, \dots, q_n) that achieve the goal position.

Test Case Derivation:

- Ensures that inverse kinematics computations return correct and feasible joint angles.
- Verifies that the end-effector reaches the expected position.

How Test Will Be Performed:

- Compute joint angles using the distance-based graph method.
- Validate against forward kinematics results.
- Check if solutions respect joint limits and geometric constraints.

2. Test ID: T4 – IK for Complex Configurations

Control: Automatic

Initial State:

- A robotic arm with n joints and predefined joint constraints.

Input:

- A target position that may have multiple valid joint configurations.

Output:

- The solver returns multiple possible configurations.
- The solver prioritizes the most optimal (e.g., minimal joint movement).

Test Case Derivation:

- Ensures that the solver can handle redundancy in joint configurations.
- Verifies that the system can optimize movement efficiency.

How Test Will Be Performed:

- Run multiple test cases with different initial configurations.
- Compare the generated solutions and their efficiency.

4.2 Tests for Nonfunctional Requirements

4.2.1 Performance and Computational Efficiency

These tests ensure that the system computes paths within acceptable time limits and does not exceed memory constraints. **Reference: SRS Section on Accuracy and Performance.**

1. Test ID: N1

Type: Performance, Automatic

Initial State: None

Input:

- A large number of obstacles (e.g., 10+)
- Randomized goal positions

Expected Output:

- Execution time statistics
- Peak memory usage report

How Test Will Be Performed:

- Profile the system while computing paths
- Measure time-to-solution for varying complexity levels
- Compare against baseline performance requirements

2. Test ID: N2

Type: Scalability, Automatic

Initial State: None

Input:

- Increasing number of degrees of freedom (DOF) in the robotic arm (e.g., from 2-DOF to 6-DOF)

Expected Output:

- System performance degradation analysis

- Success rate of path planning for different DOF levels

How Test Will Be Performed:

- Measure computation time for different arm configurations
- Evaluate feasibility of solutions at high DOF levels

4.3 Traceability Between Test Cases and Requirements

The traceability matrix below maps test cases to the corresponding requirements from the SRS to ensure complete coverage.

Table 1: Traceability Matrix for System Tests

Requirement	Test Case(s)	Comments
FR1: Single Obstacle Avoidance	T1	Ensures safe navigation around obstacles
FR2: Multiple Obstacles	T2	Tests complex environment handling
FR3: Solve Feasible IK	T3	Verifies correct IK computations
NFR1: Accuracy	N1	Validates end-effector positioning accuracy
NFR2: Performance	N2	Ensures computational efficiency

5 Unit Test Description

Unit testing will occur once the detailed designs are finalized (see the **Module Interface Specification (MIS)**). This section outlines the general approach to module-level testing, ensuring that core functionalities perform correctly and efficiently.

5.1 Unit Testing Scope

All modules described in the **MIS** are in-scope for unit testing, except for any third-party libraries. The following modules have been identified as the highest priority:

- **Inverse Kinematics (IK) Solver** – Computes joint angles for a given target position.

- **Collision Detection Module** – Ensures that paths do not intersect obstacles.
- **Path Planner Module** – Generates valid paths based on obstacles and goal configurations.

External libraries for mathematical operations (e.g., matrix solvers) are assumed to be tested by their providers and are excluded from unit testing.

5.2 Unit Testing Strategy

The testing strategy follows a combination of:

- **Black-box testing:** Verifying correct outputs given specific inputs.
- **White-box testing:** Checking internal logic using test coverage tools.
- **Edge-case testing:** Ensuring robustness for boundary conditions.
- **Automated testing:** Using scripted tests for reproducibility via continuous integration (CI) with GitHub Actions.

Unit tests will be developed in Python, following the **pytest** framework, with assertions to check correctness.

5.3 Tests for Functional Requirements

5.3.1 Collision Detection Module Tests

1. Test ID: U1 – Basic Collision Detection

Type: Functional, Automatic

Initial State: Environment with at least one circular obstacle

Input:

- A line segment representing a robot arm link.
- An obstacle defined by center position and radius.

Expected Output:

- Boolean indicating whether a collision occurs.

Test Case Derivation:

- Ensures correct detection under different cases:
 - No collision (link does not intersect obstacle)
 - Tangential collision (link touches the obstacle's boundary)
 - Full overlap (link completely inside the obstacle)

How Test Will Be Performed:

- Simulate known geometries.
 - Compare algorithm outputs with analytical results.
-

5.3.2 IK Solver Module Tests**1. Test ID: U2 – IK Feasibility Check**

Type: Functional, Automatic

Initial State: 2-link robotic arm with fixed link lengths

Input:

- A target position in Cartesian coordinates.

Expected Output:

- A set of joint angles that place the end-effector at the target.

Test Case Derivation:

- Verifies correctness under different conditions:
 - Target reachable within workspace.
 - Target at singularity points (fully extended or folded).
 - Target unreachable (should return failure).

How Test Will Be Performed:

- Compute joint angles using the IK solver.
- Compare results against analytical solutions.
- Verify feasibility of the computed joint angles.

5.3.3 Path Planner Module Tests

1. Test ID: U3 – Path Generation in Obstacle-Free Environment

Type: Functional, Automatic

Initial State: Defined workspace with no obstacles

Input:

- Start and goal positions.

Expected Output:

- A direct path connecting start and goal.

Test Case Derivation:

- Ensures path planning works correctly when there are no obstacles.

How Test Will Be Performed:

- Run the path-planning function.
- Check whether the generated path follows a direct trajectory.

5.4 Tests for Nonfunctional Requirements

5.4.1 Performance and Computational Efficiency

1. Test ID: N1 – Performance Under Heavy Obstacle Load

Type: Performance, Automatic

Initial State:

- A workspace with no obstacles (baseline).

Input:

- A varying number of obstacles (e.g., 10, 50, 100).

Expected Output:

- A table summarizing execution time for different obstacle densities.

Test Case Derivation:

- Ensures system performs within acceptable runtime limits even in complex environments.

How Test Will Be Performed:

- Profile the system using `cProfile`.
- Measure time-to-solution for varying complexity levels.

5.5 Traceability Between Test Cases and Modules

Table 2: Traceability Matrix between Modules and Tests

Test ID	Module	Requirement Covered	Reference
U1	Collision Detection	Ensures collision-free motion	SRS Section 4.2.3, 4.2.4
U2	IK Solver	Computes valid joint angles	SRS Section 4.3.2
U3	Path Planner	Generates valid paths	SRS Section 4.3.3, 4.3.4
N1	Performance	Ensures efficient execution	SRS Section 5.1

Summary: This document outlines unit test cases for the key modules in the 2D Robot Arm Path Planning System. The testing strategy incorporates functional tests for correctness, performance tests for efficiency, and numerical tests for stability, ensuring that the system is robust and scalable.

References

Author Ziyang. Software requirements specification for 2d robot arms for path planning. <https://github.com/FangZiyang/CAS741-Ryan/blob/main/docs/SRS/SRS.pdf>, February 2025. Accessed: 2025-02-10.

6 Appendix

Any symbolic constants referenced in the test cases (like tolerances or maximum obstacle counts) can be listed here for easier maintenance.

6.1 Symbolic Parameters

The definition of the test cases will call for `SYMBOLIC_CONSTANTS`. Their values are defined in this section for easy maintenance.