# Problem Statement and Goals
# 2D Robot Arms for Path Planning

Fang

Table 1: Revision History

| Date | Developer(s) | Change |
|------|-------------|--------|
| 2025-01-20 | Ziyang Fang | Initial the document. |

# 1 Problem Statement

## 1.1 Problem

The project involves developing a framework for distance-geometric representation of 2D (planar) robot arms to facilitate path planning in environments with circular obstacles. Unlike traditional inverse kinematics (IK) methods, the proposed approach uses a geometric graph representation of the manipulator and formulates the IK problem as a distance-based graph problem. The goal is to determine the joint positions and angles along a feasible path that avoids obstacles and satisfies the goal configuration.

## 1.2 Inputs and Outputs

**Inputs:**

- Environment: Circular obstacles defined by positions (x,y) and radius.

- Robot arm: Number of joints and their respective lengths.

- Initial pose: Configuration of the robot arm at the start.

- Goal: Desired end-effector position or pose.

- Number of poses: Initial value for the number of intermediate poses along the path.

**Outputs:**

- Distance-geometric representation: Joint positions at each time step.

- Angular representation: Joint angles along the path to the goal.

## 1.3 Stakeholders

- Researchers and developers in robotics and motion planning.

- Robotics engineers working on manipulators and autonomous systems.

- End users interested in robust and scalable IK solutions.

## 1.4 Environment

**Hardware:** Simulation environment.
**Software:** Python or MATLAB-based implementation, integrating with existing libraries include GraphIK and Convex Iteration-based solvers.

# 2 Goals

- Develop a framework that generalizes to various 2D robotic manipulators.

- Ensure accurate and efficient path planning through distance-geometric representations.

- Validate the approach using benchmark problems and compare with traditional IK solvers.

# 3 Stretch Goals

- Extend the framework to include angular velocity and acceleration calculations.

- Incorporate additional obstacle types or dynamic obstacles.

- Optimize the algorithm for real-time applications.

- Extend the framework to handle 3D robot arms, enabling path planning in three-dimensional space.

- Enable real-world testing on physical robotic systems to validate the algorithm's practical applicability and performance.

- Achieve higher computational efficiency compared to existing solvers, demonstrating faster convergence and lower computational resource usage.

# 4 Challenge Level and Extras

**Challenge Level:** General.
**Rationale:**

- This is a problem with a general-level challenge.

- It requires a solid understanding of robotics kinematics, inverse kinematics solving techniques, and convex optimization theories.

- Solving this problem involves integrating these theoretical foundations into a path-planning framework for planar manipulators, with a focus on handling complex configurations and constrained environments effectively.

**Extras:**

- Provide user manual for researchers and engineers.