



Kudu+Impala 新手手册

通过该手册，你将学习到如何在 **CDH5.4.7+** 版本(集群操作系统 **CentOS6.5**)上部署 Kudu；如何在 Kudu 上集成 Impala；如何通过 Impala 创建/更新 Kudu 表。

安装 Kudu

安装 CSD 文件 (使得用户可以通过 Cloudera Manager 添加服务向导部署 Kudu)
登录部署 Cloudera Manager 的机器：

```
wgethttp://archive.cloudera.com/beta/kudu/csd/KUDU-0.5.0.jar
mv KUDU-0.5.0.jar /opt/cloudera/csd/
chowncloudera-scm:cloudera-scm /opt/cloudera/csd/KUDU-0.5.0.jar
chmod 644 /opt/cloudera/csd/KUDU-0.5.0.jar
servicecloudera-scm-server restart
```

安装 Kudu Parcel 包

Parcel 包下载地址：

<http://archive.cloudera.com/beta/kudu/parcels/latest/>

通过 Cloudera Manager 管理界面(Parcel 管理界面)下载、分发、激活 Kudu Parcel 包：

| | | | |
|------|----------------------------|------------------------|------------|
| KUDU | 0.5.0-1.kudu0.5.0.p0.223 ⓘ | Distributed, Activated | Deactivate |
|------|----------------------------|------------------------|------------|

在 Cloudera Manager 管理界面添加 Kudu 服务

1. 配置 Kudu 实例

Add Service Wizard

Customize Role Assignments

You can customize the role assignments for your new service here, but note that if assignments are made incorrectly, such as assigning too many roles to a single host, performance will suffer.

You can also view the role assignments by host. [View By Host](#)

Kudu (Beta)

M Master × 1 New

TS Tablet Server × 3 New

ip-172-31-28-144.us-west-1.compute.intern

ip-172-31-28-[145-147].us-west-1.compute.

2. 配置 Kudu 参数(主要是存储 WAL、数据的文件目录)

Add Service Wizard

Review Changes

| | | | |
|---|--|--|---|
| Kudu Master WAL Directory fs_wal_dir | Master Default Group C | <input type="text" value="/mnt/sdb/kudu/wal"/> | ? |
| Missing required value: Kudu Master WAL Directory | | | |
| Kudu Master Data Directories fs_data_dirs | Master Default Group C | <input type="text" value="/mnt/sdb/kudu/master"/> <input type="text" value="/mnt/sdc/kudu/master"/> | ? |
| Missing required value: Kudu Master Data Directories | | | |
| Kudu Tablet Server WAL Directory fs_wal_dir | Tablet Server Default Group C | <input type="text" value="/mnt/sdb/kudu/wal"/> | ? |
| Missing required value: Kudu Tablet Server WAL Directory | | | |
| Kudu Tablet Server Data Directories fs_data_dirs | Tablet Server Default Group C | <input type="text" value="/mnt/sdb/kudu/tablet"/> <input type="text" value="/mnt/sdc/kudu/tablet"/> | ? |
| Missing required value: Kudu Tablet Server Data Directories | | | |

启动 Kudu 服务

| | |
|---|----------------------------------|
| <input checked="" type="checkbox"/>  Kafka | <input type="button" value="v"/> |
| <input checked="" type="checkbox"/>  Kudu (Beta) | <input type="button" value="v"/> |
| <input checked="" type="checkbox"/>  Oozie | <input type="button" value="v"/> |

安装 Impala on Kudu

卸载原先安装的 Impala 服务(stop> Delete)

重新下载 Impala on Kudu 的 Parcel 包，下载地址：

<http://archive.cloudera.com/beta/impala-kudu/parcels/latest/>

通过 Cloudera Manager 管理界面(Parcel 管理界面)下载、分发、激活 Impala on Kudu Parcel 包：

| | | | |
|-------------|------------------------|------------------------|---|
| IMPALA_KUDU | 2.3.0-1.cdH5.5.0.p0.15 | Distributed, Activated | <input type="button" value="Deactivate"/> |
|-------------|------------------------|------------------------|---|

通过添加服务向导添加 Impala 服务，添加完毕后，修改 Impala 配置

| | | |
|---|--------------------------------------|-------------------------|
| Impala Service Environment Advanced Configuration Snippet (Safety Valve) | Impala (Service-Wide) C | Show All Descriptions ? |
| <input type="text" value="IMPALA_KUDU=1"/> | | |

重启 Impala 服务



Cloudera, Inc. 1001 Page Mill Road, Palo Alto, CA 94304

1-888-789-1488 or 1-650-362-0488

cloudera.com

©2015 Cloudera, Inc. All rights reserved. Cloudera and the Cloudera logo are trademarks or registered trademarks of Cloudera Inc. in the USA and other countries. All other trademarks are the property of their respective companies. Information is subject to change without notice.

ImpalaSQL 操作

修改 Impala-shell 二进制程序

```
alternatives --display impala-shell
impala-shell - status is auto.
link currently points to /opt/cloudera/parcels/CDH-5.4.7-1.cdh5.4.7.p0.3/bin/impala-shell
/opt/cloudera/parcels/CDH-5.4.7-1.cdh5.4.7.p0.3/bin/impala-shell - priority 10
/opt/cloudera/parcels/IMPALA_KUDU-2.3.0-1.cdh5.5.0.p0.15/bin/impala-shell - priority 5
Current `best' version is /opt/cloudera/parcels/CDH-5.4.7-1.cdh5.4.7.p0.3/bin/impala-shell.
alternatives --set impala-shell /opt/cloudera/parcels/IMPALA_KUDU-2.3.0-1.cdh5.5.0.p0.15/bin/impala-shell
alternatives --display impala-shell
impala-shell - status is manual.
link currently points to /opt/cloudera/parcels/IMPALA_KUDU-2.3.0-1.cdh5.5.0.p0.15/bin/impala-shell
/opt/cloudera/parcels/CDH-5.4.7-1.cdh5.4.7.p0.3/bin/impala-shell - priority 10
/opt/cloudera/parcels/IMPALA_KUDU-2.3.0-1.cdh5.5.0.p0.15/bin/impala-shell - priority 5
Current `best' version is /opt/cloudera/parcels/CDH-5.4.7-1.cdh5.4.7.p0.3/bin/impala-shell.
```

通过 Impala-shell 验证

```
select if (version() like '%KUDU%', "all set to go!", "check your configs");
Query: select if (version() like '%KUDU%', "all set to go!", "check your configs")
+-----+
| if(version() like '%kudu%', 'all set to go!', 'check your configs') |
+-----+
| all set to go! |
+-----+
Fetched 1 row(s) in 0.01s
```

通过 Impala 创建 Kudu 表，要求构成 Primary Key 的列必须排在前面

```
create TABLE my_first_table (
  id BIGINT,
  name STRING
)
TBLPROPERTIES(
  'storage_handler' = 'com.cloudera.kudu.hive.KuduStorageHandler',
  'kudu.table_name' = 'my_first_table',
  'kudu.master_addresses' = 'ip-172-31-28-144:7051',
  'kudu.key_columns' = 'id'
);
```

创建表后，可以通过 Kudu 管理界面进行查看

Tables

| Table Name | Table Id | State |
|----------------|----------------------------------|---------|
| my_first_table | 15a057d933824bd88b5766a2ec87fa48 | Running |

通过 insert/update/delete 语句修改 Kudu 表

```
insert into my_first_table values (1, 'alex');
Query: insert into my_first_table values (1, 'alex')
Inserted 1 row(s) in 0.46s
insert into my_first_table values (2, 'dol');
Query: insert into my_first_table values (2, 'dol')
Inserted 1 row(s) in 0.11s
insert into my_first_table values (3, 'tonny');
Query: insert into my_first_table values (3, 'cheng')
Inserted 1 row(s) in 0.11s
select * from my_first_table;
Query: select * from my_first_table
+----+-----+
| id | name |
+----+-----+
| 2 | dol |
| 3 | cheng |
| 1 | alex |
+----+-----+
Fetched 3 row(s) in 0.67s

delete from my_first_table where id = 3;
Query: delete from my_first_table where id = 3
Fetched 0 row(s) in 0.15s
select * from my_first_table;
Query: select * from my_first_table
+----+-----+
| id | name |
+----+-----+
| 2 | dol |
| 1 | alex |
+----+-----+
Fetched 2 row(s) in 0.13s
```

```
update my_first_table set name = 'ding' where id = 1;
Query: update my_first_table set name = 'ding' where id = 1
Fetched 0 row(s) in 0.13s
select * from my_first_table;
Query: select * from my_first_table
+----+-----+
| id | name |
+----+-----+
| 1  | ding |
| 2  | dol  |
+----+-----+
Fetched 2 row(s) in 0.13s
```

Enjoy Kudu+Impala !

更多内容: <http://www.cloudera.com/content/www/en-us/documentation/betas/kudu/0-5-0/topics/kudu.html>