Advanced Markerless Human Pose Estimation for Clinical Gait Pathologies: A Comprehensive Analysis of Neuromuscular Diagnostics, Spinal Screening Frameworks, and Open-Source Ecosystems

The Paradigm Shift in Clinical Biomechanics and Kinematic Analysis

The clinical assessment of human locomotion, postural alignment, and neuromuscular integrity has historically relied on highly specialized, resource-intensive methodologies. Traditional three-dimensional motion capture (MoCap) systems, such as the optoelectronic Vicon system, integrated with force plates, electromyography, and instrumented pressure-sensing mats, have long represented the gold standard for clinical gait analysis (CGA).[1] These deterministic systems provide sub-millimeter accuracy in capturing spatiotemporal parameters and joint kinematics. However, they present profound logistical and socioeconomic barriers: they necessitate dedicated laboratory space, prohibitively expensive hardware, specialized technical personnel, and cooperative subjects willing to wear physical retroreflective markers or inertial measurement units (IMUs).[1] These constraints severely restrict the accessibility of longitudinal kinematic tracking and are particularly detrimental when diagnosing and monitoring pediatric populations, individuals with neurodevelopmental disorders, and patients suffering from progressive neuromuscular diseases.[1]

The advent of deep learning-driven human pose estimation (HPE) has catalyzed a fundamental paradigm shift in clinical biomechanics. By leveraging advanced convolutional neural networks (CNNs), vision transformers, and recurrent architectures to extract multidimensional skeletal keypoints from standard two-dimensional RGB video, markerless pose estimation democratizes access to high-fidelity kinematic data.[5] This technological transition enables the continuous, non-invasive quantification of gait pathologies and spinal deformities in naturalistic environments, utilizing ubiquitous consumer-grade recording devices such as smartphones and clinical tablets.[1]

The intersection of artificial intelligence and clinical orthopedics has recently yielded breakthrough computational frameworks specifically tailored for complex, progressive

conditions such as Duchenne Muscular Dystrophy (DMD), early-onset and adolescent idiopathic scoliosis (AIS), and neurodevelopmental motor delays in toddlers. The deployment of hybrid neural architectures, dual-representation clinical priors, and meticulously documented open-source analytical pipelines has demonstrated diagnostic accuracies that rival, and occasionally surpass, traditional clinical observation.[6] The capacity to perform markerless CGA translates to profound second-order implications: it facilitates early intervention, enables the quantification of micro-progression in neurodegenerative diseases, and provides a scalable mechanism for global clinical screening.[5]

This report exhaustively details the latest advancements in this domain, dissecting the foundational biomechanical research, the underlying mathematical and algorithmic mechanics, and the critical open-source ecosystems that facilitate the implementation of these transformative technologies.

Deep Learning Frameworks for the Quantification of Duchenne Muscular Dystrophy

Duchenne Muscular Dystrophy (DMD) is a severe, progressive, X-linked recessive neuromuscular disorder characterized by the absence of functional dystrophin, a protein critical for maintaining the structural integrity of muscle fibers.[12] The absence of dystrophin leads to catastrophic muscle degeneration, enzyme-induced breakdown, and ultimately, profound muscular weakness.[12] Because the disease is relentlessly progressive, the clinical manifestation of DMD is marked by highly specific, sequential alterations in locomotor biomechanics that unfold throughout early childhood and adolescence.

The Biomechanical Progression of DMD

The symptomatic progression of DMD can be distinctly mapped through observable kinematic deviations. In the early ambulatory stages (typically between ages three and five), patients frequently exhibit the Gowers' sign.[9] This clinical heuristic describes a maneuver where the patient, due to profound proximal weakness in the pelvic girdle and lower extremities, must utilize their upper extremities to "climb up" their own thighs to achieve a standing posture.[9]

As the disease advances toward the late ambulatory stage (ages six to nine), the patient develops a pronounced myopathic or "waddling" gait, clinically referred to as the Trendelenburg sign.[9] This specific pathology results from bilateral weakness in the hip abductor muscles, primarily the gluteus medius. During a normal gait cycle, the gluteus medius stabilizes the pelvis during the single-leg stance phase. In DMD, this stabilization fails, causing the pelvis to drop on the swing side.[13] To compensate and prevent falling, the patient executes an exaggerated lateral shift of their trunk over the stance leg, producing the characteristic wide-based waddling motion.[13]

Concurrently, progressive shortening and contracture of the Achilles tendon precipitate an equinus deformity.[9] This obligates the patient to abandon the normal heel-strike initiation of the gait cycle, adopting instead a forced "toe-walking" strike pattern.[9] By age ten to twelve, ambulation typically ceases entirely, and by age fourteen, the asymmetrical muscular degradation routinely induces severe secondary spinal deformities, with scoliosis occurring in approximately 90% of boys with DMD.[9]

Spatiotemporal and Kinematic Feature Extraction via HPE

Recent investigations have successfully translated these observable clinical heuristics into quantifiable mathematical matrices utilizing advanced markerless pose estimation. Research published in *Bioinformatics and Biology Insights* (2024) introduces a highly effective, cost-efficient spatiotemporal feature-analysis model designed specifically to extract clinical gait features from raw RGB video sequences and automatically classify pathological DMD gait.[5]

The methodology relies on the robust integration of 2D and 3D HPE frameworks. The researchers prominently utilized OpenPose, an established bottom-up real-time pose estimator, to extract the 2D planar coordinates of 25 distinct anatomical keypoints corresponding to the full human body.[5] For each frame of the input video, the system generates a 25-dimensional time series of keypoint matrices.[5] To extract precise sagittal joint kinematics, models like MediaPipe's BlazePose GHUM Heavy architecture are frequently employed, as they yield 33 anatomical landmarks optimized for real-time mobile perception pipelines.[18]

Furthermore, to resolve the inherent depth ambiguity of monocular video, the analytical pipeline incorporates advanced 3D lifting algorithms such as MeTRAbs (Metric-Scale Truncation-Robust Heatmaps).[5] Standard 2.5D volumetric heatmaps suffer from scale ambiguity and require external post-processing to resolve absolute metric depth.[21] MeTRAbs circumvents this by autoregressively recovering both root translation and body pose, yielding absolute 3D joint coordinates that provide objective, quantitative information regarding anatomical joint angles, mitigating errors induced by self-occlusion or complex limb articulation.[5]

By processing raw video data through these parallel estimators, researchers abstract critical time-distance variables, including overall gait speed, stride time, step length, and cadence.[5] Simultaneously, the system computes complex biomechanical parameters, specifically the sagittal flexion angles of the hip, knee, and ankle.[5]

Signal Processing and the LSTM-CNN Hybrid Architecture

Raw coordinate data derived from deep learning bounding boxes inherently contains high-frequency jitter and missing frames due to transient occlusions. To resolve this, the extracted kinematic sequences are subjected to rigorous signal processing. The standard

protocol involves an initial gap-filling interpolation, followed by the application of a 10th-order Butterworth low-pass filter (typically utilizing a normalized cut-off frequency of 0.1752).[2] This mathematical smoothing isolates the true, continuous kinematic signal, allowing for the accurate calculation of relative distance changes, joint angular velocities, and structural deviations.[2]

To accurately classify these refined kinematic sequences, the 2024 study deployed a highly sophisticated hybrid neural network architecture combining Convolutional Neural Networks (CNN) with Long Short-Term Memory (LSTM) recurrent networks.[5]

The CNN layers operate on the spatial dimensions of the tracked keypoints.[5] In the context of DMD, the CNN functions as a structural anomaly detector. It is mathematically optimized to identify the spatial deformations inherent to the waddling gait pattern—such as the atypical vertical discrepancy between the left and right hip keypoints (pelvic drop) and the pathological mediolateral shifts of the thorax keypoints relative to the root center of mass.[5]

Conversely, the LSTM layers process the temporal evolution of these spatial features across successive video frames.[5] The LSTM gates are designed to capture dynamic temporal anomalies that a static spatial analysis would miss. This includes the prolonged double-support phases characteristic of unstable ambulation, highly asymmetrical swing times, and the rhythmic irregularities associated with the equinus toe-walking foot-strike.[2]

The empirical results of this hybrid spatiotemporal approach are highly significant. The model demonstrated an exceptional prediction accuracy of 97% utilizing the deep network, and 96.2% when utilizing a Support Vector Machine (SVM) classifier with Radial Basis Functions (RBF) when tasked with distinguishing between typically developing (TD) children and those diagnosed with DMD.[5]

Model Architecture / Classifier	**Feature Extraction Focus**	**Prediction Accuracy (TD vs. DMD)**
LSTM-CNN Hybrid Network	Spatiotemporal (Sequential joint arrays)	**97.0%**
Support Vector Machine (SVM)	Engineered Kinematic Features	**96.2%**

While the current iteration of the algorithm successfully distinguishes healthy subjects from

those with DMD, future refinements aim to enable precise multi-class differentiation between DMD and other distinct neuromuscular impairments.[23]

The second-order implications of this classification capability are immense. The capacity to continuously quantify subtle kinematic precursors—such as minor increases in the mediolateral component of total power or sub-clinical reductions in step length—allows for the initiation of disease-modifying therapies, such as corticosteroids, much earlier in the disease trajectory.[22] Furthermore, because the methodology is fully automated and relies solely on ubiquitous RGB video, it completely eliminates the need for expensive laboratory equipment, calibration, or manual intervention, dramatically reducing the socioeconomic barriers to expert-level neurological screening.[5]

Validation of Markerless Kinematics in Early Neurodevelopmental Delays

The successful translation of markerless human pose estimation from controlled, adult-centric laboratory environments to pediatric clinical settings requires rigorous validation against established biomechanical baselines. The onset of locomotion is a critical motor milestone; toddlers presenting with neurodevelopmental disorders (NDDs), including Autism Spectrum Disorder (ASD), Tuberous Sclerosis Complex (TSC), and global developmental delays, frequently exhibit highly atypical motor development.[1]

These early-stage motor abnormalities often serve as the primary observable phenotype preceding cognitive or linguistic delays, making gait analysis a vital early screening tool. However, accurately assessing this demographic utilizing conventional 3D MoCap or wearable sensors presents an intractable clinical challenge. Toddlers with profound sensory sensitivities, tactile defensiveness, or severe behavioral non-compliance frequently reject the attachment of physical retroreflective markers or wearable IMUs.[1] Furthermore, their erratic, non-linear walking patterns often disrupt the standardized protocols required by stationary pressure mats.[1]

Feasibility and Accuracy in Diverse Pediatric Populations

A landmark 2025 study published in *Frontiers in Digital Health* addresses this precise diagnostic void by exhaustively validating markerless video-based gait analysis utilizing pose estimation in a large pediatric cohort.[1] The research assessed the feasibility and accuracy of OpenPose-derived kinematic outputs in 112 toddlers, explicitly representing a wide spectrum of developmental levels.[1]

The demographic composition of the study was highly diverse, with a mean participant age of 30 months (standard deviation of 8 months).[5] The diagnostic breakdown included 77 children with Autism, 13 with Tuberous Sclerosis Complex, 15 typically developing (TD) children, 6 with

non-autism developmental concerns, and 1 child with a 22q Deletion.[5] Cognitive and motor baselines were established using the Mullen Scales of Early Learning, yielding early learning composite scores ranging from 49 to 95.[5]

Diagnostic Category	Participant Count (n)	Percentage of Cohort
Autism Spectrum Disorder (ASD)	77	68.8%
Typically Developing (TD)	15	13.4%
Tuberous Sclerosis Complex (TSC)	13	11.6%
Other NDDs (Developmental Concerns, 22q)	7	6.2%
Total Cohort	**112**	**100.0%**

The methodological validation involved the simultaneous capture of locomotion using a gold-standard instrumented pressure-sensing mat (the ProtoKinetics Zeno Walkway) and concurrent frontal and sagittal video recordings.[5] The raw video streams were processed through OpenPose to execute markerless pose estimation, extracting the continuous 2D coordinates of the toddlers' lower limbs.[5]

To translate these raw coordinate arrays into clinically meaningful data, the researchers utilized a customized MATLAB analytical workflow. This workflow systematically computed average spatiotemporal gait parameters, specifically targeting velocity, step length, and step time.[24] The statistical validation, executed via rigorous Pearson correlations and Bland-Altman analysis (difference versus average plots), confirmed exceptional agreement between the markerless methodologies and the physical pressure mat.[24]

The findings provide the first empirical evidence that highly valid kinematic results can be obtained from the very initial onset of gait using only deep learning computer vision.[24] The research proves that markerless methods are not merely a cost-effective alternative, but rather the *ideal* modality for pediatric populations with NDDs, ensuring high-fidelity data collection without physical intervention.[1]

The Roemmich-Stenum Clinical Workflow

The architectural foundation driving this pediatric validation relies heavily on an open-source clinical pipeline initially engineered by researchers Jan Stenum and Ryan T. Roemmich. Originally developed to assess adult pathological gaits—such as the short, shuffling steps indicative of Parkinson's disease and the asymmetrical circumduction seen in post-stroke hemiparesis—the workflow was designed to universally democratize access to quantitative movement assessment.[25]

The Stenum-Roemmich workflow is a masterclass in algorithmic accessibility. It seamlessly interfaces standard smartphone or tablet camera outputs with cloud-hosted OpenPose instances via Google Colaboratory Jupyter Notebooks (OpenPose_JS.ipynb).[28] This elegant architecture completely bypasses the requirement for clinics to invest in local, high-performance Graphical Processing Unit (GPU) clusters, which are typically mandatory for running complex CNN perception frameworks.[28]

The downstream coordinate data is funneled into automated, highly optimized MATLAB scripts (gait.py, findframe.py, summarizegaitcsv.py) that systematically calculate critical gait events, isolate heel-strikes and toe-offs, and aggregate complex spatiotemporal symmetries (e.g., step length asymmetry calculated as $[paretic - nonparetic]/[paretic + nonparetic]$).[28]

The successful deployment of this adult-centric pipeline onto a toddler cohort reveals a profound third-order insight: robust pose estimation algorithms, despite being trained predominantly on massive datasets of adult skeletal proportions (like COCO or MPII), possess the intrinsic capacity to generalize effectively to the unique biomechanical constraints, higher cadences, and distinct morphological ratios of early childhood ambulation.[1] This establishes a new clinical operational standard wherein repeated, longitudinal kinematic measurements can be harvested seamlessly from naturalistic home environments, generating dense, multi-variate developmental trajectories rather than isolated, stress-induced clinical snapshots.[24]

Early-Onset Scoliosis and the Dual Representation Framework

Adolescent Idiopathic Scoliosis (AIS) is a highly complex, three-dimensional spinal deformity that manifests primarily during the rapid growth phases of late childhood and early adolescence, affecting approximately 3.1% of the pediatric population globally.[6] The pathology

involves lateral curvature of the spine, frequently accompanied by axial vertebral rotation and sagittal plane abnormalities.[31] If unmanaged, progressive curvature can result in severe cardiopulmonary compromise, chronic back pain, massive biomechanical asymmetry, and a profoundly diminished quality of life.[31]

The standard clinical diagnostic protocol relies entirely on the Cobb angle measurement, an angular geometric heuristic derived from full-spine, standing radiography (X-rays).[32] However, scoliosis requires continuous longitudinal monitoring to track curve progression. The cumulative radiation exposure inherent in this periodic radiographic surveillance poses substantial, documented long-term oncological risks to the developing pediatric patient.[32] Traditional non-invasive physical alternatives, such as the Adam's Forward Bend Test evaluated with a mechanical scoliometer, suffer from exceptionally high inter-rater variability and highly subjective clinical interpretation.[10]

To circumvent these critical limitations, recent state-of-the-art developments in medical computer vision have introduced entirely non-invasive, video-based scoliosis screening algorithms that utilize natural walking gait as a primary, quantifiable diagnostic biomarker.[33]

The Limitations of Silhouette Extraction and Raw Coordinates

Early artificial intelligence approaches to automated scoliosis detection relied heavily on massive-scale silhouette datasets or static back topography imaging.[10] While these methods provided a degree of diagnostic utility, they suffered from fundamental architectural flaws. Binary silhouettes frequently occlude the internal geometric structure of the patient, masking the subtle, localized, and clinically vital skeletal asymmetries that denote early-stage spinal curvature.[35]

Conversely, raw pose estimation data provides a highly intuitive, explicit mathematical representation of the underlying skeletal structure.[31] However, attempting to classify scoliosis using only raw pose coordinates presents significant algorithmic hurdles. The outputs of pose estimators are inherently discrete point arrays that are highly susceptible to high-frequency temporal noise, depth ambiguity, and localization jitter.[31] This noise floor severely hinders the neural network's ability to confidently model the incredibly subtle structural asymmetries indicative of borderline AIS.[31]

The Dual Representation Framework (DRF)

A seminal contribution resolving this dichotomy is the Dual Representation Framework (DRF), introduced prominently at the Medical Image Computing and Computer-Assisted Intervention (MICCAI) conferences (2024/2025).[6] Engineered by the Shiqi Yu Group, the DRF resolves the limitations of raw keypoints by engineering a synergistic neural architecture that explicitly leverages two distinct, parallel mathematical representations of the patient's biomechanics [31]:

1. **Continuous Skeleton Maps:** To overcome the noise-sensitive nature of discrete

coordinates, the algorithm projects the raw keypoint arrays into continuous, Gaussian-based heatmaps.[36] This transformation generates a robust, global spatial structure of the walking subject. The continuous nature of the heatmap makes the feature encoder highly resilient to isolated keypoint tracking failures, limb articulation noise, or the self-occlusion that inevitably occurs during the arm-swing phase of the natural gait cycle.[36]

2. **Postural Asymmetry Vectors (PAV):** Recognizing that deep learning models benefit immensely from domain-specific knowledge, the researchers translated traditional orthopedic diagnostic heuristics into a programmable, mathematical construct known as the PAV.[6] The PAV is an explicit, clinically inspired discrete metric designed to capture the specific, localized bilateral deformities that are pathognomonic of AIS. It calculates precise geometric matrices, including vertical deviations (e.g., asymmetrical pelvic tilt or unlevel shoulders), midline deviations (e.g., the lateral translation of the C7 vertebra relative to the central sacral vertical line), and complex angular discrepancies across the coronal and sagittal planes.[36]

The PAV-Guided Attention (PGA) Module

To seamlessly integrate these continuous and discrete data streams, the DRF architecture employs a groundbreaking proprietary mechanism: the PAV-Guided Attention (PGA) module.[6]

Standard self-attention mechanisms in deep learning (such as those used in Vision Transformers) map relationships across an entire feature space relatively blindly, relying purely on data-driven statistical correlations that may inadvertently over-index on irrelevant background artifacts or non-pathological gait variations.[6] The PGA module functions in direct opposition to this black-box paradigm. It injects the discrete PAV matrix directly into the neural network's feature learning process, acting as an immutable *clinical prior*.[6]

By utilizing the PAV vector to generate precise channel-wise (w_c) and spatial-wise (w_s) attention weights, the network is algorithmically forced to scrutinize the specific regions of the continuous Gaussian skeleton map that exhibit the highest clinical probability of structural deformity.[6] This clinical guidance mechanism essentially programs the neural network to "look" at the patient precisely as a trained orthopedic spine surgeon would—focusing intensely on shoulder elevation discrepancies, scapular winging, and pelvic unleveling.[6]

The empirical results of integrating this clinical prior are exceptional. The DRF model achieved state-of-the-art performance, significantly outperforming prior baseline skeletal models (such as ScoNet-MT). Specifically, the DRF increased overall classification accuracy by 3.5% and improved the F1-score by 4.2%.[6] Furthermore, the architecture fundamentally enhances diagnostic interpretability; the attention heatmaps generated by the PGA module provide a visual, explainable output that aligns perfectly with human clinical reasoning, bridging the trust

gap between artificial intelligence and the medical establishment.[6]

Model Guidance Source	Total Accuracy (%)	Macro-Average (%)
Random Initialization	69.4	84.2
Learnable Data-Driven Attention	75.4	84.1
All-Ones (No Attention)	82.2	80.8
PAV Clinical Prior (Proposed DRF)	**86.0**	**84.1**

The Scoliosis1K Benchmark Dataset

The extraordinary empirical success of the DRF is intrinsically linked to the concurrent release of the *Scoliosis1K* and *Scoliosis1K-Pose* datasets.[6] Serving as the first massive-scale benchmark specifically engineered for video-based spinal classification, Scoliosis1K encompasses 1,493 natural walking video sequences, yielding over 447,900 expertly annotated frames of 2D keypoints from 1,050 distinct adolescents.[38]

The dataset was collected during a real-world, school-based screening program, ensuring high ecological validity.[38] Crucially, the dataset provides expert-level diagnostic labels categorized into three clinical tiers: positive (scoliosis), neutral (borderline), or negative (non-scoliosis), all confirmed through standardized, on-site evaluations by medical professionals following rigorous screening protocols.[38]

To address stringent patient privacy concerns and Health Insurance Portability and Accountability Act (HIPAA) compliance mandates, the dataset distributes data purely in the form of derived silhouettes and 2D/3D pose representations.[38] By explicitly stripping away raw RGB footage, facial geometry, and potentially identifiable environmental markers before publication, the Scoliosis1K initiative establishes an ethical gold standard for the secure distribution of highly sensitive medical biomechanical data to the global research community.[38]

Exhaustive Directory of Open-Source Repositories and Clinical Ecosystems

The rapid maturation and clinical deployment of markerless kinematic analysis is not occurring in a vacuum; it is fueled by an aggressively collaborative, open-source software engineering community. The immediate availability of shared architectural codebases, pre-trained neural network weights, custom signal-processing libraries, and massive-scale pathological datasets is the primary catalyst driving the integration of these AI tools into global medical practice.

To facilitate profound technical research, rapid implementation, and algorithmic replication, the following structured directory exhaustively details the critical open-source links, libraries, and repositories referenced across the vanguard of clinical pose-estimation literature. This ecosystem spans the entire computational pipeline: from foundational dataset acquisition and low-level coordinate extraction to high-level clinical inference and graphical user interfaces.

Foundational Datasets and Global Frameworks

Repository / Resource Name	Primary URL(s)	Description, Clinical Utility, & Architectural Details
Scoliosis1K Project & DRF Architecture	https://zhouzi180.github.io/Scoliosis1K/ https://arxiv.org/abs/2509.00872	The official nexus for the Scoliosis1K dataset and the Dual Representation Framework (DRF). This repository contains the strict application protocols and Data Use Agreements required to securely download the 447,000-frame adolescent pose dataset (via authenticated Google Drive or BaiduYun links). Crucially, it houses the explicit Python and PyTorch implementations for the Postural Asymmetry Vectors (PAV) and the PAV-Guided Attention (PGA) modules used for

		non-invasive scoliosis screening.[6]
OpenGait Research Framework	https://github.com/ShiqiYu/OpenGait	Maintained by the Shiqi Yu Group, OpenGait is a remarkably comprehensive, flexible, and extensible gait analysis benchmark. It serves as the primary hosting infrastructure for the ScoNet and ScoNet-MT scoliosis classification algorithms. Beyond spinal analysis, the repository aggregates highly advanced, state-of-the-art multi-modal models including LidarGait++ (for 3D point cloud analysis), BiggerGait, DeepGaitV2, and the transformer-based SwinGait. With over 650 stars, it is an indispensable asset for researchers requiring robust baseline models for human locomotion.[39]
Gait Abnormality Video Dataset (GAVD)	https://github.com/Rahmyyy/GAVD	An expansive clinical computer vision dataset comprising 1,874 video sequences explicitly annotated for normal, abnormal, and pathological gait patterns. Developed by researchers at CSIRO Data61, the repository provides crucial metadata and URL links for analyzing real-world locomotor dysfunction across unconstrained clinical and

		urban environments. It is specifically optimized for training temporal action recognition networks, including Temporal Segment Networks (TSN) and SlowFast architectures.[41]

Clinical Analytical Workflows and Signal Processing Libraries

Repository / Resource Name	Primary URL(s)	Description, Clinical Utility, & Architectural Details
Roemmich-Stenum Clinical Workflow	https://github.com/janstenum/GaitAnalysis-PoseEstimation	The precise, highly validated repository utilized in the 2025 *Frontiers in Digital Health* toddler gait study. It provides an accessible, end-to-end operational pipeline. The repository features OpenPose_JS.ipynb for executing cloud-based extraction via Google Colab, paired with sophisticated custom MATLAB algorithms (gait.py, summarizegaitcsv.py) engineered to systematically filter JSON coordinate outputs and calculate vital clinical spatiotemporal parameters (step length, cadence, stance phases, and asymmetry ratios).[26]
PosePipe Movement	https://github.com/peabody	A modular, highly

Analysis	124/posepipeline	structured pipeline designed explicitly for clinical movement research. It effectively wraps numerous state-of-the-art HPE algorithms into a unified architecture. It supports absolute 3D metric-scale estimators like **MeTRAbs**, and top-down 2D detectors like RTMPose and ViTPose via the OpenMMLab ecosystem. Uniquely, it utilizes DataJoint to enforce strict relational database management, ensuring data integrity across large cohorts of video inputs and kinematic outputs.[45]
GaitPy (Accelerometer Kinematics)	https://github.com/DART-Lab-LLUI/python-gaitalytics https://pypi.org/project/gaitalytics/	An open-source Python package explicitly designed for deriving high-level temporal and spatial gait features from wearable accelerometer data (typically positioned on the lower lumbar spine). While its primary input modality is IMUs rather than video, it provides exceptional, highly optimized underlying mathematical models for bout detection, signal processing, and feature extraction that directly parallel markerless video analysis pipelines.[46]
GaitAnalysisToolKit	https://pypi.org/project/GaitAnalysisToolKit/	Developed by the Human Motion and Control Lab at

		Cleveland State University, this highly modular collection of tools facilitates deep biomechanical analysis. It features independent Octave routines and Python modules (controlid.py, motek.py). Crucially, it includes implementations for complex operations such as 2D inverse dynamics (computing joint angles and moments of a lower body model) and inertial compensation for force plate integration.[49]
KumarLabJax Gait Analysis	https://github.com/KumarLabJax/gaitanalysis	A targeted Python library developed specifically for the structural modeling, statistical summarization, and visual inference of kinematic walking cycles. It houses vital operational scripts (gaitmodeling.py, gaitinference.py, vidplot.py) that facilitate the rapid translation of raw coordinate arrays into interpretable clinical visualizations.[50]

Specialized Tools, Explainable AI, and Active Deployment Systems

Repository / Resource Name	Primary URL(s)	Description, Clinical Utility, & Architectural Details
Explainable AI for Clinical Gait	https://github.com/sebastian-lapuschkin/explaining-de	A repository exclusively focused on solving the

	ep-clinical-gait-classificatio n	"black box" problem of algorithmic transparency in biomechanics. It implements Layer-wise Relevance Propagation (LRP) to explicitly expose and visualize the specific kinematic features a deep learning model leverages when classifying pathological gait. This ensures that neural networks are learning actual biomechanical deformities (e.g., knee hyperextension) rather than exploiting spurious background artifacts in the training data.[51]
Pose-Editor (Coordinate GUI)	https://github.com/JeffZC/p ose-editor	A dedicated Graphical User Interface (GUI) engineered in Python to manually visualize, edit, refine, and correct human pose keypoint coordinates generated by underlying algorithms like OpenPose. This tool is absolutely critical for researchers attempting to create highly accurate ground-truth datasets or manually fix severe tracking errors induced by complex limb occlusions in pathological patients.[52]
S0ma0000 Gait Analysis Suite	https://github.com/s0ma00 00/gait-analysis	A highly visual Python-based analytical suite providing deep visualization tools for

		clinical kinematics. It features 3D spatial mapping arrays, generates sophisticated angular heatmaps of joint movements over time, and includes specific analytical modules (knee_angle_analysis.py) tailored for isolating individual biomechanical components during specific phases of the gait cycle.[54]
OpenPose for 2D Gait Analysis	https://github.com/batking24/OpenPose-for-2D-Gait-Analysis	A targeted, low-cost clinical repository applying the OpenPose architecture specifically for the identification of knee flexion landmarks. It excels at rapidly plotting points of foot contact and mathematically mapping derived clinical gait angles against standard normative data ranges.[55]
Pose Estimation for Gait Analysis (PEGA)	https://github.com/austineaero/pose-estimation	An end-to-end, near-real-time system designed for active deployment. PEGA integrates AlphaPose, YOLO person detection, and a CNN classifier to analyze live CCTV streams. Originally engineered to detect passengers requiring mobility assistance in airport terminals, this repository highlights the successful transition of clinical gait

		models into active, operational public safety and logistics environments.[56]
PD Motor Severity Estimation	https://github.com/mlu355/PD-Motor-Severity-Estimation	A benchmark clinical codebase focused exclusively on evaluating Parkinson's Disease (PD) gait severity. It utilizes computer-assisted pose tracking to non-intrusively map a patient's movement kinematics directly to the standardized MDS-UPDRS (Movement Disorder Society-Unified Parkinson's Disease Rating Scale) clinical metric, providing an objective biomarker for disease progression.[10]

Biomechanical Interpretability and Advanced Algorithmic Modeling

The utility of these expansive open-source tools extends far beyond simple coordinate mapping; they are designed to execute highly complex geometric and temporal operations to transform raw Cartesian pixel data into interpretable, standardized clinical markers. A deep understanding of the pathophysiology being modeled is essential for optimizing the underlying machine learning algorithms.

Algorithmic Quantification of the Trendelenburg and Waddling Gait

In healthy human locomotion, the hip abductor muscles act synergistically during the single-leg stance phase to stabilize the pelvis, strictly preventing it from dropping toward the unsupported swing leg. In severe myopathies such as Duchenne Muscular Dystrophy, profound gluteal weakness leads to catastrophic mechanical failure of this leverage system.[13] When the patient lifts one leg, the pelvis immediately drops contralaterally—the classic clinical manifestation of the Trendelenburg sign. To maintain their center of gravity within the base of support and prevent an outright fall, the patient must execute a massive compensatory lurch, violently throwing their trunk over the weakened stance leg. The bilateral presentation of this sequential compensation generates the characteristic "waddling" gait.[13]

Computer vision algorithms process this complex pathology by continuously calculating the geometric angle of the pelvic line (derived from the left and right hip keypoints, such as indices 8 and 9 in OpenPose) relative to the true horizontal plane. Advanced frameworks, such as the Dual Representation Framework, capture this explicitly via their Postural Asymmetry Vectors, identifying the absolute vertical height discrepancy between the iliac crests across the temporal axis of the gait cycle.[36] Additionally, calculating the mediolateral shift of the thorax or neck keypoints relative to the root pelvic keypoint provides a direct geometric quantification of the magnitude of the trunk compensation, serving as a highly sensitive proxy for progressive abductor weakness.[22]

Modeling Toe-Walking and the Equinus Deformity

Idiopathic toe-walking, or the equinus deformity resulting from the severe Achilles tendon contractures highly prevalent in advanced DMD, drastically alters the fundamental biomechanics of the foot-strike.[9] Normal gait initiates with a distinct, controlled heel-strike, followed by a smooth progression through mid-stance to terminal plantarflexion (toe-off).[17] Toe-walking entirely reverses or eliminates this phase, initiating ground contact exclusively with the forefoot. This results in highly aberrant ankle kinematics, a drastically reduced stride length, and severely compromised shock absorption capabilities.[17]

Open-source repositories tackle the quantification of this deformity by tracking the precise vector paths of the ankle, heel, and foot-index keypoints (e.g., OpenPose joints 11, 21, and 22 or MediaPipe keypoints 27 through 32).[9] By continuously monitoring the vertical trajectory of the heel keypoint relative to the toe index exclusively during the stance phase, algorithms can accurately determine the total absence of a heel-strike.[2] More advanced analytical systems augment this by applying mathematical derivatives to the raw positional data. By extracting angular velocities and accelerations, these systems can highlight the rapid, uncontrolled foot-slap associated with severe plantarflexion contractures, differentiating pathological equinus from normal childhood toe-walking variants.[16]

Algorithmic Precision: Addressing Depth Ambiguity and Occlusion

The fundamental, pervasive limitation of monocular 2D video analysis in clinical biomechanics is depth ambiguity—the profound inability of a single, standard camera lens to accurately ascertain the Z-axis (depth) of a limb moving toward or away from the focal plane.[20] When a subject swings their arm forward during a standard gait cycle, a pure 2D estimation model views the limb as artificially shortened in the pixel plane, leading to massively corrupted joint angle calculations and false clinical inferences.[20]

To circumvent this optical physics limitation, vanguard computational pipelines incorporate hybrid 2D-to-3D lifting algorithms. Frameworks like the aforementioned MeTRAbs utilize highly

complex, truncation-robust 2.5D volumetric heatmaps.[20] Rather than simply outputting flat X and Y pixel coordinates, these advanced networks are pre-trained on massive, multi-view datasets of actual 3D MoCap data (such as Human3.6M). Through this training, they intrinsically learn the immutable geometric constraints and kinetic proportions of the human skeleton.

When presented with 2D video, they autoregressively enforce physical laws, bone-length consistencies, and structural priors to mathematically infer absolute metric-scale depth.[5] This resolves the scale ambiguity without requiring clinics to deploy complex multi-camera arrays, depth-sensing LiDAR, or stereoscopic lenses.[5] This strict geometric enforcement is absolutely paramount when diagnosing subtle spinal rotations in early-onset scoliosis or tracking the minute hip deviations in early DMD, as these pathologies are intrinsically three-dimensional and cannot be accurately modeled on a flat coordinate plane.[31]

Ethical Deployments and Security Architecture

The transition of high-level clinical analysis from secure, localized hospital laboratories to cloud-connected smartphones and remote home environments inherently introduces substantial data privacy and cybersecurity vulnerabilities.[11] Real-world video captured for kinematic analysis not only records the patient's specific physical pathology but inadvertently captures highly identifiable facial features, environmental context, passive bystanders, and sensitive residential interiors.[11]

The architectures and ecosystems reviewed in this report mitigate these severe risks through structural, ethical algorithmic design. Frameworks heavily utilizing MediaPipe, for instance, are explicitly optimized for edge-computing paradigms; the neural network executes the complex pose estimation directly on the local CPU or neural processing unit of the mobile device itself.[18] This architecture completely eliminates the need to transmit highly sensitive, unencrypted raw video data over potentially insecure commercial networks to cloud-based GPU clusters.[11] The device only logs and securely transmits the resulting abstract mathematical arrays—typically a lightweight JSON file containing anonymous numerical coordinates representing the skeletal framework.

Similarly, massive dataset initiatives like Scoliosis1K have established a critical operational precedent for ethical medical data sharing. By pre-processing the raw RGB screening video into opaque, binary silhouettes and abstract 2D/3D skeleton maps prior to public release, the dataset entirely preserves patient anonymity.[38] This rigorous methodology ensures absolute, uncompromising compliance with global health data protection regulations (such as HIPAA and GDPR) while simultaneously providing the open-source computer vision community with the massive, high-quality data volumes necessary to train highly accurate, generalizable diagnostic models.[38]

Conclusion

The integration of deep learning-based markerless human pose estimation into clinical biomechanics and orthopedics fundamentally alters the trajectory of neuromuscular diagnostics. By synthesizing the findings of the current vanguard literature and the immense capabilities of the associated open-source repositories, several critical conclusions emerge regarding the future of computational medicine.

First, the successful deployment of targeted neural architectures, specifically the LSTM-CNN hybrid models utilized in the analysis of Duchenne Muscular Dystrophy, empirically demonstrates that kinematic time-series data extracted from standard, ubiquitous RGB video contains sufficient signal fidelity to rival the diagnostic accuracy of highly controlled, multi-million-dollar lab-based systems. Achieving accuracies exceeding 96% in pathological binary classification definitively validates the viability of deploying these software tools for remote, scalable, early-stage disease screening.

Second, the rigorous statistical validation of markerless pose estimation in highly variable, behaviorally non-compliant pediatric demographics—specifically toddlers presenting with neurodevelopmental delays like Autism and TSC—proves the extreme robustness of these algorithms against erratic, non-linear movement patterns. The widespread availability of meticulously documented open-source pipelines, such as the Roemmich-Stenum analytical workflow, empowers clinicians to effortlessly bridge the technical gap between raw computer vision outputs and standardized clinical spatiotemporal parameters.

Third, the precision engineering of dual-representation architectures, perfectly exemplified by the Dual Representation Framework for adolescent scoliosis, highlights the vital necessity of embedding structured clinical logic directly into deep learning models. By forcing spatial attention mechanisms to prioritize mathematically defined Postural Asymmetry Vectors over raw, data-driven statistical correlations, these neural networks become highly interpretable. This architectural choice aligns the algorithmic outputs seamlessly with established clinical orthopedic heuristics, effectively solving the "black box" problem of artificial intelligence in healthcare.

Ultimately, the future of clinical kinematics is inexorably bound to the open-source software ecosystem. The widespread, decentralized distribution of sophisticated mathematical frameworks, privacy-preserving multi-modal datasets like Scoliosis1K and GAVD, and highly targeted analytical Python libraries enables the rapid iteration, continuous refinement, and global peer validation of biomechanical models. As these complex computer vision pipelines successfully transition from theoretical research environments to ubiquitously deployed, edge-computed clinical applications, they will permanently democratize access to expert-level diagnostic insight. This paradigm shift will fundamentally redirect the management of neuromuscular disorders, neurodevelopmental delays, and spinal pathologies toward a highly proactive, data-rich, and globally equitable standard of care.

Works cited

1. Validation of markerless video-based gait analysis using ... - Frontiers, accessed March 17, 2026, https://www.frontiersin.org/journals/digital-health/articles/10.3389/fdgth.2025.1542012/full
2. Automated Gait Analysis Based on a Marker-Free Pose Estimation Model - PMC, accessed March 17, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC10384445/
3. Considerations for Applying MediaPipe to Gait Analysis - ThinkMind, accessed March 17, 2026, https://www.thinkmind.org/articles/global_health_2023_1_30_70069.pdf
4. (PDF) Validation of markerless video-based gait analysis using pose estimation in toddlers with and without neurodevelopmental disorders - ResearchGate, accessed March 17, 2026, https://www.researchgate.net/publication/389778785_Validation_of_markerless_video-based_gait_analysis_using_pose_estimation_in_toddlers_with_and_without_neurodevelopmental_disorders
5. Human Pose Estimation for Clinical Analysis of Gait Pathologies - PMC, accessed March 17, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC11097739/
6. Pose as Clinical Prior: Learning Dual Representations for Scoliosis Screening - arXiv.org, accessed March 17, 2026, https://arxiv.org/html/2509.00872v1
7. Verification of Markerless Gait Analysis: Multi-Camera and Single-Camera Approaches in Comparison to Marker-Based Gait Analysis - PMC, accessed March 17, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12942615/
8. Two-dimensional video-based analysis of human gait using pose estimation - PMC, accessed March 17, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC8099131/
9. (PDF) Human Pose Estimation for Clinical Analysis of Gait Pathologies - ResearchGate, accessed March 17, 2026, https://www.researchgate.net/publication/380598646_Human_Pose_Estimation_for_Clinical_Analysis_of_Gait_Pathologies
10. Pose as Clinical Prior: Learning Dual Representations for Scoliosis Screening | Request PDF - ResearchGate, accessed March 17, 2026, https://www.researchgate.net/publication/395693706_Pose_as_Clinical_Prior_Learning_Dual_Representations_for_Scoliosis_Screening
11. Classifying Simulated Gait Impairments using Privacy-preserving Explainable Artificial Intelligence and Mobile Phone Videos - arXiv, accessed March 17, 2026, https://arxiv.org/html/2412.01056v1
12. Analysis and design of passive assistive devices for patients with Duchenne Muscular Dystrophy - UPCommons, accessed March 17, 2026, https://upcommons.upc.edu/bitstreams/1cea75c9-0987-4bb8-8d60-0bb8f1e73426/download
13. © 2006, Elsevier Limited. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or - gaitlab, accessed March 17, 2026, http://www.gaitlab.ir/books/gaitlab_ref_16_Clinical_Gait_Analysis._Theory_and_Practice.pdf
14. Trendelenburg-Like Gait, Instability and Altered Step Patterns in a Mouse Model

for Limb Girdle Muscular Dystrophy 2i - PMC, accessed March 17, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC5023177/
15. Abnormal Gait and What It Means for You - Feet By Pody, accessed March 17, 2026, https://www.feetbypody.com/blog/abnormal-gait-and-what-it-means-for-you/
16. Altered Muscle Contributions are Required to Support the Stance Limb During Voluntary Toe-Walking - Frontiers, accessed March 17, 2026, https://www.frontiersin.org/journals/bioengineering-and-biotechnology/articles/10.3389/fbioe.2022.810560/full
17. Estimation of Fine-Grained Foot Strike Patterns with Wearable Smartwatch Devices - MDPI, accessed March 17, 2026, https://www.mdpi.com/1660-4601/19/3/1279
18. MediaPipe Pose Estimation for Sports Apps: Deep Dive, Deployment, and Limitations, accessed March 17, 2026, https://www.it-jim.com/blog/mediapipe-for-sports-apps/
19. Automated Gait Analysis Based on a Marker-Free Pose Estimation Model - MDPI, accessed March 17, 2026, https://www.mdpi.com/1424-8220/23/14/6489
20. MeTRAbs: Metric-Scale Truncation-Robust Heatmaps for Absolute 3D Human Pose Estimation | Request PDF - ResearchGate, accessed March 17, 2026, https://www.researchgate.net/publication/346866996_MeTRAbs_Metric-Scale_Truncation-Robust_Heatmaps_for_Absolute_3D_Human_Pose_Estimation
21. Daily Papers - Hugging Face, accessed March 17, 2026, https://huggingface.co/papers?q=whole-body%20recognition
22. Gait Characterization in Duchenne Muscular Dystrophy (DMD) Using a Single-Sensor Accelerometer: Classical Machine Learning and Deep Learning Approaches - MDPI, accessed March 17, 2026, https://www.mdpi.com/1424-8220/24/4/1123
23. Human Pose Estimation for Clinical Analysis of Gait Pathologies - PubMed, accessed March 17, 2026, https://pubmed.ncbi.nlm.nih.gov/38757143/
24. Validation of markerless video-based gait analysis using pose estimation in toddlers with and without neurodevelopmental disorders - PMC, accessed March 17, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC11893606/
25. Clinical gait analysis using video-based pose estimation: Multiple perspectives, clinical populations, and measuring change | PLOS Digital Health - Our journal portfolio - PLOS, accessed March 17, 2026, https://journals.plos.org/digitalhealth/article?id=10.1371/journal.pdig.0000467
26. Clinical gait analysis using video-based pose estimation - medRxiv.org, accessed March 17, 2026, https://www.medrxiv.org/content/10.1101/2023.01.26.23285007v1.full.pdf
27. AI in Neurorehab: Pose Estimation Makes Gait Analysis Easier and More Accessible Dr. Jan Stenum was five months into his postdoc, accessed March 17, 2026, https://asnr.com/files/ASNR_Blog_Article_on_AI_in_Neurorehab_Roemmich.pdf
28. Two-dimensional video-based analysis of human gait using pose estimation - Biomechanics, accessed March 17, 2026,

https://biomechanicssolutions.com/pdf/1.pdf
29. janstenum/GaitAnalysis-PoseEstimation: Gait analysis using marker-less pose estimation with OpenPose - GitHub, accessed March 17, 2026, https://github.com/janstenum/GaitAnalysis-PoseEstimation
30. Accuracy of Video-Based Gait Analysis Using Pose Estimation During Treadmill Walking Versus Overground Walking in Persons After Stroke - PMC, accessed March 17, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12142495/
31. Pose as Clinical Prior: Learning Dual Representations for Scoliosis Screening - arXiv, accessed March 17, 2026, https://arxiv.org/pdf/2509.00872
32. Gait Patterns as Biomarkers: A Video-Based Approach for Classifying Scoliosis - MICCAI, accessed March 17, 2026, https://papers.miccai.org/miccai-2024/paper/1763_paper.pdf
33. Gait Patterns as Biomarkers: A Video-Based Approach for Classifying Scoliosis - arXiv.org, accessed March 17, 2026, https://arxiv.org/abs/2407.05726
34. Gait Patterns as Biomarkers a Video-Based Approach for Classifying Scoliosis - Scribd, accessed March 17, 2026, https://www.scribd.com/document/1010728344/Gait-Patterns-as-Biomarkers-a-Video-Based-Approach-for-Classifying-Scoliosis
35. Daily Papers - Hugging Face, accessed March 17, 2026, https://huggingface.co/papers?q=pose%20constraints
36. Pose as Clinical Prior: Learning Dual Representations for Scoliosis Screening - MICCAI, accessed March 17, 2026, https://papers.miccai.org/miccai-2025/0706-Paper0904.html
37. SimSpine: A Biomechanics-Aware Simulation Framework for 3D Spine Motion Annotation and Benchmarking - arXiv, accessed March 17, 2026, https://arxiv.org/html/2602.20792v3
38. Scoliosis1K: A Large-Scale Dataset for Video-Based Scoliosis Screening - Zirui Zhou, accessed March 17, 2026, https://zhouzi180.github.io/Scoliosis1K/
39. A flexible and extensible framework for gait recognition. You can focus on designing your own models and comparing with state-of-the-arts easily with the help of OpenGait. · GitHub, accessed March 17, 2026, https://github.com/ShiqiYu/OpenGait
40. OpenGait: A Comprehensive Benchmark Study for Gait Recognition Towards Better Practicality - arXiv, accessed March 17, 2026, https://arxiv.org/html/2405.09138v2
41. Computer Vision for Clinical Gait Analysis: A Gait Abnormality Video Dataset, accessed March 17, 2026, https://www.researchgate.net/publication/389764074_Computer_Vision_for_Clinical_Gait_Analysis_A_Gait_Abnormality_Video_Dataset
42. Rahmyyy/GAVD: Gait Abnormality in Video Dataset (GAVD ... - GitHub, accessed March 17, 2026, https://github.com/Rahmyyy/GAVD
43. arXiv:2407.04190v1 [cs.CV] 5 Jul 2024, accessed March 17, 2026, https://arxiv.org/pdf/2407.04190
44. Clinical gait analysis using video-based pose estimation - Our journal portfolio - PLOS, accessed March 17, 2026,

https://journals.plos.org/digitalhealth/article/file?id=10.1371/journal.pdig.0000467&type=printable
45. GitHub - IntelligentSensingAndRehabilitation/PosePipeline: PosePipe is a human pose estimation (HPE) pipeline to facilitate home movement analysis from videos, accessed March 17, 2026, https://github.com/peabody124/posepipeline
46. GaitPy: An Open-Source Python Package for Gait Analysis Using an Accelerometer on the Lower Back, accessed March 17, 2026, https://joss.theoj.org/papers/10.21105/joss.01778
47. gaitalytics - PyPI, accessed March 17, 2026, https://pypi.org/project/gaitalytics/
48. GaitPy: An Open-Source Python Package for Gait Analysis Using an Accelerometer on the Lower Back - ResearchGate, accessed March 17, 2026, https://www.researchgate.net/publication/337027559_GaitPy_An_Open-Source_Python_Package_for_Gait_Analysis_Using_an_Accelerometer_on_the_Lower_Back
49. GaitAnalysisToolKit - PyPI, accessed March 17, 2026, https://pypi.org/project/GaitAnalysisToolKit/
50. GitHub - KumarLabJax/gaitanalysis: Perform gait analysis on pose estimation files., accessed March 17, 2026, https://github.com/KumarLabJax/gaitanalysis
51. Code and Data used for the paper "Explaining Machine Learning Models for Clinical Gait Analysis" - GitHub, accessed March 17, 2026, https://github.com/sebastian-lapuschkin/explaining-deep-clinical-gait-classification
52. RyanRoemmich - GitHub, accessed March 17, 2026, https://github.com/RyanRoemmich
53. A graphical user interface for editing keypoints from human pose estimation algorithms, accessed March 17, 2026, https://www.researchgate.net/publication/397881973_A_graphical_user_interface_for_editing_keypoints_from_human_pose_estimation_algorithms
54. Gait analysis in python using posture estimation. - GitHub, accessed March 17, 2026, https://github.com/s0ma0000/gait-analysis
55. OpenPose for 2D Gait Analysis: Knee Flexion Landmark Detection - GitHub, accessed March 17, 2026, https://github.com/batking24/OpenPose-for-2D-Gait-Analysis
56. austineaero/pose-estimation - GitHub, accessed March 17, 2026, https://github.com/austineaero/pose-estimation
57. Lower Limb Deformity and Gait Deviations Among Adolescents and Adults With X-Linked Hypophosphatemia - Frontiers, accessed March 17, 2026, https://www.frontiersin.org/journals/endocrinology/articles/10.3389/fendo.2021.754084/full
58. Predicting Gait Parameters of Leg Movement with sEMG and Accelerometer Using CatBoost Machine Learning - MDPI, accessed March 17, 2026, https://www.mdpi.com/2079-9292/13/9/1791
59. (PDF) Trendelenburg-Like Gait, Instability and Altered Step Patterns in a Mouse Model for Limb Girdle Muscular Dystrophy 2i - ResearchGate, accessed March 17, 2026, https://www.researchgate.net/publication/308121699_Trendelenburg-Like_Gait_In

stability_and_Altered_Step_Patterns_in_a_Mouse_Model_for_Limb_Girdle_Muscular_Dystrophy_2i