Remote Rehabilitation and Recovery Tracking: A Comprehensive Analysis of Post-Trauma and Post-Surgery Monitoring

The assessment of human locomotion and functional recovery has historically been confined to highly specialized laboratory environments. Traditional clinical gait analysis relies heavily on multi-camera optical motion capture systems, such as Vicon or Qualisys, paired with embedded force plates to quantify spatiotemporal parameters, full-body kinematics, and joint kinetics.[1] While these marker-based systems represent the established gold standard for biomechanical accuracy, their prohibitive financial costs, extensive hardware calibration requirements, and the absolute necessity for highly trained biomechanical personnel severely restrict their utility in longitudinal, real-world clinical monitoring.[1] As healthcare models shift toward value-based care and decentralized monitoring, the need to capture high-fidelity physical performance data outside the laboratory has become a critical technical challenge.

The emergence of smartphone-based markerless motion capture and advanced Inertial Measurement Unit (IMU) telemetry marks a profound paradigm shift in this domain.[5] By leveraging deep learning architectures, convolutional neural networks (CNNs), and sophisticated computer vision frameworks, clinicians and researchers can now conduct quantitative motor assessments directly in a patient's natural environment, including their home or community settings.[3] This ecological validity is paramount for patients undergoing extended rehabilitation for unilateral lower limb disabilities, such as those recovering from traumatic orthopedic injuries, Total Knee Arthroplasty (TKA), and Total Hip Arthroplasty (THA).[6] The transition from episodic, laboratory-bound evaluations to continuous, remote tele-rehabilitation tracking fundamentally alters the management of musculoskeletal and neurological disorders, enabling dynamic, data-driven modifications to physical therapy regimens.

Biomechanical Foundations of Spatiotemporal Gait Analysis

To accurately monitor post-trauma and post-surgery recovery, technological systems must capture highly specific spatiotemporal gait metrics. These parameters serve as highly sensitive digital biomarkers for functional improvement, physical degradation, or compensatory adaptation.[9] Understanding the precise mathematical and clinical definitions of these metrics is required for the effective deployment of any remote monitoring algorithm.

General gait parameters provide a macroscopic view of ambulatory health and cardiovascular efficiency, while leg-specific metrics highlight the functional asymmetries inherent in unilateral disabilities.[1] Human locomotion is a highly adaptable, complex coordinated cyclic neuromuscular process.[10] Physical changes, such as leg length discrepancies, prosthetic use, or post-surgical pain, frequently result in an asymmetric gait.[10] In patients with unilateral lower limb deficits, functional asymmetry heavily impacts forward propulsion; biomechanical adaptations often prioritize spatial symmetry over kinetic symmetry to optimize walking energetics and maintain anterior-posterior balance.[11]

The primary metrics extracted in contemporary remote rehabilitation frameworks are detailed below, demonstrating their clinical relevance in post-surgical cohorts.

Spatiotemporal Metric	Biomechanical Definition	Clinical Implications in Rehabilitation
Gait Speed (Velocity)	Measured in meters per second (m/s). Represents the overall forward progression of the body's center of mass.	A fundamental indicator of functional independence. Following TKA, walking speed typically reaches its lowest point around two weeks post-operatively (e.g., dropping to 0.79 m/s) and follows a gradual recovery trajectory, normalizing around 21 to 24 weeks.[7]
Cadence	Measured in steps per minute. Reflects the inherent rhythmicity and neural control of locomotion.	Deviations in cadence often correlate with neurological impairments or severe antalgic (pain-avoidance) gait patterns.[1]
Stride Length	Measured in centimeters (cm). The spatial distance between successive initial contacts (heel strikes) of the exact same foot.[1]	Reduced stride length is a primary compensatory mechanism for instability, effectively keeping the center of mass within a restricted base of support.[1]

Step Length	Measured in centimeters (cm). The spatial distance between the initial contact of one foot and the subsequent initial contact of the contralateral foot.[1]	Critical for identifying spatial asymmetry. Comparing the step length of the impaired leg to the non-impaired leg reveals specific compensatory movement strategies, particularly in hemiparetic or post-surgical populations.[1]
Stance Phase	Expressed as a percentage of the total gait cycle. Begins with initial contact and ends with terminal contact (toe-off) of the same limb.[1]	An asymmetric, shortened stance phase on the operative limb strongly indicates pain avoidance or muscular weakness during the weight-bearing phase.[1]
Swing Phase	Expressed as a percentage of the total gait cycle. Encompasses the period the limb is airborne and advancing forward.[1]	Requires adequate knee flexion and hip flexor strength. Post-TKA patients often exhibit altered swing phases due to joint stiffness or quadriceps inhibition.[1]
Single Limb Support	Expressed as a percentage of the stance phase. The duration where only one foot is in contact with the ground, supporting the entire body weight.[1]	A direct measure of dynamic balance and unilateral load-bearing capacity. Significantly reduced on the operative limb following THA and TKA.[1]
Double Limb Support	Expressed as a percentage of the stance phase. The time both feet are simultaneously bearing weight on the ground.[1]	Prolonged double support time is a classic, universally recognized indicator of a cautious gait strategy, observed in patients with joint instability, osteoarthritis, or vestibular dysfunction.[4]

The ability to passively collect these metrics in real-world settings allows physicians to direct

post-operative recovery using sensor-based care pathways.[7] For example, research indicates that while TKA patients recover walking speed steadily, individuals post-THA may not show significant improvements in complex movements like turning velocity or step time asymmetry between 2 and 15 months post-surgery, indicating long-term, ingrained compensatory habits that require targeted physical therapy.[8] Furthermore, cross-sectional retrospective studies reveal that remotely-collected biomechanical walking data are significantly associated with individuals' self-evaluated function, such as scores on the Lower Extremity Functional Scale (LEFS).[13]

IMU-Based Telemetry and the OneStep Smartphone Application

The integration of Micro-Electro-Mechanical Systems (MEMS) into consumer electronics has transformed the modern smartphone into a highly capable diagnostic instrument. Smartphones equipped with integrated triaxial accelerometers, gyroscopes, and magnetometers function as powerful 6-Degree-of-Freedom (6DOF) Inertial Measurement Units (IMUs). These embedded sensors provide the high-frequency raw kinematic data required for continuous remote monitoring.[13]

The clinical viability of utilizing pocket-worn smartphone sensors for formal spatiotemporal gait assessment has been rigorously evaluated, with the OneStep smartphone application serving as a primary benchmark in recent literature.[1] A comprehensive 2024 validation study analyzed the reliability and validity of the OneStep application specifically among patients undergoing rehabilitation for mild-to-moderate unilateral lower limb disability.[1]

Algorithmic Pipeline for Trajectory Reconstruction

The internal processing logic of smartphone-based IMU gait analysis involves a sophisticated mathematical and machine learning pipeline to translate raw analog signals into discrete clinical metrics [1]:

1. **6DOF Trajectory Integration:** The algorithm mathematically integrates raw signal accelerations into the sensor's spatial displacement. By continuously accounting for the device's spatial orientation via sensor fusion (combining accelerometer and gyroscope data), the software generates a continuous trajectory with six degrees of freedom.[1]
2. **Standardized Matrix Representation:** Because gait is cyclical but highly variable in duration, the integrated trajectory is time-normalized and represented in a standardized 6×100 matrix form, capturing the complex dynamics of a single standardized gait cycle.[1]
3. **Deep Learning Regression:** These normalized matrices are subsequently processed through deep learning models. Specifically, regression models utilizing deep convolutional layers are applied to predict individual spatiotemporal parameter values based on the complex features extracted from the 6DOF matrix.[1]

Clinical Validation and Reliability Testing

To validate this algorithmic approach, researchers conducted concurrent recordings utilizing three distinct devices: one smartphone running the OneStep app placed in the pocket of the participant's impaired leg, a second identical smartphone placed in the pocket of the opposite leg, and a reference standard C-Mill instrumented treadmill.[1] Walking speed was kept constant throughout the sessions, and the treadmill slope was set to zero degrees.[1] The hardware utilized included standard consumer-grade Xiaomi Redmi Note 8 smartphones.[1]

The statistical evaluation of the system yielded highly significant results regarding its applicability for tele-rehabilitation tracking. The reliability and validity were calculated using Intra-class Correlation Coefficients (ICC 3,1 utilizing a two-way mixed-effect linear model), Pearson correlation coefficients, and Wilcoxon signed-rank tests.[1]

Evaluation Metric	Statistical Finding	Clinical Interpretation
Treadmill Correlation	Pearson correlations between the smartphones and the treadmill were mostly > 0.8, ranging from 0.65 to 1.[1]	Demonstrates a strong linear relationship between the pocket-worn consumer device and the laboratory-grade instrumented treadmill.[1]
High-Validity Parameters	ICC demonstrated excellent validity for cadence and gait speed (range, 0.92–1) and moderate-to-excellent validity for other parameters (0.58–0.93).[1]	General macroscopic gait parameters are captured with near-laboratory precision, making the system highly reliable for broad mobility tracking.[1]
Low-Validity Parameter	'Step length of the impaired leg' showed poor-to-good validity, with an ICC range of 0.37–0.84.[1]	Highlights an algorithmic limitation. Pathological, unilateral movements introduce high intra-stride variability that models trained primarily on symmetrical data struggle to perfectly reconstruct.[1]
Effect Size (Systematic	Cohen's *d* effect size was small ($d < 0.5$) for all	Despite slight underestimations and

Bias)	spatiotemporal parameters.[1] Bland-Altman analysis revealed a slight relative underestimation of variables by the smartphone compared to motion systems.[6]	algorithmic noise on the impaired limb, the systematic error is negligible for longitudinal tracking. The application demonstrates high reliability for week-over-week rehabilitation progress monitoring.[6]

The operational simplicity of smartphone-based tools—requiring no complex calibration or technical expertise from the patient—allows for the collection of clinical data anywhere and at any time.[1] In clinical assessments of patients with unilateral disability, placement on either leg does not significantly alter the general accuracy, further enhancing the robust nature of remote deployment.[1]

Open-Source Markerless Pose Estimation Architectures

While pocket-worn IMUs capture excellent temporal resolution and linear acceleration data, they inherently lack the spatial mapping necessary for full-body articular kinematics. They cannot directly measure a patient's knee flexion angle or trunk coronal range of motion. Computer vision and markerless pose estimation algorithms bridge this fundamental gap by extracting two-dimensional (2D) and three-dimensional (3D) joint coordinates directly from standard digital video recordings.[3]

The transition of markerless motion capture from a highly experimental computer science novelty to a validated clinical tool is driven by several foundational, open-source architectures. These frameworks leverage massive neural networks to identify anatomical landmarks across diverse environments, lighting conditions, and clothing types.[5]

Core Computer Vision Frameworks

1. OpenPose Developed by the CMU Perceptual Computing Lab, OpenPose is historically significant as the first real-time multi-person system capable of jointly detecting human body, foot, hand, and facial keypoints.[5] The architecture utilizes Part Affinity Fields (PAFs) to solve the bipartite matching problem associated with bottom-up multi-person pose estimation, allowing it to extract up to 135 keypoints per individual.[17] A critical feature of OpenPose is its runtime invariance; the processing speed remains constant regardless of the number of people detected in the frame.[17] Clinically, OpenPose is heavily utilized for extracting 2D sagittal gait kinematics, evaluating dynamic joint angles during functional exercises, and conducting remote

ergonomic postural assessments.[5]

2. AlphaPose Authored by the MVIG-SJTU research group, AlphaPose represents a highly accurate regional multi-person pose estimation framework utilizing a top-down architectural approach.[20] Unlike bottom-up methods, AlphaPose first employs robust bounding box detectors (such as YOLO or specialized trackers) to isolate individual subjects within a frame before performing highly detailed pose estimation within that localized region.[20] To address the complexities of continuous gait analysis, AlphaPose incorporates advanced human re-identification (Re-ID) features, enabling highly stable pose tracking across sequential video frames.[21] This temporal stability is essential for capturing fluid motion without algorithmic "jitter" interrupting the spatiotemporal sequence.

3. DeepLabCut (DLC) Originally developed to revolutionize animal behavioral research, DeepLabCut has transitioned rapidly into human clinical applications due to its remarkable efficiency. DLC applies transfer learning with deep neural networks (specifically ResNet architectures) to achieve state-of-the-art pose estimation with minimal user-supplied training data.[5] The framework's modularity allows for active learning and custom curation of annotation data, making it highly adaptable for specialized, edge-case tracking.[25] For instance, tracking the complex kinematics of a patient utilizing a novel lower-limb prosthesis can be achieved by fine-tuning a DLC network on a small sample of annotated frames. The multi-animal/multi-person extension (maDLC), supported by both PyTorch and TensorFlow deep learning engines, further expands its clinical utility for tracking patient-therapist interactions.[24]

4. MediaPipe and BlazePose Google's MediaPipe framework focuses on democratizing motion capture through extreme computational efficiency. The underlying BlazePose architecture is a lightweight machine learning pipeline optimized specifically for on-device, real-time inference on standard mobile phone CPUs.[26] BlazePose tracks 33 distinct 2D landmarks on the human body.[27] Crucially, it projects these coordinates into 3D world space using GHUM, a comprehensive 3D human shape modeling pipeline.[26] The landmarks are output as normalized coordinates (values between 0 and 1), representing relative positions within the image frame, which can be effortlessly mapped to absolute pixel coordinates by multiplying by the image width and height.[28] This extreme efficiency and ease of integration make MediaPipe the foundational layer for countless bespoke commercial and clinical mobile health applications.[29]

Repository Directory: Foundational Vision Architectures

The following table provides the exhaustive programmatic links required to deploy, fine-tune, and evaluate these foundational computer vision frameworks for rehabilitation research.

Framework	Primary Language	Open-Source Repository / Documentation Link	Research Utility & Features
OpenPose	C++ / Python	(https://github.com/CMU-Perceptual-Computing-Lab/openpose) Installation Guide (https://cmu-perceptual-computing-lab.github.io/openpose/web/html/doc/md_doc_00_index.html)	Extracts 135 keypoints (body, face, hands, feet). Unmatched for high-resolution 2D sagittal joint angle calculations. Native Unity plugin for VR integration.[17]
AlphaPose	Python	(https://github.com/MVIG-SJTU/AlphaPose) (https://github.com/MVIG-SJTU/AlphaPose/blob/master/docs/run.md) (https://github.com/Amanbhandula/AlphaPose)	PyTorch 3D HPS support. Top-down YOLO detection. Unsurpassed frame-by-frame tracking stability utilizing human Re-ID algorithms.[20]
DeepLabCut	Python	(https://github.com/DeepLabCut/DeepLabCut) (https://github.com/orgs/DeepLabCut/repositories) (https://deeplabcut.github.io/DeepLabCut/docs/maDLC_U	Highly modular. Includes specialized pipelines like DLC-live, DLC2Kinematics, and CEBRA for advanced nonlinear embedding analysis of movement data.[25]

		serGuide.html) (https://github.com/DeepLabCut/DeepLabCut-Workshop-Materials)	
MediaPipe	Python / C++	(https://ai.google.dev/edge/mediapipe/solutions/vision/pose_landmarker)	GHUM 3D shape modeling. Optimal for building lightweight, real-time feedback applications directly onto consumer iOS/Android devices.[26]
PosePipe	Python	(https://github.com/peabody124/posepipeline)	Specialized pipeline utilizing DataJoint to seamlessly manage the relationships between videos, algorithms, and clinical intermediate outputs.[37]

Advanced Clinical Processing Pipelines

While extracting 2D and 3D pixel coordinates is computationally impressive, pure coordinates do not directly inform clinical decision-making. Physicians and physical therapists operate on biomechanical parameters: joint angles (kinematics), ground reaction forces (kinetics), muscle activations, and precise spatiotemporal symmetry metrics. Advanced processing pipelines have been developed specifically to bridge the gap between computer vision keypoints and actionable clinical biomechanics.

OpenCap: Democratizing Inverse Dynamics

Developed by the Neuromuscular Biomechanics Lab at Stanford University, OpenCap is an open-source platform that fundamentally disrupts traditional gait laboratory economics. The platform computes both the kinematics (motion) and dynamics (forces) of human movement using videos captured synchronously from two or more standard smartphones.[38]

OpenCap utilizes deep learning models to estimate 3D kinematics and applies physics-based simulations and rapid bilevel optimization to concurrently solve musculoskeletal scaling and inverse kinematic problems.[38] The extracted 3D marker positions are processed in an OpenSim format, a widely used open-source software for biomechanical modeling.[40] By reconstructing the movement in a physics engine, OpenCap accurately predicts complex dynamic measures—such as muscle activations, joint loads, and joint moments—without requiring patients to walk on embedded force plates.[38]

In a rigorous 100-subject field study, a clinician utilizing the OpenCap platform estimated musculoskeletal dynamics 25 times faster than a traditional laboratory-based approach, operating at less than 1% of the financial cost.[38] The platform is highly scalable; while small models can run on mobile CPUs, executing the high-resolution OpenPose pipeline locally requires a CUDA-enabled GPU with 8GB to 24GB of memory.[40]

VisionMD-Gait: Monocular Clinical Assessment

Addressing the logistical challenge of multi-camera setups, VisionMD-Gait enables clinical-grade spatiotemporal gait assessment using only a single, frontal-view smartphone video.[4] Designed for deployment in standard hospital corridors or clinic rooms, the software processes all data locally on the user's device, ensuring strict compliance with patient privacy and data protection regulations.[4]

The VisionMD-Gait algorithmic pipeline is highly specialized for clinical precision:

1. **Subject Localization:** An automated YOLO-based object detector identifies and tracks the subject of interest throughout the video.[4]
2. **3D Pose Estimation:** The MeTRAbs 3D human pose estimator processes the bounding boxes. Trained on 28 open-sourced datasets, MeTRAbs outputs 3D coordinates in true metric units, re-ordered to the Human3.6 M Dataset format and re-centered at the patient's pelvis.[4]
3. **Gait Transformer Model:** These standardized joint sequences, combined with the participant's absolute height, are fed into a customized Gait Transformer model. This model estimates lower-limb joint kinematics (hip, knee, and ankle angular displacement) and definitively identifies critical foot contact events (heel strikes and toe-offs).[4]

Utilizing these temporal events, the system computes metrics via strict mathematical definitions. For example, double support time is calculated precisely as the sum of the time both feet are in contact: ``.[4] Validation against research-grade wearable sensors in healthy adults and individuals with vestibular dizziness demonstrated strong agreement, with mean absolute errors remaining under 10%.[4] The platform successfully identified subclinical gait alterations in patients with dizziness, including reduced cadence and prolonged double support time, highlighting its transformative potential for fall risk assessment.[4]

Repository Directory: Advanced Clinical Pipelines

The programmatic implementation of these advanced physics and transformer models is accessible via the following repositories.

Platform	Primary Focus	Open-Source Repository / Documentation Link	Clinical Implementation details
OpenCap	Kinematics, Inverse Dynamics, Muscle Activation Modeling	(https://github.com/opencap-org/opencap-core) Processing Utilities (https://github.com/opencap-org/opencap-analysis) (https://github.com/stanfordnmbl/opencap-fshd-dm-analysis)	Requires synchronous capture from 2+ iOS devices. Processes outputs directly into standard OpenSim formats for physics simulations. Ideal for orthopedic load analysis.[40]
VisionMD-Gait	Single-camera frontal view, spatiotemporal parameters	(https://mea-lab.github.io/VisionMD-Tutorial/) (http://www.VisionMD.ai) (https://github.com/JeffZC/pose-editor)	Extracts speed, step length, cadence, and support times locally without cloud reliance. Utilizes MeTRAbs and proprietary Gait Transformers. Validated for vestibular tracking.[4]

Programmatic Data Processing and Python Libraries

The translation of raw analog IMU signals or matrix-based pose estimation outputs into structured, analyzable clinical datasets requires robust programmatic pipelines. A thriving ecosystem of specialized, open-source Python libraries has been developed to automate

filtering, event detection, and statistical calculation, removing the burden of manual data curation from rehabilitation researchers.

Specialized Gait Analysis Frameworks

GaitPy Designed specifically for lumbar-mounted accelerometers operating at a minimum sampling rate of 50Hz, GaitPy automates the extraction of temporal and spatial features from raw vertical acceleration data.[49] The library simplifies complex signal processing into three core functions: classify_bouts (to segment periods of walking from static standing), extract_features (to identify initial and final contact events), and plot_contacts (for visual validation).[49] The outputs are highly structured Pandas dataframes or CSV files containing precise values for stride duration, initial/terminal double support, cadence, and critical asymmetry metrics.[49]

python-gaitalytics For laboratories and clinics utilizing 3D motion capture formats (specifically the industry-standard .c3d file format), the python-gaitalytics package provides a comprehensive, automated pipeline.[51] The framework is highly configurable, adapting to various proprietary marker sets and modeling algorithms, requiring only a minimum subset of hip and foot markers.[51] It automates event detection (detect_events), segments trials into individual gait cycles (segment_trial), and calculates complex time-series features (minimum, maximum, and mean joint angles) while offering automatic time-normalization across datasets.[51]

OpenGait Recognized as a premier highlight paper at CVPR and TPAMI, OpenGait is an extensible gait analysis framework maintained by the Shiqi Yu Group.[52] The project focuses on integrating multi-modal data streams and large-scale deep learning architectures into movement analysis. Recent iterations include DeepGaitV2, SkeletonGait, and LidarGait++, expanding the boundaries of complex tracking.[52] Furthermore, specific medical extensions such as ScoNet and Scoliosis1K-Pose introduce detailed pose annotations and clinical priors tailored specifically for interpretable spinal scoliosis screening.[52]

Imucal The accuracy of any 6DOF tracking system is wholly dependent on precise hardware calibration. The imucal Python library provides a programmatic framework to execute Ferraris (1994/95) calibration methods.[53] By applying structured calibration matrices to raw analog outputs, the library ensures that sensor data is accurately translated into highly reliable angular velocity (deg/s) and linear acceleration (m/s^2) units, which is a prerequisite for accurate spatial integration.[53]

Repository Directory: Data Processing Frameworks

The necessary tools for building robust, automated data pipelines are cataloged below.

Python Library	Processing Domain	Open-Source Repository Link	Primary Functions
GaitPy	Single-sensor IMU (Lumbar)	(https://github.com/matt002/GaitPy)	classify_bouts, extract_features. Calculates cadence, single/double limb support, step length asymmetry from vertical acceleration arrays.[49]
python-gaitalytics	3D Motion Capture (.c3d)	(https://github.com/DART-Lab-LLUI/python-gaitalytics)	Time normalization, automated detect_events, handles complex proprietary marker sets.[51]
OpenGait	Multi-modal Deep Learning	(https://github.com/ShiqiYu/OpenGait)	Framework encompassing DeepGaitV2, LidarGait++, and specialized clinical tools like ScoNet for scoliosis.[52]
Imucal	Hardware Calibration	(https://github.com/mad-lab-fau/imucal)	Applies Ferraris calibration matrices to raw 6DOF IMU hardware.[53]
GaitUtils	Visualization / Mocap	Main Package (https://github.com/NCH-Motion-Laboratory/collect_gait) (https://github.com/NCH-Motion-Laboratory/gaitlab_sandb	NCH-Motion-Laboratory tools utilizing pyqt5 and plotly for extracting and visualizing Vicon Nexus data.[54]

		ox)	
PathoOpenGait	Semi-Supervised Analysis	(https://github.com/Kaminyou/PathoOpenGait)	Cloud-enabled platform empowered by semi-supervised learning techniques for pathological gait analysis.[59]
GaitMarker	Manual Video Annotation	(https://github.com/leomol/gait-marker)	GUI (OpenCV/PyQt5) to manually annotate spatiotemporal events in video frames, generating JSON data to train custom neural networks.[60]
IMU 6DOF Odom	Trajectory Reconstruction	(https://github.com/Armanasq/End-to-End-Deep-Learning-Framework-for-Real-Time-Inertial-Attitude-Estimation-using-6DoF-IMU) Inertial Odometry	Models for predicting quaternion orientations and reconstructing full 3D trajectories using deep learning.[14]
OpenPose Gait Tools	Kinematic Conversion	Feature Extractor (https://github.com/batking24/OpenPose-for-2D-Gait-Analysis) Kalman Filtering	MATLAB and Python scripts to transform raw AlphaPose/OpenPose outputs into filtered joint trajectories and clinical spatiotemporal metrics.[18]

Open-Access Deep Learning Datasets for

Tele-Rehabilitation

The efficacy, accuracy, and clinical reliability of CNNs and Transformer models in clinical gait analysis are intrinsically tied to the quality, variance, and scale of their underlying training datasets.[5] Historically, biomechanical machine learning datasets were severely limited, featuring only healthy individuals walking symmetrically on laboratory treadmills. However, modern tele-rehabilitation algorithms must function "in-the-wild," interpreting highly variable environments, diverse clothing types, and—most importantly—severely pathological, asymmetric movements.[5]

The curation and release of open-access clinical datasets represent a monumental leap forward for algorithmic training. These datasets provide the foundational ground truth necessary to teach models how to recognize the subtle kinematic signatures of specific diseases.

Foundational Clinical Datasets

- **Gait Abnormality in Video Dataset (GAVD):** Recognizing the critical shortage of clinically relevant pathological data, GAVD was assembled as the largest video gait dataset available. It comprises 1874 sequences featuring normal, abnormal, and explicitly pathological gaits.[63] The dataset includes clinically annotated RGB data sourced from online platforms, encompassing over 400 subjects who have undergone clinical-grade visual screening. Captured in highly variable settings (hospital clinics, urban uncontrolled outdoor environments), GAVD enables the training of Temporal Segment Networks (TSN) and SlowFast networks to achieve remarkable video abnormality detection rates exceeding 92% and 94%, respectively.[63]
- **WearGait-PD:** A highly specialized open-access dataset targeting the complex movement disorders associated with Parkinson's disease. The dataset contains raw IMU and sensorized insole data from individuals with PD and age-matched controls, heavily synchronized to a gold-standard clinical gait walkway reference system.[65] This allows models to learn the specific high-frequency tremor and festination characteristics of Parkinsonian locomotion.
- **GPJATK Dataset:** Designed to aid research efforts in testing and evaluating algorithms for gait-based human identification and kinematic extraction. GPJATK provides meticulously synchronized multi-view video and optical motion capture data, serving as a high-fidelity ground truth for evaluating novel computer vision pipelines.[5]

Repository Directory: Clinical Gait Datasets

The following open-access data repositories provide the necessary material to train, validate, and benchmark new rehabilitation tracking algorithms.

Dataset Name	Clinical Focus / Data Modality	Access Link / Repository	Research Utility
GAVD	Pathological Gait / RGB Video Sequences	(https://github.com/Rahmyyy/GAVD)	Contains 1874 clinically annotated sequences of abnormal gaits in uncontrolled environments. Essential for training abnormality detection models.[63]
TKA/THA Recovery	Post-Arthroplasty / IMU Telemetry	(https://doi.org/10.5281/zenodo.7014333)	Maps functional recovery utilizing Opal V2 IMUs during a standardized 2-minute walk test. Provides longitudinal sensor-derived metrics post-surgery.[8]
WearGait-PD	Parkinson's Disease / IMU & Insoles	(https://www.medrxiv.org/content/10.1101/2024.09.11.24313476v1)	IMU and sensorized insole data heavily synchronized to a reference walkway for highly precise neurological movement analysis.[65]
GPJATK	Multi-View Synchronization / Video & Mocap	(http://bytom.pja.edu.pl/projekty/hm-gpjatk/)	Provides high-fidelity optical motion capture data synchronized with standard video, serving as a ground truth validation source.[66]

Health&Gait	General Gait Analysis / Vision-Only	(https://github.com/AVAuco/healthgait)	Designed specifically to enable deep learning model training using visual information strictly without reliance on any wearable sensors.[69]
Kinect Rehab	Physical Therapy / 3D Skeleton Maps	(https://doi.org/10.5281/zenodo.4610859)	3D Kinect skeleton positions, orientations, and RGB video of clinical patients performing targeted physical therapy and low back-pain rehabilitation exercises.[70]
OpenSTL	Spatio-Temporal Predictive Learning	(https://github.com/chengtan9907/OpenSTL)	Comprehensive benchmark supporting PyTorch Lightning. Manages complex human motion trajectory datasets for temporal forecasting and modeling.[72]
CP Classification	Cerebral Palsy / Classification Trials	(https://github.com/lucabergamini/gait-analysis-dataset)	Dataset encompassing 1139 trials acquired from 178 patients affected by varying severity stages of Cerebral Palsy.[73]
XAI Gait Research	Explainable AI /	(https://github.com/	Provides code and

	Model Evaluation	sebastian-lapuschkin/explaining-deep-clinical-gait-classification)	data specifically exploring Explainable AI (XAI) attributions and spectral relevance analysis in clinical gait classification.[74]
PD Severity Estimation	Parkinson's Disease / UPDRS Scoring	(https://github.com/mlu355/PD-Motor-Severity-Estimation) (https://github.com/mittrayash/Parkinson-s-Disease-Detection-using-Gait-Analysis)	Code and datasets focusing on the vision-based estimation of MDS-UPDRS Gait Scores to objectively assess motor severity.[54]
MS Prediction	Multiple Sclerosis / Vision-Based Analysis	(https://github.com/kaurrachneet6/Vision-Based-Gait-Analysis-Framework-for-Predicting-Multiple-Sclerosis)	Deep learning framework focusing on the distinct kinematic signatures associated with Multiple Sclerosis progression.[76]

Integration of Large Language Models (LLMs) in Rehabilitation

The absolute frontier of remote tele-rehabilitation lies beyond the simple extraction of kinematic coordinates; it involves the integration of Large Language Models (LLMs) to synthesize complex, high-dimensional numerical data into actionable, easily interpretable clinical insights. Advanced generative models, including GPT-4, Gemini 2.5 Pro, and DeepSeek V3.1, are currently being investigated for their capacity to ingest raw rehabilitation data, generate highly personalized exercise prescriptions, and automate tedious clinical reporting processes.[77]

Sequence-to-Sequence Kinematic Translation

In highly advanced, state-of-the-art applications, LLMs are being adapted to perform sequence-to-sequence modeling between semantic textual data and physical kinematic

motion.[80] By algorithmically mapping physical joint coordinates to distinct "motion tokens" and aligning them with semantic "text tokens," LLMs can perform seamless bi-directional translation.[80] The architecture can ingest a sequence of motion inputs generated by a smartphone camera processing a patient's exercise and automatically generate a highly structured, medically accurate textual description of the patient's exercise form (motion-to-text).[80] Conversely, the model can ingest a physical therapist's written prescription and translate it into a highly accurate 3D avatar demonstration to guide the patient at home (text-to-motion).[80]

Clinical Documentation and Automated Reasoning

The administrative burden of physical therapy is vast, requiring constant synthesis of multimodal data streams. LLMs effectively automate the generation of specialized medical documentation, such as International Classification of Functioning, Disability and Health (ICF) codes, based on integrated patient inputs and kinematic assessments.[79] For example, in managing a complex stroke rehabilitation case, an LLM acting as a multidisciplinary coordinator can synthesize data regarding gait speed, spatiotemporal asymmetry, and patient-reported pain to generate comprehensive rehabilitation prescriptions and risk management plans.[79]

In home-based rehabilitation environments, conversational LLM agents provide constant, 24/7 interaction. These fully customizable agents reduce patient anxiety, significantly improve exercise adherence through real-time guidance, and actively parse subjective mobility complaints.[13] Experimental randomized clinical trials investigating degenerative knee disease demonstrate that integrating LLM-assisted exercise prescriptions (utilizing models like ChatGPT-5 or Gemini 2.5 Pro) with conventional physiotherapy yields measurable improvements in patient-reported functioning, pain reduction, and quality of life.[77] The models demonstrate particular superiority in generating guidance for basic knowledge, alternative treatments, and general rehabilitation practices.[82]

Repository Directory: LLM Prompting and Semantic Medical Data

Fine-tuning foundation models to operate safely and accurately in a medical capacity requires highly specialized, clinically accurate conversational datasets.

Dataset / Tool	Clinical Focus / Data Modality	Access Link / Repository	Research Utility
OrthoQA-300	Orthopedic QA / Textual Prompts	(https://huggingface.co/datasets/stratum-research/orthoqa-300)	Contains structured Q&A pairs specifically regarding physical

			therapy protocols, return-to-activity timelines, and surgical rehabilitation (e.g., ACL reconstruction).[83]
MedSynth	Clinical Documentation / SOAP Notes	(https://huggingface.co/datasets/Ahmad0067/MedSynth)	Synthetic medical dataset providing highly structured SOAP notes, physical exam summaries, and detailed PT treatment plans for musculoskeletal complaints.[84]
ShareGPT-PT	Generative AI Output / Behavioral Obs.	(https://github.com/Tencent/AngelSlim/blob/main/dataset/sharegpt_gpt4_qwen/sharegpt_gpt4-qwen3_a22B_output.jsonl)	Compiles LLM interaction outputs and instruction prompts covering detailed physical therapy protocols, Skilled Nursing Facility (SNF) goals, and patient behavioral observations.[85]
Medical QA	Broad Medical Exams / Question Answering	(https://github.com/huggingface/tokenizers)	Large-scale open-domain QA dataset derived from medical exams, covering complications of arthritis treatments, joint replacement surgery, and physical therapy basics.[86]

Strategic Insights and Future Trajectories

The extensive aggregation of mathematical models, deep learning frameworks, and clinical validation studies presented above yields several critical secondary and tertiary insights into the future trajectory of computational biomechanics and rehabilitation medicine.

1. The Decentralization and Democratization of Biomechanical Expertise

Historically, the generation of highly complex biomechanical data—specifically inverse dynamics, the calculation of internal joint moments, and muscle activation forces—necessitated multimillion-dollar gait laboratories and teams of specialized engineers.[1] The emergence and maturation of frameworks like OpenCap fundamentally democratize this capability.[38] The ripple effect of this technological decentralization is profound for clinical research. Large-scale, multi-center orthopedic trials can now easily utilize standardized kinetic outcomes without shipping fragile, post-surgical patients to centralized research hubs. This paradigm shift enables the rapid compilation of massively diverse, population-scale biomechanical datasets, which will exponentially accelerate the discovery of novel digital biomarkers for predicting osteoarthritis progression, falls risk, or early arthroplasty failure.[7]

2. The Algorithmic Blind Spot of Unilateral Pathology

Rigorous statistical validation metrics consistently expose an algorithmic bias embedded within modern pose estimation and IMU integration models. In the clinical validation of the OneStep application, the system demonstrated moderate-to-excellent validity across almost all parameters; however, the explicit calculation of the "step length of the impaired leg" demonstrated highly variable, poor-to-good validity (ICC 0.37-0.84).[15] This localized underperformance highlights a critical, often-overlooked insight: baseline deep learning models are heavily over-indexed on symmetrical, healthy gait patterns.[15]

When a post-surgical patient utilizes severe, erratic compensatory mechanisms—such as lateral trunk lean, vaulting, hip hiking, or a highly variable cautious gait—the predictive neural networks struggle to classify the highly volatile temporal sequences.[4] The algorithms attempt to force pathological data into normative mathematical distributions. Therefore, the widespread incorporation of explicitly pathological datasets (such as GAVD, WearGait-PD, and specific post-arthroplasty datasets) is not merely beneficial, but architecturally mandatory for the next generation of predictive rehabilitation models.[63] Without training on severe functional asymmetry, remote systems risk masking the very clinical deteriorations they are deployed to detect.

3. The Symbiosis of Generative AI and Kinematic Telemetry

The future of post-surgical recovery tracking will ultimately be defined by the seamless fusion

of numerical kinematics and semantic artificial intelligence. Currently, state-of-the-art platforms extract geometric data (e.g., detecting a 15% increase in double limb support time) and present it statically on clinical dashboards.[1] While valuable, this still requires extensive cognitive load from the clinician to interpret.

However, by automatically routing this quantified kinematic telemetry directly into advanced LLMs (employing sequence-to-sequence motion-to-text modeling), the entire system can instantly generate natural language clinical interpretations, update electronic health records autonomously, and dynamically adjust the patient's home exercise prescription.[77] The LLM effectively acts as an advanced reasoning engine, translating abstract geometric coordinates and high-frequency accelerometer fluctuations into actionable, empathetic, and patient-facing physiological guidance.[78] This synthesis closes the feedback loop in remote care, transforming tele-rehabilitation from a passive monitoring tool into an active, intelligent therapeutic intervention.

Works cited

1. The Reliability and Validity of the OneStep Smartphone Application ..., accessed March 18, 2026, https://www.mdpi.com/1424-8220/24/11/3594
2. Verification of Markerless Gait Analysis: Multi-Camera and Single-Camera Approaches in Comparison to Marker-Based Gait Analysis - PMC, accessed March 18, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12942615/
3. Smartphone-Based Gait Analysis with OpenCap: A Narrative Review - MDPI, accessed March 18, 2026, https://www.mdpi.com/2673-7078/5/4/88
4. VisionMD-Gait: scalable clinical gait assessment from smartphone ..., accessed March 18, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12868619/
5. Applications of Pose Estimation in Human Health and Performance ..., accessed March 18, 2026, https://www.mdpi.com/1424-8220/21/21/7315
6. The validity and reliability of the OneStep smartphone application under various gait conditions in healthy adults with feasibility in clinical practice - PubMed, accessed March 18, 2026, https://pubmed.ncbi.nlm.nih.gov/36104792/
7. Stepping beyond Counts in Recovery of Total Knee Arthroplasty: A Prospective Study on Passively Collected Gait Metrics - PMC, accessed March 18, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC10305196/
8. Objective monitoring of functional recovery after total knee and hip ..., accessed March 18, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC9526408/
9. Monitoring Gait Recovery After Total Knee Arthroplasty Using ..., accessed March 18, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12604452/
10. Comparing Gait with Multiple Physical Asymmetries Using Consolidated Metrics - Frontiers, accessed March 18, 2026, https://www.frontiersin.org/journals/neurorobotics/articles/10.3389/fnbot.2018.00002/full
11. Gait adaptations in step length and push-off force during walking with functional asymmetry - PMC, accessed March 18, 2026,

https://pmc.ncbi.nlm.nih.gov/articles/PMC11985528/
12. Comprehensive analysis of total knee arthroplasty kinematics and functional recovery: Exploring full-body gait deviations in patients with knee osteoarthritis - Our journal portfolio - PLOS, accessed March 18, 2026, https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0314991
13. Spatiotemporal parameters from remote smartphone-based gait analysis are associated with lower extremity functional scale categories - PMC, accessed March 18, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC10410151/
14. Armanasq/End-to-End-Deep-Learning-Framework-for-Real-Time-Inertial-Attitude-Estimation-using-6DoF-IMU - GitHub, accessed March 18, 2026, https://github.com/Armanasq/End-to-End-Deep-Learning-Framework-for-Real-Time-Inertial-Attitude-Estimation-using-6DoF-IMU
15. The Reliability and Validity of the OneStep Smartphone Application for Gait Analysis among Patients Undergoing Rehabilitation for Unilateral Lower Limb Disability - PubMed, accessed March 18, 2026, https://pubmed.ncbi.nlm.nih.gov/38894386/
16. The Reliability and Validity of the OneStep Smartphone Application for Gait Analysis among Patients Undergoing Rehabilitation for Unilateral Lower Limb Disability - Tel Aviv University, accessed March 18, 2026, https://cris.tau.ac.il/en/publications/the-reliability-and-validity-of-the-onestep-smartphone-applicatio
17. OpenPose: Real-time multi-person keypoint detection library for body, face, hands, and foot estimation · GitHub, accessed March 18, 2026, https://github.com/CMU-Perceptual-Computing-Lab/openpose
18. gait-analysis/README.md at main - GitHub, accessed March 18, 2026, https://github.com/sansrien/gait-analysis/blob/main/README.md
19. OpenPose for 2D Gait Analysis: Knee Flexion Landmark Detection - GitHub, accessed March 18, 2026, https://github.com/batking24/OpenPose-for-2D-Gait-Analysis
20. MVIG-SJTU/AlphaPose: Real-Time and Accurate Full-Body Multi-Person Pose Estimation&Tracking System - GitHub, accessed March 18, 2026, https://github.com/MVIG-SJTU/AlphaPose
21. AlphaPose/docs/run.md at master - GitHub, accessed March 18, 2026, https://github.com/MVIG-SJTU/AlphaPose/blob/master/docs/run.md
22. Real-Time Pose Estimation using AlphaPose, PyTorch, and Deep Learning - DebuggerCafe, accessed March 18, 2026, https://debuggercafe.com/real-time-pose-estimation-using-alphapose-pytorch-and-deep-learning/
23. Workshop material for using DeepLabCut - GitHub, accessed March 18, 2026, https://github.com/DeepLabCut/DeepLabCut-Workshop-Materials
24. Official implementation of DeepLabCut: Markerless pose estimation of user-defined features with deep learning for all animals incl. humans - GitHub, accessed March 18, 2026, https://github.com/DeepLabCut/DeepLabCut
25. DeepLabCut for Multi-Animal Projects - GitHub Pages, accessed March 18, 2026, https://deeplabcut.github.io/DeepLabCut/docs/maDLC_UserGuide.html

26. Pose landmark detection guide | Google AI Edge, accessed March 18, 2026, https://ai.google.dev/edge/mediapipe/solutions/vision/pose_landmarker
27. Human Pose Estimation Using MediaPipe Pose and Optimization Method Based on a Humanoid Model - MDPI, accessed March 18, 2026, https://www.mdpi.com/2076-3417/13/4/2700
28. Efficient Human Pose Estimation: Leveraging Advanced Techniques with MediaPipe, accessed March 18, 2026, https://arxiv.org/html/2406.15649v1
29. (PDF) Real-Time Human Pose Estimation Using Media-Pipe an Artificial Intelligence Applications in Health and Fitness - ResearchGate, accessed March 18, 2026, https://www.researchgate.net/publication/388945247_Real-Time_Human_Pose_Estimation_Using_Media-Pipe_an_Artificial_Intelligence_Applications_in_Health_and_Fitness
30. Real-Time Human Pose Estimation Using Media-Pipe an Artificial Intelligence Applications in Health and Fitness - IEEE Xplore, accessed March 18, 2026, https://ieeexplore.ieee.org/document/10870725/
31. A data acquisition tool utilizing MediaPipe's Human Pose Estimation for gait analysis applications. - GitHub, accessed March 18, 2026, https://github.com/Eli-Bro/CV-Gait-Analysis-SU2023
32. OpenPose: OpenPose Doc, accessed March 18, 2026, https://cmu-perceptual-computing-lab.github.io/openpose/web/html/doc/md_doc_00_index.html
33. openpose/doc/installation/0_index.md at master - GitHub, accessed March 18, 2026, https://github.com/CMU-Perceptual-Computing-Lab/openpose/blob/master/doc/installation/0_index.md
34. AlphaPose Implementation in Pytorch along with the pre-trained weights - GitHub, accessed March 18, 2026, https://github.com/Amanbhandula/AlphaPose
35. DeepLabCut - GitHub, accessed March 18, 2026, https://github.com/deeplabcut
36. DeepLabCut repositories - GitHub, accessed March 18, 2026, https://github.com/orgs/DeepLabCut/repositories
37. GitHub - IntelligentSensingAndRehabilitation/PosePipeline: PosePipe is a human pose estimation (HPE) pipeline to facilitate home movement analysis from videos, accessed March 18, 2026, https://github.com/peabody124/posepipeline
38. OpenCap: Human movement dynamics from smartphone videos - PMC, accessed March 18, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC10586693/
39. Evaluation of a Smartphone-based Motion Capture System for Athletic Movement Screening - UC San Diego, accessed March 18, 2026, https://escholarship.org/content/qt2bw98461/qt2bw98461.pdf
40. opencap-org/opencap-core: Main OpenCap processing ... - GitHub, accessed March 18, 2026, https://github.com/opencap-org/opencap-core
41. Utilities for processing OpenCap data. - GitHub, accessed March 18, 2026, https://github.com/stanfordnmbl/opencap-processing
42. VisionMD-Gait: scalable clinical gait assessment from smartphone videos - ResearchGate, accessed March 18, 2026,

https://www.researchgate.net/publication/399546791_VisionMD-Gait_scalable_clinical_gait_assessment_from_smartphone_videos
43. Example visualizations from the gait transformer. Keypoints on the... - ResearchGate, accessed March 18, 2026, https://www.researchgate.net/figure/Example-visualizations-from-the-gait-transformer-Keypoints-on-the-ankle-become-colored_fig3_378239647
44. stanfordnmbl/opencap-fshd-dm-analysis - GitHub, accessed March 18, 2026, https://github.com/stanfordnmbl/opencap-fshd-dm-analysis
45. opencap-org/opencap-analysis - GitHub, accessed March 18, 2026, https://github.com/opencap-org/opencap-analysis
46. VisionMD | An user-friendly, open-source software platform designed to automate video-based kinematic analysis of motor tasks for assessment of motor dysfunction in movement disorders - MEA-Lab, accessed March 18, 2026, https://mea-lab.github.io/VisionMD-Tutorial/
47. Measuring changes in gait that occur due to changes in gait speed, accessed March 18, 2026, https://www.researchgate.net/figure/Measuring-changes-in-gait-that-occur-due-to-changes-in-gait-speed-in-persons-post-stroke_fig6_379307775
48. (PDF) Validation of portable in-clinic video-based gait analysis for prosthesis users, accessed March 18, 2026, https://www.researchgate.net/publication/378239647_Validation_of_portable_in-clinic_video-based_gait_analysis_for_prosthesis_users
49. matt002/GaitPy - GitHub, accessed March 18, 2026, https://github.com/matt002/GaitPy
50. GaitPy: An Open-Source Python Package for Gait Analysis Using an Accelerometer on the Lower Back - ResearchGate, accessed March 18, 2026, https://www.researchgate.net/publication/337027559_GaitPy_An_Open-Source_Python_Package_for_Gait_Analysis_Using_an_Accelerometer_on_the_Lower_Back
51. DART-Lab-LLUI/python-gaitalytics: Python package to ... - GitHub, accessed March 18, 2026, https://github.com/DART-Lab-LLUI/python-gaitalytics
52. A flexible and extensible framework for gait recognition. You can focus on designing your own models and comparing with state-of-the-arts easily with the help of OpenGait. · GitHub, accessed March 18, 2026, https://github.com/ShiqiYu/OpenGait
53. GitHub - mad-lab-fau/imucal: A Python library to calibrate 6 DOF IMUs, accessed March 18, 2026, https://github.com/mad-lab-fau/imucal
54. gait-analysis · GitHub Topics, accessed March 18, 2026, https://github.com/topics/gait-analysis?o=desc&s=stars
55. New Children's Hospital Motion Laboratory - GitHub, accessed March 18, 2026, https://github.com/NCH-Motion-Laboratory
56. GitHub - NCH-Motion-Laboratory/gaitlab_sandbox: Small scripts and programs for the Helsinki movement analysis lab., accessed March 18, 2026, https://github.com/NCH-Motion-Laboratory/gaitlab_sandbox
57. NCH-Motion-Laboratory/collect_gait: Utility scripts for collecting gait data. - GitHub, accessed March 18, 2026,

https://github.com/NCH-Motion-Laboratory/collect_gait
58. NCH-Motion-Laboratory/gaitutils: Extract and visualize gait data - GitHub, accessed March 18, 2026, https://github.com/NCH-Motion-Laboratory/gaitutils
59. Kaminyou/PathoOpenGait: An open source gait analysis system with a 3D imaging system - GitHub, accessed March 18, 2026, https://github.com/Kaminyou/PathoOpenGait
60. leomol/gait-marker: Video spatial and temporal annotator for gait analysis - GitHub, accessed March 18, 2026, https://github.com/leomol/gait-marker
61. jpsml/6-DOF-Inertial-Odometry: IMU-Based 6-DOF Odometry - GitHub, accessed March 18, 2026, https://github.com/jpsml/6-DOF-Inertial-Odometry
62. TaatiTeam/gait_features_from_pose: A collection of MATLAB scripts for calculating gait features from pose-tracked data - GitHub, accessed March 18, 2026, https://github.com/TaatiTeam/gait_features_from_pose
63. Computer Vision for Clinical Gait Analysis: A Gait Abnormality Video Dataset - arXiv, accessed March 18, 2026, https://arxiv.org/html/2407.04190v1
64. Computer Vision for Clinical Gait Analysis: A Gait Abnormality Video Dataset - IEEE Xplore, accessed March 18, 2026, https://ieeexplore.ieee.org/document/10921672/
65. WearGait-PD: An Open-Access Wearables Dataset for Gait in Parkinson's Disease and Age-Matched Controls | medRxiv, accessed March 18, 2026, https://www.medrxiv.org/content/10.1101/2024.09.11.24313476v1
66. The GaitST dataset Release Agreement, accessed March 18, 2026, http://www.am.sanken.osaka-u.ac.jp/BiometricDB/doc/OU-GaitST_ReleaseAgreement.pdf
67. (PDF) Calibrated and synchronized multi-view video and motion capture dataset for evaluation of gait recognition - ResearchGate, accessed March 18, 2026, https://www.researchgate.net/publication/334949888_Calibrated_and_synchronized_multi-view_video_and_motion_capture_dataset_for_evaluation_of_gait_recognition
68. Rahmyyy/GAVD: Gait Abnormality in Video Dataset (GAVD) is the largest collection of online links to gait videos with clinical annotations. The dataset is designed for Clinical Gait Analysis using computer vision however has many applicaitons such as gait recognition and abnormality action detection. · GitHub, accessed March 18, 2026, https://github.com/Rahmyyy/GAVD
69. GitHub - AVAuco/healthgait: Health and Gait dataset: multimodal features from videos, accessed March 18, 2026, https://github.com/AVAuco/healthgait
70. IntelliRehabDS (IRDS)—A Dataset of Physical Rehabilitation Movements - MDPI, accessed March 18, 2026, https://www.mdpi.com/2306-5729/6/5/46
71. A Medical Low-Back Pain Physical Rehabilitation Dataset for Human Body Movement Analysis This work is partially supported by the EU FP7 grant ECHORD++ KERAAL and by the European Regional Fund via the VITAAL Contrat Plan Etat Region. - arXiv.org, accessed March 18, 2026, https://arxiv.org/html/2407.00521v1
72. OpenSTL: A Comprehensive Benchmark of Spatio-Temporal Predictive Learning - GitHub, accessed March 18, 2026, https://github.com/chengtan9907/OpenSTL

73. lucabergamini/gait-analysis-dataset: Raw dataset from "Signal Processing and Machine Learning for Diplegia Classification" and "Gait-Based Diplegia Classification Using LSMT Networks" - GitHub, accessed March 18, 2026, https://github.com/lucabergamini/gait-analysis-dataset
74. Code and Data used for the paper "Explaining Machine Learning Models for Clinical Gait Analysis" - GitHub, accessed March 18, 2026, https://github.com/sebastian-lapuschkin/explaining-deep-clinical-gait-classification
75. mlu355/PD-Motor-Severity-Estimation: Code for the paper "Vision-based Estimation of MDS-UPDRS Gait Scores for Assessing Parkinson's Disease Motor Severity" - GitHub, accessed March 18, 2026, https://github.com/mlu355/PD-Motor-Severity-Estimation
76. kaurrachneet6/Vision-Based-Gait-Analysis-Framework-for-Predicting-Multiple-Sclerosis - GitHub, accessed March 18, 2026, https://github.com/kaurrachneet6/Vision-Based-Gait-Analysis-Framework-for-Predicting-Multiple-Sclerosis
77. Study Details | NCT07267962 | LLM-Guided Rehabilitation in Degenerative Knee Disease | ClinicalTrials.gov, accessed March 18, 2026, https://clinicaltrials.gov/study/NCT07267962
78. Application of Large Language Models in Stroke Rehabilitation Health Education: 2-Phase Study - PMC, accessed March 18, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12306586/
79. View of Use of artificial intelligence large language models as a clinical tool in rehabilitation medicine: a comparative test case, accessed March 18, 2026, https://medicaljournalssweden.se/jrm/article/view/13373/22490
80. (LiFT) Lightweight Fitness Transformer: A language-vision model for Remote Monitoring of Physical Training - arXiv, accessed March 18, 2026, https://arxiv.org/html/2506.06480v1
81. Best 3 Fully Customizable LLM Agents for Physical Therapy (2025), accessed March 18, 2026, https://agentiveaiq.com/listicles/best-3-fully-customizable-llm-agents-for-physical-therapy
82. AI-Powered Physiotherapy: Evaluating LLMs Against Students in Clinical Rehabilitation Scenarios - MDPI, accessed March 18, 2026, https://www.mdpi.com/2076-3417/16/3/1165
83. stratum-research/orthoqa-300 · Datasets at Hugging Face, accessed March 18, 2026, https://huggingface.co/datasets/stratum-research/orthoqa-300
84. Ahmad0067/MedSynth · Datasets at Hugging Face, accessed March 18, 2026, https://huggingface.co/datasets/Ahmad0067/MedSynth
85. AngelSlim/dataset/sharegpt_gpt4_qwen/sharegpt_gpt4-qwen3_a22B_output.jsonl at main, accessed March 18, 2026, https://github.com/Tencent/AngelSlim/blob/main/dataset/sharegpt_gpt4_qwen/sharegpt_gpt4-qwen3_a22B_output.jsonl
86. BioMedLM: A 2.7B Parameter Language Model Trained On Biomedical Text - arXiv.org, accessed March 18, 2026, https://arxiv.org/html/2403.18421v1

87. A Review of Innovative Medical Rehabilitation Systems with Scalable AI-Assisted Platforms for Sensor-Based Recovery Monitoring - MDPI, accessed March 18, 2026, https://www.mdpi.com/2076-3417/15/12/6840