



Partner API - Onboarding external

<https://partner-service-develop.preprod.otto.vodfactory.com/docs/index.html#free-headings-GETapi-free-headings--id->

API overview

This API lets content providers distribute their SVOD catalog to multiple streaming partners from a single integration.

You push your content once — metadata, media assets (images, videos, subtitles, audio) and availability windows — and we transform and deliver it to each partner in the format they require.

Partners are of two kinds:

- **Distribution** (full content delivery): Amazon (Prime Video Channels), FreeTV, Molotov, Betv
- **Discovery** (catalog referencing only): Allociné, Justwatch, SamsungTV

Full API reference



Partner API docs: <https://partner-service-develop.preprod.otto.vodfactory.com/docs/index.html>

Setup

Get an API key (Bearer token)

Our team will provide you with an API key.

This API key will be linked to your platform and must be sent in the headers (Bearer token) for each API request.

Private storage access (AWS S3)

If your videos and assets are stored in a **private S3 bucket** (without public access), we will need the following information:

Name	Description	Example
Access key	Access key used to authenticate to the S3 storage	xxx
Secret key	Secret key paired with the access key	yyy

Name	Description	Example
Endpoint	Endpoint URL of the S3 service	<code>s3.eu-west-1.amazonaws.com</code>
Region	AWS region where the bucket is located	<code>eu-west-1</code>
Provider	Provider name	<code>AWS</code>
Bucket name	Name of the bucket where videos and assets are stored	<code>bucket_name</code>

If your videos and assets (images, subtitles, and audio) have public HTTP access, we won't need these.

Making requests

Base URL

<https://otto-partner.vodfactory.com/api>

Headers

Bearer token

Always send the API key as a Bearer token.

Accept-Language (or "Locale")

Always send a header "Accept-Language" with the format "fr-FR".

Use it to set the language of the data you send and receive.

You can find more information about language codes here:

Content type

The "Content-Type" should always be "application/json".

Errors

All API errors share the same response envelope:

```
{
  "status": "error",
  "message": "The given data was invalid.",
  "error_code": "invalid_data",
  "warnings": [],
  "errors": {
    "external_id": ["The external_id field is required."]
  }
}
```

HTTP status codes:

- 401 — unauthenticated: Bearer token missing or invalid
- 403 — unauthorized: token valid but not allowed
- 404 — not_found: resource not found
- 422 — invalid_data: validation failed (details per field in the errors map)
- 400 — malformed request
- 409 — conflict

Successful responses use the same envelope with "status": "success" and a results key.

Quickstart

Prerequisites: your API key (Bearer token) and the required headers (Authorization, Accept-Language, Content-Type: application/json).

Recommended order to publish a title:

1. (Optional) Browse reference data to get valid codes: genres (GET /genres), languages (GET /languages), countries (GET /countries).
2. Create the people you will reference (cast & crew): POST /persons. Required first — a content references a person by external_id + job, so the person must already exist.
3. Create the content: POST /contents — send metadata, genres, countries, identifiers, persons, images and availabilities in the same payload. For a series, create the serie first, then its seasons (parent_external_id = serie), then episodes (parent_external_id = season).
4. Attach videos: POST /contents/{externalId}/videos, including subtitles, audios and audiotracks. The content must exist first.
5. Check readiness: GET /contents/{externalId}/action-statuses — per partner/action, tells you if everything required is set (ready) or what is missing (incomplete).
6. Deliver: either wait for the automatic nightly send (contents modified in the last 24h), or trigger it manually with POST /contents/{externalId}/send.

Core concepts

External ID

Each time you create an element (content, video, person, ...) you must send an "external_id", which corresponds to the ID of this element in your system.

This way, you don't have to store an internal identifier generated by the Partner API. The external ID is the one used in your API requests.

This external_id must be a string.

Language codes

This API uses the language codes defined by Amazon: [Support – Video Central](#)

You can find the complete list by calling the endpoint: <https://otto-partner.vodfactory.com/api/languages>

Examples: en-US, en-GB, fr-FR, fr-BE, pl-PL, ...

If you send another language code ("fr" or "fre" instead of "fr-FR") it will be automatically converted to the correct code.

▼ MCP server (AI)

Connect your AI assistant (Claude, Cursor, Windsurf...) directly to the Partner API using the MCP protocol. Once connected, your assistant can browse, create, and update your catalog without leaving your workflow.

Prerequisites

- Your API Bearer token
- A compatible MCP client (Claude Code, Claude Desktop, Cursor, Windsurf, VS Code...)

Connection details

Server URL	https://otto-partner.vodfactory.com/mcp
Protocol	MCP Streamable HTTP
Authentication	Bearer token (Sanctum)

Setup — Claude Code

Run this single command in your terminal:

```
claude mcp add --transport http apiPartner https://otto-partner.vodfactory.com/mcp --header "Authorization: Bearer YOUR_TOKEN_HERE"
```

Replace `YOUR_TOKEN_HERE` with your personal Bearer token. The server appears immediately — no restart needed.

Setup — Claude Desktop

1. Open your Claude Desktop configuration file:

- **macOS:** `~/Library/Application Support/Claude/claude_desktop_config.json`
- **Windows:** `%APPDATA%\Claude\claude_desktop_config.json`

2. Add the following block inside `mcpServers`:

```
{
  "mcpServers": {
    "apiPartner": {
      "type": "streamableHttp",
      "url": "https://otto-partner.vodfactory.com/mcp",
      "headers": {
        "Authorization": "Bearer YOUR_TOKEN_HERE"
      }
    }
  }
}
```

Replace `YOUR_TOKEN_HERE` with your personal Bearer token.

3. Restart Claude Desktop. A **apiPartner** server will appear in the tools panel.



Note: If your version of Claude Desktop does not support `streamableHttp`, use the legacy proxy method instead: set `"command"` to `npx` with args `-y mcp-remote https://otto-partner.vodfactory.com/mcp --header "Authorization:Bearer YOUR_TOKEN_HERE"`. This requires Node.js >= 20.

Setup — Cursor / Windsurf / VS Code

Add a new MCP server in your IDE settings:

- **Type:** `http`
- **URL:** `https://otto-partner.vodfactory.com/mcp`
- **Headers:** `Authorization: Bearer YOUR_TOKEN_HERE`



Fallback: If your IDE only supports `command` type, use: command `npx`, args: `-y mcp-remote https://otto-partner.vodfactory.com/mcp --header "Authorization:Bearer YOUR_TOKEN_HERE"`. This requires Node.js >= 20.

Available tools

Once connected, your assistant has access to the following tools:

Tool	Description
<code>get_genres</code>	List all available genre codes
<code>get_languages</code>	List available languages
<code>get_countries</code>	List available countries
<code>get_contents</code>	Search and list your contents
<code>get_content</code>	Get a specific content by ID (full metadata, videos, images, availabilities)

Tool	Description
<code>create_content</code>	Create a new content
<code>update_content</code>	Update an existing content (full replacement)
<code>patch_content</code>	Partially update a content (only provided fields)
<code>delete_content</code>	Delete a content
<code>get_content_availability</code>	Get availability windows per partner
<code>update_content_availability</code>	Update availability windows per partner
<code>send_content_to_partners</code>	Publish a content to partners
<code>unpublish_content</code>	Unpublish a content
<code>get_persons</code>	List persons (cast & crew)
<code>get_person</code>	Get a specific person
<code>create_person</code>	Create a person
<code>update_person</code>	Update a person
<code>delete_person</code>	Delete a person
<code>get_videos</code>	List videos attached to a content
<code>get_video</code>	Get a specific video (with audios, subtitles, audiotracks)
<code>create_video</code>	Add a video to a content
<code>update_video</code>	Update a video
<code>delete_video</code>	Delete a video
<code>create_subtitle</code>	Add a subtitle file to a video
<code>create_audio</code>	Add an audio file to a video
<code>get_plans</code>	List subscription plans
<code>create_plan</code>	Create a plan

Partner-specific tools (Free, Molotov) are also available — your assistant will discover them automatically.

Resources

The server exposes reference data that your assistant can read at any time:

Resource	Description
<code>vf://referential/genres</code>	Complete list of genre codes (general + Amazon-specific)
<code>vf://referential/languages</code>	Language codes in BCP 47 format (fr-FR, en-US...)
<code>vf://referential/countries</code>	Country codes (ISO 3166-2 and ISO 3166-3)

Guided prompts

The server includes guided workflows that walk your assistant through complex operations step by step:

Prompt	When to use
<code>manage_content</code>	Creating or updating a content — the assistant asks for each required field
<code>manage_video</code>	Creating or updating a video — guided through partner, type, URL, formats
<code>send_content_to_partners</code>	Sending to partners — ensures all partner-specific rules are met before sending



Tip: You don't need to call these prompts explicitly. Just describe what you want in natural language (e.g. *"Create a new movie called Horizon"*) and the assistant will use the appropriate prompt automatically

Example prompts

Once connected, you can ask your assistant:

| *"List my 10 most recent contents"*

"Create a new movie titled 'Horizon' with genre Action and language French"

"Update the description of content ABC-123"

"What are the available genre codes for documentaries?"

"Send content 12345 to Amazon and Free"

"Show me the availability windows for content 67890"

Troubleshooting

"Server disconnected"

Check that the server URL is exactly `https://otto-partner.vodfactory.com/mcp` (with `/mcp` at the end).

"Unauthorized"

Check that your Bearer token is valid and correctly copied (no extra spaces).

"Client session not initialized"

This is handled automatically by MCP clients. If using a custom client, send a `notifications/initialized` after `initialize`.

Contents

▼ Example payload for a Program:

```
{
  "type": "program",
  "external_id": "1234",
  "title": "Lorem ipsum",
  "sku_code": "lorem_ipsum_1234",
  "availabilities": {
    "amazon": [
      {
        "country_code": "FRA",
        "format_profile": "HD",
        "starts_at": "2025-09-01 00:00:00",
        "ends_at": "2030-09-01 00:00:00"
      }
    ]
  }
}
```

▼ Example payload for a Serie:

```
{
  "type": "serie",
  "external_id": "12345",
  "title": "Lorem ipsum serie",
  "sku_code": "lorem_ipsum_serie_1234"
}
```

▼ Example payload for a Season:

```
{
  "type": "season",
  "parent_external_id": "12345",
  "rank": 1,
```

```

    "external_id": "123456",
    "title": "Season 1",
    "sku_code": "lorem_ipsum_season_1_123456"
  }

```

▼ Example payload for a Season:

```

{
  "type": "season",
  "parent_external_id": "12345",
  "rank": 1,
  "external_id": "123456",
  "title": "Season 1",
  "sku_code": "lorem_ipsum_season_1_123456"
}

```

▼ Example payload for an Episode:

```

{
  "type": "episode",
  "parent_external_id": "123456",
  "rank": 1,
  "external_id": "123456",
  "title": "Episode 1",
  "sku_code": "lorem_ipsum_episode_1_1234567"
}

```

An episode must be linked to a season.

Attributes

external_id	The external ID of the content. String
type	program / serie / season / episode — send serie exactly, not series
sku_code	A unique identifier used by partners. Usually "{title}_{externalId}". Examples: "superman_1234", "star_wars_episode_1_6543"
parent_external_id	The external ID of the parent, only for a season or episode. String
rank	Starting at 1, the rank of the content in its parent. The last rank must match the number of contents in the current parent. Only for a season or episode

Requirements for series

Each series must have at least one season.

Each time you create an episode, you have to attach it to a season parent (attribute parent_external_id).

Metadata

Partner	Label	Type	Restriction	Description
	title	text	150 characters	Title
	original_title	text	150 characters	Title in the original language
	synopsis	text	400 characters	Synopsis
	short_synopsis	text	150 characters	Short synopsis
	persons	list		List of people with external ID and job. At least one director is required for Amazon

Partner	Label	Type	Restriction	Description
	countries	list of country codes		List of country codes
	duration	integer		Duration in seconds
	release_date	date		Release date in "YYYY-MM-DD" format. If you only know the year: "YYYY-01-01"
	owner	text	150 characters	Studio credit line
	video_quality	text	SD/HD/UHD	Video quality
	original_language	language code		Localized language code. fr-FR, en-US, ...
	rating	integer	0/10/12/16/18	CSA rating. 0 = all audiences
	genres	list of codes	3 max for Amazon	List of genre codes
Molotov	molotov_tags	molotov_tag		Custom tags
Betv	betv_categories	betv_category		Custom categories
Allociné, Justwatch & SamsungTV	front_url	text	255 characters	The URL to watch the content

Required attributes

✓ : program, serie, season, and episode

Attribute	Amazon	Free	Molotov	Betv	Allociné	Justwatch	Google
title	✓	✓	✓	✓	✓	✓	✓
original_title					✓		
synopsis	✓		✓	✓		✓	
short_synopsis	✓						
persons	✓				✓ (directors)		
countries	✓						
duration	program & episode		program & episode	✓			
release_date	✓	program & episode			✓		
owner	✓						
video_quality				✓			
original_language	✓						
rating	✓	program & episode	✓	✓			
genres	✓						
molotov_tags							
betv_categories				✓			
front_url					✓		✓

Genres

Genre is a metadata field used to group categories/themes/genres from all partners.

For Amazon, it is required, and at most three unique genres are accepted..

A list of available genres for each marketplace is provided in the following Excel file:

[partners-genres.xlsx](#)

You can get this list using the endpoint: GET <https://otto-partner.vodfactory.com/api/genres>

People (cast and crew)

You can send a list of actors, directors, etc.

Available roles: *actor, director, producer, writer, creator.*

Create a person

▼ POST <https://otto-partner.vodfactory.com/api/persons>

```
{
  "external_id": "456",
  "firstname": "George",
  "lastname": "Clooney",
  "name": "George Clooney", // Required if firstname and lastname are omitted
  "gender": "male", // male or female
  "birth_date": "1961-05-06",
  "image": "https://media.themoviedb.org/t/p/w300_and_h450_bestv2/dt0a7DT0SQeHb7NpURD6ifyEzsN.jpg",
  "identifiers": {
    "imdb": "nm0000123",
    "tmdb": "1461"
  }
}
```

Fields

Field	Required	Description	Used by
firstname	If no name is provided		Amazon/Free/Molotov/Betv
lastname	If no name is provided		Amazon/Free/Molotov/Betv
name	If no firstname/lastname is provided		Amazon/Free/Molotov/Betv
gender	No	"male" or "female"	Amazon/Free
birth_date	No	Date in format "YYYY-MM-DD"	Free
image	No	URL	Free
identifiers	No	Identifiers list:	Amazon/Free

Attach people to a content

▼ Example payload:

```
{
  "persons": [
    {
      "external_id": "456",
      "job": "actor"
    },
    {
      "external_id": "456",
      "job": "director"
    }
  ]
}
```

Countries

You can send a list of country codes in ISO2 or ISO3 format: FRA, FR, USA, US, ...

You can find these codes by calling the endpoint: <https://otto-partner.vodfactory.com/api/countries>

Availabilities

An availability defines when and where your content is available.

Each availability has a start and end date, a country_code, a format_profile (quality), and a licence type (SVOD by default).

Availability attribute ends_at is not required. If not set, the content stays available with no end date (until you set one).

Dates (starts_at and ends_at) are expressed in UTC, formatted as YYYY-MM-DD HH:MM:SS.

Format profiles: SD / HD / UHD

Licence types (licence_type, defaults to SVOD):

- SVOD — Subscription Video On Demand
- AVOD — Advertising Video On Demand
- FVOD — Free Video On Demand
- VOD — Video On Demand (rental / TVOD)
- EST — Electronic Sell-Through (purchase / TVOD)
- POEST — Pre-Order Electronic Sell-Through

▼ Example payload:

```
{
  "availabilities": {
    "amazon": [
      {
        "country_code": "FRA",
        "format_profile": "HD", // UHD, HD or SD
        "licence_type": "SVOD", // Not required. SVOD by default
        "starts_at": "2025-08-01 10:00:00",
        "ends_at": null // Not required
      }
    ],
    "free": [
      {
        "country_code": "FRA",
        "format_profile": "HD",
        "starts_at": "2025-10-01 12:00:00",
        "ends_at": "2026-12-31 23:00:00"
      },
      {
        "country_code": "FRA",
        "format_profile": "HD",
        "starts_at": "2027-01-01 00:00:00",
        "ends_at": "2027-12-31 23:00:00"
      }
    ]
  }
}
```

Image formats

Partner	Name	Ratio	Minimum resolution	Max size	Format	Required	Content
Free	cover_poster	3:4	315×420	—	jpg / png	Yes	

Partner	Name	Ratio	Minimum resolution	Max size	Format	Required	Content
Free	cover_wide	16:9	736×414	—	jpg / png	Yes	
Free	backdrop_wide	16:9	1920×1080	—	jpg / png	Yes	
Free	banner_wide	320:103	1920×618	—	jpg / png	No	
Amazon	box_art	3:4	1200×1600	10MB	jpg/png	Yes	Program
Amazon	cover_art	16:9	1920×1080	10MB	jpg/png	Yes	Program & Season
Amazon	poster_art	2:3	2000×3000	10MB	jpg/png	Yes	Program & Season
Amazon	hero_art	16:9	1920×1080	10MB	jpg/png	Yes	Program & Season
Amazon	title_art	Flexible	1100×660	1MB	png	No	Program & Season
Amazon	season_box_art	4:3	1600×1200	10MB	jpg/png	Yes	Season
Amazon	episodic_art	16:9	1920×1080	10MB	jpg/png	No	Episode
Molotov	poster	16:21	1000×1314	—	jpg / png	Yes	
Molotov	poster_23	2:3	2000×3000	—	jpg / png	No	
Molotov	backdrop	16:9	1920×1080	—	jpg / png	Yes	
Molotov	landscape	16:9	1920×1080	—	jpg / png	Yes	
Betv	poster	3:4	1200×1600	—	jpg / png	Yes	
Betv	wallpaper	16:9	1920×1080	—	jpg / png	Yes	



More details about Amazon's artwork specifications: <https://videocentral.amazon.com/support/delivery-experience/artwork/artwork-specifications>



More details about Amazon's artwork requirements: <https://videocentral.amazon.com/support/delivery-experience/artwork/artwork-requirements>

▼ Example payload:

```
{
  "images": {
    "amazon": {
      "cover_art": "https://path/to/amazon/cover_art.jpg",
      "box_art": "https://path/to/amazon/box_art.jpg",
      "poster_art": "https://path/to/amazon/poster_art.jpg",
      "hero_art": "https://path/to/amazon/hero_art.jpg",
      "title_art": "https://path/to/amazon/title_art.jpg",
      "season_box_art": "https://path/to/amazon/season_box_art.jpg",
      "episodic_art": "https://path/to/amazon/episodic_art.jpg"
    },
    "free": {
      "cover_poster": "https://path/to/free/cover_poster.jpg",
      "cover_wide": "https://path/to/free/cover_wide.jpg",
      "backdrop_wide": "https://path/to/free/backdrop_wide.jpg"
    },
    "molotov": {
      "poster": "https://path/to/molotov/poster.jpg",
      "landscape": "https://path/to/molotov/wallpaper.jpg",
      "backdrop": "https://path/to/molotov/backdrop.jpg"
    },
    "betv": {
      "poster": "https://path/to/betv/poster.jpg",
      "wallpaper": "https://path/to/betv/wallpaper.jpg"
    }
  }
}
```

Identifiers

Identifiers are used to identify contents and people.

Usage by partner:

Identifier	Amazon	Free	Molotov	Betv	Allociné	Justwatch	Google
imdb	✓	✓	✓		✓	✓	✓
tmdb		✓	✓			✓	
allocine		✓	✓		✓		
eidr	✓		✓		✓	✓	✓
isan	✓		✓	✓	✓		
plurimedia		✓	✓				
tms		✓					✓
tvdb		✓					
webedia					✓		

▼ Example payload:

```
"identifiers": {
  "imdb": "10403420",
  "tmdb": "663712",
  "allocine": "285418",
  "eidr": null,
  "isan": "0000-0004-903B-0000-Y-0000-0000-9",
  "plurimedia": null,
  "tms": null,
}
```

```

    "tvdb": null,
    "webedia": null
  }

```

Listing & filtering contents

GET /contents returns your contents, paginated.

Pagination (query params):

- page — page number (default 1)
- per_page — items per page (default 10)

The response includes a pagination object: count, current_page, first_item, last_item, last_page, per_page, total, total_pages.

Filters (query params):

- type — filter by content type (program, serie, season, episode)
- parent_external_id — only the children of this parent (e.g. a serie's seasons, a season's episodes)
- light — true returns a lightweight version of each content (base fields + title only), omitting metadata, images, videos, availabilities and identifiers. Useful for fast listing/sync. Also available on GET /contents/{externalId}.

Videos

 <https://partner-service-develop.preprod.otto.vodfactory.com/docs/index.html#videos-POSTapi-contents--contentId--videos>

Attributes

Label	Description	Required
external_id		✓
partner	amazon, free, molotov, or betv	✓
type	main, bonus, or trailer	✓
url	Direct URL to the video file (.mp4, .mov...). s3:// or http(s)	✓
dash_url	URL to a DASH manifest (.mpd, http(s) only)	Optional
duration		✓
is_drmised	The video has DRM	
drm_key_id		If DRM
drm_key		If DRM
drm_initialization_vector		If DRM

url vs dash_url: url is the direct link to your video file and is always required. dash_url is optional and sent in addition to url — use it when your video is delivered as a DASH package (.mpd) that must be ingested and un-packaged before distribution (applies to main and bonus videos). When dash_url is set, the video is pulled and un-packaged from the manifest instead of transferring the file directly.

DRM

If your source video is encrypted, set is_drmised to true and provide the decryption key so we can process it:

- drm_key_id — the Key ID (KID). Required if DRM.
- drm_key — the content key. Required if DRM.
- drm_initialization_vector — the initialization vector (IV). Optional.

All three are strings (max 50 characters).

Create a video

You must create a content item before creating a video linked to it.

POST <https://otto-partner.vodfactory.com/api/contents/{externalId}/videos>

▼ Example payload to create a video:

```
{
  "external_id": "1234",
  "partner": "amazon",
  "type": "main", // main, trailer or bonus
  "url": "s3://bucket/path/to/video.mp4",
  "duration": 3600, // In seconds
  "subtitles": [
    {
      "external_id": "9876",
      "language_code": "fr-FR", // Amazon code
      "version": "normal", // normal, sdh, forced
      "url": "http://path/to/subtitle_fr.vtt" // Or s3:// url
    }
  ],
  "audios": [
    {
      "external_id": "6543",
      "language_code": "fr-FR",
      "url": "http://path/to/audio_fr.wav" // Or s3:// url
    }
  ],
  "audiotracks": [
    {
      "language_code": "en-US",
      "is_original_version": true
    },
    {
      "language_code": "fr-FR",
      "is_original_version": false
    }
  ]
}
```

In the URL, `externalId` corresponds to the external ID of the content.

▼ Create a standalone video

You can create a video without linking it directly to a content item:

POST <https://otto-partner.vodfactory.com/api/contents/videos>

To link it to a content later, send the video's external ID in the content payload:

```
{
  "title": "Lorem Ipsum",
  "video": {
    "amazon": {
      "main": "1234", // video external ID
      "trailer": ["6545", "9876"] // external IDs
    },
    "free": {
      "main": "4567"
    }
  }
}
```

```
}  
}
```

Subtitles

Subtitle types

- "normal": spoken dialogue
- "sdh": deaf and hard of hearing
- "forced": Forced Narratives (forced subtitles)

Supported formats

- Amazon: srt
- Free: vtt and ttml

▼ Example payload:

```
{  
  "subtitles": [  
    {  
      "external_id": "654",  
      "language_code": "fr-FR",  
      "url": "s3://bucket/path/to/subtitles_fr-fr.srt"  
    },  
    {  
      "external_id": "655",  
      "language_code": "fr-FR",  
      "version": "sdh",  
      "url": "s3://bucket/path/to/subtitles_fr-fr.srt"  
    },  
    {  
      "external_id": "656",  
      "language_code": "en-US",  
      "url": "http://example.org/subtitles/en-us.srt"  
    }  
  ]  
}
```

Audio tracks

The list of audio tracks must be provided.

▼ Example payload:

```
{  
  "audiotracks": [  
    {  
      "language_code": "en-US",  
      "is_original_version": true  
    },  
    {  
      "language_code": "fr-FR"  
    }  
  ]  
}
```

Audio files

Required only for Amazon videos.

Amazon

Supported formats:

- PCM (ipcm) audio in a QuickTime .mov container
- PCM (ipcm) audio in an MPEG-2 transport stream
- AAC audio in an .mp4 container
- PCM (ipcm) audio in a self-contained .wav file

▼ Amazon requires separate audio files, except for the original audio version, so you must specify them in the payload:

```
{
  "audios": [
    {
      "external_id": "567",
      "language_code": "fr-FR",
      "url": "s3://bucket/path/to/audio_fr-fr.mp4"
    },
    {
      "external_id": "568",
      "language_code": "fr-BE",
      "url": "s3://bucket/path/to/audio_fr-be.mp4"
    }
  ]
}
```

Delivering to partners

Automation

Once a day (at midnight), every content modified in the last 24 hours is sent to partners.

Depending on what has changed, only certain files will be sent.

For example, if you update only the availability dates of your content, only the avails files will be sent to Amazon.

If you update the metadata of your content, only the MEC file will be sent to Amazon.

If you update the subtitles of a video already sent, only the new subtitles will be sent to Amazon.

Send manually to partners

If you don't want to wait for automation, you can send your content to partners manually.

Available actions

For Amazon, you can send a specific action or all actions.

For Free, Molotov, and Bets, there is only one action.

- Amazon
 - *amazon_avails*: update availability dates only
 - *amazon_data*: update MEC file (metadata) only
 - *amazon_pictures*: update pictures only
 - *amazon_videos*: update MMC file and videos only
- Free:
 - *free_videos_send*: send videos and their subtitles to Free, then encode

- *free_videos_encode*: encode already delivered videos only (force re-encoding)
- *free_subtitles_encode*: update the encoded video with new subtitles only
- Molotov:
 - *molotov*: send all. Metadata, images, and videos
 - *molotov_update*: update metadata and images only
- Betv:
 - *betv*: send all. Metadata, images, and videos
 - *betv_update*: update metadata and images only

Send

POST <https://otto-partner.vodfactory.com/api/contents/{externalId}/send>

```
{
  "amazon_avails": true,
  "amazon_data": true,
  "amazon_pictures": true,
  "amazon_videos": true,
  "free_videos_send": true,
  "molotov": true,
  "betv": true
}
```

By default, an already delivered video/asset won't be resent. Add `force_send_amazon` or `force_send_free` (boolean) to the payload above to force a resend to that partner.

Unpublish

You can unpublish content from partner(s).

POST <https://otto-partner.vodfactory.com/api/contents/{externalId}/unpublish>

```
{
  "partners": [
    "amazon" // Partners list
  ],
  "country_code": "FRA", // Only for Amazon
  "amazon_full_delete": false // Delete all delivered files
}
```

For each partner, this sets the availability end date to yesterday and then sends the files to the partners.

Delivery statuses

You can check the delivery statuses of your content.

You will know if your content can be sent (all required data is set) and whether it has been sent successfully.

Check these statuses before sending your content manually.

You can see why your content wasn't sent automatically... : missing metadata, missing pictures, process errors, etc.

Getting delivery statuses

GET <https://otto-partner.vodfactory.com/api/contents/{externalId}/action-statuses>

You will receive a response in which each action has its status.

▼ Complete example:

```
{
  "status": "success",
  "results": {
    "amazon": {
      "enabled": true,
      "status": "incomplete",
      "sent_at": null,
      "message": null,
      "actions": {
        "amazon_avails": {
          "enabled": true, // Amazon is activated and the availability dates a
re set

          "status": "success", // The files have been sent
          "sent_at": "2025-04-09T16:26:13.000000Z", // Datetime when the files
were sent

          "message": null // No error message
        },
        "amazon_data": {
          "enabled": true, // All required metadata is set
          "status": "ready", // The files have not been sent yet
          "sent_at": null, // Not sent yet
          "message": null // No error message
        },
        "amazon_pictures": {
          "enabled": true, // All required pictures are set
          "status": "ready", // The files have not been sent yet
          "sent_at": null, // Not sent yet
          "message": null // No error message
        },
        "amazon_videos": {
          "enabled": false, // Cannot send because the content has no Amazon v
ideo

          "status": "incomplete", // Video missing
          "sent_at": null,
          "message": "No video found"
        }
      }
    },
    "free": {
      "enabled": true,
      "status": "success",
      "sent_at": "2025-04-09T16:26:13.000000Z",
      "message": null,
      "actions": {
        "free_videos_send": {
          "enabled": true,
          "status": "ready",
          "sent_at": null,
          "message": null
        },
        "free_videos_encode": {
          "enabled": false,
          "status": "incomplete",
          "sent_at": null,
          "message": "Video not delivered"
        }
      }
    }
  }
}
```

```

        "free_subtitles_encode": {
            "enabled": false,
            "status": "incomplete",
            "sent_at": null,
            "message": "Video not encoded"
        }
    },
    "molotov": {
        "enabled": true,
        "status": "success",
        "sent_at": "2025-04-09T16:26:13.000000Z",
        "message": null,
        "actions": {
            "molotov_update": {
                "enabled": true,
                "status": "ready",
                "sent_at": null,
                "message": null
            }
        }
    },
    "betv": {
        "enabled": false,
        "status": "incomplete",
        "sent_at": null,
        "message": null,
        "actions": {
            "betv_update": {
                "enabled": false,
                "status": "not_created",
                "sent_at": null,
                "message": null
            }
        }
    }
},
"warnings": [],
"errors": []
}

```

Getting notified via callback

Instead of polling `GET /contents/{externalId}/action-statuses`, you can be notified directly when a transfer or ingest to a partner completes.

This callback is configured per platform on our side (URL, HTTP method, optional custom headers) — contact us to set it up or change it.

We call your URL once per `partner` + `action` pair, only when it reaches a final state (`success` or `error`), never for intermediate states. A single transfer can involve several actions (for example, Amazon: avails, data, pictures, videos), so you may receive several calls for the same content.

▼ Example payload :

```

{
  "occurred_at": "2026-08-10T10:15:00+00:00",
  "content": {
    "external_id": "ABC123",

```

```

    "sku_code": "the_content_sku",
    "title": "The content title"
  },
  "partner": "amazon",
  "action": "amazon_avails",
  "status": "success",
  "error_message": null,
  "sent_at": "2026-08-10T10:14:58+00:00"
}

```

`error_message` is only filled when `status` is `"error"`.

This is a best-effort notification: we make a single attempt and do not retry on failure. If your endpoint was unreachable at the time, fall back on `GET /contents/{id}/action-statuses` for that transfer.

Partner specifications

Partners fall into two categories:

- Distribution partners (Amazon, Free, Molotov, Betcv): you deliver the full content — metadata, images and video files. Each has its own technical specifications below.
- Discovery partners (Allociné, Justwatch, SamsungTV): they only reference your catalog (no video delivery). Your content just needs to be valid for them — see the validation rules per partner below.

▼ Amazon

Amazon Video Specifications

Quality	Minimum resolution	Codec / Container	Minimum / Preferred bitrate	Key technical points
4K UHD	≥ 3840×2160	ProRes 422 HQ, MOV	≥ 250 Mbps	Rec. 2020 / DCI-P3, 10-bit, 4:2:2, progressive
4K HDR	≥ 3840×2160	ProRes 422 HQ	≥ 250 Mbps	HDR metadata, Legal YUV, MaxCLL/FALL, etc.
HD	≥ 1280×720	ProRes 422 HQ, MPEG-2, H.264	20–88 Mbps	Rec. 709, variable fps, multiple containers
SD	≥ 640×260	Same as HD	10–50 Mbps	Rec. 601, interlaced allowed
Audio	—	PCM, MPEG-2 Layer II, AC-3, AAC	192–960 kbps	48 kHz, 16–24 bit, mono / stereo / 5.1
Subtitles	—	TTML, SCC, STL, WebVTT, SRT	—	Must be time-coded, language-tagged, include SDH/CC when required

More details on the media technical specifications

 [Media Technical Standards - Amazon Prime Video](#)

People

Amazon requires at least one director. Others are optional.

Amazon genres

Find the full list of codes: <https://m.media-amazon.com/images/G/01/CooperWebsite/dvp/downloads/Genres.xlsx>

You can get the full list with the endpoint: GET `/api/amazon/genres`:

```
{
  "status": "success",
  "results": [
    {
      "code": "av_genre_action",
      "breadcrumb": "Action/Adventure",
      "definition": "Action - Fictional titles that feature a number of spectacular
and/or destructive action sequences in which a heroic character is pitted against a force or enemy of some kind, resulting in physical confrontations and challenges often with overwhelming odds against the hero."
    },
    {
      "code": "av_subgenre_action_comedy",
      "breadcrumb": "Action/Adventure > Comedy",
      "definition": "Action - Comedy - Action-based, fictional titles with an added
comedic element. These types of titles usually involve the hero engaging in physical situations while spouting witty or clever dialogue."
    }
  ]
}
```

You can get details of each genre by calling: GET `/api/amazon/genres/{code}` :

```
{
  "status": "success",
  "results": {
    "code": "av_genre_action",
    "breadcrumb": "Action/Adventure",
    "definition": "Action - Fictional titles that feature a number of spectacular and/
or destructive action sequences in which a heroic character is pitted against a force or enemy of some kind, resulting in physical confrontations and challenges often with overwhelming odds against the hero."
  }
}
```

▼ Free TV

Your content will appear in search only if you provide a Plurimedia identifier.

You need at least one plan.

▼ Plans

You can manage plans with the `api/plans` endpoints.

- external_id: your ID
- price: the price of the plan in cents (999 for €9.99). Required
- name: the unique name of the plan. Required
- description: short description. Required
- price_description: description of the price. Optional
- starts_at: the start date of the plan. Required
- ends_at: the end date of the plan. Optional

▼ Animation - Build your rows

FreeTV lets you define the editorial configuration of your portal.

You can configure the appearance and organize how your content is presented.

Create blocks (rows) with items.

A block can be of type "row" (multiple items) or "banner" (one item).

An item can be a content item (program, serie, season) or a "heading" (group of contents).



<https://partner-service-develop.preprod.otto.vodfactory.com/docs/index.html#free-blocks-POSTapi-free-blocks>

Create a block with items

POST <https://otto-partner.vodfactory.com/api/free/blocks>

```
{
  "external_id": "1234",
  "type": "row", // "row" or "banner"
  "image_format": "auto", // "auto" (recommended), "poster", "wide"
  "title": "Our latest content",
  "rank": 1,
  "items": [
    {
      "external_id": "456",
      "rank": 1,
      "content_external_id": "789" // The external ID of the content
    },
    {
      "external_id": "963",
      "rank": 2,
      "content_external_id": "790"
    }
  ]
}
```

Headings



<https://partner-service-develop.preprod.otto.vodfactory.com/docs/index.html#free-headings-GETapi-free-headings--id->

You can group content into "Free headings". It works like a category.

POST <https://otto-partner.vodfactory.com/api/free/headings>

```
{
  "external_id": "987654",
  "display_format": "grid", // "grid" or "rows"
  "image_format": "auto",
  "title": "Horror movies",
  "images": {
    "cover_poster": "https://path/to/free/cover_poster.jpg",
    "cover_wide": "https://path/to/free/cover_wide.jpg"
  },
  "contents": [
    {
      "external_id": "789",
      "rank": 1
    },
    {
      "external_id": "790",

```

```

    "rank": 2
  }
]
}

```

Then you can add this heading to a block:

POST <https://otto-partner.vodfactory.com/api/free/blocks>

```

{
  "external_id": "1235",
  "type": "row",
  "image_format": "auto",
  "title": "Our categories",
  "rank": 2,
  "items": [
    {
      "external_id": "457",
      "rank": 1,
      "heading_external_id": "987654" // The external ID of the heading
    }
  ]
}

```

▼ Automation

For Free, there is no need to send metadata and images to the partner. The partner fetches this information from the API once a day at night.

Once you update your content on the Partner API, it can take up to 48 hours to be updated on the FreeTV platform.

▼ FreeTV Video Specifications

Quality	Minimum resolution	Codec / Container	Bitrate (Min / Rec.)	Key technical points
Full HD	1920×1080	MP4 (AVC / HEVC High Profile)	≥ 30 Mbps	GOP ≤ 2s. Aspect ratio 16:9. Progressive scan. Natural framerate (24/25/30/50/60 supported)
Audio	—	HE-AAC / AAC / AC-3	Stereo: AC-3 192 kbps / AAC 320 kbps 5.1: AC-3 448 kbps / AAC 768 kbps	Up to 5.1 channels. 48 kHz sampling. Language tag per track in MP4. Audio levels must comply with EBU R128 / ITU-R BS.1770 (LUFS -23, peak -3 dB)
Subtitles	—	WebVTT, TTML (IMSC1 text profile only)	—	Standalone files (1 per language and version). Types: standard / hearing impaired (sme). Paths in S3 bucket must be declared in encoding task

More details on the media technical specifications

 [Media Technical Standards for FreeTV Integration](#)

▼ Molotov

Animation

Molotov lets you define the editorial configuration of your portal.

You can configure the appearance and organize how your content is presented.

Create blocks (rows) with items.



<https://partner-service-develop.preprod.otto.vodfactory.com/docs/index.html#free-blocks-POSTapi-molotov-blocks>

Molotov Tags

Molotov tags are a custom list of tags.

Molotov Video Specifications

Quality	Minimum resolution	Codec / Container	Minimum / Preferred bitrate	Key technical points
HD	1920×1080	H.264, MPEG-2 (in MP4 or TS)	10–50 Mbps	Progressive, mixed audio and video in the same file
Audio	—	AAC, AC-3, MPEG Audio (inside MP4/TS)	Stereo / 5.1 (in a single audio track)	Multi-audio allowed. Each audio track must have a language tag
Subtitles	—	SRT, VTT, STL	—	Separate subtitle file, language-tagged. Types: standard / CC (hard of hearing) / forced narrative

▼ Betv

Betv Video Specifications

Quality	Minimum resolution	Codec / Container	Bitrate (Max / Rules)	Key technical points
SD	720×576 (PAL)	H.264 MP@L3.1 (AVC), MPEG-2 TS (SPTS)	≤ 2.5 Mbps (CBR only)	Aspect ratio 16:9 or 4:3. I-frame every 0.5–1s. Multiplexed audio and video. No VBR allowed
HD	1920×1080 (PAL)	H.264 High@L4.0 (AVC), MPEG-2 TS (SPTS)	≤ 7.5 Mbps (CBR only)	Aspect ratio 16:9. I-frame every 0.5–1s. Same transport rules as SD
Audio	—	Dolby AC-3 stereo (2.0) or 5.1	192 kbps (stereo), 384 kbps (5.1)	French audio mandatory if available. If only OV, French subs must be burned in
Subtitles	—	DVB Bitmap (in TS). For OTT: PAC, SRT, STL	~200 kbps (bitmap in TS)	If no FR audio → burned-in French subs required. If multi-language → separate DVB subtitling or text files for OTT
Age rating	—	Burned-in icon (CSA rules)	—	Logo must be visible bottom-right during the entire program (10, 12, 16, 18)

▼ Allociné

Once a day, all the contents will be sent to Allociné.

To be valid, each content needs to have at least one identity, have availabilities and have all required metadatas (title, original title, release date, directors and front url).

▼ Justwatch

Each day, all the contents will be get by Justwatch.

To be valid, each content needs to have at least one identity, have availabilities and have all required metadatas (title & synopsis).

▼ SamsungTV

Each day, all the contents will be get by SamsungTV.

To be valid, each content needs to have availabilities and : a TMS identity OR a title + images.

Glossary

- **Avails** — availability (licensing) windows: when and where a content can be watched. The avails file is the document sent to Amazon listing these windows.
- **MEC (Media Entertainment Core)** — the XML metadata file sent to Amazon (title, synopsis, cast, genres...).
- **MMC (Media Manifest Core)** — the XML manifest sent to Amazon that maps a content's media files (video, audio, subtitles).
- **SVOD** — Subscription Video On Demand: the license type used for availabilities.
- **SDH** — Subtitles for the Deaf and Hard of hearing.

▼ Documentation changelog

Version	Date	Description
1.1.1	2026-08-10	API callback
1.1.0	2026-06-25	Improvements
1.0.9	2026-05-21	SamsungTV details added
1.0.8	2026-03-19	MCP server (AI)
1.0.7	2025-12-30	Availabilities end dates are now not required
1.0.6	2025-12-24	Justwatch details added
1.0.5	2025-11-11	Add new molotov image format specs : "poster_23"
1.0.4	2025-11-10	Edited payloads, as external_id and parent_external_id are now strings
1.0.3	2025-10-20	Allociné details added
1.0.2	2025-09-10	Molotov blocks informations added.
1.0.1	2025-09-09	Metadata "Genres" added. Persons : details added for each field.

▼ API changelog

Version	Date	Description
1.3.0	2026-08-10	New POST <code>/contents/{externalId}/send</code> parameters <code>force_send_amazon</code> and <code>force_send_free</code> to force resend an already delivered video/asset to Amazon or Free. New transfer/ingest callback : once a transfer or ingest to a partner reaches a final state (success or error), we call back a URL on your side, so you don't have to poll GET <code>/contents/{id}/action-statuses</code> .
1.1.0	2026-07-10	Availabilities now support more licence types: AVOD, FVOD, VOD, EST, POEST (in addition to SVOD). New pricing fields on availabilities: <code>price_value</code> and <code>price_currency</code> (public price, VAT included) — required when the licence type is transactional (VOD, EST, POEST), not allowed otherwise. Returned in GET responses for those licence types. Supported currencies: EUR (default), CHF, GBP, USD, CAD, SEK. API rate limiting: 120 requests per minute per API key. Responses include <code>X-RateLimit-Limit</code> / <code>X-RateLimit-Remaining</code> headers; exceeding the limit returns a 429 with a <code>Retry-After</code> header.
1.0.4	2026-06-18	MCP server (AI): connect an AI assistant (Claude, Cursor...) directly to the API via the MCP protocol
1.0.0	2026-06-17	Ottomate
0.9.0	2026-05-21	SamsungTV feature added
0.8.15	2026-05-18	Amazon subtitles in trailers must be burned into the video
0.7.0	2026-01-08	Justwatch feature added + new param "light" in endpoint GET "contents"
0.6.0	2025-12-30	Availabilities end dates are now not required
0.5.0	2025-12-02	Daily reports can now be sent by email
0.4.1	2025-11-11	New Molotov image format : "poster_23" with ratio 2/3

0.4.0	2025-11-10	All the attributes external_id and parent_external_id are now strings
0.3.0	2025-10-20	Allociné feature added
0.2.0	2025-09-29	Metadata "Genres" added. Endpoint "/api/genres" to get the full list.
0.1.3	2025-08-27	API Doc fixes. Rules fixes. Add person identifiers in Amazon MEC.
0.1.2	2025-08-20	Update required metadatas list