



IBM Developer
SKILLS NETWORK

Winning Space Race with Data Science

Abdihamid Ali
30th Nov 2023



Outline

- Executive Summary
- Introduction
- Methodology
- Results
- Conclusion
- Appendix

Executive Summary

- Summary of methodologies
 - Data Collection through API
 - Data Collection with Web Scraping
 - Data Wrangling
 - Exploratory Data Analysis with SQL
 - Exploratory Data Analysis with Data Visualization
 - Interactive Visual Analytics with Folium
 - Machine Learning Prediction
- Summary of all results
 - Exploratory Data Analysis result
 - Interactive analytics in screenshots
 - Predictive Analytics result

Introduction

- Project background and context

Space X advertises Falcon 9 rocket launches on its website with a cost of 62 million dollars; other providers cost upward of 165 million dollars each, much of the savings is because Space X can reuse the first stage. Therefore, if we can determine if the first stage will land, we can determine the cost of a launch. This information can be used if an alternate company wants to bid against space X for a rocket launch. This goal of the project is to create a machine learning pipeline to predict if the first stage will land successfully.

- Problems you want to find answers

- What factors determine if the rocket will land successfully?
- The interaction amongst various features that determine the success rate of a successful landing.
- What operating conditions needs to be in place to ensure a successful landing program.

Section 1

Methodology

Methodology

Executive Summary

- Data collection methodology:
 - Data was collected using SpaceX API and web scraping from Wikipedia.
- Perform data wrangling
 - One-hot encoding was applied to categorical features
- Perform exploratory data analysis (EDA) using visualization and SQL
- Perform interactive visual analytics using Folium and Plotly Dash
- Perform predictive analysis using classification models
 - How to build, tune, evaluate classification models

Data Collection

- The data was collected using various methods
 - Data collection was done using get request to the SpaceX API.
 - Next, we decoded the response content as a Json using `.json()` function call and turn it into a pandas dataframe using `.json_normalize()`.
 - We then cleaned the data, checked for missing values and fill in missing values where necessary.
 - In addition, we performed web scraping from Wikipedia for Falcon 9 launch records with BeautifulSoup.
 - The objective was to extract the launch records as HTML table, parse the table and convert it to a pandas dataframe for future analysis.

Data Collection – SpaceX API

- We used the get request to the SpaceX API to collect data, clean the requested data and did some basic data wrangling and formatting.
- The link to the notebook is https://github.com/Farah100/Final_presentation/blob/main/spaceX_Data_collection.ipynb

1. Get request for rocket launch data using API

```
In [6]: spacex_url="https://api.spacexdata.com/v4/launches/past"
```

```
In [7]: response = requests.get(spacex_url)
```

2. Use json_normalize method to convert json result to dataframe

```
In [12]: # Use json_normalize method to convert the json result into a dataframe  
# decode response content as json  
static_json_df = res.json()
```

```
In [13]: # apply json_normalize  
data = pd.json_normalize(static_json_df)
```

3. We then performed data cleaning and filling in the missing values

```
In [30]: rows = data_falcon9['PayloadMass'].values.tolist()[0]  
  
df_rows = pd.DataFrame(rows)  
df_rows = df_rows.replace(np.nan, PayloadMass)  
  
data_falcon9['PayloadMass'][0] = df_rows.values  
data_falcon9
```


Data Collection - WebScraping

- We applied web scrapping to webscrap Falcon 9 launch records with BeautifulSoup
- We parsed the table and converted it into a pandas dataframe.
- The link to the notebook is https://github.com/Farah100/Final_presentation/blob/main/spaceX_web_scrapping.ipynb

```
1. Apply HTTP Get method to request the Falcon 9 rocket launch page

In [4]: static_url = "https://en.wikipedia.org/w/index.php?title=List_of_Falcon_9_and_Falcon_Heavy_launches&oldid=1027686922"

In [5]: # use requests.get() method with the provided static_url
        # assign the response to a object
        html_data = requests.get(static_url)
        html_data.status_code

Out[5]: 200

2. Create a BeautifulSoup object from the HTML response

In [6]: # Use BeautifulSoup() to create a BeautifulSoup object from a response text content
        soup = BeautifulSoup(html_data.text, 'html.parser')

        Print the page title to verify if the BeautifulSoup object was created properly

In [7]: # Use soup.title attribute
        soup.title

Out[7]: <title>List of Falcon 9 and Falcon Heavy launches - Wikipedia</title>

3. Extract all column names from the HTML table header


In [10]: column_names = []

        # Apply find_all() function with 'th' element on first_launch_table
        # Iterate each th element and apply the provided extract_column_from_header() to get a column name
        # Append the Non-empty column name ('if name is not None and len(name) > 0') into a list called column_names

        element = soup.find_all('th')
        for row in range(len(element)):
            try:
                name = extract_column_from_header(element[row])
                if (name is not None and len(name) > 0):
                    column_names.append(name)
            except:
                pass

4. Create a dataframe by parsing the launch HTML tables
5. Export data to csv
```


Data Wrangling



- We performed exploratory data analysis and determined the training labels.
- We calculated the number of launches at each site, and the number and occurrence of each orbits
- We created landing outcome label from outcome column and exported the results to CSV.
- The link to the notebook is https://github.com/Farah100/Final_presentation/blob/main/spaceX_Data_wrangling.ipynb

EDA with Data Visualization

- We explored the data by visualizing the relationship between flight number and launch Site, payload and launch site, success rate of each orbit type, flight number and orbit type, the launch success yearly trend.



- The link to the notebook is https://github.com/Farah100/Final_presentation/blob/main/spaceX_exploring%26preppingdata.ipynb

EDA with SQL

- We loaded the SpaceX dataset into a PostgreSQL database without leaving the jupyter notebook.
- We applied EDA with SQL to get insight from the data. We wrote queries to find out for instance:
 - The names of unique launch sites in the space mission.
 - The total payload mass carried by boosters launched by NASA (CRS)
 - The average payload mass carried by booster version F9 v1.1
 - The total number of successful and failure mission outcomes
 - The failed landing outcomes in drone ship, their booster version and launch site names.
- The link to the notebook is
https://github.com/Farah100/Final_presentation/blob/main/spaceXSQL.ipynb

Build an Interactive Map with Folium

- We marked all launch sites, and added map objects such as markers, circles, lines to mark the success or failure of launches for each site on the folium map.
- We assigned the feature launch outcomes (failure or success) to class 0 and 1.i.e., 0 for failure, and 1 for success.
- Using the color-labeled marker clusters, we identified which launch sites have relatively high success rate.
- We calculated the distances between a launch site to its proximities. We answered some question for instance:
 - Are launch sites near railways, highways and coastlines.
 - Do launch sites keep certain distance away from cities.
- The link to the notebook is
https://github.com/Farah100/Final_presentation/blob/main/spaceX_visualization_with_folium.ipynb

Build a Dashboard with Plotly Dash

- We developed an interactive dashboard using Plotly Dash. Within the dashboard, we utilized pie charts to visually represent the total number of launches categorized by specific sites. Additionally, we generated scatter graphs to illustrate the correlation between Outcome and Payload Mass (in kilograms) across various booster versions.
- The link to the notebook is
https://github.com/Farah100/Final_presentation/blob/main/spaceX_plotly.py

Predictive Analysis (Classification)

- We loaded the data using numpy and pandas, transformed the data, split our data into training and testing.
- We built different machine learning models and tune different hyperparameters using GridSearchCV.
- We used accuracy as the metric for our model, improved the model using feature engineering and algorithm tuning.
- We found the best performing classification model.
- The link to the notebook is
[*https://github.com/Farah100/Final_presentation/blob/main/spaceX_prediction.ipynb*](https://github.com/Farah100/Final_presentation/blob/main/spaceX_prediction.ipynb)

Results

- Exploratory data analysis results
- Interactive analytics demo in screenshots
- Predictive analysis results




Section 2


Insights drawn from EDA

Flight Number vs. Launch Site

By examining the plot, it became evident that a higher number of flights at a launch site corresponds to a higher success rate at that particular site.




Payload vs Launch Site



The success rate of the rocket increases with the greater payload mass at launch site CCAFS SLC 40.


Success Rate vs. Orbit Type

The plot illustrates that ES-L1, GEO, HEO, SSO, and VLEO exhibit the highest success rates.




Flight Number vs. Orbit Type

The plot below illustrates the correlation between Flight Number and Orbit type. It is evident that in the LEO orbit, success is associated with the number of flights, while in the GTO orbit, there is no discernible relationship between flight number and orbit




Payload vs. Orbit Type

It can be noted that successful landings are more prevalent for payloads with substantial weight in the PO, LEO, and ISS orbits.



Launch Success Yearly Trend

The graph indicates a continuous increase in success rates from 2013 to 2020.



All Launch Site Names

The keyword DISTINCT was employed to display only unique launch sites from the SpaceX data.

Display the names of the unique launch sites in the space mission

```
In [10]: task_1 = '''  
          SELECT DISTINCT LaunchSite  
          FROM SpaceX  
          ...  
          create_pandas_df(task_1, database=conn)
```

```
Out[10]:
```

	launchsite
0	KSC LC-39A
1	CCAFS LC-40
2	CCAFS SLC-40
3	VAFB SLC-4E

Launch Site Names Begin with 'CCA'

We employed the below query to present five records featuring launch sites that start with 'CCA'.

Display 5 records where launch sites begin with the string 'CCA'

In [11]:

```
task_2 = '''
    SELECT *
    FROM SpaceX
    WHERE LaunchSite LIKE 'CCA%'
    LIMIT 5
    '''

create_pandas_df(task_2, database=conn)
```

Out[11]:

	date	time	boosterversion	launchsite	payload	payloadmasskg	orbit	customer	missionoutcome	landingoutcome
0	2010-04-06	18:45:00	F9 v1.0 B0003	CCAFS LC-40	Dragon Spacecraft Qualification Unit	0	LEO	SpaceX	Success	Failure (parachute)
1	2010-08-12	15:43:00	F9 v1.0 B0004	CCAFS LC-40	Dragon demo flight C1, two CubeSats, barrel of...	0	LEO (ISS)	NASA (COTS) NRO	Success	Failure (parachute)
2	2012-05-22	07:44:00	F9 v1.0 B0005	CCAFS LC-40	Dragon demo flight C2	525	LEO (ISS)	NASA (COTS)	Success	No attempt
3	2012-08-10	00:35:00	F9 v1.0 B0006	CCAFS LC-40	SpaceX CRS-1	500	LEO (ISS)	NASA (CRS)	Success	No attempt
4	2013-01-03	15:10:00	F9 v1.0 B0007	CCAFS LC-40	SpaceX CRS-2	677	LEO (ISS)	NASA (CRS)	Success	No attempt

Total Payload Mass

The total payload transported by NASA boosters was computed as 45,596 using the following query:

```
Display the total payload mass carried by boosters launched by NASA (CRS)

In [12]: task_3 = '''
          SELECT SUM(PayloadMassKG) AS Total_PayloadMass
          FROM SpaceX
          WHERE Customer LIKE 'NASA (CRS)'
          '''
          create_pandas_df(task_3, database=conn)

Out[12]:
```

	total_payloadmass
0	45596

Average Payload Mass by F9 v1.1

The average payload mass transported by the booster version F9 v1.1 was calculated to be 2,928.4.

```
Display average payload mass carried by booster version F9 v1.1

In [13]: task_4 = '''
          SELECT AVG(PayloadMassKG) AS Avg_PayloadMass
          FROM SpaceX
          WHERE BoosterVersion = 'F9 v1.1'
          '''
          create_pandas_df(task_4, database=conn)

Out[13]: avg_payloadmass
0        2928.4
```

First Successful Ground Landing Date

We observed that the dates of the first successful landing outcome on ground pad was 22nd December 2015

```
In [14]: task_5 = '''
          SELECT MIN(Date) AS FirstSuccessfull_landing_date
          FROM SpaceX
          WHERE LandingOutcome LIKE 'Success (ground pad)'
          '''
          create_pandas_df(task_5, database=conn)
```

```
Out[14]:
```

	firstsuccessfull_landing_date
0	2015-12-22

Successful Drone Ship Landing with Payload between 4000 and 6000

We employed the WHERE clause to narrow down boosters that achieved a successful landing on a drone ship. Additionally, we applied the AND condition to identify successful landings with a payload mass exceeding 4000 but less than 6000.

```
In [15]: task_6 = '''
          SELECT BoosterVersion
          FROM SpaceX
          WHERE LandingOutcome = 'Success (drone ship)'
              AND PayloadMassKG > 4000
              AND PayloadMassKG < 6000
          ...
          create_pandas_df(task_6, database=conn)
```

```
Out[15]:
```

	boosterversion
0	F9 FT B1022
1	F9 FT B1026
2	F9 FT B1021.2
3	F9 FT B1031.2

Total Number of Successful and Failure Mission Outcomes

We utilized wildcard characters such as '%' to filter records where the MissionOutcome was either a success or a failure.

List the total number of successful and failure mission outcomes

```
In [16]: task_7a = '''
          SELECT COUNT(MissionOutcome) AS SuccessOutcome
          FROM SpaceX
          WHERE MissionOutcome LIKE 'Success%'
          '''

          task_7b = '''
          SELECT COUNT(MissionOutcome) AS FailureOutcome
          FROM SpaceX
          WHERE MissionOutcome LIKE 'Failure%'
          '''

          print('The total number of successful mission outcome is:')
          display(create_pandas_df(task_7a, database=conn))
          print()
          print('The total number of failed mission outcome is:')
          create_pandas_df(task_7b, database=conn)
```

The total number of successful mission outcome is:

	successoutcome
0	100

The total number of failed mission outcome is:

```
Out[16]:
```

	failureoutcome
0	1

Boosters Carried Maximum Payload

We identified the booster that carried the maximum payload by employing a subquery within the WHERE clause along with the MAX() function.

List the names of the booster_versions which have carried the maximum payload mass. Use a subquery

```
In [17]: task_8 = '''
          SELECT BoosterVersion, PayloadMassKG
          FROM SpaceX
          WHERE PayloadMassKG = (
                                SELECT MAX(PayloadMassKG)
                                FROM SpaceX
                              )
          ORDER BY BoosterVersion
          '''
          create_pandas_df(task_8, database=conn)
```

```
Out[17]:
```

	boosterversion	payloadmasskg
0	F9 B5 B1048.4	15600
1	F9 B5 B1048.5	15600
2	F9 B5 B1049.4	15600
3	F9 B5 B1049.5	15600
4	F9 B5 B1049.7	15600
5	F9 B5 B1051.3	15600
6	F9 B5 B1051.4	15600
7	F9 B5 B1051.6	15600
8	F9 B5 B1056.4	15600
9	F9 B5 B1058.3	15600
10	F9 B5 B1060.2	15600
11	F9 B5 B1060.3	15600

2015 Launch Records

We employed a combination of the WHERE clause, LIKE, AND, and BETWEEN conditions to narrow down failed landing outcomes on drone ships, their corresponding booster versions, and launch site names for the year 2015.

```
List the failed landing_outcomes in drone ship, their booster versions, and launch site names for in year 2015

In [18]: task_9 = '''
          SELECT BoosterVersion, LaunchSite, LandingOutcome
          FROM SpaceX
          WHERE LandingOutcome LIKE 'Failure (drone ship)'
              AND Date BETWEEN '2015-01-01' AND '2015-12-31'
          ...
          create_pandas_df(task_9, database=conn)

Out[18]:
```

	boosterversion	launchsite	landingoutcome
0	F9 v1.1 B1012	CCAFS LC-40	Failure (drone ship)
1	F9 v1.1 B1015	CCAFS LC-40	Failure (drone ship)

Rank Landing Outcomes Between 2010-06-04 and 2017-03-20

We chose landing outcomes and the COUNT of landing outcomes from the dataset, utilizing the WHERE clause to focus on landing outcomes between June 4, 2010, and March 20, 2010. Employing the GROUP BY clause, we grouped the landing outcomes, and with the ORDER BY clause, we arranged the grouped landing outcomes in descending order.

Rank the count of landing outcomes (such as Failure (drone ship) or Success (ground pad))

```
In [19]: task_10 = '''
          SELECT LandingOutcome, COUNT(LandingOutcome)
          FROM SpaceX
          WHERE DATE BETWEEN '2010-06-04' AND '2017-03-20'
          GROUP BY LandingOutcome
          ORDER BY COUNT(LandingOutcome) DESC
          '''
          create_pandas_df(task_10, database=conn)
```

```
Out[19]:
```

	landingoutcome	count
0	No attempt	10
1	Success (drone ship)	6
2	Failure (drone ship)	5
3	Success (ground pad)	5
4	Controlled (ocean)	3
5	Uncontrolled (ocean)	2
6	Precluded (drone ship)	1
7	Failure (parachute)	1

Section 4


Launch Sites Proximities Analysis





All launch sites global map markers



Markers showing launch sites with color labels



Launch Site distance to landmarks



- Are launch sites in close proximity to railways? No
- Are launch sites in close proximity to highways? No
- Are launch sites in close proximity to coastline? Yes
- Do launch sites keep certain distance away from cities? Yes




Section 5

Build a Dashboard with Plotly Dash


Pie chart showing the success percentage achieved by each launch site

Total Success Launches By all sites




We can see that KSC LC-39A had the most successful launches from all the sites

Pie chart showing the Launch site with the highest launch success ratio



KSC LC-39A achieved a 76.9% success rate while getting a 23.1% failure rate

Scatter plot of Payload vs Launch Outcome for all sites, with different payload selected in the range slider



We can see the success rates for low weighted payloads is higher than the heavy weighted payloads



Section 6

Predictive Analysis (Classification)

Classification Accuracy

Among the models considered, the decision tree classifier exhibits the highest accuracy in classification.

```
models = {'KNeighbors': knn_cv.best_score_,
          'DecisionTree': tree_cv.best_score_,
          'LogisticRegression': logreg_cv.best_score_,
          'SupportVector': svm_cv.best_score_}


bestalgorithm = max(models, key=models.get)
print('Best model is', bestalgorithm, 'with a score of', models[bestalgorithm])
if bestalgorithm == 'DecisionTree':
    print('Best params is :', tree_cv.best_params_)
if bestalgorithm == 'KNeighbors':
    print('Best params is :', knn_cv.best_params_)
if bestalgorithm == 'LogisticRegression':
    print('Best params is :', logreg_cv.best_params_)
if bestalgorithm == 'SupportVector':
    print('Best params is :', svm_cv.best_params_)
```

Best model is DecisionTree with a score of 0.8732142857142856

Best params is : {'criterion': 'gini', 'max_depth': 6, 'max_features': 'auto', 'min_samples_leaf': 2, 'min_samples_split': 5, 'splitter': 'random'}

Confusion Matrix

The confusion matrix of the decision tree classifier indicates its ability to differentiate between various classes. The primary issue lies in false positives, where unsuccessful landings are incorrectly identified as successful landings by the classifier.



Conclusions

In summary:

- i. A positive correlation is observed between the number of flights at a launch site and the success rate at that site.
- ii. The launch success rate has shown a consistent upward trend from 2013 to 2020.
- iii. Orbits ES-L1, GEO, HEO, SSO, and VLEO exhibit the highest success rates.
- iv. Among all launch sites, KSC LC-39A has recorded the highest number of successful launches.
- v. The Decision tree classifier stands out as the most effective machine learning algorithm for this particular task.

Thank you! 🚀

