

Skip to end of metadata

Created by Faraz Ali, Muhammad, last modified by Jafri, Abbas on Dec 22, 2022

Go to start of metadata

1. Go to PowerShell command line and type `ssh-keygen -b 4096`:

```
PS C:\Users\muhammad.faraz> ssh-keygen -b 4096
```

2. When prompted for a filename or phrase make sure to leave it blank:

```
Generating public/private rsa key pair.  
Enter file in which to save the key (C:\Users\muhammad.faraz/.ssh/id_rsa):  
Enter passphrase (empty for no passphrase):  
Enter same passphrase again:
```

3. The complete output should look like this:

```
PS C:\Users\muhammad.faraz> ssh-keygen -b 4096  
Generating public/private rsa key pair.  
Enter file in which to save the key (C:\Users\muhammad.faraz/.ssh/id_rsa):  
Enter passphrase (empty for no passphrase):  
Enter same passphrase again:  
Your identification has been saved in C:\Users\muhammad.faraz/.ssh/id_rsa.  
Your public key has been saved in C:\Users\muhammad.faraz/.ssh/id_rsa.pub.  
The key fingerprint is:  
SHA256:ybe1hLGhX/RwaJX9A32CvRVpNN76kRMS6shxnJSEJls afiniti\muhammad.faraz@WDC-GD-MUHAMMAD  
The key's randomart image is:  
+---[RSA 4096]-----+  
|  
|  oo.+++o|  
| . Eo.+++++|  
| =.o==.+++|  
| o.o=B +oo+|  
| So+.t o+.|  
| o = . .o|  
| o . .|  
|  
+-----[SHA256]-----+  
PS C:\Users\muhammad.faraz> cd .ssh  
PS C:\Users\muhammad.faraz\.ssh> ls -alh  
Get-ChildItem: A parameter cannot be found that matches parameter name 'alh'.  
PS C:\Users\muhammad.faraz\.ssh> ls  
  
Directory: C:\Users\muhammad.faraz\.ssh  
  
Mode                LastWriteTime         Length Name  
----                -  
-a---             10/31/2022 12:22 PM          3414 id_rsa  
-a---             10/31/2022 12:22 PM           765 id_rsa.pub  
-a---             10/25/2022  5:55 PM          1615 known_hosts
```

4. Navigate to the `.ssh` directory and get the list of files by `dir` or `ls`

5. You can cat id_rsa.pub file for the key, copy the key and go to your Linux machine.
6. Navigate to /home/psg/.ssh
 - a. If the directory does not exist you can make it by mkdir .ssh (chmod 700 ~/.ssh)
7. vi authorized_keys
8. Paste the key at the end if there are already any keys in there
9. Write and quit with ->escape →:wq
10. chmod 600 authorized_keys
11. Now you should be able to ssh into this machine without a password.