NAME	Farhan Amin
REGISTRATION NUMBER	5123574
DPAEPARTMENT	ELECTRICAL (Power)
SECTION	“A”
SEMISTER	2nd
SUBJECT	COMPUTER PROGRAMING

1. Objective

The primary goal of this lab is to master selection and flow control in C++ using the switch statement and its associated keywords. Students will learn to:

- Implement switch as an alternative to multiple if-else blocks.
- Utilize break to manage program flow and prevent "fall-through".
- Apply the continue statement within loops.
- Develop interactive, menu-driven programs.

---

2. Technical Overview

The Switch Statement

The switch statement is a **multiple-selection statement** that executes a specific block of code based on the value of a constant integral expression (integers or characters).

Key Components:

- **Case:**

  Defines the starting point for execution if the expression matches the case value.

- **Break:**

Terminstes the statement sequence and jumps the control flow to the line following the switch block.

- ***Default:***

  An optional section that executes if no case matches the provided expression.

Important Rules

- The switch expression must result in a **constant value**.
- **Duplicate case values** are strictly prohibited.
- If break is omitted, execution will continue into the next case automatically.

EXAMPLE # 1

```
#include <iostream>
using namespace std;
int main()
    {
        char grade=0;
        cout<<"enter your grade (A,B,C,D,E,F)"<<endl;
        cin>>grade;

        switch(grade)
    {
            case 'A':
            case 'a':
cout<<"excellent";
break;


        case'B':
            case 'b':
cout<<"very good";
break;

    case 'C':
        case 'c':
cout<<"good";
break;

    case 'D':
        case 'd':
cout<<"Pass";
break;

    case 'E':
        case 'e':
cout<<"barely passed";
break;

    case 'F':
        case 'f':
cout<<"repeat again";
break;


default:
    cout<<"enter correct grade";

}

return 0;
}
```

EXAMPLE # 2

```
#include <iostream>
using namespace std;
int main()
    {

    int a=0;
    cout<<"select one option\n 1.convert kilometers to meters\n 2.convert meters to centimeters\n 3convert kilogram to gram\n 4.convert celcius to fahrenheit\n";
    cin>>a;

    switch (a){

        case 1:{

        float kilometers=0;
        float meters=0;
        cout<<"enter kilometers"<<endl;
        cin>>kilometers;
        meters=kilometers*1000;
        cout<<"there are  "<< meters<<"  meters in  "<<kilometers<<"  kilometers  ";
        break;
}
        case (2):{
        float meters=0;
        float centimeters=0;
        cout<<"enter meters"<<endl;
        cin>>meters;
        centimeters=meters*100;
        cout<<"there are  "<< centimeters<<"  centimeters in  "<<meters<<"  meters  ";
        break;
    }

    case (3):{
        float kilogram=0;
        float grams=0;
        cout<<"enter kilograms"<<endl;
        cin>>kilogram;
        grams=kilogram*1000;
        cout<<"there are  "<< grams<<"  grams in  "<<kilogram<<"  kilograms  ";
        break;
    }

    case (4):{
        float celcius=0;
        float fahrenheit=0;
        cout<<"enter celcius"<<endl;
        cin>>celcius;
        fahrenheit=(celcius*9/5) + 32;
        cout<<"there are  "<< fahrenheit<<"  fahrenheit in  "<<celcius<<"  celcius  ";
        break;



    }
}

return 0;
}
```

EXAMPLE # 3

```
#include <iostream>
using namespace std;
int main()
    {
        int day=0;
        cout<<"enter a number ( 1 - 7)"<<endl;
        cin>>day;

        switch(day)
    {
        case (1):
cout<<"monday";
break;


        case(2):
cout<<"tuesday";
break;

    case(3):
cout<<"wednesday";
break;

    case(4):
cout<<"thursday";
break;

    case(5):
cout<<"friday";
break;

    case(6):
cout<<"saturday";
break;

    case(7):
cout<<"sunday";
break;

default:
    cout<<"enter a valid number";

}

return 0;
}
```