

SoundCloud API

SoundCloud is an open source audio streaming service that allows users to upload, share and promote their audio content to users globally. This documentation provides a brief overview of some of the SoundCloud APIs and its python SDK.

Note: This is a sample revised version of the existing SoundCloud API documentation. You will find the sample Python SDK for SoundCloud at the end of the document.

Authentication

SoundCloud provides a RESTful API service that allows your web application to integrate with its platform. To get started, you should register your application with SoundCloud by creating an account. Refer to the instructions in [Sign in with SoundCloud](#).

SoundCloud uses OAuth 2.1 to authorize your application with a stateless transaction where the information regarding the user credentials are not stored. To know more about OAuth setup and authentication refer to [Authentication Code Flow](#).

SoundCloud APIs

The SoundCloud APIs are accessible through REST-ful syntax from HTTPS calls. The base URL for all requests is:

```
https://api.soundcloud.com
```

Service endpoints	
tracks	Uploads and manages new tracks or an audio file.
	POST/tracks
	GET/tracks{track_id}
	DELETE/tracks{track_id}
	PUT/tracks{track_id}
search	Finds the required track based on the query
	GET/playlists

	GET/users
--	-----------

REST Resources

tracks

Post tracks

POST /tracks

Upload a song or audio file or a track. The supported audio formats are `AIFF`, `WAV`, `FLAC`, `OGG`, `MP2`, `MP3`, `AAC`, `AMR` and `WMA`. The maximum size is 500MB per audio file. To upload a track, send a POST request with a multipart/form-data media type to the /tracks endpoint.

PATH Parameters

There are no path parameters for uploading an audio file.

Request

Name	Data Type	Required	Description
multipart/form-data	string	Yes	Content type of the track or audio file including some metadata.
track[asset_data]	Binary string	Yes	Audio file

Example

```
$ curl -X POST "https://api.soundcloud.com/tracks" \  
  -H "accept: application/json; charset=utf-8" \  
  -H "Authorization: OAuth ACCESS_TOKEN" \  
  -H "Content-Type: multipart/form-data" \  
  -F "track[title]=YOUR_TITLE" \  
  -F "track[purchase_url]: null" \  
  -F "track[asset_data]"
```

```
-F "track[label_name]: some label" \
-F "track[streamable]: true" \
-F "track[asset_data]=@JF5_IDL_DZ_C2_M3.wav;type=audio/wav" \
-F "downloadable": true
```

Fields

Name	Data Type	Required	Description
title	string	Yes	Name of the track
purchase_url	string	No	Link where the track was purchased
label_name	string	No	Name of the song album
streamable	boolean	Yes	Required values: Yes: If the song is streamable No: If the song can't be streamed
downloadable	boolean	No	Values: Yes: If the song can be downloaded No: if the song can't be downloaded.

JSON representation

```
{
  "title": YOUR_TITLE,
  "purchase_url": null,
  "label_name": "some label",
  "streamable": true,
  "downloadable": true
}
```

HTTP Response status

Code	Message
201	Success(OK)
400	Bad Request
401	Unauthorized
422	Unprocessable Entity

Get tracks

```
GET /tracks/{track_id}
```

Returns a track. You should specify the track ID along with a token if you need to fetch your private tracks or playlists.

PATH Parameters

Name	Data Type	Required	Description
track_id	string	Yes	The ID of the track
secret_token	string	Optional	A secret token to fetch private playlist or tracks

Example

```
$ curl -X GET
  "https://api.soundcloud.com/tracks/308946187?secret_token=1234"\
  -H "accept: application/json; charset=utf-8" \
```

JSON Representation

```
{
  "id": 1234,
  "sharing": "public",
  "label_name": "some label",
  "description": "Your sample description of the track"
}
```

HTTP Response status

Code	Message
200	Success(OK)
404	Not Found
401	Unauthorized

Delete tracks

```
DELETE /tracks/{track_id}
```

Deletes a track.

PATH Parameters

Name	Data Type	Required	Description
track_id	integer	Yes	ID of the audio file.

Example

```
$ curl -X 'DELETE' \
  'https://api.soundcloud.com/tracks/308946187' \
  -H 'accept: application/json; charset=utf-8'
```

JSON Representation

```
{
  "code": 401,
  "message": "",
  "link": "https://developers.soundcloud.com/docs/api/explorer/open-api",
  "status": "401 - Unauthorized",
  "errors": [],
  "error": null
}
```

HTTP Response status

Code	Message
200	Success
401	Unauthorized
404	Not Found

Put tracks

Updates the track's information.

```
PUT /tracks/{track_id}
```

PATH Parameters

Name	Data Type	Required	Description
track_id	integer	Yes	ID of the audio file

Example

```
$ curl -X 'PUT' \  
  'https://api.soundcloud.com/tracks/308946187' \  
  -H 'accept: application/json; charset=utf-8' \  
  -H 'Content-Type: multipart/form-data' \  
  -F 'track[description]=Taylor Swift' \  
  -F 'track[sharing]=public' \  
  -F 'track[streamable]=true' \  
  -F 'track[commentable]=true' \  
  -F 'track[title]=Fortnight'
```

JSON Representation

```
{  
  "commentable": true,  
  "description": Taylor Swift,  
  "sharing": "public",  
  "streamable": true,  
  "title": "Fortnight",  
  "user": {  
    "$ref": "#/components/examples/User/value"  
  },  
  "user_favorite": true,  
  "user_playback_count": 1,  
  "waveform_url": "https://wave.sndcdn.com/someString.png",  
  "access": "playable"  
}
```

search

Get playlists

Performs a playlist search based on a query

```
GET /playlists
```

PATH Parameters

Name	Data Type	Required	Description
q	string	Yes	The search query
access	array[string]	Yes	Filters content by level of access the user has to the track
show_tracks	boolean	Yes	A boolean flag to request a playlist with or without tracks. Default is true.
limit	integer	Yes	Number of results to return in the collection.
linked_partitioning	boolean	Yes	Returns paginated collection of items (recommended, returning a list without pagination is deprecated and should not be used)

Example

```
$ curl -X 'GET' \
'https://api.soundcloud.com/playlists?q=hello&access=playable%2Cpreview&show_tracks=true&limit=2&offset=0&linked_partitioning=true' \
-H 'accept: application/json; charset=utf-8'
```

JSON Representation

```
{
  "collection": {
    "$ref": "#/components/examples/Playlist/value"
  },
}
```



```
"next_href":  
"https://api.soundcloud.com/collection?page_size=10&cursor=1234567"  
}
```

Python SDK

SoundCloud SDK provides a set of libraries or tools to integrate SoundCloud features into your application. Some of the primary methods used for integrating include initialization, uploading, embed and audio and play an audio using the Widget API. The documentation provided in the SoundCloud SDK is in Javascript. This guide provides implementation in Python. Refer to [Javascript SDK](#).

initialize method

The `initialize` method is used to set up and configure your application for handling user authentication. Refer to the Javascript example [here](#).

Example

```
import requests  
  
def initialize_soundcloud(client_id, redirect_uri):  
    return {  
        "client_id": client_id,  
        "redirect_uri": redirect_uri,  
        "auth_url":  
        "https://soundcloud.com/connect?client_id={client_id}&redirect_uri={redirect_uri}&response_type=token"  
    }
```

upload method

`upload` method is used to upload audio files and recording. This method requires the user's browser to support FormData. Upload takes longer duration depending on the file size and so this method also returns the progress of upload. Refer to the Javascript example [here](#).

```
import requests

def upload_track_to_soundcloud(file_path, title):
    # Open the audio file in binary mode
    with open(file_path, "rb") as file:
        files = {
            "track[asset_data]": file # The audio file
        }
        data = {
            "track[title]": title # The track title
        }
```