

[HOME](#) [CONTESTS](#) [GYM](#) [PROBLEMSET](#) [GROUPS](#) [RATING](#) [API](#) [AIM TECH ROUND](#)  [VK CUP](#)  [SECTIONS](#)
[PROBLEMS](#) [SUBMIT](#) [STATUS](#) [STANDINGS](#) [CUSTOM TEST](#)

## B. Passwords

time limit per test: 2 seconds

memory limit per test: 256 megabytes

input: standard input

output: standard output

Vanya is managed to enter his favourite site Codehorses. Vanya uses  $n$  distinct passwords for sites at all, however he can't remember which one exactly he specified during Codehorses registration.

Vanya will enter passwords in order of non-decreasing their lengths, and he will enter passwords of same length in arbitrary order. Just when Vanya will have entered the correct password, he is immediately authorized on the site. Vanya will not enter any password twice.

Entering any passwords takes one second for Vanya. But if Vanya will enter wrong password  $k$  times, then he is able to make the next try only 5 seconds after that. Vanya makes each try immediately, that is, at each moment when Vanya is able to enter password, he is doing that.

Determine how many seconds will Vanya need to enter Codehorses in the best case for him (if he spends minimum possible number of second) and in the worst case (if he spends maximum possible amount of seconds).

### Input

The first line of the input contains two integers  $n$  and  $k$  ( $1 \leq n, k \leq 100$ ) — the number of Vanya's passwords and the number of failed tries, after which the access to the site is blocked for 5 seconds.

The next  $n$  lines contains passwords, one per line — pairwise distinct non-empty strings consisting of latin letters and digits. Each password length does not exceed 100 characters.

The last line of the input contains the Vanya's Codehorses password. It is guaranteed that the Vanya's Codehorses password is equal to some of his  $n$  passwords.

### Output

Print two integers — time (in seconds), Vanya needs to be authorized to Codehorses in the best case for him and in the worst case respectively.

### Examples

input
<pre>5 2 cba abc bb1 abC ABC abc</pre>
output
<pre>1 15</pre>

input
<pre>4 100 11 22 1</pre>

### Codeforces Round #374 (Div. 2)

Finished

Practice



### → Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ACM-ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

[Start virtual contest](#)

### → Submit?

Language: GNU G++ 5.1.0 ▼

Choose file: [Choose File](#) No file chosen

Be careful: there is 50 points penalty for submission which fails the pretests or resubmission (except failure on the first test, denial of judgement or similar verdicts). "Passed pretests" submission verdict doesn't guarantee that the solution is absolutely correct and it will pass system tests.

[Submit](#)

### → Last submissions


Submission	Time	Verdict
<a href="#">21245316</a>	Oct/06/2016 23:22	Accepted
<a href="#">21243424</a>	Oct/06/2016 21:32	Wrong answer on test 5

### → Problem tags

[sortings](#) [strings](#)

No tag edit access

### → Contest materials

- Announcement 
- Tutorial 

2
22

output
--------

3 4
-----

**Note**

Consider the first sample case. As soon as all passwords have the same length, Vanya can enter the right password at the first try as well as at the last try. If he enters it at the first try, he spends exactly 1 second. Thus in the best case the answer is 1. If, at the other hand, he enters it at the last try, he enters another 4 passwords before. He spends 2 seconds to enter first 2 passwords, then he waits 5 seconds as soon as he made 2 wrong tries. Then he spends 2 more seconds to enter 2 wrong passwords, again waits 5 seconds and, finally, enters the correct password spending 1 more second. In summary in the worst case he is able to be authorized in 15 seconds.

Consider the second sample case. There is no way of entering passwords and get the access to the site blocked. As soon as the required password has length of 2, Vanya enters all passwords of length 1 anyway, spending 2 seconds for that. Then, in the best case, he immediately enters the correct password and the answer for the best case is 3, but in the worst case he enters wrong password of length 2 and only then the right one, spending 4 seconds at all.

---

[Codeforces](#) (c) Copyright 2010-2016 Mike Mirzayanov  
The only programming contests Web 2.0 platform  
Server time: Oct/07/2016 02:32:48<sup>UTC+6</sup> (c3).  
Desktop version, switch to [mobile version](#).