

6.4 Summary

In this chapter, we mainly studied two algorithms about Bandits.

A bandit problem is about the balance of exploit & explore, the goal of such a problem is to find the optimal action at each time. We care about the estimate of the regret.

First we learned the K-Armed Bandit Problem.

Pseudo code of UCB algorithm:

- 1: Play each arm once, denote as $\{a_i | i=1, \dots, K\}$
- 2: for $t=1 \rightarrow T-K$ do
- 3: $I_t = \operatorname{argmax}_{i \in [K]} \left(\hat{\mu}_i^t + \sqrt{\frac{\log(TK/\delta)}{N_i^t}} \right)$
- 4: $r_t := r_{I_t}$
- 5: end for

The regret of the algorithm above can be concluded as:

[Th 6.1] with prob. $\geq 1-\delta$,

$$R_T = O\left(\min\left\{\sqrt{KT \cdot \ln(TK/\delta)}, \sum_{a \neq a^*} \frac{\ln(TK/\delta)}{\Delta_a}\right\} + K\right)$$

Then to deal with a large/infinite K arms, we learned the Linear Bandits.

Pseudo code: The Linear UCB algorithm

Input: λ, β_t

- 1: for $t=0, 1, \dots$ do
- 2: Execute $x_t = \operatorname{argmax}_{x \in \mathcal{D}} \max_{\mu \in \text{BALL}_t} \mu \cdot x$

and observe r_t

3: Update $BALL_{t+1}$

4: End for.

The estimate of the regret can be concluded as:

[Th. 6.3] Suppose $|\mu^* \cdot x| \leq 1$ for all $x \in D$, $\|\mu^*\| \leq W$, $\|x\| \leq B$ and η_t is σ^2 sub-Gaussian. Set

$$\lambda = \sigma^2 / W^2, \quad \beta_t := \sigma^2 (2 + 4d \log(1 + \frac{tB^2W^2}{d}) + 8 \log(4/\delta))$$

We have that with prob. $\geq 1 - \delta$, for all $T \geq 0$

$$R_T \leq c\sigma\sqrt{T} (d \log(1 + \frac{TB^2W^2}{d\sigma^2}) + \log(4/\delta))$$

where the prob. comes from the prob. that $\mu^* \in BALL_t$.

Addition:

The idea of upper confidence bounds comes from the estimate of $|\hat{\mu}(a) - \mu(a)|$ by the Hoeffding's inequality, which says

$$|\hat{\mu}(a) - \mu(a)| \leq \sqrt{\ln(TK/\delta)/N(a)} \quad \text{with prob } \geq 1 - \delta.$$

There are two reasons for trying the arm I_t with highest UCB:

(i): I_t has large confidence interval, which means it has not been tried many times yet. [high uncertainty]

i.e. We do exploration in this case!

(ii): It has small confidence interval, then it is simply a good arm.

i.e. We do exploitation in this case!

