

POKER NIGHT

Final Feature, Function & Release Acceptance Checklist

Website • Web App • Android • iOS • TV Mode • Tournament Engine • Cash Game

Extremely detailed mutual verification document for developer delivery and client acceptance

Client		Developer / Company	
Contract / Platform		Agreed fixed price	
Planned delivery date		Revision rounds	
Post-launch bug-fix period		Checklist version	1.0

FINAL PAYMENT CONDITION

Every in-scope item must be implemented, functional, tested and delivered. No more and no less than the mutually approved checklist is required.
Missing, placeholder or non-functional items do not count as complete.

Prepared: 2026-07-27

How to Use This Checklist

1. 1. The developer performs a complete internal test and marks the Developer box only after the item works in the agreed production-like build.
2. 2. The client independently checks the same item and marks the Client box only after seeing the result or evidence.
3. 3. The Evidence / Notes column should contain a URL, build number, video, screenshot, test account, defect ID or short explanation.
4. 4. A blank Client box means the item is not accepted. A failed item must be corrected and retested.
5. 5. N/A is allowed only when both parties approve a written exception. The exception must be listed in the final sign-off section.
6. 6. A feature is not complete merely because the screen exists. The complete user flow, database action, realtime update, permissions, recovery and error handling must work.
7. 7. The final accepted build must match the source code and production deployment delivered to the client.

Column key: Developer = developer self-verification. Client = client acceptance. Evidence / Notes = proof, defect reference or signed exception.

Checklist Sections

8. 1. Acceptance Rules and Scope Lock
9. 2. Delivery Package, Ownership and Project Access
10. 3. Public Website and Browser Entry Points
11. 4. Cross-Platform Application Shell and Design
12. 5. Authentication, Accounts and Roles
13. 6. Groups, Codes and Basic Settings
14. 7. Invitations, RSVP, Guests and Check-In
15. 8. Chat, Polls and Notifications
16. 9. Tournament Presets and Game Creation
17. 10. Chip Sets, Physical Inventory and Stack Preparation
18. 11. Tournament Structure Engine
19. 12. Live Tournament Administration
20. 13. Seating, Tables and Final Table
21. 14. Prize Pool, Organizer Amount, Bounties and Visibility
22. 15. Player View, Guest View, TV Mode and Voice
23. 16. Group Game History and Basic Statistics
24. 17. Minimal Cash-Game Module
25. 18. Realtime Synchronisation, Local Recovery and Offline Behaviour
26. 19. Security, Privacy and Data Visibility
27. 20. Validation, Errors and Edge Cases
28. 21. UI Quality, Responsiveness and Accessibility
29. 22. End-to-End User Acceptance Scenarios
30. 23. Compatibility, Performance and Reliability
31. 24. Deployment, App Stores and Production Launch
32. 25. Baseline Payout Style Regression Checks
33. 26. Final Defect Closure and Sign-Off

1. Acceptance Rules and Scope Lock

These checks define how the developer and client decide whether the product is complete. They apply to every platform and every feature in this document.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
1.1 Contract and acceptance principles				
01-001	The final agreed price, delivery date, revision count and post-launch support period are written into the contract before development starts.	☐	☐	
01-002	This checklist is attached to, linked from or explicitly incorporated into the official project agreement.	☐	☐	
01-003	Every checklist item is treated as in scope unless both parties approve a written exception before final acceptance.	☐	☐	
01-004	No feature may be silently removed, replaced, postponed, reduced to a mock-up or marked “coming soon”.	☐	☐	
01-005	No additional feature outside this checklist is required unless both parties approve it in writing.	☐	☐	
01-006	A feature counts as complete only when its full user flow works with real saved data, not only with demo data.	☐	☐	
01-007	Buttons, links, menus, forms and controls that appear in the interface perform the described action.	☐	☐	
01-008	There are no dead buttons, placeholder screens, lorem ipsum text, temporary links or unfinished navigation paths.	☐	☐	
01-009	All calculations use production logic and are not manually hardcoded for a single test case.	☐	☐	
01-010	The developer performs a complete self-check and marks the Developer column before client testing begins.	☐	☐	
01-011	The client checks the same item independently and marks the Client column only after verifying it.	☐	☐	
01-012	A failed item is recorded in the defect log with steps to reproduce, severity and responsible party.	☐	☐	
01-013	An item may be marked N/A only through a written, mutually approved scope exception.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
01-014	Evidence may include a live URL, screen recording, test account, screenshot, build file, repository link or automated test result.	☐	☐	
01-015	Final payment is released only after every in-scope item passes, required evidence is delivered and all blocking defects are closed.	☐	☐	
01-016	The developer may not require final payment merely because code exists if the agreed feature does not work end to end.	☐	☐	
01-017	Minor cosmetic defects may be accepted only when they are recorded, do not block use and have a written correction date.	☐	☐	
01-018	Security, data-loss, calculation, login, deployment and store-build defects are always blocking defects.	☐	☐	
01-019	The client receives enough access and documentation to continue operating the product without the original developer.	☐	☐	
01-020	All third-party accounts used for production are owned by or transferred to the client before acceptance.	☐	☐	
1.2 Final product boundaries				
01-021	The deliverable includes a public website, full browser web application, Android application, iOS application and read-only TV browser view.	☐	☐	
01-022	The Android, iOS and web applications use the same backend and show consistent data for the same game.	☐	☐	
01-023	There is one administrator per game in this MVP; simultaneous multi-admin control is not required.	☐	☐	
01-024	The only user categories are Administrator, Registered Player and Guest.	☐	☐	
01-025	Spotify integration is not included.	☐	☐	
01-026	Dedicated Chromecast, AirPlay or proprietary casting integration is not included; normal browser use and screen mirroring may be used.	☐	☐	
01-027	Actual payment processing, card charging, bank transfers and payment-status tracking are not included.	☐	☐	
01-028	Poker Night records game contributions needed for calculations, but not whether a person physically paid.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
01-029	Advanced player financial statistics, ROI, personal profit graphs and individual rebuy/add-on history are not included in player views.	☐	☐	
01-030	Friends, social feeds, achievements, seasons and advanced leaderboards are not included.	☐	☐	
01-031	Voice commands are not included; English voice announcements are included.	☐	☐	
01-032	Poker Night does not deal cards, evaluate hands, track pots, identify hand winners or replace the human dealer.	☐	☐	
01-033	Poker Night does not track ongoing dealer-button movement after initial seating or final-table redraw.	☐	☐	
01-034	The cash-game section is intentionally simpler than the tournament section.	☐	☐	

2. Delivery Package, Ownership and Project Access

The product is not accepted until the client can access, build, deploy and operate every agreed part of it.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
2.1 Source code and repositories				
02-001	The client receives the complete source code for the website, web app, Android app, iOS app, backend functions and database configuration.	☐	☐	
02-002	All production source code is stored in a repository owned by the client or transferred to the client before final payment.	☐	☐	
02-003	The repository includes meaningful commit history or, at minimum, a clean final commit with all files required to build the product.	☐	☐	
02-004	No essential production file is kept only on the developer's computer.	☐	☐	
02-005	No source file is deliberately obfuscated, encrypted or withheld.	☐	☐	
02-006	The client receives a list of all frameworks, packages, plugins and exact versions used.	☐	☐	
02-007	The project builds from a fresh clone by following the written setup instructions.	☐	☐	
02-008	All package lockfiles and dependency manifests are included.	☐	☐	
02-009	Unused secrets, personal developer credentials and test keys are removed before handover.	☐	☐	
02-010	Open-source licences are compatible with commercial use and listed in the documentation.	☐	☐	
2.2 Accounts and credentials				
02-011	The client owns or controls the production hosting account.	☐	☐	
02-012	The client owns or controls the production database/backend account.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
02-013	The client owns or controls the production domain and DNS settings.	☐	☐	
02-014	The client owns or controls the email-sending and notification configuration used in production.	☐	☐	
02-015	The client owns the Google Play Console account used for release.	☐	☐	
02-016	The client owns the Apple Developer and App Store Connect accounts used for release.	☐	☐	
02-017	The developer receives only the minimum temporary permissions necessary to complete deployment.	☐	☐	
02-018	Temporary developer access can be revoked without breaking the production product.	☐	☐	
02-019	A secure credential handover document identifies where every production secret is stored.	☐	☐	
02-020	No production password or API secret is placed directly inside public source code.	☐	☐	
2.3 Documentation and handover				
02-021	A README explains local setup, required tools, environment variables and how to run each platform.	☐	☐	
02-022	A deployment guide explains how to deploy the website/web app and backend.	☐	☐	
02-023	An Android release guide explains signing, AAB generation and Play Console upload.	☐	☐	
02-024	An iOS release guide explains certificates, bundle ID, archive creation and App Store Connect upload.	☐	☐	
02-025	A database document lists the main tables/collections, important fields and relationships.	☐	☐	
02-026	A backup and restore guide explains how production data is backed up and recovered.	☐	☐	
02-027	An admin user guide explains how to create a group, create a game, run a tournament and complete a cash session.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
02-028	A known-limitations section lists only genuinely approved limitations, not unfinished features.	☐	☐	
02-029	The developer provides a final walkthrough or screen recording showing the major user flows.	☐	☐	
02-030	The client receives all design files, app icons, logos, images and editable assets created for the project.	☐	☐	

3. Public Website and Browser Entry Points

The public website must explain the product, provide entry to the web app and allow code/QR access without exposing private data.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
3.1 Public website pages				
03-001	The production domain opens over HTTPS without certificate warnings.	☐	☐	
03-002	The homepage loads without requiring login.	☐	☐	
03-003	The homepage clearly identifies the product as Poker Night.	☐	☐	
03-004	The homepage briefly explains tournament and cash-game functionality in understandable language.	☐	☐	
03-005	The homepage contains a clear Log In button for registered users.	☐	☐	
03-006	The homepage contains a clear Create Account button for new registered users.	☐	☐	
03-007	The homepage contains a clearly visible “Enter Game Code” field or equivalent join action.	☐	☐	
03-008	The website includes a Privacy Policy page reachable from the footer.	☐	☐	
03-009	The website includes a Terms page reachable from the footer.	☐	☐	
03-010	The website includes a Contact or Support method.	☐	☐	
03-011	The website displays links to the Android and iOS applications once store URLs are available.	☐	☐	
03-012	The website does not display Spotify, advanced statistics or other removed features.	☐	☐	
03-013	The website uses the final approved branding, colours, typography and logo consistently.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
03-014	All public pages have valid page titles and descriptions.	☐	☐	
03-015	All public navigation links lead to the correct destination.	☐	☐	
03-016	The public website is usable on small mobile screens, tablets and desktop browsers.	☐	☐	
3.2 Web application entry				
03-017	Registered users can open the full web application from the public website.	☐	☐	
03-018	An authenticated user returning to the web app remains signed in according to the approved session policy.	☐	☐	
03-019	An unauthenticated user opening a protected route is redirected to login and returned to the intended route after login.	☐	☐	
03-020	The web app is installable as a PWA when the browser supports installation.	☐	☐	
03-021	The web app has a valid manifest, icon set and application name.	☐	☐	
03-022	The web app does not show browser-console errors during normal use.	☐	☐	
03-023	Refreshing a normal web-app page does not produce a server 404 error.	☐	☐	
03-024	Deep links to a group or game route open the intended screen after authentication.	☐	☐	
3.3 Code and QR access				
03-025	Every created game receives a unique human-readable access code.	☐	☐	
03-026	Every created game receives a QR code representing a valid HTTPS link.	☐	☐	
03-027	Scanning the QR code with an iPhone camera opens the correct game landing page.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
03-028	Scanning the QR code with a typical Android camera opens the correct game landing page.	☐	☐	
03-029	The QR code remains readable when displayed on another phone, printed or shown on a TV.	☐	☐	
03-030	The manual code entry produces the same destination as the QR link.	☐	☐	
03-031	Codes are case-insensitive if letters are used.	☐	☐	
03-032	Ambiguous characters are avoided or handled clearly.	☐	☐	
03-033	Entering an invalid code shows a clear "Game not found" message and allows another attempt.	☐	☐	
03-034	Entering an expired or closed-game code shows a clear state-specific message.	☐	☐	
03-035	The public code page never exposes admin controls or private organizer data.	☐	☐	
03-036	A guest can use the QR/code flow without creating an account.	☐	☐	
03-037	A registered user opening a code can continue in the app/web app without losing the selected game.	☐	☐	
03-038	If a native app is installed, supported deep links open the correct app screen; otherwise the web fallback works.	☐	☐	
03-039	The developer demonstrates at least one real QR scan on iOS and one on Android before acceptance.	☐	☐	

4. Cross-Platform Application Shell and Design

The same core product must work consistently on web, Android and iOS while respecting each platform's navigation and device behaviour.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
4.1 Shared application behaviour				
04-001	The same registered account can sign in on web, Android and iOS.	☐	☐	
04-002	A game created on one platform appears on the other platforms after synchronisation.	☐	☐	
04-003	Game codes, group names, player names and results are identical across platforms.	☐	☐	
04-004	The main navigation exposes only features included in this checklist.	☐	☐	
04-005	The application has clear loading, empty, success and error states.	☐	☐	
04-006	Back navigation does not accidentally discard saved data.	☐	☐	
04-007	Unsaved form changes trigger a confirmation before being lost where appropriate.	☐	☐	
04-008	Destructive actions require clear confirmation.	☐	☐	
04-009	The user can sign out from every platform.	☐	☐	
04-010	The app returns to a safe screen after an expired session.	☐	☐	
04-011	The app does not freeze after repeated navigation between screens.	☐	☐	
04-012	Date and time formatting is consistent and understandable.	☐	☐	
04-013	Money values in game interfaces are normally shown without a currency symbol as approved.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
04-014	KO amounts use the approved format such as “15 + 5”.	☐	☐	
04-015	All user-facing English text is grammatically correct and free of obvious spelling errors.	☐	☐	
4.2 Android application				
04-016	A release-ready Android application is produced from the final source code.	☐	☐	
04-017	The Android package name is unique and owned by the client.	☐	☐	
04-018	The Android app icon and splash screen use final assets.	☐	☐	
04-019	The Android app launches without a white-screen or startup crash.	☐	☐	
04-020	Android back-button behaviour is logical and does not unexpectedly close active forms.	☐	☐	
04-021	Android notification permission is requested only when needed and handled if denied.	☐	☐	
04-022	The Android app handles backgrounding and reopening an active tournament without losing admin state.	☐	☐	
04-023	The Android app is tested on at least one current phone-size device and one different screen size/emulator.	☐	☐	
04-024	A signed Android App Bundle is delivered and can be uploaded to Play Console.	☐	☐	
4.3 iOS application				
04-025	A release-ready iOS application is produced from the final source code.	☐	☐	
04-026	The iOS bundle identifier is unique and owned by the client.	☐	☐	
04-027	The iOS app icon and launch screen use final assets.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
04-028	The iOS app launches without a blank screen or startup crash.	☐	☐	
04-029	The iOS app handles safe areas, notches and home indicators correctly.	☐	☐	
04-030	iOS notification permission is requested only when needed and handled if denied.	☐	☐	
04-031	The iOS app handles backgrounding and reopening an active tournament without losing admin state.	☐	☐	
04-032	The iOS app is tested on at least one current iPhone size and one additional size/simulator.	☐	☐	
04-033	A release archive/build is delivered and can be uploaded to App Store Connect.	☐	☐	

5. Authentication, Accounts and Roles

Only three user categories exist. Permissions must be enforced by the backend, not only hidden in the interface.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
5.1 Registration and login				
05-001	A new registered user can create an account using the approved authentication method.	☐	☐	
05-002	Required registration fields are clearly marked.	☐	☐	
05-003	Invalid email addresses are rejected with a clear message.	☐	☐	
05-004	Password requirements are displayed before submission.	☐	☐	
05-005	Duplicate accounts using the same email are handled safely.	☐	☐	
05-006	A registered user can log in with valid credentials.	☐	☐	
05-007	Invalid credentials do not reveal whether a specific account exists.	☐	☐	
05-008	A user can request a password reset.	☐	☐	
05-009	Password-reset links expire and cannot be reused after success.	☐	☐	
05-010	A user can log out and protected data is no longer accessible on that device.	☐	☐	
05-011	Authentication tokens are stored securely for each platform.	☐	☐	
05-012	An account can update its display name.	☐	☐	
05-013	Player display names are validated for length and unsupported characters.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
05-014	A deleted or disabled account cannot continue using a stale session.	☐	☐	
5.2 Administrator role				
05-015	The user who creates a group/game becomes its administrator.	☐	☐	
05-016	The administrator can create, edit, start, run and complete games.	☐	☐	
05-017	The administrator can manage players, guests, rebuys, add-ons, eliminations and seating.	☐	☐	
05-018	The administrator can see private prize calculations and organizer amounts.	☐	☐	
05-019	The administrator can create chat messages, polls and notifications.	☐	☐	
05-020	The administrator can access cash-game reconciliation.	☐	☐	
05-021	Only the administrator can perform admin actions for the game.	☐	☐	
05-022	A player or guest cannot call admin API actions by manually changing a URL or request.	☐	☐	
05-023	There is no unfinished assistant-admin or multi-admin interface in the MVP.	☐	☐	
5.3 Registered player role				
05-024	A registered player can join a group/game through the intended flow.	☐	☐	
05-025	A registered player can respond to invitations.	☐	☐	
05-026	A registered player can check themselves in when check-in is open.	☐	☐	
05-027	A registered player can view public game information and their assigned seat.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
05-028	A registered player can use chat and vote in polls.	☐	☐	
05-029	A registered player can receive supported notifications.	☐	☐	
05-030	A registered player cannot record a rebuy, add-on, elimination or payout.	☐	☐	
05-031	A registered player cannot see organizer amounts or private contribution records.	☐	☐	
05-032	A registered player cannot see individual prize amounts after the game.	☐	☐	
05-033	A registered player cannot see personal financial statistics, personal rebuy history or personal add-on history.	☐	☐	
5.4 Guest role				
05-034	A guest can enter through the website code/QR flow without an account.	☐	☐	
05-035	A guest can identify their inviter and select an available guest slot.	☐	☐	
05-036	A guest can enter their name and request/check in.	☐	☐	
05-037	A guest can view the timer, blinds, ante, announcements, table and seat after confirmation.	☐	☐	
05-038	A guest cannot use chat or polls without registering.	☐	☐	
05-039	A guest cannot access permanent group history or private player data.	☐	☐	
05-040	A guest cannot perform admin actions.	☐	☐	
05-041	A guest session is limited to the intended game and does not expose other groups.	☐	☐	

6. Groups, Codes and Basic Settings

Groups provide the reusable home for players, presets, chat, polls and game history.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
6.1 Group creation and access				
06-001	An administrator can create a group with a valid name.	☐	☐	
06-002	Group-name length and invalid characters are validated.	☐	☐	
06-003	A newly created group receives a permanent group code or join mechanism.	☐	☐	
06-004	The group code can be copied and shared.	☐	☐	
06-005	A registered player can use the group code to reach the correct group join flow.	☐	☐	
06-006	An invalid group code produces a clear error.	☐	☐	
06-007	The administrator can see the current member list.	☐	☐	
06-008	Duplicate group membership is prevented.	☐	☐	
06-009	A user can belong to more than one group if supported by the navigation.	☐	☐	
06-010	The administrator can edit the group name and basic settings.	☐	☐	
06-011	Group data is isolated from unrelated groups.	☐	☐	
6.2 Group home				
06-012	The group home shows upcoming games.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
06-013	The group home shows completed group game history.	☐	☐	
06-014	The group home provides access to chat.	☐	☐	
06-015	The group home provides access to polls.	☐	☐	
06-016	The group home provides access to saved tournament presets.	☐	☐	
06-017	The group home displays a clear create-game action for the administrator.	☐	☐	
06-018	Players do not see admin-only controls.	☐	☐	
06-019	Empty states explain what to do when there are no games, messages, polls or presets.	☐	☐	

7. Invitations, RSVP, Guests and Check-In

Attendance must be easy for registered players and guests, while preventing duplicate guest slots or late unauthorised changes.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
7.1 Invitations and RSVP				
07-001	The administrator can invite registered group members to a game.	☐	☐	
07-002	An invited registered player can select exactly one RSVP option.	☐	☐	
07-003	The options are Going, Going +1, Going +2, Going +3, Going +4, Maybe and Cannot Come.	☐	☐	
07-004	Going counts as one confirmed person.	☐	☐	
07-005	Going +1 counts as the registered player plus one guest.	☐	☐	
07-006	Going +2 counts as the registered player plus two guests.	☐	☐	
07-007	Going +3 counts as the registered player plus three guests.	☐	☐	
07-008	Going +4 counts as the registered player plus four guests.	☐	☐	
07-009	Maybe does not count as a confirmed player for final setup.	☐	☐	
07-010	Cannot Come does not count toward attendance.	☐	☐	
07-011	The player can change the RSVP until one hour before the scheduled start time.	☐	☐	
07-012	After the one-hour cutoff, the player sees that changes are closed.	☐	☐	
07-013	The administrator can see each RSVP and the calculated confirmed-person total.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
07-014	Guest slots are created according to the selected +guest RSVP.	☐	☐	
07-015	Changing from Going +3 to Going +1 removes or closes the extra unused guest slots safely.	☐	☐	
07-016	The game setup can use confirmed attendance and an administrator override before starting.	☐	☐	
7.2 Guest identification and check-in				
07-017	A guest entering the game code sees the list of people who declared guest slots.	☐	☐	
07-018	The guest selects the person who invited them.	☐	☐	
07-019	The guest selects one available slot such as Guest 1 or Guest 2.	☐	☐	
07-020	A slot already confirmed by another guest cannot be selected again.	☐	☐	
07-021	A slot temporarily selected on another device is protected from duplicate confirmation.	☐	☐	
07-022	The guest enters a valid display name.	☐	☐	
07-023	The guest submits the check-in request.	☐	☐	
07-024	The administrator sees the pending guest with inviter and slot.	☐	☐	
07-025	The administrator can approve the guest check-in.	☐	☐	
07-026	The administrator can reject or correct an incorrect guest check-in.	☐	☐	
07-027	A guest is not treated as fully checked in until admin confirmation.	☐	☐	
07-028	After approval, the guest sees the correct game and check-in state.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
07-029	The administrator can manually check in a guest if needed.	☐	☐	
07-030	A guest who refreshes the page can recover the same approved guest session on that device.	☐	☐	
07-031	A guest cannot claim a slot after late registration closes.	☐	☐	
7.3 Registered-player check-in				
07-032	A registered player can check themselves in while check-in/registration is open.	☐	☐	
07-033	The administrator can check in a registered player manually.	☐	☐	
07-034	Duplicate check-in does not create duplicate entries.	☐	☐	
07-035	The check-in dashboard distinguishes invited, confirmed, maybe, checked-in and absent people.	☐	☐	
07-036	Checked-in totals include approved guests.	☐	☐	
07-037	Only checked-in players receive seats when seating is generated.	☐	☐	
07-038	A checked-in player sees their table and seat after assignment.	☐	☐	
07-039	Late registration remains open only until the configured closing level, normally the end of Level 6.	☐	☐	
07-040	No player or guest can be added after late registration closes.	☐	☐	

8. Chat, Polls and Notifications

These social features are required for registered users but intentionally simple for the MVP.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
8.1 Chat				
08-001	Each group has a text chat available to registered members.	☐	☐	
08-002	Registered players can send plain-text messages.	☐	☐	
08-003	The administrator can send plain-text messages.	☐	☐	
08-004	Guests cannot access chat without registering.	☐	☐	
08-005	Messages show sender name and time.	☐	☐	
08-006	Messages appear in chronological order.	☐	☐	
08-007	New messages synchronise to other online registered users.	☐	☐	
08-008	Empty messages cannot be sent.	☐	☐	
08-009	Excessively long messages are limited with a clear validation message.	☐	☐	
08-010	Repeated send taps do not create duplicate messages.	☐	☐	
08-011	Chat remains usable on mobile and web layouts.	☐	☐	
08-012	Image, audio and file uploads are not required.	☐	☐	
08-013	Deleted or disabled users do not expose private credentials through chat records.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
8.2 Polls				
08-014	The administrator can create a poll in a group.	☐	☐	
08-015	A poll has a clear question and at least two options.	☐	☐	
08-016	Empty or duplicate options are rejected.	☐	☐	
08-017	Registered players can vote in an open poll.	☐	☐	
08-018	Guests cannot vote through the guest website.	☐	☐	
08-019	A player cannot create duplicate votes unless vote changing is intentionally enabled.	☐	☐	
08-020	If vote changing is allowed, the latest selection replaces the earlier one rather than adding another vote.	☐	☐	
08-021	Poll totals update for authorised users.	☐	☐	
08-022	The administrator can close a poll.	☐	☐	
08-023	Closed polls no longer accept votes.	☐	☐	
08-024	Polls can be used for date, time, buy-in, KO option, duration, location or a custom question.	☐	☐	
08-025	Attendance RSVP remains separate from ordinary polls.	☐	☐	
08-026	A poll result can be used to suggest a matching tournament preset.	☐	☐	
8.3 Notifications				
08-027	Registered users can receive an invitation notification.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
08-028	Registered users can receive an RSVP reminder where configured.	☐	☐	
08-029	Registered users can receive a game-start reminder.	☐	☐	
08-030	Registered users can receive a check-in/open-registration notification.	☐	☐	
08-031	Registered users can receive important admin announcements.	☐	☐	
08-032	Registered users can receive a poll-created notification.	☐	☐	
08-033	Notifications link to the correct group or game screen.	☐	☐	
08-034	Denied notification permission does not break the app.	☐	☐	
08-035	Notification preferences or a basic enable/disable control are available if implemented.	☐	☐	
08-036	A notification is not sent multiple times for one event unless explicitly repeated by the administrator.	☐	☐	
08-037	Web, Android and iOS notification behaviour is tested in supported environments.	☐	☐	

9. Tournament Presets and Game Creation

The administrator enters only the necessary event and game preferences. The engine generates the playable structure.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
9.1 Tournament preset management				
09-001	The administrator can create a named tournament preset.	☐	☐	
09-002	A preset can store buy-in, KO bounty setting, rebuy setting, add-on setting, duration, chip set, organizer percentage and ante preference.	☐	☐	
09-003	A preset does not store a permanently fixed blind structure; the structure is regenerated for actual attendance and chips.	☐	☐	
09-004	The administrator can edit a preset.	☐	☐	
09-005	The administrator can delete a preset after confirmation.	☐	☐	
09-006	Using a preset pre-fills the creation form correctly.	☐	☐	
09-007	A matching preset is suggested when poll results and expected attendance align with it.	☐	☐	
09-008	When two presets match, the administrator can choose between the best candidates.	☐	☐	
09-009	The administrator can ignore a suggested preset and start from scratch.	☐	☐	
9.2 Event details				
09-010	The administrator can enter a tournament name.	☐	☐	
09-011	The tournament name is required and validated for length.	☐	☐	
09-012	The administrator can select a date.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
09-013	The administrator can select a start time.	☐	☐	
09-014	The administrator can enter or select a location.	☐	☐	
09-015	The administrator can enter the expected number of players or use calculated attendance.	☐	☐	
09-016	Expected player count must be a positive whole number.	☐	☐	
09-017	The administrator can select a target duration of 3, 3.5, 4, 4.5, 5, 5.5 or 6 hours.	☐	☐	
09-018	The default target duration is 3.5 hours.	☐	☐	
09-019	The application explains that duration is an estimate rather than a guaranteed finish time.	☐	☐	
9.3 Financial and format inputs				
09-020	The administrator can enter a numeric buy-in without a currency symbol.	☐	☐	
09-021	Buy-in accepts only valid non-negative numeric input according to the approved format.	☐	☐	
09-022	KO bounty is off by default unless a preset changes it.	☐	☐	
09-023	When KO bounty is enabled, the administrator enters the bounty amount separately.	☐	☐	
09-024	The combined display uses a format such as "15 + 5".	☐	☐	
09-025	Rebuy is on by default.	☐	☐	
09-026	The default rebuy closing point is the end of Level 6.	☐	☐	
09-027	The administrator can select another allowed rebuy closing level before the game starts.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
09-028	Default rebuy price equals the buy-in.	☐	☐	
09-029	The administrator can change the rebuy price.	☐	☐	
09-030	Re-entry can be enabled as a separate, secondary option.	☐	☐	
09-031	Add-on can be enabled or disabled.	☐	☐	
09-032	The administrator enters only the add-on price; the engine recommends the chip amount.	☐	☐	
09-033	Default add-on price equals the buy-in.	☐	☐	
09-034	The administrator can enter an organizer percentage for equipment, drinks and snacks.	☐	☐	
09-035	The interface never labels the organizer percentage as rake.	☐	☐	
09-036	The administrator can enable or disable antes.	☐	☐	
09-037	When enabled, Big Blind Ante is the default type.	☐	☐	
09-038	The administrator can select Individual Ante instead.	☐	☐	
9.4 Creation review and generation				
09-039	The creation form validates all required fields before generation.	☐	☐	
09-040	The administrator can save progress or safely return to previous steps without losing entered values.	☐	☐	
09-041	The selected chip set is shown before generation.	☐	☐	
09-042	The engine receives actual expected player count, duration, chip information and tournament options.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
09-043	A loading state is shown while the structure is generated.	☐	☐	
09-044	A generation failure shows a clear retryable error without losing inputs.	☐	☐	
09-045	The generated review shows starting stack, chip composition, opening blinds, all levels, break/settlement point, ante plan and estimated finish.	☐	☐	
09-046	The administrator can accept the generated structure.	☐	☐	
09-047	The administrator can regenerate after changing inputs.	☐	☐	
09-048	The administrator can edit future blind values and allowed level durations before starting.	☐	☐	
09-049	The administrator cannot create an impossible structure that requires unavailable chip values without receiving a warning.	☐	☐	
09-050	The final accepted structure is saved with the game and used on every platform.	☐	☐	

10. Chip Sets, Physical Inventory and Stack Preparation

The chip system must work with numbered or unnumbered home sets and produce physically usable stacks.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
10.1 Saved chip sets				
10-001	The administrator can create a reusable chip-set preset.	☐	☐	
10-002	A chip set has a unique name within the group or clear duplicate handling.	☐	☐	
10-003	The administrator can add any number of chip colours within practical UI limits.	☐	☐	
10-004	Every chip colour has exactly one tournament value after configuration.	☐	☐	
10-005	Two colours are never allowed to share the same value.	☐	☐	
10-006	The administrator can edit a saved chip set.	☐	☐	
10-007	The administrator can delete an unused chip set after confirmation.	☐	☐	
10-008	A chip set used by past games remains historically understandable after later edits.	☐	☐	
10.2 Exact inventory mode				
10-009	The administrator can select Exact Inventory mode.	☐	☐	
10-010	For each colour, the administrator can choose/enter a colour label.	☐	☐	
10-011	For numbered chips, the administrator enters the printed numeric value.	☐	☐	
10-012	The administrator enters the exact quantity available for each colour.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
10-013	Chip quantities accept only whole numbers of zero or more.	☐	☐	
10-014	Chip values accept only valid positive numbers.	☐	☐	
10-015	Duplicate values are blocked.	☐	☐	
10-016	The engine does not allocate more chips than the entered inventory.	☐	☐	
10-017	The review shows used and remaining quantities for each colour.	☐	☐	
10.3 Quick inventory mode				
10-018	The administrator can select Quick Inventory mode.	☐	☐	
10-019	The administrator can indicate whether chips are numbered or unnumbered.	☐	☐	
10-020	For numbered chips, printed values are entered even when exact quantities are not entered.	☐	☐	
10-021	For unnumbered chips, the administrator selects the available colours.	☐	☐	
10-022	The administrator can order colours from most available to least available by drag-and-drop or equivalent control.	☐	☐	
10-023	The engine recommends unique values for unnumbered colours.	☐	☐	
10-024	The most available colour is assigned to the denomination expected to be used most, not automatically always the lowest value.	☐	☐	
10-025	The administrator can review and change recommended values before generation.	☐	☐	
10-026	The app shows the number of chips required for the generated setup.	☐	☐	
10-027	Because quantities are estimated, the administrator must confirm that enough physical chips exist.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
10-028	If the administrator reports a shortage, the app allows regeneration with a simpler allocation.	☐	☐	
10.4 Starting-stack generation				
10-029	The starting stack and opening blinds are calculated together rather than using a fixed minimum stack.	☐	☐	
10-030	The stack is practical for the selected tournament duration and player count.	☐	☐	
10-031	The stack uses only configured chip values.	☐	☐	
10-032	The stack can be assembled from the available inventory.	☐	☐	
10-033	The stack contains enough small chips to post early blinds without constant change.	☐	☐	
10-034	The stack avoids an unnecessarily large number of physical chips.	☐	☐	
10-035	The stack is easy to count and visually practical.	☐	☐	
10-036	The engine shows the exact number of each colour per player.	☐	☐	
10-037	The engine shows the total number of each colour needed for all starting players.	☐	☐	
10-038	The engine reserves inventory for expected/relevant rebuys and add-ons where possible.	☐	☐	
10-039	The engine warns when the chip set cannot support the expected game.	☐	☐	
10.5 Rebuy stacks and chip exchanges				
10-040	A rebuy always has the same total chip value as the starting stack.	☐	☐	
10-041	A later rebuy may use more high-value chips and fewer obsolete low-value chips.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
10-042	A rebuy stack still contains denominations usable for the current blinds.	☐	☐	
10-043	The administrator sees the exact physical chip composition for a rebuy at the current level.	☐	☐	
10-044	The system provides clear colour-up/exchange instructions such as exchanging a specific number of one colour for another.	☐	☐	
10-045	Exact exchanges are preferred whenever possible.	☐	☐	
10-046	Small indivisible remainders can be rounded upward under the default home-game method.	☐	☐	
10-047	Any upward rounding is recorded in total chips in play.	☐	☐	
10-048	A formal chip race may be offered as an advanced alternative but is not required as the default.	☐	☐	
10-049	The system never recommends exchanging two colours that have the same value.	☐	☐	

11. Tournament Structure Engine

The engine is the product's core value. It must generate a coherent, physically playable structure rather than select a fixed template.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
11.1 Inputs and invariants				
11-001	The engine uses player count, target duration, chip values, chip availability mode, rebuy settings, add-on settings and ante settings.	☐	☐	
11-002	The engine uses a formula-based or search-based approach rather than a single hardcoded blind table.	☐	☐	
11-003	The engine produces the same result for the same saved inputs and algorithm version unless randomness is intentionally documented.	☐	☐	
11-004	Every generated blind can be posted using active chip denominations without unreasonable change-making.	☐	☐	
11-005	Level duration is always exactly 10, 15 or 20 minutes.	☐	☐	
11-006	The default aim is one consistent level duration throughout the tournament.	☐	☐	
11-007	A structure may use different 10/15/20-minute phases only when justified by the target duration and clearly shown.	☐	☐	
11-008	No generated structure contains a 12-minute, 18-minute or other unsupported level length.	☐	☐	
11-009	The engine does not assume the big blind is always exactly twice the small blind.	☐	☐	
11-010	Values such as 20/50 or 1,200/2,500 are allowed when they improve physical usability and progression.	☐	☐	
11-011	Blind labels are easy to read and announce.	☐	☐	
11-012	The engine avoids huge early blind jumps.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
11-013	The engine does not create a future level lower than the preceding level.	☐	☐	
11-014	The full structure contains enough levels to support the expected game without requiring level removal.	☐	☐	
11.2 Opening blinds and starting depth				
11-015	Opening blinds are chosen from the configured chip set rather than fixed globally.	☐	☐	
11-016	Possible openings may include 5/10, 10/20, 25/50, 50/100 or another practical pair.	☐	☐	
11-017	The engine avoids openings that require denominations not available.	☐	☐	
11-018	The engine balances starting depth, target duration and physical chip count.	☐	☐	
11-019	A fixed 5,000 minimum is not imposed when a different stack/blind pair is mathematically better.	☐	☐	
11-020	The generated starting depth avoids immediate push/fold play.	☐	☐	
11-021	The generated structure aims for meaningful early play through the rebuy period.	☐	☐	
11-022	The structure review displays starting stack in chips and starting depth in big blinds.	☐	☐	
11.3 Blind progression				
11-023	The progression increases pressure gradually in early levels.	☐	☐	
11-024	The progression can accelerate later to reach the target finish.	☐	☐	
11-025	Every level is ordered correctly and uniquely identified.	☐	☐	
11-026	The next-level display always matches the saved structure.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
11-027	When a new denomination becomes necessary, the structure supports a practical exchange point.	☐	☐	
11-028	The engine can insert an intermediate blind level when a jump would otherwise be too large.	☐	☐	
11-029	The engine never automatically removes or skips an existing approved level.	☐	☐	
11-030	The engine estimates expected finish time and displays it as an estimate.	☐	☐	
11-031	The engine includes the rebuy-close/settlement point in its duration model.	☐	☐	
11-032	The engine accounts for ante pressure when antes are enabled.	☐	☐	
11.4 Level timing and clock plan				
11-033	Every level has a saved duration of 10, 15 or 20 minutes.	☐	☐	
11-034	The selected target duration is 3 to 6 hours in approved half-hour steps.	☐	☐	
11-035	The default target is 3.5 hours.	☐	☐	
11-036	The system explains when the exact target cannot be guaranteed because poker eliminations vary.	☐	☐	
11-037	The settlement break after the rebuy period has no fixed countdown duration.	☐	☐	
11-038	The tournament remains paused until the administrator confirms settlement is complete.	☐	☐	
11-039	Future duration changes begin from the next level, never by shortening the active level.	☐	☐	
11.5 Antes				
11-040	A tournament can run with no ante.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
11-041	Big Blind Ante is the default ante format when antes are enabled.	☐	☐	
11-042	The default Big Blind Ante amount equals the current big blind unless the generated structure specifies another approved practical amount.	☐	☐	
11-043	Big Blind Ante remains active at the final table and heads-up by default.	☐	☐	
11-044	Individual Ante is available as the second ante type.	☐	☐	
11-045	Individual Ante is calculated approximately from the big blind divided by expected table size and rounded to an active denomination.	☐	☐	
11-046	The engine recalculates expected pressure and finish time when an ante is enabled.	☐	☐	
11-047	The engine warns if the selected ante would make the game substantially faster than the target.	☐	☐	
11-048	Antes normally begin after the rebuy period, usually after Level 6, unless the approved generated structure says otherwise.	☐	☐	
11.6 Engine output review				
11-049	The review shows every level in order.	☐	☐	
11-050	The review shows small blind, big blind, ante type/amount and level duration for each level.	☐	☐	
11-051	The review identifies the rebuy-closing level.	☐	☐	
11-052	The review identifies expected chip exchanges.	☐	☐	
11-053	The review shows starting-stack composition.	☐	☐	
11-054	The review shows rebuy-stack guidance.	☐	☐	
11-055	The review shows the estimated finish time/range.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
11-056	The administrator can return to inputs and regenerate.	☐	☐	
11-057	The administrator can accept and lock the pre-start structure.	☐	☐	
11-058	The accepted structure is identical on admin, player and TV views.	☐	☐	

12. Live Tournament Administration

The administrator must be able to run the complete game from one clear control screen and safely correct mistakes.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
12.1 Pre-start checks				
12-001	The admin dashboard shows tournament name, start time, expected duration and current status.	☐	☐	
12-002	The dashboard shows checked-in player count.	☐	☐	
12-003	The dashboard shows unconfirmed guests and unresolved attendance issues.	☐	☐	
12-004	The dashboard shows whether seating has been generated.	☐	☐	
12-005	The dashboard shows the accepted blind structure.	☐	☐	
12-006	The dashboard shows the required starting-stack preparation.	☐	☐	
12-007	The Start Tournament action is disabled or warns when critical setup is incomplete.	☐	☐	
12-008	Starting the tournament records a reliable server timestamp and local recovery state.	☐	☐	
12-009	The admin can confirm the initial dealer position generated by the system.	☐	☐	
12.2 Clock controls				
12-010	The administrator can start the tournament clock.	☐	☐	
12-011	The administrator can pause the clock.	☐	☐	
12-012	The administrator can resume the clock.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
12-013	The timer does not lose or gain material time after pause/resume cycles.	☐	☐	
12-014	The timer is calculated from timestamps rather than relying only on a drifting local interval.	☐	☐	
12-015	The administrator can move to the next level after confirmation where appropriate.	☐	☐	
12-016	The current level number, blinds, ante and remaining time update together.	☐	☐	
12-017	The next-level information updates immediately after a level change.	☐	☐	
12-018	When time reaches zero, the application transitions/alerts according to the approved flow without skipping data updates.	☐	☐	
12-019	The clock remains readable when the admin device is locked/unlocked or backgrounded, subject to platform limits.	☐	☐	
12-020	An accidental double-tap does not advance two levels.	☐	☐	
12-021	Critical clock actions are added to the audit/event history.	☐	☐	
12.3 Player additions and late registration				
12-022	The administrator can add a registered player while late registration is open.	☐	☐	
12-023	The administrator can approve/add a guest while late registration is open.	☐	☐	
12-024	A late player receives a full fresh starting stack.	☐	☐	
12-025	The late player is assigned to the recommended balanced table and an available seat after confirmation.	☐	☐	
12-026	Adding a player recalculates total chips, average stack and estimated finish.	☐	☐	
12-027	The system may recommend future blind or level-duration changes but never applies them automatically.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
12-028	Late registration closes permanently at the end of the rebuy period.	☐	☐	
12-029	No admin override can add another player after the closing confirmation in this MVP.	☐	☐	
12.4 Elimination and rebuy				
12-030	Only the administrator can mark a player eliminated.	☐	☐	
12-031	Elimination requires selecting the correct active player.	☐	☐	
12-032	An eliminated player is removed from players remaining.	☐	☐	
12-033	Average stack and players remaining update after elimination.	☐	☐	
12-034	If rebuys are open, an eliminated player can receive a rebuy.	☐	☐	
12-035	A rebuy is allowed only after elimination/zero chips.	☐	☐	
12-036	Rebuys are unlimited by default unless the game setting says otherwise.	☐	☐	
12-037	The rebuy stack total value equals the original starting stack.	☐	☐	
12-038	The UI shows the current-level physical rebuy composition.	☐	☐	
12-039	Recording a rebuy returns the player to active status.	☐	☐	
12-040	The player normally keeps the same seat when available.	☐	☐	
12-041	The rebuy contributes to total chips and private prize calculations.	☐	☐	
12-042	The administrator can undo an incorrect elimination.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
12-043	The administrator can undo an incorrect rebuy without corrupting later state.	☐	☐	
12-044	Undo restores player status, counts, total chips and calculations consistently.	☐	☐	
12.5 Re-entry				
12-045	Re-entry is available only when enabled before the game.	☐	☐	
12-046	Re-entry is treated separately from the normal rebuy record.	☐	☐	
12-047	A re-entering player receives the approved entry stack.	☐	☐	
12-048	A re-entering player receives an available seat according to seating rules.	☐	☐	
12-049	Re-entry closes with late registration/rebuys.	☐	☐	
12-050	Re-entry contributes to private prize calculations.	☐	☐	
12-051	The admin can correct an incorrectly recorded re-entry.	☐	☐	
12.6 End-of-rebuy settlement				
12-052	When the configured final rebuy level ends, the tournament clock pauses.	☐	☐	
12-053	The app clearly announces that rebuys and late registration are closing.	☐	☐	
12-054	The settlement screen opens or is clearly accessible.	☐	☐	
12-055	No fixed break countdown is imposed.	☐	☐	
12-056	The administrator can record final eligible rebuys from hands that began before closure, according to the approved process.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
12-057	The administrator can select add-on purchasers from active players.	☐	☐	
12-058	Each active player can receive no more than one add-on.	☐	☐	
12-059	Every active player is eligible for one add-on by default.	☐	☐	
12-060	The system displays the recommended add-on chip value and physical composition.	☐	☐	
12-061	The administrator can override the add-on amount after seeing a warning/impact summary.	☐	☐	
12-062	Recorded add-ons increase total chips and private prize calculations.	☐	☐	
12-063	The settlement screen displays required chip exchanges/colour-ups.	☐	☐	
12-064	The settlement screen confirms the ante type and activation for the next phase.	☐	☐	
12-065	Late registration, rebuys and re-entry are permanently closed after final confirmation.	☐	☐	
12-066	The administrator explicitly confirms settlement completion.	☐	☐	
12-067	The next level starts only when the administrator manually resumes/starts it.	☐	☐	
12-068	The public "Estimated Prize Pool" changes to "Prize Pool" after settlement confirmation.	☐	☐	
12-069	The administrator can correct settlement entries before final confirmation.	☐	☐	
12-070	After confirmation, corrections require an explicit admin correction flow and audit record.	☐	☐	
12.7 Live pace changes				
12-071	The administrator can open a Speed Up control during the game.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
12-072	The administrator can open a Slow Down control during the game.	☐	☐	
12-073	The system can recommend a pace change based on current progress.	☐	☐	
12-074	A recommendation explains the reason and estimated finish impact.	☐	☐	
12-075	The preview compares the current future structure with the proposed future structure.	☐	☐	
12-076	Speed Up may reduce future 20-minute levels to 15 or future 15-minute levels to 10.	☐	☐	
12-077	Speed Up may enable an already permitted ante or increase future blind pressure.	☐	☐	
12-078	Slow Down may increase future 10-minute levels to 15 or future 15-minute levels to 20.	☐	☐	
12-079	Slow Down may insert an intermediate future blind level or delay an ante.	☐	☐	
12-080	No live pace action changes the active level duration.	☐	☐	
12-081	No live pace action removes an approved level.	☐	☐	
12-082	Every pace change requires explicit admin confirmation.	☐	☐	
12-083	Cancelling the preview leaves the structure unchanged.	☐	☐	
12-084	Accepted changes synchronise to player and TV views.	☐	☐	
12-085	The accepted change is recorded in the audit/event history.	☐	☐	
12.8 Completing and correcting a tournament				
12-086	The administrator can record final finishing positions.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
12-087	The complete paid podium can contain more than three positions.	☐	☐	
12-088	The administrator can correct a finishing position before final completion.	☐	☐	
12-089	Completing the tournament stops the clock and closes live controls.	☐	☐	
12-090	The completed game appears in group history.	☐	☐	
12-091	Public/player completed results show paid positions without amounts.	☐	☐	
12-092	The admin retains access to private calculations.	☐	☐	
12-093	An accidental completion requires a clear controlled reopen/correction flow or support-safe mechanism.	☐	☐	

13. Seating, Tables and Final Table

Seating must be transparent, random when requested and easy for the admin to confirm physically.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
13.1 Initial seating				
13-001	The administrator can choose Fully Random seating.	☐	☐	
13-002	The administrator can choose Manual seating.	☐	☐	
13-003	The administrator can choose to keep guests with their inviter.	☐	☐	
13-004	The administrator can choose to separate guests from their inviter.	☐	☐	
13-005	Skill-balanced seating is not included.	☐	☐	
13-006	The default maximum table size is 9 unless a supported setting changes it.	☐	☐	
13-007	Up to 9 checked-in players can be seated at one table.	☐	☐	
13-008	More than 9 checked-in players create multiple tables automatically.	☐	☐	
13-009	No player is assigned twice.	☐	☐	
13-010	No two players are assigned to the same seat at the same table.	☐	☐	
13-011	Every checked-in active player receives exactly one seat.	☐	☐	
13-012	The initial dealer position is randomly assigned and clearly shown.	☐	☐	
13-013	The administrator confirms physical seating before play starts.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
13-014	Players/guests see only their own table and seat plus allowed public information.	☐	☐	
13.2 Table balancing				
13-015	The system detects when table sizes become meaningfully unbalanced.	☐	☐	
13-016	The system recommends which player should move and the destination table/seat.	☐	☐	
13-017	The recommendation is understandable to the administrator.	☐	☐	
13-018	No move is applied until the administrator confirms it.	☐	☐	
13-019	After confirmation, source and destination seats update consistently.	☐	☐	
13-020	Cancelling a recommendation changes nothing.	☐	☐	
13-021	A manually chosen move is validated to prevent duplicate seats.	☐	☐	
13-022	Players affected by a confirmed move see the updated seat.	☐	☐	
13.3 Final-table redraw				
13-023	If the tournament used multiple tables, final-table redraw is triggered when 9 players remain.	☐	☐	
13-024	The game pauses for the redraw.	☐	☐	
13-025	All 9 remaining players are randomly assigned to final-table seats.	☐	☐	
13-026	A random initial dealer-button position is assigned for the final table.	☐	☐	
13-027	The admin sees the full redraw and confirms physical seating.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
13-028	Player and guest views show updated seats after confirmation.	☐	☐	
13-029	Voice may announce final-table seating and dealer if audio is enabled.	☐	☐	
13-030	The game resumes only after admin confirmation.	☐	☐	
13-031	If the tournament began and remained one table, an unnecessary redraw is not forced.	☐	☐	
13-032	The system does not track subsequent physical dealer-button rotation.	☐	☐	

14. Prize Pool, Organizer Amount, Bounties and Visibility

All monetary calculations must reconcile exactly while public/player views remain intentionally limited.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
14.1 Contribution calculations				
14-001	The regular prize-pool calculation includes original buy-ins.	☐	☐	
14-002	The regular prize-pool calculation includes rebuys.	☐	☐	
14-003	The regular prize-pool calculation includes re-entries.	☐	☐	
14-004	The regular prize-pool calculation includes add-ons.	☐	☐	
14-005	KO bounty amounts are excluded from the regular prize pool.	☐	☐	
14-006	KO bounty amounts are excluded from the organizer percentage calculation.	☐	☐	
14-007	All contribution records required for calculation are visible only to the administrator.	☐	☐	
14-008	Poker Night does not record whether cash was physically paid.	☐	☐	
14-009	The displayed player count reflects unique players, not contribution count.	☐	☐	
14.2 Organizer percentage and rounding				
14-010	The admin interface calls the field "Percentage retained for equipment, drinks and snacks" or equivalent approved wording.	☐	☐	
14-011	The word rake is not used in the product UI.	☐	☐	
14-012	The organizer percentage applies to buy-in, rebuy, re-entry and add-on money.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
14-013	The calculation shows total eligible contributions, requested percentage, exact amount, recommended rounded amount and resulting prize pool to the admin.	☐	☐	
14-014	The algorithm prefers a rounded organizer amount that leaves a clean prize pool distributable in tens.	☐	☐	
14-015	For an eligible total of 165 and a target near 10%, retaining 15 and producing a prize pool of 150 is accepted.	☐	☐	
14-016	If two rounded choices are equally close, the system prefers retaining less and returning more to the prize pool.	☐	☐	
14-017	The admin can review the rounding adjustment before final confirmation.	☐	☐	
14-018	Players and guests never see the organizer percentage or retained amount.	☐	☐	
14.3 Paid places and payout generation				
14-019	The number of paid places depends on a combination of unique players and final prize pool.	☐	☐	
14-020	The payout structure is fair and meaningfully differentiates positions.	☐	☐	
14-021	The last paid place may be below the original buy-in when required for the fairest structure.	☐	☐	
14-022	Payout amounts are normally multiples of 10.	☐	☐	
14-023	Payouts ending in 5 such as 55, 65 or 75 are avoided.	☐	☐	
14-024	All payout amounts sum exactly to the final prize pool.	☐	☐	
14-025	First place receives the largest payout.	☐	☐	
14-026	No lower place receives more than a higher place.	☐	☐	
14-027	The engine can produce 1, 2, 3, 4 or more paid places when appropriate.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
14-028	The supplied baseline payout schedule from 50 to 700 is used as the intended style/reference.	☐	☐	
14-029	The admin can review the full private payout calculation before completing the game.	☐	☐	
14-030	The admin may manually adjust payouts while the app validates that the full prize pool still reconciles.	☐	☐	
14-031	Equal split, chip-count split, ICM/custom deal or leave-something-for-first controls are included only if present in the final agreed build; otherwise no inactive deal buttons appear.	☐	☐	
14.4 Bounties				
14-032	A KO tournament displays the buy-in and bounty separately, such as 15 + 5.	☐	☐	
14-033	The bounty amount does not increase the regular prize pool.	☐	☐	
14-034	The bounty amount does not increase the organizer amount.	☐	☐	
14-035	Only one killer is recorded for each eliminated player.	☐	☐	
14-036	The app does not require split-bounty calculation.	☐	☐	
14-037	Bounty events are visible to the administrator and reflected in allowed basic statistics such as knockouts.	☐	☐	
14.5 Monetary visibility				
14-038	During the game, registered players and TV viewers can see the total Estimated Prize Pool before settlement.	☐	☐	
14-039	After settlement, registered players and TV viewers can see the confirmed Prize Pool during the live game.	☐	☐	
14-040	No transaction breakdown is shown publicly.	☐	☐	
14-041	Rebuy count and add-on count are not shown to players or guests.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
14-042	Individual payout amounts are never shown to players or guests.	☐	☐	
14-043	After the game, the total prize-pool amount is not shown in player/public completed results.	☐	☐	
14-044	After the game, all paid podium positions are shown without monetary amounts.	☐	☐	
14-045	Players do not see their own investment, rebuys, add-ons, winnings, profit or ROI.	☐	☐	
14-046	The administrator can see the private calculation history required to audit the game.	☐	☐	

15. Player View, Guest View, TV Mode and Voice

Every non-admin projection must show only the data approved for that audience.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
15.1 Registered player live view				
15-001	A registered player can open the correct live game from the app or web app.	☐	☐	
15-002	The view shows tournament name and live status.	☐	☐	
15-003	The view shows the current timer.	☐	☐	
15-004	The view shows current blinds.	☐	☐	
15-005	The view shows current ante when active.	☐	☐	
15-006	The view shows next-level blinds/ante.	☐	☐	
15-007	The view shows players remaining.	☐	☐	
15-008	The view shows average stack or average big blinds when calculated.	☐	☐	
15-009	The view shows Estimated Prize Pool before settlement and Prize Pool during the game after settlement.	☐	☐	
15-010	The view shows the player's table and seat.	☐	☐	
15-011	The view reflects admin pause, resume and level changes in realtime.	☐	☐	
15-012	The view does not show admin controls.	☐	☐	
15-013	The view does not show private financial details.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
15.2 Guest live view				
15-014	An approved guest can reopen their game view through the guest web session.	☐	☐	
15-015	The guest view shows timer, blinds, ante, next level and public announcements.	☐	☐	
15-016	The guest view shows the guest's table and seat.	☐	☐	
15-017	The guest view shows players remaining and live prize pool where approved.	☐	☐	
15-018	The guest view does not expose chat or polls.	☐	☐	
15-019	The guest view does not expose admin controls or financial details.	☐	☐	
15-020	An unapproved guest sees a pending-confirmation state rather than live private details.	☐	☐	
15.3 TV browser mode				
15-021	The game code/landing page offers a clear Display on TV option.	☐	☐	
15-022	TV Mode opens without requiring an admin login.	☐	☐	
15-023	TV Mode is strictly read-only.	☐	☐	
15-024	TV Mode displays a large readable countdown timer.	☐	☐	
15-025	TV Mode displays current blinds prominently.	☐	☐	
15-026	TV Mode displays current ante when active.	☐	☐	
15-027	TV Mode displays the next level.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
15-028	TV Mode displays players remaining.	☐	☐	
15-029	TV Mode displays average stack/average big blinds when available.	☐	☐	
15-030	TV Mode displays Estimated Prize Pool before settlement and Prize Pool after settlement during the game.	☐	☐	
15-031	TV Mode displays break/settlement status.	☐	☐	
15-032	TV Mode displays visual announcements.	☐	☐	
15-033	TV Mode displays the final-table screen when triggered.	☐	☐	
15-034	TV Mode displays all paid podium positions without amounts after completion.	☐	☐	
15-035	TV Mode never displays organizer percentage, contributions, individual payouts or admin actions.	☐	☐	
15-036	TV Mode remains legible at common 16:9 television resolutions.	☐	☐	
15-037	TV Mode can be opened directly in a smart-TV browser or by ordinary screen mirroring.	☐	☐	
15-038	The MVP does not show inactive Chromecast or AirPlay integration buttons.	☐	☐	
15-039	If connection is interrupted, TV Mode clearly indicates stale/disconnected status while preserving the last safe display.	☐	☐	
15.4 Voice announcements				
15-040	English browser/device speech synthesis is available on supported devices.	☐	☐	
15-041	The administrator manually selects which connected device is the Audio Master.	☐	☐	
15-042	Only the selected Audio Master plays announcements by default.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
15-043	Changing Audio Master prevents duplicate simultaneous speech.	☐	☐	
15-044	The administrator can mute/unmute announcements.	☐	☐	
15-045	A tournament-start announcement is supported.	☐	☐	
15-046	A new-level announcement is supported.	☐	☐	
15-047	A five-minutes-remaining announcement is supported.	☐	☐	
15-048	A one-minute-remaining announcement is supported.	☐	☐	
15-049	A rebuys-closed announcement is supported.	☐	☐	
15-050	A final-table announcement is supported.	☐	☐	
15-051	A winner announcement is supported.	☐	☐	
15-052	Initial dealer and final-table dealer names may be announced.	☐	☐	
15-053	Elimination-name announcements are optional and disabled by default.	☐	☐	
15-054	Voice failure does not stop the timer or tournament controls.	☐	☐	
15-055	Voice commands are not present in the MVP.	☐	☐	

16. Group Game History and Basic Statistics

History and statistics remain intentionally simple and group-focused.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
16.1 Completed game history				
16-001	Completed tournaments appear in group history.	☐	☐	
16-002	Completed cash sessions appear in the appropriate simple history.	☐	☐	
16-003	A history item shows game name, date and game type.	☐	☐	
16-004	A tournament history item shows the final paid podium without amounts.	☐	☐	
16-005	History does not expose organizer amounts or private contribution records to players.	☐	☐	
16-006	History records remain stable after app reinstall or new-device login.	☐	☐	
16-007	The administrator can open the private completed-game record.	☐	☐	
16-008	Registered players can view allowed group history.	☐	☐	
16-009	Guests cannot access permanent group history without registering.	☐	☐	
16.2 Basic statistics				
16-010	The group can display games played.	☐	☐	
16-011	The group can display tournament winners.	☐	☐	
16-012	The group can display podium finishes.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
16-013	The group can display average finishing position where enough data exists.	☐	☐	
16-014	The group can display knockouts when bounty/elimination records support it.	☐	☐	
16-015	Statistics are recalculated after a completed result is corrected.	☐	☐	
16-016	No player-facing profit, ROI, amount invested, winnings, rebuy or add-on statistic is shown.	☐	☐	
16-017	No advanced graph, streak, achievement, season or complex leaderboard appears in the MVP.	☐	☐	

17. Minimal Cash-Game Module

Cash Poker is a separate, simpler area. It records chip-value movements for reconciliation but does not process money.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
17.1 Cash-game setup				
17-001	The administrator can create a cash-game session.	☐	☐	
17-002	The administrator can enter/select small blind and big blind.	☐	☐	
17-003	Cash-game blinds remain fixed throughout the session.	☐	☐	
17-004	The administrator can enter minimum and maximum buy-in when included by the final UI.	☐	☐	
17-005	The administrator can add players to the session.	☐	☐	
17-006	The administrator can assign initial seats.	☐	☐	
17-007	The session has a clear start action.	☐	☐	
17-008	Cash-game setup is visually separated from tournament creation.	☐	☐	
17.2 Live cash session				
17-009	The live screen shows fixed blinds.	☐	☐	
17-010	The live screen shows the player list and seats.	☐	☐	
17-011	The live screen shows elapsed session time.	☐	☐	
17-012	Only the administrator records initial buy-ins.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
17-013	Only the administrator records top-ups.	☐	☐	
17-014	Top-ups can be recorded multiple times.	☐	☐	
17-015	Only the administrator records cash-outs.	☐	☐	
17-016	A player can join or leave while the session is active, subject to the simple seating flow.	☐	☐	
17-017	The app records chip-value amounts for reconciliation, not physical payment status or method.	☐	☐	
17-018	Players do not see private profit/loss calculations during the game.	☐	☐	
17-019	The app does not track hands, pots or card outcomes.	☐	☐	
17-020	The admin can correct an incorrectly entered buy-in, top-up or cash-out.	☐	☐	
17-021	A refresh/reopen recovers the active cash session on the admin device.	☐	☐	
17.3 Cash reconciliation and completion				
17-022	The admin can end the cash session.	☐	☐	
17-023	The reconciliation screen lists total initial buy-ins.	☐	☐	
17-024	The reconciliation screen lists total top-ups.	☐	☐	
17-025	The reconciliation screen lists total cash-outs.	☐	☐	
17-026	The app checks whether total cash-outs equal total buy-ins plus top-ups.	☐	☐	
17-027	A mismatch produces a clear warning and difference amount.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
17-028	The administrator can correct entries before final completion.	☐	☐	
17-029	The final record retains the reconciliation result.	☐	☐	
17-030	Completed cash history does not expose financial amounts to ordinary players unless expressly approved.	☐	☐	
17-031	No actual payment is processed by Poker Night.	☐	☐	
17-032	Advanced cash waiting lists, multiple tables, straddle automation and detailed profit statistics are not required in this reduced MVP.	☐	☐	

18. Realtime Synchronisation, Local Recovery and Offline Behaviour

One administrator is authoritative. Player and TV devices receive updates, while the admin device retains enough local state to recover.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
18.1 Realtime updates				
18-001	Admin clock start, pause and resume propagate to registered player views.	☐	☐	
18-002	Admin clock start, pause and resume propagate to guest views.	☐	☐	
18-003	Admin clock start, pause and resume propagate to TV Mode.	☐	☐	
18-004	Level changes propagate to all online views.	☐	☐	
18-005	Blind and ante changes propagate to all online views.	☐	☐	
18-006	Player-count changes propagate to all online views.	☐	☐	
18-007	Seating confirmations propagate to affected players/guests.	☐	☐	
18-008	Settlement status and live prize-pool label/value propagate to allowed views.	☐	☐	
18-009	Chat messages propagate to registered users.	☐	☐	
18-010	Poll updates propagate to registered users.	☐	☐	
18-011	Realtime events are idempotent or protected from duplicate application.	☐	☐	
18-012	A temporarily disconnected viewer resynchronises to the current authoritative state after reconnecting.	☐	☐	
18.2 Authoritative admin and conflicts				

ID	Acceptance requirement	Dev	Client	Evidence / Notes
18-013	Only the designated administrator can mutate game state.	☐	☐	
18-014	A player or guest request cannot overwrite admin state.	☐	☐	
18-015	Repeated action submissions are protected against duplicates.	☐	☐	
18-016	The backend stores a clear game status and current structure version.	☐	☐	
18-017	Updates rejected due to stale state show a clear retry/reload message.	☐	☐	
18-018	The MVP does not require two offline administrators to merge conflicting game histories.	☐	☐	
18.3 Local admin recovery				
18-019	The active tournament state is saved locally on the admin device at meaningful changes.	☐	☐	
18-020	The active cash-session state is saved locally on the admin device at meaningful changes.	☐	☐	
18-021	Refreshing the admin web page restores the active game safely.	☐	☐	
18-022	Closing and reopening the app restores the active game safely.	☐	☐	
18-023	Temporary internet loss does not erase the admin's current game.	☐	☐	
18-024	The clock resumes from a correct timestamp after recovery rather than restarting the level.	☐	☐	
18-025	Queued admin changes synchronise when connection returns, subject to the one-admin model.	☐	☐	
18-026	The admin is told when the device is offline and when synchronisation is restored.	☐	☐	
18-027	Players and TV require internet for live updates and show a clear disconnected state when unavailable.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
18-028	No stale viewer is allowed to display itself as fully live without a connection indicator.	☐	☐	

19. Security, Privacy and Data Visibility

The application holds private group and game data. Access rules must be enforced server-side.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
19.1 Security baseline				
19-001	All production traffic uses HTTPS/TLS.	☐	☐	
19-002	Passwords are handled by a secure authentication provider or appropriate hashing system.	☐	☐	
19-003	Backend rules verify user identity and role for every protected operation.	☐	☐	
19-004	Admin-only endpoints reject player and guest requests.	☐	☐	
19-005	Group data cannot be read by unrelated authenticated users.	☐	☐	
19-006	Guest access tokens/cookies are scoped to the intended game.	☐	☐	
19-007	Guessing sequential IDs does not expose another group or game.	☐	☐	
19-008	Input is validated on the server as well as in the interface.	☐	☐	
19-009	Chat and name fields are protected against script injection.	☐	☐	
19-010	Rate limiting or equivalent abuse protection exists for login, code lookup and message sending.	☐	☐	
19-011	Production secrets are stored in environment/secret management, not source control.	☐	☐	
19-012	Database backups are configured and tested.	☐	☐	
19-013	Logs do not expose passwords, auth tokens or private secrets.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
19-014	Dependencies have no known critical unaddressed vulnerabilities at release.	☐	☐	
19.2 Privacy projections				
19-015	The administrator can see private organizer and contribution calculations.	☐	☐	
19-016	Registered players see only approved live public data, seat information, chat, polls and allowed history.	☐	☐	
19-017	Guests see only the intended game's limited live data and their seat.	☐	☐	
19-018	TV Mode receives a dedicated read-only projection with no private fields.	☐	☐	
19-019	Private fields are omitted by the backend response, not merely hidden with CSS.	☐	☐	
19-020	Player/public completed results contain no monetary amounts.	☐	☐	
19-021	Player-facing data contains no personal rebuy/add-on totals.	☐	☐	
19-022	Cash reconciliation details are limited to the administrator.	☐	☐	
19-023	The privacy policy accurately describes account, group, chat, notification and game data usage.	☐	☐	
19-024	Account deletion/data-request handling is documented even if manually processed in the MVP.	☐	☐	

20. Validation, Errors and Edge Cases

The product must fail safely and clearly. Error messages should help the user recover without corrupting game state.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
20.1 General validation				
20-001	Required fields cannot be submitted empty.	☐	☐	
20-002	Numeric fields reject letters and malformed values.	☐	☐	
20-003	Negative buy-ins, chip values, quantities, player counts and durations are rejected.	☐	☐	
20-004	Whole-number-only fields reject decimals where decimals are not allowed.	☐	☐	
20-005	Duplicate player entries are prevented or clearly resolved.	☐	☐	
20-006	Duplicate chip values are rejected.	☐	☐	
20-007	Form errors identify the specific field and required correction.	☐	☐	
20-008	A network failure does not erase completed form input.	☐	☐	
20-009	Loading states prevent accidental repeated submission.	☐	☐	
20.2 Tournament edge cases				
20-010	The engine handles a very small valid tournament without crashing.	☐	☐	
20-011	The engine handles more than one table.	☐	☐	
20-012	The engine handles a numbered chip set with no 5-value or 25-value chip.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
20-013	The engine handles an unnumbered chip set after values are assigned.	☐	☐	
20-014	The engine rejects or explains a chip set that cannot create any playable structure.	☐	☐	
20-015	The engine handles buy-in with KO bounty correctly.	☐	☐	
20-016	The engine handles no rebuy, no add-on and no ante.	☐	☐	
20-017	The engine handles rebuy plus add-on plus Big Blind Ante.	☐	☐	
20-018	The engine handles Individual Ante with practical rounding.	☐	☐	
20-019	The game can be paused for an extended settlement break without timer corruption.	☐	☐	
20-020	A player eliminated exactly near the rebuy-closing boundary is handled according to the approved settlement flow.	☐	☐	
20-021	A player cannot receive two add-ons.	☐	☐	
20-022	A player cannot rebuy while still active.	☐	☐	
20-023	No player can be added after late registration closes.	☐	☐	
20-024	An undo does not produce negative counts or duplicate active players.	☐	☐	
20-025	A final-table redraw triggers at 9 remaining only when multiple tables were used.	☐	☐	
20-026	The app handles all players eliminated/completed without a stuck live state.	☐	☐	
20.3 QR, guest and attendance edge cases				
20-027	A QR link to a deleted game shows a safe message.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
20-028	An expired guest session can restart the code flow without exposing another slot.	☐	☐	
20-029	Two guests attempting the same slot cannot both be approved.	☐	☐	
20-030	A player reducing guest count releases unused slots safely.	☐	☐	
20-031	An inviter changing RSVP after a guest checked in is handled with an admin-visible conflict before the cutoff.	☐	☐	
20-032	A guest name matching another player does not create the same record accidentally.	☐	☐	
20-033	A registered player cannot check in twice through app and web.	☐	☐	
20-034	A code cannot be used to access admin routes.	☐	☐	
20.4 Clock and realtime edge cases				
20-035	Refreshing during an active level preserves the correct remaining time.	☐	☐	
20-036	Backgrounding the admin app and returning preserves the correct remaining time.	☐	☐	
20-037	A viewer joining mid-level receives the correct current time and blinds.	☐	☐	
20-038	A viewer reconnecting after several levels receives current state, not replayed state screens.	☐	☐	
20-039	Two rapid admin taps do not create duplicate rebuys, eliminations or level advances.	☐	☐	
20-040	A server error during an admin action leaves a clear retry state and does not falsely show success.	☐	☐	
20-041	A delayed realtime message cannot roll the client back to an older level.	☐	☐	
20.5 Prize and cash edge cases				

ID	Acceptance requirement	Dev	Client	Evidence / Notes
20-042	Prize calculations reconcile when the eligible total is not a multiple of 10 before organizer rounding.	☐	☐	
20-043	Payout generation never creates an unexplained remainder.	☐	☐	
20-044	KO bounty contributions never leak into the regular pool.	☐	☐	
20-045	A manual payout edit that breaks the total is rejected.	☐	☐	
20-046	Cash reconciliation detects both positive and negative differences.	☐	☐	
20-047	Deleting/correcting a cash top-up recalculates totals.	☐	☐	
20-048	A cash session cannot be completed with unresolved required data without a warning.	☐	☐	

21. UI Quality, Responsiveness and Accessibility

The product must look intentional and remain usable across device sizes, not merely technically render.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
21.1 Visual consistency				
21-001	A consistent design system is used for colours, typography, spacing, buttons, inputs and cards.	☐	☐	
21-002	Primary, secondary, destructive and disabled buttons are visually distinct.	☐	☐	
21-003	Admin controls are visually separated from read-only information.	☐	☐	
21-004	The timer and blinds are the strongest visual elements in live/TV views.	☐	☐	
21-005	Forms are grouped into understandable steps rather than one confusing wall of fields.	☐	☐	
21-006	All icons have understandable labels or tooltips where meaning is not obvious.	☐	☐	
21-007	Error, warning, success and offline states use consistent treatment.	☐	☐	
21-008	The design is polished enough for public launch and contains no default framework demo styling.	☐	☐	
21.2 Responsive layouts				
21-009	The public website works at common mobile widths without horizontal scrolling.	☐	☐	
21-010	The web app works at common mobile widths without clipped controls.	☐	☐	
21-011	The web app works on tablets in portrait and landscape.	☐	☐	
21-012	The web app works on common laptop and desktop widths.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
21-013	The TV view fills the screen and remains readable at 1920×1080.	☐	☐	
21-014	Long player names are truncated/wrapped safely without breaking seating layouts.	☐	☐	
21-015	On-screen keyboards do not hide required mobile form controls.	☐	☐	
21-016	Safe areas and status bars do not overlap content on iOS/Android.	☐	☐	
21.3 Accessibility basics				
21-017	Text contrast is sufficient for normal and large text.	☐	☐	
21-018	Important information is not communicated by colour alone.	☐	☐	
21-019	Chip colours are accompanied by names/values.	☐	☐	
21-020	Interactive controls have accessible labels.	☐	☐	
21-021	Keyboard users can navigate the web app's essential flows.	☐	☐	
21-022	Visible focus indicators appear on web controls.	☐	☐	
21-023	Form fields have labels, not placeholder-only identification.	☐	☐	
21-024	Error messages are associated with the affected field.	☐	☐	
21-025	Touch targets are large enough for mobile use.	☐	☐	
21-026	TV text remains readable from a reasonable room distance.	☐	☐	
21-027	Voice announcements have equivalent visual announcements.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
21-028	Reduced-motion preferences are respected for nonessential animation where practical.	☐	☐	

22. End-to-End User Acceptance Scenarios

These scenarios must be demonstrated with production-like data. Passing isolated screens is not enough.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
22.1 Account and group scenarios				
22-001	UAT-001: A new user registers, logs in, creates a group and reaches the empty group home without developer intervention.	☐	☐	
22-002	UAT-002: The admin shares the group code; a registered player joins the correct group and cannot see another group.	☐	☐	
22-003	UAT-003: The user logs out and back in on a second platform and sees the same group.	☐	☐	
22.2 Tournament creation scenarios				
22-004	UAT-010: Admin creates a tournament from scratch with 8 players, 3.5 hours, buy-in 15, unnumbered chips, rebuys and add-on.	☐	☐	
22-005	UAT-011: The app recommends unique values for unnumbered chip colours and generates a physically understandable stack.	☐	☐	
22-006	UAT-012: Admin creates a second game using a saved preset and actual attendance regenerates the structure.	☐	☐	
22-007	UAT-013: Admin creates a numbered-chip game without a 25-value chip and the engine avoids impossible 25-based blinds.	☐	☐	
22-008	UAT-014: Admin enables KO bounty and the UI/calculations separate buy-in and bounty.	☐	☐	
22-009	UAT-015: Admin enables Individual Ante and the generated ante is compatible with chips and shown on all views.	☐	☐	
22.3 Invitation and guest scenarios				
22-010	UAT-020: A player selects Going +2 and two guest slots appear.	☐	☐	
22-011	UAT-021: Guest A scans the QR on iOS, selects inviter and Guest 1, enters a name and is approved by the admin.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
22-012	UAT-022: Guest B enters the manual code on Android, selects Guest 2 and is approved.	☐	☐	
22-013	UAT-023: A third device cannot claim the already used Guest 1 or Guest 2 slot.	☐	☐	
22-014	UAT-024: A registered player checks in from the app and the admin sees the updated count.	☐	☐	
22-015	UAT-025: After the one-hour RSVP cutoff, a player cannot alter the RSVP without admin handling.	☐	☐	
22.4 Seating and start scenarios				
22-016	UAT-030: Admin generates random seating for more than 9 players and receives multiple valid tables.	☐	☐	
22-017	UAT-031: Every checked-in person receives exactly one unique seat.	☐	☐	
22-018	UAT-032: Player and guest devices display their correct seat after admin confirmation.	☐	☐	
22-019	UAT-033: TV Mode opens from the code page and shows only approved public data.	☐	☐	
22-020	UAT-034: Admin starts the game and timer/blinds synchronise across web, Android, iOS and TV.	☐	☐	
22.5 Live play scenarios				
22-021	UAT-040: Admin pauses and resumes the clock; all online views stay consistent.	☐	☐	
22-022	UAT-041: A player is eliminated, players remaining and average stack update.	☐	☐	
22-023	UAT-042: The eliminated player rebuys, returns active in the same seat and receives the correct current-level chip composition.	☐	☐	
22-024	UAT-043: Admin records an incorrect elimination and undo restores all affected data.	☐	☐	
22-025	UAT-044: Admin adds a late player before registration closes; seat and estimates update.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
22-026	UAT-045: Admin attempts to add a player after registration closes and the app blocks it.	☐	☐	
22-027	UAT-046: Admin previews Speed Up, cancels it and confirms nothing changed.	☐	☐	
22-028	UAT-047: Admin previews Slow Down, accepts an inserted future level and all views receive the new future structure.	☐	☐	
22.6 Settlement and prize scenarios				
22-029	UAT-050: End of Level 6 pauses the game and opens settlement without a fixed break timer.	☐	☐	
22-030	UAT-051: Admin records final rebuys and selects add-ons, with no player receiving more than one add-on.	☐	☐	
22-031	UAT-052: Admin confirms ante activation and chip exchanges.	☐	☐	
22-032	UAT-053: Public label changes from Estimated Prize Pool to Prize Pool after settlement.	☐	☐	
22-033	UAT-054: Eligible total 165 and organizer target near 10% produces an acceptable clean result such as organizer 15 / prize pool 150.	☐	☐	
22-034	UAT-055: KO bounty money remains excluded from organizer and prize-pool calculations.	☐	☐	
22-035	UAT-056: Generated payouts sum exactly to the prize pool and use clean rounded values.	☐	☐	
22.7 Final table and completion scenarios				
22-036	UAT-060: A multi-table tournament reaches 9 players and pauses for a full random final-table redraw.	☐	☐	
22-037	UAT-061: Final seats and initial dealer are confirmed and synchronised.	☐	☐	
22-038	UAT-062: Admin records final paid positions and completes the game.	☐	☐	
22-039	UAT-063: Player and TV completed views show all paid positions with no monetary amounts.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
22-040	UAT-064: The completed game appears in group history and basic statistics update.	☐	☐	
22.8 Chat, poll and notification scenarios				
22-041	UAT-070: Admin sends a chat message and registered users receive it; guest web view does not expose chat.	☐	☐	
22-042	UAT-071: Admin creates a poll, registered player votes once and totals update.	☐	☐	
22-043	UAT-072: Admin closes the poll and further votes are blocked.	☐	☐	
22-044	UAT-073: A game notification opens the correct game on Android, iOS or supported web environment.	☐	☐	
22.9 Recovery scenarios				
22-045	UAT-080: Admin refreshes the web page during an active level and recovers the correct timer/state.	☐	☐	
22-046	UAT-081: Admin backgrounds and reopens the mobile app and recovers the correct timer/state.	☐	☐	
22-047	UAT-082: Internet disconnects on the admin device, local state remains available and resynchronises after reconnection.	☐	☐	
22-048	UAT-083: TV/player view disconnects and clearly indicates stale/offline state before resynchronising.	☐	☐	
22.10 Cash-game scenarios				
22-049	UAT-090: Admin creates a cash session with fixed blinds and seats players.	☐	☐	
22-050	UAT-091: Admin records initial buy-ins, multiple top-ups and cash-outs.	☐	☐	
22-051	UAT-092: The app calculates a matching reconciliation when totals balance.	☐	☐	
22-052	UAT-093: The app warns and shows the difference when totals do not balance.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
22-053	UAT-094: Admin corrects an entry and completes the cash session.	☐	☐	

23. Compatibility, Performance and Reliability

The product must be usable on the agreed platforms with reasonable speed and stability.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
23.1 Browser and device compatibility				
23-001	The public website and web app are tested on current Chrome.	☐	☐	
23-002	The public website and web app are tested on current Safari.	☐	☐	
23-003	The public website and web app are tested on current Firefox or Edge.	☐	☐	
23-004	The TV view is tested in at least one common smart-TV browser or an equivalent TV-resolution browser environment.	☐	☐	
23-005	Android and iOS builds use supported OS versions documented in release notes.	☐	☐	
23-006	Unsupported browser/OS behaviour is documented rather than silently failing.	☐	☐	
23.2 Performance and stability				
23-007	The homepage and login page load within a reasonable time on normal broadband/mobile data.	☐	☐	
23-008	The admin live screen remains responsive during a multi-hour session.	☐	☐	
23-009	Realtime updates normally appear within a reasonable short delay.	☐	☐	
23-010	The application does not leak memory or become unusably slow during repeated level changes.	☐	☐	
23-011	Large chat history is paginated/limited enough to avoid freezing the group screen.	☐	☐	
23-012	Database queries used by live screens are indexed/structured to avoid obvious scaling issues.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
23-013	Uncaught production errors are logged in a client-owned error-monitoring solution or documented alternative.	☐	☐	
23-014	A production backup exists before major deployment changes.	☐	☐	

24. Deployment, App Stores and Production Launch

The project is not finished when it only runs on the developer's machine. Production deployment and release-ready mobile builds are required.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
24.1 Production web deployment				
24-001	The final public website is deployed to the client's production domain.	☐	☐	
24-002	The final web app is deployed and reachable from the production website.	☐	☐	
24-003	The backend/database uses production configuration, not test credentials.	☐	☐	
24-004	HTTPS works on all production routes.	☐	☐	
24-005	Direct links and refreshes work in production.	☐	☐	
24-006	Production code does not expose debug banners, developer menus or test accounts.	☐	☐	
24-007	The production environment has a documented rollback or redeploy procedure.	☐	☐	
24-008	The client can deploy a future version using the written instructions.	☐	☐	
24.2 Android release				
24-009	The final Android package name matches the client-owned Play Console application.	☐	☐	
24-010	The app name, icon, screenshots and description assets required for submission are delivered or clearly assigned.	☐	☐	
24-011	A signed production AAB is generated from the accepted source code.	☐	☐	
24-012	The signing-key ownership and secure backup arrangement are documented.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
24-013	The app is uploaded to the client's Play Console or the developer assists live with upload.	☐	☐	
24-014	Required data-safety/privacy declarations are supported with accurate technical information.	☐	☐	
24-015	Code-related Play Console warnings/rejections are corrected by the developer.	☐	☐	
24-016	The final build is published or accepted for release, except for delays caused solely by the client's account status or platform-controlled testing rules.	☐	☐	
24.3 iOS release				
24-017	The final bundle identifier matches the client-owned App Store Connect application.	☐	☐	
24-018	The app name, icon, screenshots and description assets required for submission are delivered or clearly assigned.	☐	☐	
24-019	A production archive is generated from the accepted source code.	☐	☐	
24-020	Certificates/profiles are configured through the client's Apple account.	☐	☐	
24-021	The build is uploaded to App Store Connect/TestFlight or the developer assists live with upload.	☐	☐	
24-022	Required privacy labels are supported with accurate technical information.	☐	☐	
24-023	Code-related App Store validation errors/rejections are corrected by the developer.	☐	☐	
24-024	The final build is published or accepted for release, except for delays caused solely by the client's account status or independent Apple review decisions not caused by code.	☐	☐	
24.4 Launch verification				
24-025	The live production website loads from a device not used during development.	☐	☐	
24-026	A new production account can register and log in.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
24-027	A production group and test game can be created.	☐	☐	
24-028	A production QR code can be scanned and used successfully.	☐	☐	
24-029	Production realtime updates work across at least two devices.	☐	☐	
24-030	Production voice announcements work on a supported selected device.	☐	☐	
24-031	Production local recovery works after refresh/reopen.	☐	☐	
24-032	Production privacy/terms/support links work.	☐	☐	
24-033	No critical or high-severity defects remain open at launch.	☐	☐	

25. Baseline Payout Style Regression Checks

The engine need not hardcode this table, but its output should preserve this approved style unless the algorithm's documented player-count logic justifies a different paid-place count. Each sample must still reconcile and use clean amounts.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
25.1 Reference payout samples				
25-001	For a final prize pool of 50, the engine output is checked against the approved reference style 40 / 10; any material deviation is documented and justified.	☐	☐	
25-002	For a final prize pool of 60, the engine output is checked against the approved reference style 40 / 20; any material deviation is documented and justified.	☐	☐	
25-003	For a final prize pool of 70, the engine output is checked against the approved reference style 50 / 20; any material deviation is documented and justified.	☐	☐	
25-004	For a final prize pool of 80, the engine output is checked against the approved reference style 50 / 30; any material deviation is documented and justified.	☐	☐	
25-005	For a final prize pool of 90, the engine output is checked against the approved reference style 60 / 30; any material deviation is documented and justified.	☐	☐	
25-006	For a final prize pool of 100, the engine output is checked against the approved reference style 60 / 30 / 10; any material deviation is documented and justified.	☐	☐	
25-007	For a final prize pool of 110, the engine output is checked against the approved reference style 70 / 30 / 10; any material deviation is documented and justified.	☐	☐	
25-008	For a final prize pool of 120, the engine output is checked against the approved reference style 70 / 40 / 10; any material deviation is documented and justified.	☐	☐	
25-009	For a final prize pool of 130, the engine output is checked against the approved reference style 80 / 40 / 10; any material deviation is documented and justified.	☐	☐	
25-010	For a final prize pool of 140, the engine output is checked against the approved reference style 80 / 40 / 20; any material deviation is documented and justified.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
25-011	For a final prize pool of 150, the engine output is checked against the approved reference style 90 / 40 / 20; any material deviation is documented and justified.	☐	☐	
25-012	For a final prize pool of 160, the engine output is checked against the approved reference style 90 / 50 / 20; any material deviation is documented and justified.	☐	☐	
25-013	For a final prize pool of 170, the engine output is checked against the approved reference style 100 / 50 / 20; any material deviation is documented and justified.	☐	☐	
25-014	For a final prize pool of 180, the engine output is checked against the approved reference style 110 / 50 / 20; any material deviation is documented and justified.	☐	☐	
25-015	For a final prize pool of 190, the engine output is checked against the approved reference style 110 / 60 / 20; any material deviation is documented and justified.	☐	☐	
25-016	For a final prize pool of 200, the engine output is checked against the approved reference style 110 / 60 / 30; any material deviation is documented and justified.	☐	☐	
25-017	For a final prize pool of 210, the engine output is checked against the approved reference style 120 / 60 / 30; any material deviation is documented and justified.	☐	☐	
25-018	For a final prize pool of 220, the engine output is checked against the approved reference style 130 / 60 / 30; any material deviation is documented and justified.	☐	☐	
25-019	For a final prize pool of 230, the engine output is checked against the approved reference style 130 / 70 / 30; any material deviation is documented and justified.	☐	☐	
25-020	For a final prize pool of 240, the engine output is checked against the approved reference style 140 / 70 / 30; any material deviation is documented and justified.	☐	☐	
25-021	For a final prize pool of 250, the engine output is checked against the approved reference style 140 / 80 / 30; any material deviation is documented and justified.	☐	☐	
25-022	For a final prize pool of 260, the engine output is checked against the approved reference style 150 / 80 / 30; any material deviation is documented and justified.	☐	☐	
25-023	For a final prize pool of 270, the engine output is checked against the approved reference style 150 / 80 / 40; any material deviation is documented and justified.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
25-024	For a final prize pool of 280, the engine output is checked against the approved reference style 160 / 80 / 40; any material deviation is documented and justified.	☐	☐	
25-025	For a final prize pool of 290, the engine output is checked against the approved reference style 160 / 90 / 40; any material deviation is documented and justified.	☐	☐	
25-026	For a final prize pool of 300, the engine output is checked against the approved reference style 170 / 90 / 40; any material deviation is documented and justified.	☐	☐	
25-027	For a final prize pool of 310, the engine output is checked against the approved reference style 180 / 90 / 40; any material deviation is documented and justified.	☐	☐	
25-028	For a final prize pool of 320, the engine output is checked against the approved reference style 180 / 100 / 40; any material deviation is documented and justified.	☐	☐	
25-029	For a final prize pool of 330, the engine output is checked against the approved reference style 190 / 100 / 40; any material deviation is documented and justified.	☐	☐	
25-030	For a final prize pool of 340, the engine output is checked against the approved reference style 190 / 100 / 50; any material deviation is documented and justified.	☐	☐	
25-031	For a final prize pool of 350, the engine output is checked against the approved reference style 200 / 100 / 50; any material deviation is documented and justified.	☐	☐	
25-032	For a final prize pool of 360, the engine output is checked against the approved reference style 200 / 110 / 50; any material deviation is documented and justified.	☐	☐	
25-033	For a final prize pool of 370, the engine output is checked against the approved reference style 210 / 110 / 50; any material deviation is documented and justified.	☐	☐	
25-034	For a final prize pool of 380, the engine output is checked against the approved reference style 210 / 120 / 50; any material deviation is documented and justified.	☐	☐	
25-035	For a final prize pool of 390, the engine output is checked against the approved reference style 220 / 120 / 50; any material deviation is documented and justified.	☐	☐	
25-036	For a final prize pool of 400, the engine output is checked against the approved reference style 220 / 120 / 40 / 20; any material deviation is documented and justified.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
25-037	For a final prize pool of 410, the engine output is checked against the approved reference style 230 / 120 / 40 / 20; any material deviation is documented and justified.	☐	☐	
25-038	For a final prize pool of 420, the engine output is checked against the approved reference style 240 / 120 / 40 / 20; any material deviation is documented and justified.	☐	☐	
25-039	For a final prize pool of 430, the engine output is checked against the approved reference style 240 / 130 / 40 / 20; any material deviation is documented and justified.	☐	☐	
25-040	For a final prize pool of 440, the engine output is checked against the approved reference style 250 / 130 / 40 / 20; any material deviation is documented and justified.	☐	☐	
25-041	For a final prize pool of 450, the engine output is checked against the approved reference style 250 / 140 / 40 / 20; any material deviation is documented and justified.	☐	☐	
25-042	For a final prize pool of 460, the engine output is checked against the approved reference style 260 / 140 / 40 / 20; any material deviation is documented and justified.	☐	☐	
25-043	For a final prize pool of 470, the engine output is checked against the approved reference style 260 / 140 / 50 / 20; any material deviation is documented and justified.	☐	☐	
25-044	For a final prize pool of 480, the engine output is checked against the approved reference style 270 / 140 / 50 / 20; any material deviation is documented and justified.	☐	☐	
25-045	For a final prize pool of 490, the engine output is checked against the approved reference style 270 / 150 / 50 / 20; any material deviation is documented and justified.	☐	☐	
25-046	For a final prize pool of 500, the engine output is checked against the approved reference style 280 / 150 / 50 / 20; any material deviation is documented and justified.	☐	☐	
25-047	For a final prize pool of 510, the engine output is checked against the approved reference style 290 / 150 / 50 / 20; any material deviation is documented and justified.	☐	☐	
25-048	For a final prize pool of 520, the engine output is checked against the approved reference style 290 / 160 / 50 / 20; any material deviation is documented and justified.	☐	☐	
25-049	For a final prize pool of 530, the engine output is checked against the approved reference style 300 / 160 / 50 / 20; any material deviation is documented and justified.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
25-050	For a final prize pool of 540, the engine output is checked against the approved reference style 300 / 160 / 60 / 20; any material deviation is documented and justified.	☐	☐	
25-051	For a final prize pool of 550, the engine output is checked against the approved reference style 310 / 160 / 60 / 20; any material deviation is documented and justified.	☐	☐	
25-052	For a final prize pool of 560, the engine output is checked against the approved reference style 310 / 170 / 60 / 20; any material deviation is documented and justified.	☐	☐	
25-053	For a final prize pool of 570, the engine output is checked against the approved reference style 320 / 170 / 60 / 20; any material deviation is documented and justified.	☐	☐	
25-054	For a final prize pool of 580, the engine output is checked against the approved reference style 320 / 180 / 60 / 20; any material deviation is documented and justified.	☐	☐	
25-055	For a final prize pool of 590, the engine output is checked against the approved reference style 330 / 180 / 60 / 20; any material deviation is documented and justified.	☐	☐	
25-056	For a final prize pool of 600, the engine output is checked against the approved reference style 330 / 180 / 70 / 20; any material deviation is documented and justified.	☐	☐	
25-057	For a final prize pool of 610, the engine output is checked against the approved reference style 340 / 180 / 70 / 20; any material deviation is documented and justified.	☐	☐	
25-058	For a final prize pool of 620, the engine output is checked against the approved reference style 340 / 190 / 70 / 20; any material deviation is documented and justified.	☐	☐	
25-059	For a final prize pool of 630, the engine output is checked against the approved reference style 350 / 190 / 70 / 20; any material deviation is documented and justified.	☐	☐	
25-060	For a final prize pool of 640, the engine output is checked against the approved reference style 350 / 190 / 80 / 20; any material deviation is documented and justified.	☐	☐	
25-061	For a final prize pool of 650, the engine output is checked against the approved reference style 360 / 190 / 80 / 20; any material deviation is documented and justified.	☐	☐	
25-062	For a final prize pool of 660, the engine output is checked against the approved reference style 360 / 200 / 80 / 20; any material deviation is documented and justified.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
25-063	For a final prize pool of 670, the engine output is checked against the approved reference style 370 / 200 / 80 / 20; any material deviation is documented and justified.	☐	☐	
25-064	For a final prize pool of 680, the engine output is checked against the approved reference style 370 / 210 / 80 / 20; any material deviation is documented and justified.	☐	☐	
25-065	For a final prize pool of 690, the engine output is checked against the approved reference style 380 / 210 / 80 / 20; any material deviation is documented and justified.	☐	☐	
25-066	For a final prize pool of 700, the engine output is checked against the approved reference style 390 / 210 / 80 / 20; any material deviation is documented and justified.	☐	☐	

26. Final Defect Closure and Sign-Off

This section is completed only after all detailed checks and UAT scenarios have been performed.

ID	Acceptance requirement	Dev	Client	Evidence / Notes
26.1 Defect closure				
26-001	Every defect found during developer testing has a unique ID and recorded resolution.	☐	☐	
26-002	Every defect found during client UAT has a unique ID and recorded resolution.	☐	☐	
26-003	All critical defects are closed and retested.	☐	☐	
26-004	All high-severity defects are closed and retested.	☐	☐	
26-005	No medium/low defect blocks a core flow or contradicts this checklist.	☐	☐	
26-006	Regression testing is completed after the final bug-fix build.	☐	☐	
26-007	The final build numbers/commit hash are recorded in the sign-off section.	☐	☐	
26-008	The live production deployment matches the signed-off source code/build.	☐	☐	
26.2 Final acceptance package				
26-009	Developer checklist is fully marked and signed.	☐	☐	
26-010	Client checklist is fully marked and signed.	☐	☐	
26-011	Evidence links/files are available for all major modules.	☐	☐	
26-012	Source repository ownership is confirmed.	☐	☐	

ID	Acceptance requirement	Dev	Client	Evidence / Notes
26-013	Production account ownership is confirmed.	☐	☐	
26-014	Web production URL is confirmed.	☐	☐	
26-015	Android release/build status is confirmed.	☐	☐	
26-016	iOS release/build status is confirmed.	☐	☐	
26-017	All credentials and documentation are delivered.	☐	☐	
26-018	The support/bug-fix period start and end dates are written.	☐	☐	
26-019	Any accepted exceptions are listed in the signed exception table.	☐	☐	
26-020	Final payment release is authorised only after the client signs final acceptance.	☐	☐	

Defect Log

Record every failed item here. Use one row per distinct defect. Add pages if required.

Defect ID	Checklist ID	Description / steps	Severity	Owner	Target date	Retest evidence	Status

Defect ID	Checklist ID	Description / steps	Severity	Owner	Target date	Retest evidence	Status

Mutually Approved Exceptions (if any)

An exception is valid only when both parties sign it. A verbal message or an unapproved developer assumption is not enough.

Exception ID	Checklist ID(s)	Exact change / reason	Developer approval	Client approval	Date

Final Release and Payment Sign-Off

Total acceptance checks in this document: 1019.

The developer confirms that every in-scope item has been implemented and that the delivered source code matches the tested production build.

The client confirms that every in-scope item has been tested and accepted, except only the signed exceptions listed above.

Final payment may be released only after the client signs this page.

Final source commit / tag		Production web URL	
Android version / build		Android release status	
iOS version / build		iOS release status	
Backend environment		Database project	
Support period ends		Open accepted minor defects	

Developer name: _____ Date: _____

Developer signature: _____

Client name: _____ Date: _____

Client signature: _____

FINAL CLIENT DECISION

☐ **ACCEPTED** — release final payment ☐ **NOT ACCEPTED** — unresolved checklist items remain