

Working with Data in Python Cheat Sheet

Reading and writing files

Package/Method Description		
File opening modes	Different modes to open files for specific operations.	Syntax: r (reading) w (writing) a (appending) + (updating: read/write) b (binary, otherwise text) <div>1. 1</div> <div>1. Examples: with open("data.txt", "r") as file: content = file.read() print(content) with open("output.txt",</div> <div>Copied!</div>
		Syntax: <div>1. 1</div> <div>2. 2</div> <div>3. 3</div> <div>1. file.readlines() # reads all lines as a list</div> <div>2. readline() # reads the next line as a string</div> <div>3. file.read() # reads the entire file content as a string</div>
File reading methods	Different methods to read file content in various ways.	<div>Copied!</div> <div>Example:</div> <div>1. 1</div> <div>2. 2</div> <div>3. 3</div> <div>4. 4</div> <div>1. with open("data.txt", "r") as file:</div> <div>2. lines = file.readlines()</div> <div>3. next_line = file.readline()</div> <div>4. content = file.read()</div> <div>Copied!</div>
		Syntax: <div>1. 1</div> <div>2. 2</div> <div>1. file.write(content) # writes a string to the file</div> <div>2. file.writelines(lines) # writes a list of strings to the file</div>
File writing methods	Different write methods to write content to a file.	<div>Copied!</div> <div>Example:</div> <div>1. 1</div> <div>2. 2</div> <div>3. 3</div> <div>1. lines = ["Hello\n", "World\n"]</div> <div>2. with open("output.txt", "w") as file:</div> <div>3. file.writelines(lines)</div> <div>Copied!</div>
		Syntax: <div>1. 1</div> <div>1. for line in file: # Code to process each line</div>
Iterating over lines	Iterates through each line in the file using a `loop`.	<div>Copied!</div> <div>Example:</div> <div>1. 1</div> <div>2. 2</div> <div>1. with open("data.txt", "r") as file:</div> <div>2. for line in file: print(line)</div> <div>Copied!</div>
		Syntax: <div>1. 1</div> <div>2. 2</div>
Open() and close()	Opens a file, performs operations, and explicitly closes the file using the close() method.	<div>1. file = open(filename, mode) # Code that uses the file</div> <div>2. file.close()</div> <div>Copied!</div> <div>Example:</div> <div>1. 1</div> <div>2. 2</div> <div>3. 3</div> <div>1. file = open("data.txt", "r")</div> <div>2. content = file.read()</div> <div>3. file.close()</div> <div>Copied!</div>
		with open() Opens a file Syntax: using a with

```
block,      1. 1
ensuring    1. with open(filename, mode) as file: # Code that uses the file
automatic
file closure
after usage. Copied!
```

Example:

```
1. 1
2. 2

1. with open("data.txt", "r") as file:
2. content = file.read()
```

Copied!

Pandas

Package/Method	Description	Syntax and Code Example
.read_csv()	Reads data from a `.CSV` file and creates a DataFrame.	Syntax: dataframe_name = pd.read_csv("filename.csv") Example: df = pd.read_csv("data.csv")  Syntax:  1. 1  1. dataframe_name = pd.read_excel("filename.xlsx")  Copied!
.read_excel()	Reads data from an Excel file and creates a DataFrame.	Example:  1. 1  1. df = pd.read_excel("data.xlsx")  Copied!  Syntax:  1. 1  1. dataframe_name.to_csv("output.csv", index=False)  Copied!
.to_csv()	Writes DataFrame to a CSV file.	Example:  1. 1  1. df.to_csv("output.csv", index=False)  Copied!  Syntax:  1. 1 2. 2  1. dataframe_name["column_name"] # Accesses single column 2. dataframe_name[["column1", "column2"]] # Accesses multiple columns  Copied!
Access Columns	Accesses a specific column using [] in the DataFrame.	Example:  1. 1 2. 2  1. df["age"] 2. df[["name", "age"]]  Copied!  Syntax:  1. 1  1. dataframe_name.describe()
describe()	Generates statistics summary of numeric columns in the DataFrame.	Copied!  Example:  1. 1  1. df.describe()
drop()	Removes specified rows or columns from the DataFrame. axis=1 indicates columns. axis=0 indicates rows.	Copied!  Syntax:  1. 1 2. 2  1. dataframe_name.drop(["column1", "column2"], axis=1, inplace=True) 2. dataframe_name.drop(index=[row1, row2], axis=0, inplace=True)  Copied!  Example:  1. 1 2. 2

		<div>about:blank</div> <div><div>1. df.drop(["age", "salary"], axis=1, inplace=True) # Will drop columns</div><div>2. df.drop(index=[5, 10], axis=0, inplace=True) # Will drop rows</div></div> <div>Copied!</div> <div>Syntax:</div> <div><div>1. 1</div><div>1. dataframe_name.dropna(axis=0, inplace=True)</div></div>
dropna()	Removes rows with missing NaN values from the DataFrame. axis=0 indicates rows.	<div>Copied!</div> <div>Example:</div> <div><div>1. 1</div><div>1. df.dropna(axis=0, inplace=True)</div></div> <div>Copied!</div> <div>Syntax:</div> <div><div>1. 1</div><div>1. dataframe_name.duplicated()</div></div>
duplicated()	Duplicate or repetitive values or records within a data set.	<div>Copied!</div> <div>Example:</div> <div><div>1. 1</div><div>1. duplicate_rows = df[df.duplicated()]</div></div> <div>Copied!</div> <div>Syntax:</div> <div><div>1. 1</div><div>1. filtered_df = dataframe_name[(Conditional_statements)]</div></div>
Filter Rows	Creates a new DataFrame with rows that meet specified conditions.	<div>Copied!</div> <div>Example:</div> <div><div>1. 1</div><div>1. filtered_df = df[(df["age"] &gt; 30) &amp; (df["salary"] &lt; 50000)]</div></div> <div>Copied!</div> <div>Syntax:</div> <div><div>1. 1</div><div>2. 2</div><div>1. grouped = dataframe_name.groupby(by, axis=0, level=None, as_index=True, sort=True, group_keys=True, squeeze=False, observed=False, dropna=True)</div></div>
groupby()	Splits a DataFrame into groups based on specified criteria, enabling subsequent aggregation, transformation, or analysis within each group.	<div>Copied!</div> <div>Example:</div> <div><div>1. 1</div><div>1. grouped = df.groupby(["category", "region"]).agg({"sales": "sum"})</div></div> <div>Copied!</div> <div>Syntax:</div> <div><div>1. 1</div><div>1. dataframe_name.head(n)</div></div>
head()	Displays the first n rows of the DataFrame.	<div>Copied!</div> <div>Example:</div> <div><div>1. 1</div><div>1. df.head(5)</div></div> <div>Copied!</div> <div>Syntax:</div> <div><div>1. 1</div><div>1. import pandas as pd</div></div>
Import pandas	Imports the Pandas library with the alias pd.	<div>Copied!</div> <div>Example:</div> <div><div>1. 1</div><div>1. import pandas as pd</div></div> <div>Copied!</div>

		<div>Syntax:<div>1. 1</div><div>1. dataframe_name.info()</div></div> <div>Copied!</div>
info()	Provides information about the DataFrame, including data types and memory usage.	<div>Example:<div>1. 1</div><div>1. df.info()</div></div> <div>Copied!</div>
merge()	Merges two DataFrames based on multiple common columns.	<div>Syntax:<div>1. 1</div><div>1. merged_df = pd.merge(df1, df2, on=["column1", "column2"])</div></div> <div>Copied!</div> <div>Example:<div>1. 1</div><div>1. merged_df = pd.merge(sales, products, on=["product_id", "category_id"])</div></div> <div>Copied!</div>
print DataFrame	Displays the content of the DataFrame.	<div>Syntax:<div>1. 1</div><div>1. print(df) # or just type df</div></div> <div>Copied!</div> <div>Example:<div>1. 1</div><div>2. 2</div><div>1. print(df)</div><div>2. df</div></div> <div>Copied!</div>
replace()	Replaces specific values in a column with new values.	<div>Syntax:<div>1. 1</div><div>1. dataframe_name["column_name"].replace(old_value, new_value, inplace=True)</div></div> <div>Copied!</div> <div>Example:<div>1. 1</div><div>1. df["status"].replace("In Progress", "Active", inplace=True)</div></div> <div>Copied!</div>
tail()	Displays the last n rows of the DataFrame.	<div>Syntax:<div>1. 1</div><div>1. dataframe_name.tail(n)</div></div> <div>Copied!</div> <div>Example:<div>1. 1</div><div>1. df.tail(5)</div></div> <div>Copied!</div>

Numpy

Package/Method	Description	Syntax and Code Example
Importing NumPy	Imports the NumPy library.	<div>Syntax:<div>1. 1</div><div>1. import numpy as np</div></div> <div>Copied!</div> <div>Example:<div>1. 1</div><div>1. import numpy as np</div></div> <div>Copied!</div>
np.array()	Creates a one or multi-dimensional array, Syntax:	<div>1. 1</div>

```
2. 2

1. array_1d = np.array([list1 values]) # 1D Array
2. array_2d = np.array([list1 values], [list2 values]) # 2D Array
```

Copied!

Example:

```
1. 1
2. 2

1. array_1d = np.array([1, 2, 3]) # 1D Array
2. array_2d = np.array([1, 2], [3, 4]) # 2D Array
```

Copied!

Example:

```
1. 1
2. 2
3. 3
4. 4
5. 5

1. np.mean(array)
2. np.sum(array)
3. np.min(array)
4. np.max(array)
5. np.dot(array_1, array_2)
```

Copied!

- Numpy Array Attributes
- Calculates the mean of array elements
  - Calculates the sum of array elements
  - Finds the minimum value in the array
  - Finds the maximum value in the array
  - Computes dot product of two arrays



© IBM Corporation. All rights reserved.