

Main code

```
#define buzzerL_pin 4
#define buzzerR_pin A2
#define trigPinL 3 // Trigger Pin
#define echoPinL 2 // Echo Pin
#define trigPinR A1 // Trigger Pin
#define echoPinR A0 // Echo Pin
long durationL, distanceL; // Duration used to calculate distance
long durationR, distanceR; // Duration used to calculate distance
void setup()
{
  Serial.begin(9600);
  pinMode(trigPinL, OUTPUT);
  pinMode(echoPinL, INPUT);
  pinMode(trigPinR, OUTPUT);
  pinMode(echoPinR, INPUT);
  pinMode(buzzerL_pin, OUTPUT);
  pinMode(buzzerR_pin, OUTPUT);
  delay(500);
}
void loop()
{
  /*******
  digitalWrite(trigPinL, LOW);
  delayMicroseconds(2);
  digitalWrite(trigPinL, HIGH);
  delayMicroseconds(10);
  digitalWrite(trigPinL, LOW);
  durationL = pulseIn(echoPinL, HIGH);
  distanceL = durationL / 58.2;
  Serial.print("distanceL");
  Serial.println(distanceL);
  /*******
  digitalWrite(trigPinL, LOW);
  delayMicroseconds(2);
  digitalWrite(trigPinL, HIGH);
  delayMicroseconds(10);
  digitalWrite(trigPinL, LOW);
  durationL = pulseIn(echoPinL, HIGH);
  distanceL = durationL / 58.2;
  Serial.print("distanceL");
  Serial.println(distanceL);
  if (distanceL > 50)
  {
    digitalWrite(buzzerL_pin, LOW);
  }
  else
  {
    digitalWrite(buzzerL_pin, HIGH);
```

```

delay(distanceL * 5);
digitalWrite(buzzerL_pin, LOW);
delay(distanceL);
}
//*****
digitalWrite(trigPinR, LOW);
delayMicroseconds(2);
digitalWrite(trigPinR, HIGH);
delayMicroseconds(10);
digitalWrite(trigPinR, LOW);
durationR = pulseIn(echoPinR, HIGH);
distanceR = durationR / 58.2;
Serial.print("distanceR");
Serial.println(distanceR);
if (distanceR > 50)
{
digitalWrite(buzzerR_pin, LOW);
}
else
{
digitalWrite(buzzerR_pin,
HIGH); delay(distanceR * 5);
digitalWrite(buzzerR_pin, LOW);
delay(distanceR);
}
delay(50);
//*****
}

```