



# NAFFCO Sales Order Details for Workorder Creation

Report Date and Time : 9/7/2023 17:31 PM

Page 1 of 3

|   |   |
|---|---|
| <b>SO NO</b> : 902382   | Customer Name : 11731 - Al Bader Gen. Cont. Est.    |
| <b>Booking Status</b> : <b>BOOKED</b>   | Location : P37346-AIR DEFENSE BDE/71 CMW-21024-C001 |
| <b>Status</b> : <b>Approved</b>   | PO.No : Subcontract Agreement dated 17/04/23        |
| Order Date : 19-JUL-23  | Salesman Name : Ali Khaled Abdul Ghani              |
| Type : NAD Project Sales Order  | Delivery Date :                                     |
| Currency : AED  | Payment Term : Immediate                            |
| Remarks : CMW-21024-C001, Construction for Air Defence Brigade/71 Command in Barakah. |   |

| SL   | Item Code   | Description   | UOM | Qty | Unit Price | Amount    |
|------|-------------|---|-----|-----|------------|-----------|
| 1.1  | 12502402060 | Fire Pump 300 GPM @ 6 Bar Coupled with Electric Motor and Standard Accessories, UL/FM Approved - Naffco   | SET | 1   | 21,852.00  | 21,852.00 |
| 2.1  | 12522402060 | Fire Pump 300 GPM @ 6 Bar Coupled with Diesel Engine and Standard Accessories, UL/FM Approved - Naffco  | SET | 1   | 22,427.00  | 22,427.00 |
| 3.1  | 30604035250 | Vertical Multistage Full Stainless Steel Pump NF-VL 4-100, With 3HP (2.2KW), 380-415V, 3Phase, 2900 RPM, 50Hz/IP55 Class F Motor, Red colour - NAFFCO   | PCS | 1   | 3,222.00   | 3,222.00  |
| 4.1  | 30658051212 | Electric Fire Pump Controller Microprocessor Based 40HP, 380 - 415V/3Ph, 50/60Hz, Wye Delta Open Transition Starter, NEMA 4 Standard, NFPA 20, UL/FM Approved, Model: NFY-SDM1-NAFFCO   | PCS | 1   | 5,752.00   | 5,752.00  |
| 5.1  | 30658051414 | Diesel Fire Pump Controller Microprocessor Based 12V DC, 220/230V AC, 1 Ph, 50/60Hz, Complete Auto and Manual Operation, NEMA 4 Enclosure, NFPA-20, UL/FM Approved, Model: NFY-DM1-NAFFCO   | PCS | 1   | 4,602.00   | 4,602.00  |
| 6.1  | 30658051753 | Jockey Pump Controller 3HP (2.2kW), 380-415V, 3Ph, 50 Hz, Across the Line Starter Type, NEMA 4 Standard, NFPA-20, UL Listed, Model: NFY JDO1 - NAFFCO   | PCS | 1   | 2,877.00   | 2,877.00  |
| 7.1  | 30607071804 | Flow Meter 4" Grooved Type, Class 150, Flow Range 150-600 GPM, Venturi Type, FM Approved, Model: 4-300-G - Global Vision, USA   | PCS | 1   | 2,532.00   | 2,532.00  |
| 8.1  | 30659051070 | Above Ground Storage Tank (Diesel Tank), Capacity : 70 Gln, Tank Size: 600mm Dia x 1050mm L x 430mm W and with Min. Leg Length 500mm, Red Painted, Model: NFDI 70, UL Listed - NAFFCO   | PCS | 1   | 2,302.00   | 2,302.00  |
| 9.1  | 30309475101 | Lead Acid Battery 100Ah x 12V   | PCS | 2   | 577.00     | 1,154.00  |
| 10.1 | 70505510110 | Servicing Charges ***Additional Valves & Accessories for Fire Pump***   | EAH | 1   | 11,502.00  | 11,502.00 |
| 11.1 | 11001308701 | Gate Valve 8", D.I Body to AWWA C515, Non-Rising Stem, EPDM Coated Resilient Wedge With HANDLE w/o Post Indicator Flange, Flanged Ends to ANSI B16.1, Class 125, WP 200 Psi, RED RAL3000 FBE Coating, Model:SD-NRS200FF-D, UL/FM Approv -Shield | PCS | 1   | 1,582.00   | 1,582.00  |
| 12.1 | 11001308601 | Gate Valve 4", D.I Body to AWWA C515, Non-Rising Stem, EPDM Coated Resilient Wedge With HANDLE w/o Post Indicator Flange, Flanged Ends to ANSI B16.1, Class 125, WP 200 Psi, RED RAL3000 FBE Coating, Model:SD-NRS200FF-D, UL/FM Approv -Shield | PCS | 1   | 581.00     | 581.00    |

## NAFFCO Sales Order Details for Workorder Creation

Report Date and Time : 9/7/2023 17:31 PM

Page 2 of 3

| SL   | Item Code   | Description  | UOM | Qty | Unit Price | Amount    |
|------|-------------|--|-----|-----|------------|-----------|
| 13.1 | 11001308561 | Gate Valve 2-1/2", D.I Body to AWWA C515, Non-Rising Stem, EPDM Coated Resilient Wedge W/HANDLE w/o Post Indicator Flange, Flanged Ends to ANSI B16.1, Class 125, WP 200 Psi, RED RAL3000 FBE Coating, Model:SD-NRS200FF-D, UL/FM Approv -Shield | PCS | 3   | 388.00     | 1,164.00  |
| 14.1 | 11001308551 | Gate Valve 2", D.I Body to AWWA C515, Non-Rising Stem, EPDM Coated Resilient Wedge With HANDLE w/o Post Indicator Flange, Flanged Ends to ANSI B16.1, Class 125, WP 200 Psi, RED RAL3000 FBE Coating, Model:SD-NRS200FF-D, FM Approved -Shield   | PCS | 4   | 348.00     | 1,392.00  |
| 15.1 | 11302910300 | Double Vertical Hose Reel Cabinet, Recessed Type, Solid Door, Complete Stainless Steel 304 (Mirror) - 1mm Thickness - Naffco ***Size: 1600 x 700 x 280*** (PIANO Hinges)   | PCS | 2   | 1,693.00   | 3,386.00  |
| 15.2 | 11302910300 | <b>Double Vertical Hose Reel Cabinet, Recessed Type, Solid Door, Complete Stainless Steel 304 (Mirror) - 1mm Thickness - Naffco ***Size: 1600 x 700 x 280*** (PIANO Hinges)</b>  | PCS | 8   | 1,693.00   | 13,544.00 |
| 16.1 | 10661110330 | <b>Fire Hose Reel 1" x 30 Mtr. Cabinet Mounted, Automatic with Plastic Nozzle, Conforming to BS EN 671-1:2012, CE0086, Model: 25 NFH-020A, "Kite marked"/LPCB Approved - Naffco</b>  | PCS | 10  | 459.00     | 4,590.00  |
| 17.1 | 11003010127 | 1" Lock Shield Valve with Key, Double Female BSPT Threaded to ISO 7-1, Material: Brass Grade CZ122, Pressure Rating: PN20, Comply to BS EN 12288, Kitemark Approved, Model: NLSV-25 - NAFFCO   | PCS | 10  | 37.00      | 370.00    |
| 18.1 | 11081008525 | 1" Pressure Reducing/Regulating Valve, Female Threaded, W/P 25Bar (360 Psi), Nickel Plated, Kite Mark Approved, P/N.# SD-91430K-125, Model: SD-91430K - Shield   | PCS | 10  | 86.00      | 860.00    |
| 19.1 | 10111010802 | <b>Co2 Extinguisher, Portable Type, Capacity: 2 Kg, Black Color with Horn &amp; Bracket, Model: NC 2 - Naffco, UAE</b>   | PCS | 35  | 100.00     | 3,500.00  |
| 20.1 | 10101010516 | <b>Dry Powder Extinguisher, Portable Pressure Type, Capacity 6 Kg, Blue Color, NP- 6,, Naffco, UAE</b>   | PCS | 22  | 103.00     | 2,266.00  |
| 21.1 | 11463010200 | Double Extinguisher Cabinet Surface Mounted Wired Glass Complete Stainless Steel (Mirror) naffco ***Size: 850 x 500 x 220*** (PIANO Hinges)  | PCS | 2   | 1,325.00   | 2,650.00  |
| 22.1 | 11001308551 | Gate Valve 2", D.I Body to AWWA C515, Non-Rising Stem, EPDM Coated Resilient Wedge With HANDLE w/o Post Indicator Flange, Flanged Ends to ANSI B16.1, Class 125, WP 200 Psi, RED RAL3000 FBE Coating, Model:SD-NRS200FF-D, FM Approved -Shield   | PCS | 7   | 348.00     | 2,436.00  |
| 23.1 | 11900510025 | Air Release Valve 1" BSPT Threaded, PN20 (20 Bar W/P), Forged Brass, Model: NWR 104  | PCS | 6   | 36.00      | 216.00    |
| 24.1 | 11140108525 | 1" Ball Valve, NPT Double Female Threaded, Brass Nickel Plated, Steel Lever Handle, W/P: 600WOG, UL Listed, Model: SD-BVLT95 - Shield  | PCS | 6   | 34.00      | 204.00    |
| 25.1 | 10558522525 | Pressure Gauge 0-250 Psi, 3-1/2" Dia, 1/4" BSPT end Connection, UL Listed, Model.# SD-P - Shield   | PCS | 6   | 40.00      | 240.00    |
| 26.1 | 10184010052 | <b>Foam Extinguisher AFFF, Mobile Type, Capacity 50 Ltr, Cream Color, NTF 50, Naffco,</b>  | PCS | 1   | 643.00     | 643.00    |



## NAFFCO Sales Order Details for Workorder Creation

Report Date and Time : 9/7/2023 17:31 PM

Page 3 of 3

| SL   | Item Code   | Description  | UOM | Qty | Unit Price | Amount     |
|------|-------------|--|-----|-----|------------|------------|
|      |             | <b>UAE</b>   |     |     |            |            |
| 27.1 | 10181010090 | Foam Extinguisher AFFF, Portable Pressure Type, Capacity 9 Ltr, Cream Color, NF 9, Naffco, UAE   | PCS | 1   | 84.00      | 84.00      |
| 28.1 | 10186010175 | Foam Master Tank, Capacity: 500 Ltr, S/Steel 316, Yellow Color, With 2 x 2-1/2" Duralux Fire Hose 30mtr Length, Model: NFM 500L - Naffco | PCS | 2   | 39,386.00  | 78,772.00  |
| 29.1 | 70505510110 | Servicing Charges ***Foam Concentrate - Qty to be Finalize with Engg Dept***   | EAH | 2   | 4,025.00   | 8,050.00   |
| 30.1 | 70505510110 | Servicing Charges ***NO BOQ for FM200 Sys - 1Room***   | EAH | 1   | 35,771.00  | 35,771.00  |
| 31.1 | 70501010111 | Installation With Piping, Testing & Commissioning Charges  | LOT | 1   | 179,477.00 | 179,477.00 |

**SO Amount Total: 0.00**

**VAT Amount: 21,000.00**

=====

**Total Amount:**